


20° PRESSURE ANGLE

PHONE: 516.328.3300 • FAX: 516.326.8827 • WWW.SDP-SI.COM

> MATERIAL:
Steel



METRIC COMPONENT

Catalog Number	No. of Teeth	P.D.	D Dia.	D ₁ Shank Dia.	L Minimum Usable Length
Module 0.8					
* A 1C29MY08012	12	9.6	11.2	6	80
* A 1C29MY08014	14	11.2	12.8	6	80
* A 1C29MY08016	16	12.8	14.4	6	80
* A 1C29MY08018	18	14.4	16	6	80
* A 1C29MY08024	24	19.2	20.8	6	80
* A 1C29MY08030	30	24	25.6	12	80
A 1C29MY08032	32	25.6	27.2	12	150
A 1C29MY08036	36	28.8	30.4	12	150
A 1C29MY08040	40	32	33.6	12	150
A 1C29MY08045	45	36	37.6	12	150
A 1C29MY08050	50	40	41.6	12	150
A 1C29MY08060	60	48	49.6	12	200
A 1C29MY08064	64	51.2	52.8	12	200
A 1C29MY08075	75	60	61.6	16	200
A 1C29MY08080	80	64	65.6	16	200
A 1C29MY08090	90	72	73.6	16	200
Module 1					
A 1C29MY10014	14	14	16	6	80
A 1C29MY10016	16	16	18	6	80
A 1C29MY10020	20	20	22	6	80
A 1C29MY10024	24	24	26	12	80
A 1C29MY10028	28	28	30	12	150
A 1C29MY10030	30	30	32	12	150
A 1C29MY10032	32	32	34	12	150
A 1C29MY10036	36	36	38	12	150
A 1C29MY10040	40	40	42	12	200
A 1C29MY10045	45	45	47	12	200
A 1C29MY10048	48	48	50	12	200
A 1C29MY10050	50	50	52	12	200
A 1C29MY10060	60	60	62	16	200
A 1C29MY10064	64	64	66	16	200
A 1C29MY10072	72	72	74	16	200

* Minimum usable length: 75 mm to 80 mm