

HUBLESS SPUR GEARS • 80 PITCH



AGMA 10
1/8 FACE
3/8 BORE
20° PRESSURE ANGLE



PHONE: 516.328.3300 • FAX: 516.326.8827 • WWW.SDP-SI.COM

► MATERIAL:

303 Stainless Steel
2024 Aluminum, Anodized
T4 or T351 Aluminum Alloy,
Anodized before cutting

Available on special order:
14-1/2° P.A., teeth not listed, different
bore size and/or material, passivation
for Stainless Steel.

All gears over 2-1/8 Dia. supplied with lightening holes.
See Index for hubs.
Assembled upon request at nominal charge.
Hubs are available in Pin, Clamp, or Fairloc® type.



INCH COMPONENT

Catalog Number		No. of Teeth	P.D.	O.D.	B Dia.	C Dia.
303 Stainless Steel	2024 Aluminum Anodized					
S1268Z-080S048	S1268Z-080A048	48	.6000	.625	—	—
S1268Z-080S050	S1268Z-080A050	50	.6250	.650	—	—
S1268Z-080S052	S1268Z-080A052	52	.6500	.675	—	—
S1268Z-080S054	S1268Z-080A054	54	.6750	.700	—	—
S1268Z-080S056	S1268Z-080A056	56	.7000	.725	—	—
S1268Z-080S058	S1268Z-080A058	58	.7250	.750	—	—
S1268Z-080S060	S1268Z-080A060	60	.7500	.775	—	—
S1268Z-080S062	S1268Z-080A062	62	.7750	.800	—	—
S1268Z-080S070	S1268Z-080A070	70	.8750	.900	—	—
S1268Z-080S080	S1268Z-080A080	80	1.0000	1.025	—	—
S1268Z-080S090	S1268Z-080A090	90	1.1250	1.150	—	—
S1268Z-080S100	S1268Z-080A100	100	1.2500	1.275	—	—
S1268Z-080S110	S1268Z-080A110	110	1.3750	1.400	—	—
S1268Z-080S120	S1268Z-080A120	120	1.5000	1.525	—	—
S1268Z-080S127	S1268Z-080A127	127	1.5875	1.613	—	—
S1268Z-080S130	S1268Z-080A130	130	1.6250	1.650	—	—
S1268Z-080S140	S1268Z-080A140	140	1.7500	1.775	—	—
S1268Z-080S150	S1268Z-080A150	150	1.8750	1.900	—	—
S1268Z-080S160	S1268Z-080A160	160	2.0000	2.025	—	—
S1268Z-080S170	S1268Z-080A170	170	2.1250	2.150	.375	1.375
S1268Z-080S180	S1268Z-080A180	180	2.2500	2.275	.375	1.375
S1268Z-080S190	S1268Z-080A190	190	2.3750	2.400	.375	1.375
S1268Z-080S200	S1268Z-080A200	200	2.5000	2.525	.375	1.375
S1268Z-080S210	S1268Z-080A210	210	2.6250	2.650	.375	1.750
S1268Z-080S220	S1268Z-080A220	220	2.7500	2.775	.375	1.750
S1268Z-080S240	S1268Z-080A240	240	3.0000	3.025	.375	1.750
S1268Z-080S260	S1268Z-080A260	260	3.2500	3.275	.500	2.000
S1268Z-080S280	S1268Z-080A280	280	3.5000	3.525	.500	2.000
S1268Z-080S300	S1268Z-080A300	300	3.7500	3.775	.500	2.250
S1268Z-080S320	S1268Z-080A320	320	4.0000	4.025	.500	2.250

