

BLHI30
BLHO30
BLHB30

e-cad
Drawings
Available

GEARBOXES


Bevel Bore Heavy Duty Gearbox

Hardened Bevels - Bore Type 1.32 – 4.4 Nm **1:1 - 2:1**

BLHI30 (Bore Input) & BLHO30 (Bore Output) Type 1:1 ratio BLHI30 only




BLHI30



BLHB30 Type (Bore Input & Bore Output)



BLHB30



Part Number	Ratio	Efficiency at 1000 Rpm
BLHI30-1 BLHB30-1	1:1	88%
BLHO30-2 or BLHI30-2 BLHB30-2	2:1	88%

Output Backlash: ≈1°.

Max. Input Speed: 3,000 Rpm.

Greased for Life: Shell Gadus S2 V220AD 2.

Shaft Key: K12-14.

Bores (pin driven): DH / DP, SEP / EP, SAP / SRP 2mm x 12 long.

Testing in your application is necessary.

You will need to assess duty cycles and confirm gearbox suitability with your own calculations.

All figures listed are to be used for guidance only.

Output Torque Nm

Rpm Input	Reduction Ratio	
	1:1	2:1
3000	1.65	1.32
2000	1.81	1.45
1000	2.20	1.76
500	2.51	2.00
100	3.38	2.70
50	3.70	3.00
10	4.40	3.54

ondrives.US Corp.

☎ 516-771-6777
📠 516-771-6444

📧 sales@ondrives.us
🌐 www.ondrives.us