



**J66
XJ66**

e-cad
Drawings
Available

GEARBOXES

Inline Spur Gear Reducers

6mm Double or Single Shaft, 0.9 – 2.8 Nm **1:1 - 256:1**



Part Number	Ratio	Efficiency at 1000 Rpm	Nm Output at 1000 Rpm	Standard Direction
J66-50 XJ66-50	50:1	85%	1.18	Same
J66-80 XJ66-80	80:1	85%	1.30	Same
J66-96 XJ66-96	96:1	85%	1.33	Same
J66-128 XJ66-128	128:1	85%	1.39	Same
J66-160 XJ66-160	160:1	85%	1.44	Same
J66-192 XJ66-192	192:1	85%	1.60	Same
J66-256 XJ66-256	256:1	85%	1.85	Same
J66-SP XJ66-SP	1:1 - 256:1	Special Ratios : Replace SP with required ratio		

J66 Weight: 0.34 kg.

Backlash: Depends on ratio.

Max. Input Speed: 4,000 Rpm.

Greased for Life: Shell Gadus S5 V42P 2.5.

Max. Overhung and Thrust Loads at 1000 Rpm:

Output Overhung Load (F_{a0}) = 5 kg. Output Thrust Load (F_{t0}) = 5 kg.

Shaft Keys: KK2-14.

Testing in your application is necessary.

You will need to assess duty cycles and confirm gearbox suitability with your own calculations.

All figures listed are to be used for guidance only.

Output Torque Nm

Rpm Input	Reduction Ratio						
	50:1	80:1	96:1	128:1	160:1	192:1	256:1
4000	0.90	1.01	1.05	1.09	1.13	1.25	1.40
2000	1.04	1.13	1.18	1.24	1.30	1.40	1.55
1000	1.18	1.30	1.33	1.39	1.44	1.60	1.85
500	1.40	1.44	1.50	1.58	1.64	1.78	2.00
200	1.60	1.73	1.80	1.87	1.96	2.18	2.42
100	1.82	1.96	2.10	2.17	2.28	2.47	2.80
50	2.02	2.28	2.45	2.61	2.80	2.80	2.80
10	2.50	2.80	2.80	2.80	2.80	2.80	2.80