


NOTES:

- 1.) REFER TO UL1681 PAGE 10, FIG. C1.5, AND CLAUSE 4.12.2 IN CSA C22.2 WHICH REFERENCES NEMA WD-16-1988.
- 2.) CRITICAL DIMENSION TO BE CHECKED AS PART OF THE IN-PROCESS INSPECTION (SPC).

  
**HEXCO PRODUCTS, INC.**  
 TOMS RIVER, NEW JERSEY  
 FAX (732) 244-8843  
 (732) 286-1800

PART DRAWING

TOLERANCES +/-: .XX=.01 .XXX=.005 ANG.=2°
MATL.: BRASS FINISH: TINNED
THICK: .021 WIRE STRIP LENGTH: .21
WIRE RANGE (AWG): 18-14
TOOLING: UNIV. DIE-A001, PUNCH-C236, ANVIL-C254 /DIE BASE-0629, PUNCHES-0C73(18), 0K18(16-14), ANVILS-00A9
DRAWN: M.S. DATE: 09/26/91
REVISION: MEG DATE: 06/28/01
APPROVED: DATE:

112-8-TIN-W/ANGLED TIP-R/L  
DESCRIPTION

5085	5080-012	G
PART NUMBER	CATALOG NUMBER	REVISION



LS-91824

