




NOTES:

- 1.) REFER TO UL1681 PAGE 10, FIG. C1.5, AND CLAUSE 4.12.2 IN CSA C22.2 WHICH REFERENCES NEMA WD-16-1988.
- 2.) CRITICAL DIMENSION TO BE CHECKED AS PART OF THE IN-PROCESS INSPECTION (SPC).



LS-91824



UNWINDING INFORMATION  
 FEED FROM LEFT TO RIGHT.  
 CRIMP IN FRONT & UPRIGHT.

**HEYCO**  
 HEYCO PRODUCTS, INC.  
 TOMS RIVER, NEW JERSEY  
 (732) 286-4336 FAX (732) 244-8843

PART DRAWING

TOLERANCES +/-: .XX=.01 .XXX=.005 ANG.=2°	
MATL.: BRASS	FINISH: POST NICKEL
THICK: .021	WIRE STRIP LENGTH: .19
WIRE RANGE (AWG): 18-14	
TOOLING: UNIV. DIE-A011, PUNCH-C236, ANVIL-C254 /DIE BASE-0504, PUNCHES-0C73(18), 0K18(16-14), ANVILS-00A9	
DRAWN: M.S.	APPROVED:
DATE: 05/11/93	DATE: 06/28/01

103-N-PAD-POL-PN-L/R	
DESCRIPTION	
5187	5100-721
PART NUMBER	CATALOG NUMBER
	REVISION
	G