



NOTES:

- 1.) REFER TO UL1681 PAGE 10, FIG. C1.5, AND CLAUSE 4.12.2 IN CSA C22.2 WHICH REFERENCES NEMA WD-16-1988.
- 2.) Δ CRITICAL DIMENSION TO BE CHECKED AS PART OF THE IN-PROCESS INSPECTION (SPC).



LS-91824



 <p>HEYCO PRODUCTS, INC. TOMS RIVER, NEW JERSEY FAX (732) 244-8843</p>			
PART DRAWING			
TOLERANCES +/-: .XX=.01 .XXX=.005 ANG.=2°			
MATL: BRASS	FINISH: POST NICKEL		
THICK: .028	WIRE STRIP LENGTH: .19		
WIRE RANGE (AWG): 18-14			
TOOLING: UNIV. DIE-A011, PUNCH-C453, ANVL-C327			
DIE BASE- , PUNCHES- , ANVLS-			
DRAWN: SJH	REVISED: MEG	APPROVED:	
DATE: 03/15/94	DATE: 06/29/01	DATE:	
BGBS-L/R-POST NICKEL			
DESCRIPTION			
5794	5790-021		
PART NUMBER	CATALOG NUMBER		REVISION
			1

UNWINDING INFORMATION
FEED FROM LEFT TO RIGHT
CRIMP IN FRONT & UPRIGHT

