



VIEW: CRIMP

NOTE:

1.) $\triangle C$ CRITICAL DIMENSION TO BE CHECKED AS PART OF THE IN-PROCESS INSPECTION (SPC).

TOOLING: UNIV. DIE-N/A, PUNCH-N/A, ANVIL-N/A
 DIE BASE: 6000SOX5, PUNCH-OV23, ANVIL-OV22
 INSERT 6 OR 8 INTO DIE BASE "X" DEPENDING ON AWG

TOLERANCE UNLESS OTHERWISE SPECIFIED: .XX± 0.015 .XXX± 0.005 ANGULAR± 1.0 °

MATERIAL:	<div> <div>HEYCO</div> <div>HEYCO PRODUCTS, INC. TOMS RIVER, NEW JERSEY</div> </div> <div> HEYCO PRODUCTS, INC. claims proprietary rights to the material disclosed hereon. This drawing and/or technical information is the property of HEYCO PRODUCTS, INC. is issued in confidence for use only as authorized and may not be reproduced or described or shown to others without written permission from HEYCO PRODUCTS, INC. </div>		
BRASS			
FINISH:			
THICKNESS:			
.045	DESCRIPTION: CATALOG DRAWING 6000-000 127-BULK WIRE RANGE (AWG): 8-6 WIRE STRIP LENGTH: .31		6000 PART No. REV.: J