


NOTE:
 1.) \triangle CRITICAL DIMENSION TO BE CHECKED AS PART OF THE IN-PROCESS INSPECTION (SPC).

TOOLING: UNIV. DIE-N/A, PUNCH-N/A, ANVIL-N/A
 DIE BASE: 6000S0X5, PUNCH-OV23, ANVIL-OV22
 INSERT 6 OR 8 INTO DIE BASE "X" DEPENDING ON AWG

TOLERANCE UNLESS OTHERWISE SPECIFIED: .XX ± 0.015 .XXX ± 0.005 ANGULAR ± 1.0 °

MATERIAL:	BRASS	
FINISH:	TINNED	
THICKNESS:	.045	
 HEYCO PRODUCTS, INC. TOMS RIVER, NEW JERSEY		
DESCRIPTION: CATALOG DRAWING	6010-010	6011
DESCRIPTION: CATALOG DRAWING	127-3-TIN-BULK	
DESCRIPTION: CATALOG DRAWING	WIRE RANGE (AWG): 8-6	PART No.
DESCRIPTION: CATALOG DRAWING	WIRE STRIP LENGTH: .31	REV.: E

HEYCO PRODUCTS, INC. claims proprietary rights to the material disclosed herein. This drawing and/or technical information is the property of HEYCO PRODUCTS, INC. and is issued in confidence for use only as authorized and may not be reproduced or described or shown to others without written permission from HEYCO PRODUCTS, INC.