



VIEW: KNEES

NOTES:

1. DIMS. FROM CUSTOMER PRINT APPLY THIS PRINT FOR MFG. REF. ONLY
2. CONTACT AREA & EDGES TO BE BURR FREE.
3. ALIGNMENT OF TIP AND/OR HOLE .010 MAX.
4. BLADE SQUARE TO FOLDOVER WITHIN .002.
5. FOLDED SECTION MUST BE CLOSED.
6. KNEE SQUARE & PARALLEL TO TIP .015 MAX.
7. $\triangle C$ CRITICAL DIMENSION TO BE CHECKED AS PART OF THE IN-PROCESS INSPECTION (SPC).

HEYCO	HEYCO PRODUCTS, INC.	
	TOMS RIVER, NEW JERSEY	
(908) 286-1800	FAX (908) 244-8843	

PRODUCTION DRAWING

TOLERANCES +/-: .XX=.01 .XXX=.005 ANG.=2°

MATL.: BRASS	FINISH:
--------------	---------

THICK: .028	WIRE STRIP LENGTH: .19
-------------	------------------------

WIRE RANGE (AWG):

TOOLING: UNIV. DIE-	PUNCH-
ANVIL-	
DIE BASE-	PUNCHES-
	ANVILS-

DRAWN: TMC	REVISED: WJC	APPROVED: WSC
DATE: 6/18/91	DATE: 6/10/97	DATE: 7/11/97

TRANS BLADE
DESCRIPTION

8063	8063-000	A
PART NUMBER	CATALOG NUMBER	REVISION