

Tyna-Myte Series 1/4-inch ports, 2-way, 3-way, 4-way, Direct operating

VALVES

Option Code	2 Way	3 Way	Norm. Closed	Norm. Open	w/Out Mount. Base	With Mount. Base	Grom-met Leads (18")	Con-duit Leads (18")	DIN Con-ector	Grom-met Leads (72")	Cap-tured Exhaust	Cover Seal	Flow Con-trols	Manual Over-ride	Viton Seals	Specify Voltage with option code			
																120v 50/60Hz, 240/50/60 (ID not avail-able on E1)	24VAC 50/60 w/"Flywheel" Rectifiers for CD	12VDC 24VDC	
Option Code	2	3	10	11	20	21	35	36	39	LL	60	61	70	80	w/VAI	CD	ID	CD	ID
Model																			
062E1	SP	N/C	N/C	N/C	N/C	SP	N/C	SP	SP	SP	STD	SP	NA	SP	SP	N/C	NA	SP	NA
062E2	SP	N/C	NA	NA	N/C	SP	NA	N/C	SP	SP	STD	SP	NA	NA	SP	SP	N/C	SP	SP
062-4E1	NA	NA	NA	NA	N/C	SP	N/C	SP	SP	SP	STD	SP	SP	SP	SP	N/C	NA	SP	NA
062-4E2	NA	NA	NA	NA	N/C	SP	NA	N/C	SP	SP	STD	SP	SP	NA	SP	SP	N/C	SP	SP
T062E1	SP	N/C	N/C	N/C	NA	NA	N/C	SP	SP	SP	SP	SP	NA	SP	SP	N/C	NA	SP	NA
T062E2	SP	N/C	NA	NA	NA	NA	NA	N/C	SP	SP	SP	SP	NA	NA	SP	SP	N/C	SP	SP
T062-4E1	NA	NA	NA	NA	NA	NA	N/C	SP	SP	SP	SP	SP	SP	SP	SP	N/C	NA	SP	NA
T062-4E2	NA	NA	NA	NA	NA	NA	NA	N/C	SP	SP	SP	SP	SP	NA	SP	SP	N/C	SP	SP
125E1	SP	N/C	N/C	N/C	N/C	SP	N/C	SP	SP	SP	STD	STD	NA	SP	SP	N/C	NA	SP	NA
125E2	SP	N/C	NA	NA	N/C	SP	NA	N/C	SP	SP	STD	STD	NA	NA	SP	SP	N/C	SP	SP
125-4E1	NA	NA	NA	NA	N/C	SP	N/C	SP	SP	SP	STD	STD	SP	NA	SP	N/C	NA	SP	NA
T125E1	SP	N/C	N/C	N/C	NA	NA	N/C	SP	SP	SP	SP	STD	NA	SP	SP	N/C	NA	SP	NA
T125E2	SP	N/C	NA	NA	NA	NA	NA	N/C	SP	SP	SP	STD	NA	NA	SP	SP	N/C	SP	SP
T125-4E1	NA	NA	NA	NA	NA	NA	N/C	SP	SP	SP	STD	SP	NA	SP	SP	N/C	NA	SP	NA

CD=Continuous Duty; ID=Intermittent Duty

Note: Code 39 not available on Models T/062E2, T/062-4E2, and T/125E2 when specifying Option "CD" (continuous coils).

MANIFOLDS

Model	
TM1	TM7
TM2	
TM3	
TM4	
TM5	
TM6	

Manifold Selection: includes screws, mounting legs, and 1/8" NPT plugs (two per station).

Multi-Pressure Manifold — (Non-Stock Item) — Specify. TM Series Manifold only. Example: TM5.

ACCESSORIES

Model	Description
HS4	DIN Connector for use with Code 39 Valves.
8-32A	Block-off Plate.

NOTE: Valves, Manifolds, and Accessories are shipped detached, ready to be mounted according to specific application requirements.

HOW TO ORDER

Starting with Model Number specify options in order from left to right.

Example: To Order Model 062E1-3-11-21-36

3-Way Operation	(062E1-3)
Normally Open	(062E1-3-11)
Mounting Base	(062E1-3-11-21)
Conduit	(062E1-3-11-21-36)
Captured EXH, and that is STD	(062E1-3-11-21-36)
Voltage 12VDC	(062E1-3-11-21-36 12VDC)

Remember: Option Codes marked STD and NA are not used as part of the Model Number when ordering. N/C indicates no charge but Option Code must be included in the Model Number. OS indicates that Option must be ordered separately and is not used as part of the Model Number.

N/C=No charge	STD=Standard
NA =Not available	SP=Specify, additional charge for this option
OS =Order separately, additional charge for this option	