

FEATURES

- Perfect for tight, hard to reach spaces!
- Minimizes parts that protrude by tightening together versus tightening away from.
- Deep socket tools not required.
- 300 Stainless steel construction.



TWO BARREL HARDWARE CLAMPS				
PART NO	DESCRIPTION	MIN/MAX DIAMETER	MAX TORQUE	QTY
BC090	3/4" 300 SS Floating Bridgew/Lockwasher	0.91"/0.98"	75 in-lbs	1
BC114	1" 300 SS Floating Bridge w/Lockwasher	1.14"/1.22"	75 in-lbs	1

BANJO MAN		
PART NO	DESCRIPTION	QTY
BANJOMAN	18" x 29"- Assembly Required	1

Banjo Super Clamps

FEATURES

- Stainless steel construction.
- 304 Stainless steel bolt with 316 SS nut to prevent seizing.
- 360° sealing surface.
- Ideal for high torque applications.
- Strong, positive connections where ordinary hose clamps fail.
- T-bolt design.
- 3 spot welds for extra strength.



**Torque Specifications: Working Torque: 50-80 inch pounds.
Maximum Torque: 125 inch pounds**

BANJO SUPER CLAMPS				
PART NO	DESCRIPTION	MIN/MAX DIAMETER	MAX TORQUE	QTY
TC120	1" T-Bolt Hose Clamp	1.20"/1.34"	75 in-lbs	10/bag
TC130	1 1/4" T-Bolt Hose Clamp	1.30"/1.70"	75 in-lbs	10/bag
TC150	1 1/2" T-Bolt Hose Clamp	1.50"/1.75"	125 in-lbs	10/bag
TC162	1 1/4" T-Bolt Hose Clamp	1.62"/1.87"	125 in-lbs	10/bag
TC181	1 1/2" T-Bolt Hose Clamp	1.81"/2.06"	125 in-lbs	10/bag
TC193	1 1/2" T-Bolt Hose Clamp	1.93"/2.18"	125 in-lbs	10/bag
TC206	2" T-Bolt Hose Clamp	2.06"/2.40"	125 in-lbs	10/bag
TC218	2" T-Bolt Hose Clamp	2.18"/2.50"	125 in-lbs	10/bag
TC224	2" T-Bolt Hose Clamp	2.24"/2.55"	125 in-lbs	10/bag
TC231	2" T-Bolt Hose Clamp	2.31"/2.62"	125 in-lbs	10/bag
TC250	2" T-Bolt Hose Clamp	2.50"/2.81"	125 in-lbs	10/bag
TC287	2" T-Bolt Hose Clamp	2.87"/3.18"	125 in-lbs	10/bag
TC312	3" T-Bolt Hose Clamp	3.12"/3.49"	125 in-lbs	10/bag
TC331	3" T-Bolt Hose Clamp	3.31"/3.62"	125 in-lbs	10/bag
TC343	3" T-Bolt Hose Clamp	3.50"/3.82"	125 in-lbs	10/bag
TC425	4" T-Bolt Hose Clamp	4.25"/4.56"	125 in-lbs	10/bag
TC438	4" T-Bolt Hose Clamp	4.38"/4.76"	125 in-lbs	10/bag
TC456	4" T-Bolt Hose Clamp	4.56"/4.94"	125 in-lbs	10/bag