



Smart fluid handling
to take you forward, faster.



Smart fluid handling to take you forward, faster ● ● ●

CPC (Colder Products Company) has been designing and manufacturing quick disconnect couplings, fittings and connectors since 1978. Our broad range of products are found in thousands of applications across many life sciences, specialty industrial and chemical handling markets. Used in a wide range of products, machinery, devices and processes, CPC's innovative coupling and connection technologies allow flexible tubing to be quickly and safely connected and disconnected. The robust and easy-to-use design of CPC's quick disconnect couplings and fittings provides reliable, secure and leak-free connections for fluid and air management. CPC makes people's lives better by developing innovative high quality products that make fluid handling safe and easy.

WHERE TO BUY

Find your local distributor by visiting cpcworldwide.com or call CPC's Customer Service at 1-800-444-2474 or 651-645-0091. You can also send an email to info@cpcworldwide.com.

QUALITY

CPC meets or exceeds our customers' expectations. Everyone is involved, from our suppliers to our distribution network, and most importantly, our employees. CPC measures and continually improves our standards of product quality, support services and overall customer and employee satisfaction. CPC's Quality System conforms to ISO 9001:2008 and ISO 13485 standards. Our cleanroom is ISO Class 7 certified.

NEW PRODUCTS

Exciting additions to CPC's product offering include:

- | | |
|--|----------|
| • NS1 Series Connectors | Page 24 |
| • NS4 Series Connectors – Elbow | Page 60 |
| • LQ4 Series Connectors | Page 62 |
| • LQ6 Series Connectors | Page 66 |
| • BQ45GL Series Connectors | Page 86 |
| • Hybrid Connectors | Page 88 |
| • MPC/MPX Back-to-Back Insert Adapters | Page 109 |
| • Genderless AseptiQuik® G Connectors | Page 122 |
| • AseptiQuik® G STC Connectors | Page 132 |

OUR CAPABILITIES



CPC's engineered, custom solutions improve the overall functionality and design of the equipment and processes in which they are used. Special product features include precise hose barbs for superior grip, built-in shutoff valves to prevent product spills and an easy-to-use, push-button thumb latch for quick connecting and disconnecting.

CPC's patented Hybrid Connector technology platform eliminates misconnections by integrating electrical, fluid and gas lines into a single connection point. RFID-enabled IdentiQuik® couplings redefine what's possible for controlling, protecting and streamlining fluid handling processes. IdentiQuik technology allows the robust transfer of fluid and information to identify device type or connected media, verify line connection accuracy or capture fluid and product data. Specific applications for CPC connection technologies include:

• LIFE SCIENCES

CPC's products are used across a broad range of medical devices and equipment, including surgical, dialysis, blood pressure monitoring, patient therapy devices, and in vitro diagnostics. A de facto standard in several applications, CPC connectors improve patient safety, prevent misconnections and increase the overall usability and effectiveness of medical devices. Medical device OEMs around the world choose CPC connectors because of our proven performance in the operating room, the life science lab and the home healthcare setting.

CPC is the leader in single-use connection technology for bioprocessing applications, offering a wide variety of solutions including sterile connect and sterile disconnect. Our innovative designs offer the flexibility to easily combine multiple components and systems including process containers, tubing manifolds, transfer lines, bioreactors and other bioprocess equipment. CPC's robust connectors maintain media sterility and integrity while improving production yields, reducing costs and decreasing time to market for biopharmaceutical manufacturers. Genderless connector technology simplifies the design process, reduces supply chain complexity and eases manufacturing integration for biopharmaceutical manufacturers.



• SPECIALTY INDUSTRIAL

CPC's couplings and fittings are installed in thousands of product applications. Our broad offering appeals to product manufacturers in a wide range of industrial and consumer-based markets, including analytical instrumentation, printing and ink management, engine systems, biohazard detection equipment, electronic cooling and portable hydration systems.

• CHEMICAL HANDLING

CPC's extensive options for chemically resistant quick disconnect fittings, closures, couplings, and chemical dispensing systems provide non-spill operation and improve the safety of chemical management environments. Applications include semiconductor, LCD, solar, pharmaceutical manufacturing and chemical management, pump, filter and de-ionized water connections, cleaning, soap and detergent dispensing, bulk ink management and consumer-based applications.

Closed-loop dispensing systems enable fast, easy and economic chemical extraction from drums, IBCs and jerry cans. These systems increase workplace safety and protect workers and the environment from hazardous leaks and spills.



ENGINEERED SOLUTIONS WORLDWIDE

CPC innovates on the leading edge of what is possible and collaborates to develop the best solution for each customer. Many of CPC's standard couplings and fittings began as custom engineered solutions that found broader use in applicable markets. CPC delivers unmatched product design and quality with local engineering support in the United States, Europe and Asia. To date, CPC has produced over 10,500 custom and standard products to meet the fluid handling challenges of various industries worldwide.



INTRODUCTION



Global Distribution

Find your local distributor by visiting cpcworldwide.com/ContactUs or call CPC's Customer Service at 1-800-444-2474 or 651-645-0091.

Quality

Quality is a key component of CPC's success. We are ISO 9001:2008 and ISO 13485:2003 certified and our cleanroom is ISO Class 7 certified.

How to Choose the Right Connector

INTRODUCTION

With so many connection options, it can often be an overwhelming task to decide which connector is best suited for an application. By understanding your application requirements and selecting the correct connection type, you will have better performance and sealing results.

ASSESSING THE APPLICATION

Understanding your application is the key to selecting the proper connection. Use the following guide to simplify your selection.

FLOW

What is your required flow and pressure drop? Be sure to allow for the effect of shutoff valves and tubing connections on your calculations.

TUBING

What size tubing, both inner and outer diameter, are you using?

MEDIA

The viscosity and corrosiveness of the fluid going through the connection need to be considered. Make sure the media is chemically compatible with ALL coupling materials - including the seals, o-rings and springs. Double-check media compatibility.

TEMPERATURE

Know your minimum and maximum temperature range. Standard temperature ranges are from -40° to 200° F (-40° to 93° C) depending on connection material.

PRESSURE

What is the maximum pressure your connection will need to withstand during operation? Quick disconnects rated to 250 psi (17 bar) will handle most low pressure applications.

TUBING CONNECTIONS

Type: Hose barb, compression fittings and push-to-connect are the most common termination styles.

Size: You will need to know ID for hose barbs, OD for push-in-fittings and tube ID and OD for compression.

SHUTOFF OPTIONS

Do you need automatic or integral shutoff valves? Shutoff options are single, double and non-spill.

MOUNTING OPTIONS

How is the connection going to be configured into your application? Common mounting options include pipe thread, panel mount, in-line or elbow.

SPECIAL REQUIREMENTS

Sterilization, NSF listed, USP Class VI approved materials, special packaging, color coding, keying, lot traceability, etc.



Visit us online for interactive web tools

cpcworldwide.com



cpcworldwide.com/Bio



cpcworldwide.com/DrumQuik



cpcworldwide.com/FitQuik



cpcworldwide.com/BPcuffs



ALSO ON THE WEB

- Part Specifier
- Chemical Compatibility
- Ask Our Engineers
- CAD Models
- Watch Product Videos



**FIND A
DISTRIBUTOR**

cpcworldwide.com

Quick Disconnect Couplings
and Connectors.



MATERIAL OPTIONS

Material Options

The type of media flowing through a connection can affect the strength, surface appearance, color and performance of the connection. Here are some guidelines for the different types of material.

THERMOPLASTICS

ABS

Economical, medical-grade thermoplastic that withstands gamma and e-beam sterilization. It is commonly used in medical devices. ABS is an amorphous material with good physical properties and high resistance to chemical attack.

ACETAL

Strong, lightweight and economical material used for a wide variety of chemical and mechanical components. Acetal offers high strength and rigidity over a broad temperature range, low wear, toughness and resistance to repeated use.

POLYAMIDE

(NYLON)

Very resistant to wear and abrasion, good mechanical properties even at elevated temperatures, low permeability to gases and good chemical resistance.

PEEK

(POLYETHERETHERKETONE)

Highly temperature resistant, engineered thermoplastic with excellent chemical and fatigue resistance. It exhibits superior mechanical and electrical properties.

POLYCARBONATE

Resistant to some chemicals, withstands sterilization and is typically transparent. It is commonly used in medical devices and offers impact resistance, outstanding dimensional stability and good optical properties.

POLYETHYLENE

Low-cost, chemically resistant thermoplastic. It is opaque and can withstand reasonably high temperature.

POLYPROPYLENE

Excellent general purpose resin that is highly resistant to chemical attack from solvents and chemicals in harsh environments. In general, polypropylene is resistant to environmental stress cracking and it can be exposed to challenging environments.

POLYSULFONE

Rigid material with excellent strength, good chemical resistance; withstands repeated sterilization and higher temperatures than other thermoplastics. Its high hydrolytic stability allows its use in medical applications requiring repeated high temperature autoclave and steam sterilization.

PPS

(POLYPHENYLENE SULFIDE)

Broadest resistance to chemicals as an advanced engineering plastic.

FLUOROPOLYMERS

PTFE

Chemically resistant to all chemicals and solvents with the exception of some molten metals, molten sodium hydroxide, elemental fluorine and certain fluorinating agents. PTFE offers chemical resistance and stability at high temperature.

PVDF

Tough engineering thermoplastic with a balance of physical and chemical properties that qualifies it for high performance in a wide range of applications. It is mechanically strong and tough, has good ductility and has a broad, useful temperature range.

ALLOYS

ALUMINUM

Lightweight metal with an available hard anodized finish for durability. Aluminum is non-toxic, non-magnetic, non-sparking and is known for its high strength to weight ratio.

CHROME-PLATED BRASS

Rugged metallic material with an attractive appearance, chrome-plated brass is excellent for higher pressure and temperature.

DIE-CAST ZINC

Durable and lightweight (about 20% less than comparable brass) material that withstands high pressure and temperature.

STAINLESS STEEL

Offers excellent rust resistance and is often used for connector components such as valve springs.

O-RING SELECTION

Selecting the correct o-ring is directly related to your application. One o-ring can offer you better chemical resistance, another can offer better heat resistance, a third can offer cold flexibility. Here are some guidelines for the different types of o-rings.

BUNA-N

The most common o-ring material is Buna-N due to its solvent, oil and water resistance. It has a temperature range of -40° to 250° F (-40° to 121° C).

EPDM

Ethylene-propylene-diene rubber (EPDM, also sometimes referred to as EPR) is a chemically-resistant family of compounds. CPC uses high quality peroxide-cured EPDMs that provide exceptional resistance to temperatures when using a wide range of chemicals.

FFKM (CHEMRAZ®, SIMRIZ®, KALREZ®)

Broadest range of chemical resistance of any elastomeric material, combining the resilience and sealing force of an elastomer with chemical resistance approaching that of PTFE.

FKM

Well-known for its outstanding resistance to heat, oxidation, weathering and ozone. The temperature range is -15° to 400° F (-26° to 204° C).

PFA & FEP ENCAPSULATED SEALS

Encapsulated seals combine the resiliency of the elastomer with the superior chemical resistance of the fluoropolymer to achieve a seal that is lower cost than a pure fluoroelastomer FFKM seal.

SILICONE

Seals have good temperature resistance. The temperature range is -70°F to 400°F (-57°C to 204°C) with special compounds that can reach up to 450°F (232°C). Silicone can also be supplied with Class VI requirements for life sciences applications.

ELASTOMERS

TPE

Thermoplastic Elastomer (TPE) is a blend of additives and copolymers in a special formulation that forms extremely durable bonds to a substrate, while offering the traditional properties of soft-touch overmold.

TPV

Thermoplastic Vulcanizate (TPV) is an alloy of polypropylene thermoplastic and fully vulcanized EPDM rubber. TPV is typically resistant to water, acids and bases.

THE RIGHT NUMBER OF BARBS



Many things work together to determine the quality of the connection between a hose barb and the tubing it connects. The sharpness of the barb, surface finish and the barb angle all contribute to the overall quality of the connection. Failing to optimize these technical aspects will result in a poor connection, regardless of the number of hose barbs used.

CPC offers a variety of hose barb styles and connection options for tubing ranging from 1/16" to 1" ID.

CUSTOM CAPABILITIES

Connector solutions from CPC

add value to your product by making your fluid and air connections easy to use and more reliable, increasing your product's modularity and serviceability and providing an overall cleaner, faster, safer and smarter way to make a connection. If you can't find the perfect solution from one of our thousands of standard products or you'd like to simply off-load the connector portion of your project to allow you to focus on your core technologies, CPC Engineered Solutions can help.

HYBRID COUPLINGS

Connect both fluid and electronics – at the same time in a single connection.



RFID-ENABLED INTELLIGENT FLUID CONNECTIONS

Redefine what's possible for controlling, protecting and streamlining fluid handling processes. Identify misconnections, control usage and protect your brand.



METAL NON-SPILL COUPLINGS

Robust housing with high flow plastic valves.



CUSTOM MATERIALS

A wide range of materials are available to meet application needs.



Manifold



Packaged bottle cap
dip-tube assembly




Polycarbonate
elbow




Metal non-spill
without thumb latch



Cap with vent



Industrial
Design



MULTI-TUBE COUPLINGS

Connect multiple lines with one easy connection.



CUSTOM TUBE CONNECTIONS

Connect to a wide variety of types and sizes of tubing.



Custom designed products are exclusively produced for a specific customer. These proprietary products might not be for sale. Contact your local distributor for more information.

MOUNTING OPTIONS

Application-specific connections including threads, caps, snap-fits and more.




Consider a Custom-Designed Connector When:

- >> A quick disconnect will add value to your product, make it easier to use and more reliable
- >> Your specifications cannot be met by an existing standard CPC product
- >> Unique requirements, budgets or timing warrant your designer's collaboration with CPC's Engineered Solutions Team

2-way valve




Dual-line connector



Air/fluid/electronic tube set



RFID weight scale connector



RFID panel




In-line filter



TABLE OF CONTENTS

LEGEND



Note: Product images may not be to scale

General Purpose Couplings


PAGE | DESCRIPTION



18 SMC & SMF1: Twist-to-connect design provides reliable and secure alternative to luer-type connections.

Material: Acetal, polypropylene, ABS, chrome-plated brass

Tubing ID Sizes: 1/16" to 1/8" (1.6mm to 3.2mm)



22 SNAPQUIK®: Small break away connector for low pressure applications. Unique internal latching mechanism creates a smooth streamlined exterior that is easy to use and clean.

Material: Acetal

Tubing ID Sizes: 3/32" to 1/8" (2.4mm to 3.2mm)



24 NS1: Smallest plastic non-spill coupling features enable secure connection and drip-free disconnect.

Material: Glass-filled polypropylene, PEEK®, polypropylene


Tubing: Microbore to 1/8" (Microbore to 3.2mm)



26 PMC: Features one-hand connection and disconnection and integral terminations; easier to use than ball-and-sleeve designs.

Material: Acetal



Tubing ID Sizes: 1/16" to 1/4" (1.6mm to 6.4mm)



30 PMC12: Offered with a variety of configurations and chemical resistance for demanding applications; gamma sterilizable.

Material: Polypropylene



Tubing ID Sizes: Microbore to 1/4" (Microbore to 6.4mm)



34 MC: Durable and able to withstand higher pressure and temperature; easy one-hand connection and disconnection.

Material: Chrome-plated brass

Tubing ID Sizes: 1/8" to 1/4" (3.2mm to 6.4mm)



38 NS212: Twist-to-connect design features non-spill valves designed to provide fast, safe and virtually leak-free fluid line connections.

Material: Glass-filled polypropylene

Tubing ID Sizes: 1/8" to 1/4" (3.2mm to 6.4mm)



40 PLC: Widest selection of sizes and configurations offered; resistant to most mild chemical solutions.

Material: Acetal


Tubing ID Sizes: 1/4" to 3/8" (6.4mm to 9.5mm)



44 PLC12: Materials of construction offer broad chemical resistance for demanding applications; gamma sterilizable.

Material: Polypropylene

Tubing ID Sizes: 1/4" to 3/8" (6.4mm to 9.5mm)



General Purpose Couplings


PAGE | DESCRIPTION



48 LC: Durable and able to withstand higher pressure and temperature; easy one-hand connection and disconnection.

Material: Chrome-plated brass


Tubing ID Sizes: 1/4" to 3/8" (6.4mm to 9.5mm)



52 APC: Features plastic thumb latch, fewer moving parts and a smooth contoured design to deliver ease-of-use and excellent flow.

Material: Acetal


Tubing ID Sizes: 1/4" to 3/8" (6.4mm to 9.5mm)



56 BREAKAWAY®: Provides safe and easy fluid transfer with protection from costly product loss and equipment damage.

Material: Acetal


Tubing ID Sizes: 1/4" and 3/8" (6.4mm and 9.5mm)



58 EFC12: High-efficiency valve design provides high flow capability; bulkhead panel mount option facilitates tight seals against tank walls and drums.

Material: Polypropylene

Tubing ID Sizes: 1/4" and 3/8" (6.4mm and 9.5mm)



60 NS4: Non-spill coupling that virtually eliminates spills, minimizes downtime and enhances operator safety.

Material: Glass-filled polypropylene, ABS

Tubing ID Sizes: 1/8" to 3/8" (3.2mm to 9.5mm)



62 LQ4: Liquid cooling non-spill coupling guarantees a secure, reliable connection and dripless disconnect.

Material: Chrome-plated brass

Tubing ID Sizes: 1/4" to 3/8" (6.4mm to 9.5mm)



64 NS6: Durable, yet lightweight construction that features non-spill valves and is compatible with many chemicals.


Material: Glass-filled polypropylene

Tubing ID Sizes: 3/8" and 1/2" (9.5mm and 12.7mm)



TABLE OF CONTENTS

LEGEND



Note: Product images may not be to scale

General Purpose Couplings

PAGE | DESCRIPTION



- 66 LQ6:** Liquid cooling non-spill coupling guarantees a secure, reliable connection and dripless disconnect.
Material: Chrome-plated brass
Tubing ID Sizes: 3/8" to 1/2" ID (9.5mm to 12.7mm ID)



- 68 NSH:** Pressure-balanced non-spill design with 100% metal-free, spring-free flow path.
Material: Glass-filled polypropylene
Tubing ID Sizes: 3/8" to 3/4" (9.5mm to 19.0mm)



- 70 HFC12:** Efficient valve design leads to high flow and exceptionally low spillage; shrouded thumb latch is easy to grip and simple to operate.
Material: Polypropylene
Tubing ID Sizes: 3/8" to 3/4" (9.5mm to 19.0mm)



- 74 HFC35 & 57:** Withstand harsh environments and offered with or without UV-resistant materials to withstand harmful rays without affecting performance.
Material: Polysulfone (white), UV-resistant polysulfone (black)
Tubing ID Sizes: 3/8" to 3/4" (9.5mm to 19.0mm)



- 78 FFC35:** Features non-valved and unobstructed flow path to increase flow and minimize turbulence.
Material: Polysulfone
Tubing ID Sizes: 3/4" (19.0mm)

Specialty Products

PAGE | DESCRIPTION



- 80 TENTUBE™:** Allows connection and disconnection of up to ten lines with one slide latch; tubing orientation ensured by physical keying.
Material: Nylon, acetal, polypropylene
Tubing ID Sizes: 1/16" to 1/8" (1.6mm to 3.2mm)

Specialty Products (cont.)


PAGE | DESCRIPTION



82 SIXTUBE™: Snap-in panel mount design and flexibility to connect and disconnect six separate lines with or without valves.

Material: Acetal, polypropylene


Tubing ID Sizes: 1/16" to 1/8" (1.6mm to 3.2mm)



TWIN TUBE™: One easy-to-use quick disconnect for two separate non-valved flow paths.

Material: Acetal, ABS


Tubing ID Sizes: 1/16" to 1/8" (1.6mm to 3.2mm)



84 MULTI-MOUNT: Connects three to five lines at once; keyed to prevent mismatched connections.


Material: Acetal, chrome-plated brass

Tubing ID Sizes: 1/8" to 3/8" (3.2mm to 9.5mm)



86 BQ45GL: Quick disconnect coupling or fitting integrated into a cap designed for 45GL bottles.

Material: Polyethylene



88 HYBRID CONNECTOR: One integrated connector combining 2 fluid lines with non-spill couplings and 4 electrical lines to simplify the user interface.

Material: Glass-filled polypropylene



90 MINI HYBRID CONNECTOR: A compact, single connection point combining 1 fluid line with 2 electrical lines with a breakaway mechanism for ease of use.

Material: Glass-filled polypropylene



Intelligent Fluid Connections

PAGE | DESCRIPTION




92 INTELLIGENT FLUID CONNECTIONS: Redefine what's possible for controlling, protecting and streamlining fluid handling with RFID-enabled couplings.

Material: Acetal, polypropylene, glass-filled polypropylene



TABLE OF CONTENTS

LEGEND



Note: Product images may not be to scale

Life Sciences - Medical & Bioprocessing

PAGE | DESCRIPTION



- 102 SMC:** Twist-to-connect design manufactured and packaged in a cleanroom.
Material: Medical-grade polycarbonate
Tubing ID Sizes: 1/16" to 1/8" (1.6mm to 3.2mm)



- 104 SRC:** A unique small bore connector that eliminates the potential for misconnections with luer fittings.
Material: Medical-grade polypropylene
Tubing ID Sizes: 1/8" to 3/16" (3.2mm to 4.8mm)



- 106 MPC:** Easy-to-use and secure connection for critical fluid applications; includes pressure sealing caps and plugs with optional locking sleeves.
Material: Medical-grade ABS, medical-grade polycarbonate and polysulfone (USP Class VI, ADCF)
Tubing ID Sizes: 1/8" to 3/8" (3.2mm to 9.5mm)




- 109 BACK-TO-BACK ADAPTERS:** Allow end users to connect single-use systems that may feature identical connections at the end of their tubing.
Material: Medical-grade polycarbonate and polysulfone, USP Class VI, ADCF



- 110 MPX:** Larger flow, easy-to-use and secure connection for critical fluid applications; includes pressure sealing caps and plugs with optional locking sleeves.
Material: Medical-grade polycarbonate and polysulfone, USP Class VI, ADCF
Tubing ID Sizes: 3/8" to 1/2" (9.5mm to 12.7mm)



- 112 SANITARY SERIES:** Attaches directly to 3/4", 1" and 1-1/2" sanitary terminations to provide greater flexibility for integrating components into single-use or hybrid process systems.
Material: Medical-grade polysulfone, USP Class VI, ADCF
Termination Sizes: 3/4", 1" and 1-1/2" sanitary



- 114 SANIQUIK™:** Integral sanitary termination attaches to hard-plumbed systems with tri-clover clamps; permits quick and easy connection to single-use bag systems, manifolds or tube sets.
Material: 316L stainless steel
Termination Sizes: 3/4" and 1-1/2" sanitary



- 116 MPU:** Larger flow twist-to-connect design features easy-to-use locking mechanism that guards against accidental disconnects.
Material: Medical-grade polysulfone, USP Class VI, ADCF
Tubing ID Sizes: 3/4" (19.0mm)





118 HFC39: Features sterile disconnect functionality with automatic shutoff valve, preventing external organisms from entering the media flow path upon disconnection.

Material: Medical-grade polysulfone, USP Class VI, ADCF

Termination Sizes: 1/4", 3/8" and 1/2" HB (6.4mm, 9.5mm, 12.7mm)



120 ASEPTIQUIK® S: Genderless design provides quick and easy sterile connections for small-flow applications.

Material: Medical-grade polycarbonate, USP Class VI, ADCF

Termination Sizes: 1/8", 1/4" and 3/8" HB (3.2mm, 6.4mm and 9.5mm), 3/4" sanitary and MPC insert



122 ASEPTIQUIK® G: Robust genderless connectors provide quick and easy sterile connections and simplify systems integration.

Material: Medical-grade polycarbonate, USP Class VI, ADCF

Termination Sizes: 1/4", 3/8", 1/2", 3/4" ID hose barb (6.4mm, 9.5mm, 12.7mm, 19.0mm) and 3/4" sanitary



124 ASEPTIQUIK® C: Provides a quick and easy sterile connection, even in non-sterile environments.

Material: Medical-grade polycarbonate, USP Class VI, ADCF

Termination Sizes: 3/8" and 1/2" HB (9.5mm and 12.7mm) and 3/4" sanitary



126 ASEPTIQUIK® DC: All-in-one, single-use connection technology offering both a sterile connect and a sterile disconnect.

Material: Medical-grade polycarbonate, USP Class VI, ADCF

Termination Sizes: 1/4", 3/8" and 1/2" HB (6.4mm, 9.5mm, 12.7mm)



128 ASEPTIQUIK® X: Robust large format design enables quick sterile transfer for high flow single-use applications.

Material: Medical-grade polycarbonate, USP Class VI, ADCF

Termination Sizes: 3/4" and 1" ID hose barb (19.0mm and 25.4mm) and 1-1/2" sanitary



130 STEAM-THRU® CONNECTIONS: Allow quick and easy sterile connection via SIP between biopharmaceutical processing equipment and disposable bag and tube assemblies.

Material: Medical-grade polysulfone, USP Class VI, ADCF

Termination Sizes: 3/8" and 1/2" HB (9.5mm and 12.7mm) and 3/4" sanitary




132 ASEPTIQUIK® STC: Allows a gendered or genderless AseptiQuik sterile connection to be steamed on to stainless equipment via SIP.

Material: Medical-grade polycarbonate and polysulfone, USP Class VI, ADCF



TABLE OF CONTENTS

LEGEND



Note: Product images may not be to scale

High Purity Couplings

PAGE | DESCRIPTION

138 CHEMQUIK® CQH06/CQV06: All plastic design for ultra-pure media and high chemical resistance.

Material: Natural, virgin polypropylene and PVDF

Tubing Sizes: 1/4" to 1/2" flare; 3/8" to 3/4" NPT



Pictured: CQV06



140 CHEMQUIK CQG06: Spring-free and metal-free flow path for high flow capacity and non-spill, high purity connections.

Material: Natural, virgin polypropylene

Tubing Sizes: 3/8" to 3/4" flare; 3/8" to 3/4" NPT



141 CHEMQUIK DUAL CONTAINMENT SYSTEM: Flare nuts and panel mount fittings that facilitate double containment of critical chemical lines.

Material: Natural, virgin polypropylene



Dispensing Connectors

PAGE | DESCRIPTION


142 DRUMQUIK® PRO & DRUMQUIK PUR: Closed chemical dispensing system with a reusable coupler and a recyclable dip-tube assembly for chemical extraction from drums, jerry cans and IBCs.

Material: Food grade, virgin polypropylene and polyethylene

Thread Sizes:

Drum Inserts: 2" American buttress, BCS 56x4 and 2" NPS (G8), 70mm for BCS 70x5 and BCS70x6

Couplers: 1/2" NPT, 3/4" hose barb and 3/4" BSPP



145 DRUMQUIK ADAPTORS AND ACCESSORIES: CPC offers many accessories intended for use with DrumQuik® PRO and DrumQuik PUR systems. These include vent check valves, foot valves, fittings and more.

Dispensing Connectors (cont.)

PAGE | DESCRIPTION



148 DRUMQUIK® 3-PORT UDA: Used with 3/4" male NPT coupling terminations to adapt dip-tubes to standard drum closures for closed system dispensing.

Material: Food grade, virgin polypropylene

Thread Sizes: UDA 3-Port: 3/4" male NPT; UDA: none

BOTTLE ADAPTOR KITS: Intended for use on reagent bottles with SP400-38mm threads.

Material: Natural, virgin polypropylene

Thread Sizes: SP400-38mm

DRUMQUIK ASIAN DRUM ADAPTORS, PLUGS AND CAPS



150 UDC: Provides closed connection to bag-in-box packaging with 38mm threaded and snap-in necks.

Material: Polypropylene and acetal


Tubing ID Sizes: 3/8" to 3/4" (9.5mm to 19.0mm)



152 PUNCTURE SEAL: Provides closed connection to Hedwin Cubitainer® bag-in-box container systems and flexible bags or bottles with SP400 38mm threads.

Material: Polypropylene (coupling) and polyethylene (cap)

Tubing ID Sizes: 1/4" and 3/8" (6.4mm and 9.5mm)



Fittings, Luers, and Blood Pressure Connectors

PAGE | DESCRIPTION



156 FITQUIK® CONNECTORS: High-quality fittings for leak-free tubing connections. These precision-molded fittings are designed to eliminate tubing leak points in applications such as medical devices, analytical instrumentation or air-driven equipment.

Additional Products and Information

PAGE | DESCRIPTION



162 ACCESSORIES: Offering includes a variety of ancillary components from fittings and luers to PTF nuts and dust caps.

163 STERILIZATION AND DISINFECTANT METHODS

164 REGULATORY AND COMPLIANCE

SMC SERIES CONNECTOR





The SMC and SMF1 are among CPC's smallest couplings. These twist-to-connect couplings provide a reliable and more secure alternative to luer-type connections. They also allow for the tubing to rotate freely when connected. This important feature prevents both kinked tubing and accidental disconnection during use. The SMC Series is also available with optional RFID (Radio Frequency Identification) capability (page 98) and in polycarbonate material (page 102).

FEATURES

- Twist to connect
- Free coupling rotation
- Quarter turn latch clicks when connected

BENEFITS

- Prevents accidental disconnects
- Eliminates kinked tubing
- Prevents damage due to over torquing



Specifications

PRESSURE:

Vacuum to 100 psi, 6.9 bar

TEMPERATURE:

Acetal, Chrome-Plated Brass:
-40°F to 180°F (-40°C to 82°C)

Polypropylene:
32°F to 180°F (0°C to 82°C)

ABS:
-40°F to 160°F (-40°C to 71°C)

MATERIALS:

Main Components: ABS, acetal, polypropylene, chrome-plated brass, stainless steel

Locking sleeves: Acetal

Valves: Acetal

Valve spring: 316 stainless steel

O-rings: Buna-N with acetal or chrome-plated brass, EPDM with polypropylene

COLOR:

Main components: Natural white (acetal and ABS), almond (polypropylene), chrome and black

TUBING SIZES:


1/16" to 1/8" ID, 1.6mm to 3.2mm and 5.0mm

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions.

Polycarbonate
SMC products
manufactured in
CPC's cleanroom also
available. See page
102.



These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.



Liquid Flow Rate Information for Couplings

The chart below shows the flow rate for CPC couplings. Each coupling was tested with water at 70°F (21°C). To determine flow rates for specific coupling configurations use the formula below.

C_v VALUES FOR SUBMINIATURE COUPLINGS


BODIES	INSERTS	SMM01	SMM02
	SMF01	.03	.03
	SMFD01	.03	.03
	SMF02	.03	.19
	SMFD02	.03	.08
	SMPT02	.03	.19
	SMFD02	.03	.08

$$Q=C_v\sqrt{\frac{\Delta P}{S}}$$

- Q = Flow rate in gallons per minute
- C_v = Average coefficient across various flow rates (see chart)
- ΔP = Pressure drop across coupling (psi)
- S = Specific gravity of liquid

NOTES:

SMC DIMENSIONS



A = Height/Diameter **B** = Total Length **C** = Hex Size on Main Component

Panel Dimensions

	PANEL OPENING	PANEL THICKNESS MAX. – MIN.	PANEL NUT HEX	PANEL NUT THREAD
COUPLING BODIES	7/16	.21 – .03	1/2	7/16-24UNF
COUPLING INSERTS	7/16	.21 – .03	1/2	7/16-24UNF

Coupling Bodies • ACETAL



TERMINATION IN-LINE PIPE THREAD

IN-LINE HOSE BARB

PANEL MOUNT HOSE BARB

IN-LINE HOSE BARB



TUBING/THREAD SIZE METRIC EQ.

1/8" NPT
1/8" NPT

1/16" ID 1.6mm ID
1/16" ID 1.6mm ID
3.0mm ID
3.0mm ID
1/8" ID 3.2mm ID
1/8" ID 3.2mm ID

1/16" ID 1.6mm ID
1/16" ID 1.6mm ID
3.0mm ID
3.0mm ID
1/8" ID 3.2mm ID
1/8" ID 3.2mm ID

1/16" ID 1.6mm ID
1/8" ID 3.2mm ID

STRAIGHT THRU

SMPT02
SMPT02BLK

SMF01
SMF01MBLK
SMFM3
SMFM3MBLK
SMF02
SMF02MBLK

SMFPM01
SMFPM01BLK
SMFPM03
SMFPM03BLK
SMFPM02
SMFPM02BLK

iSMFT0103
iSMFT0203

SHUTOFF

SMPTD02
SMPTD02BLK

SMFD01
SMFD01MBLK
SMFDM3
SMFDM3MBLK
SMFD02
SMFD02MBLK

SMFPM01
SMFPM01BLK
SMFPM03
SMFPM03BLK
SMFPM02
SMFPM02BLK

iSMFDT0103
iSMFDT0203

A

B

C

.51
.51
.48
.48
.48
.48
.48
.48
.58
.58
.58
.58
.58
.58
.76
.76
.75/.90
.75/.90
1.00
1.00
.90
.90
.75/.90
.75/.90
1.00
1.00
1.00
1.00
.91/.91
.91/.91

• POLYPROPYLENE



TERMINATION IN-LINE PIPE THREAD

IN-LINE HOSE BARB

(Acetal Locking Sleeve)

PANEL MOUNT HOSE BARB

(Acetal Locking sleeve)

IN-LINE HOSE BARB



TUBING/THREAD SIZE METRIC EQ.

1/8" NPT

1/16" ID 1.6mm ID
1/8" ID 3.2mm ID

1/16" ID 1.6mm ID
1/8" ID 3.2mm ID

1/16" ID 1.6mm ID
1/8" ID 3.2mm ID

STRAIGHT THRU

SMPT0212

SMF0112
SMF0212

SMFPM0112
SMFPM0212

iSMFT0100
iSMFT0200

A

B

C

.51
.86
7/16
.48
.75/.90
.48
.90
.58
.75/.90
.58
.90
1/2
1/2
.76
.76
.76
.91

SMF1 Disposable Bodies • ABS



TERMINATION IN-LINE HOSE BARB

TUBING/THREAD SIZE METRIC EQ.

1/8" ID 3.2mm ID
1/8" ID 3.2mm ID

5mm ID 5mm ID
5mm ID 5mm ID

STRAIGHT THRU

SMF10297
SMF10297MBLK
SMF1M597
SMF1M597MBLK

A

B

.38
.42
.42
.42
.82
.82
.69
.69

CPC has added a proprietary lubrication step to our SMF1 manufacturing process. This revolutionary technique allows the lube to be placed only where you need it, ensuring consistent connection forces throughout the lifetime of the connectors even when aggressive cleaning techniques are used.

Coupling Inserts

• ACETAL

	TERMINATION IN-LINE HOSE BARB	TUBING/ THREAD SIZE	METRIC EQ.	STRAIGHT THRU	A	B
		1/16" ID	1.6mm ID	SMM01	.48	.75
		1/16" ID	1.6mm ID	SMM01MBLK	.48	.75
			3.0mm ID	SMMM3	.48	.80
			3.0mm ID	SMMM3MBLK	.48	.80
		1/8" ID	3.2mm ID	SMM02	.48	.90
		1/8" ID	3.2mm ID	SMM02MBLK	.48	.90
			4.0mm ID	SMMM4	.48	1.02
			5.0mm ID	SMMM5	.48	1.00
	PANEL MOUNT HOSE BARB	1/16" ID	1.6mm ID	SMMPM01	.50	.75
		1/16" ID	1.6mm ID	SMMPM01BLK	.50	.75
			3.0mm ID	SMMPM03	.50	.80
			3.0mm ID	SMMPM03BLK	.50	.80
		1/8" ID	3.2mm ID	SMMPM02	.50	.90
		1/8" ID	3.2mm ID	SMMPM02BLK	.50	.90
	IN-LINE HOSE BARB (Acetal Locking Sleeve)	1/16" ID	1.6mm ID	iSMMT0100	.76	.76
		1/8" ID	3.2mm ID	iSMMT0200	.76	.91

• CHROME-PLATED BRASS

	TERMINATION IN-LINE HOSE BARB	TUBING/ THREAD SIZE	METRIC EQ.	STRAIGHT THRU	A	B
		1/8" ID	3.2mm ID	SMM02CBMBLK	.48	.90
	PANEL MOUNT HOSE BARB	1/8" ID	3.2mm ID	SMMPM02CBBLK	.50	.90

• POLYPROPYLENE

	TERMINATION IN-LINE HOSE BARB (Acetal Locking Sleeve)	TUBING/ THREAD SIZE	METRIC EQ.	STRAIGHT THRU	A	B
		1/16" ID	1.6mm ID	SMM0112	.48	.75
		1/8" ID	3.2mm ID	SMM0212	.48	.90
	PANEL MOUNT HOSE BARB (Acetal Locking Sleeve)	1/16" ID	1.6mm ID	SMMPM0112	.50	.75
		1/8" ID	3.2mm ID	SMMPM0212	.50	.90
	IN-LINE HOSE BARB (Acetal Locking Sleeve)	1/16" ID	1.6mm ID	iSMMT0103	.76	.76
		1/8" ID	3.2mm ID	iSMMT0203	.76	.91

SMC Complete In-Line Couplings

• ACETAL

	TERMINATION IN-LINE HOSE BARB	TUBING/ THREAD SIZE	METRIC EQ.	STRAIGHT THRU	SHUTOFF	B
		1/16" ID	1.6mm ID	SMC01	SMCD01	1.32/1.46
		1/16" ID	1.6mm ID	SMC01MBLK	SMCD01MBLK	1.32/1.46
			3.0mm ID	SMCM3	SMCDM3	1.62
			3.0mm ID	SMCM3MBLK	SMCDM3MBLK	1.62
		1/8" ID	3.2mm ID	SMC02	SMCD02	1.61
		1/8" ID	3.2mm ID	SMC02MBLK	SMCD02MBLK	1.61

• POLYPROPYLENE

	TERMINATION IN-LINE HOSE BARB	TUBING/ THREAD SIZE	METRIC EQ.	STRAIGHT THRU	B
		1/16" ID	1.6mm ID	SMC0112	1.32
		1/8" ID	3.2mm ID	SMC0212	1.61

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. MBLK = molded black material. BLK = dyed black material.

SNAPQUIK SERIES CONNECTOR

Specifications ● ● ●

PRESSURE:

Vacuum to 15 psi, 1.0 bar

TEMPERATURE:

32°F to 122°F (0°C to 50°C)

MATERIALS:

Main components: Acetal

O-ring: Buna-N

COLOR:

Natural White

TUBING SIZES:

3/32" and 1/8" ID

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions.

SnapQuik® Series Connectors are ideal for small bore applications. The compact design delivers high flow fluid transfer in a small profile. Featuring a unique internal latching mechanism that creates a smooth, streamlined exterior that is easy to clean and use. The user-friendly break away design of SnapQuik prevents misconnections with luers, protects equipment and ensures patient safety.

FEATURES

Break away latch

Internal latch design

Audible click at connection

Does not mate to luer fittings

BENEFITS



Intuitive, rapid disconnection

Streamlined exterior is easy to clean

Assures reliable connection is made


Improved patient safety

SnapQuik's revolutionary lubrication technique ensures consistent connection forces throughout the lifetime of the connectors, even when aggressive cleaning techniques are used.



These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of the graph represents the operating range of the product family, i.e. upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.

SNAPQUIK DIMENSIONS



A = Height/Diameter
B = Total Length

Coupling Bodies • ACETAL



**TERMINATION
IN-LINE
HOSE BARB**

TUBING SIZE
 3/32" ID
 1/8" ID

METRIC EQ.
 2.4mm
 3.2mm

STRAIGHT THRU
 BSQ17015
 BSQ1702

A
 0.36
 0.36

B
 1.09
 1.09

Coupling Inserts • ACETAL



**TERMINATION
IN-LINE
HOSE BARB**

TUBING SIZE
 3/32" ID
 1/8" ID

METRIC EQ.
 2.4mm
 3.2mm

STRAIGHT THRU
 BSQ22015
 BSQ2202

A
 0.42
 0.42

B
 1.14
 1.14


All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.

DID YOU KNOW?

AN ALTERNATIVE TO LUERS

An alternative to luers, SnapQuik® will not mate with luers designed to the ISO 594 standards

NS1 SERIES CONNECTOR



Specifications ● ● ●

PRESSURE:

Vacuum to 15 psi, 1.0 bar

TEMPERATURE:

32°F to 120°F (0°C to 49°C)

MATERIALS:

Main Components:

Glass-filled polypropylene, PEEK®, polypropylene

Thumb latch: PEEK®

Springs: 316 stainless steel

O-rings: EPDM

COLOR: Gray

TUBING SIZES:

Microbore to 1/8" ID (Microbore to 3.2mm)

SPILLAGE:

0.02 cc per disconnect rated @ 15 psi

INCLUSION: 0.01 cc per connect

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions.

NS1 Series couplings compact design is packed full of features including non-spill shutoff valves that ensure drip-free disconnects, and eliminate the need to purge air from the system. The smallest plastic non-spill coupling on the market, NS1 is perfect for applications with tubing from 1/8-inch and smaller. Its rotating design allows tubing to move freely without kinks. Ideal for applications that need to be connected and disconnected often, the ergonomic, user-friendly interface enables a secure, reliable connect and disconnect.

FEATURES

Non-spill design

Ultra low air inclusion

Intuitive interface

Rotating design

Chemically resistant materials

BENEFITS

Closed system for drip-free disconnect


Minimizes contaminants, eliminates the need to purge air bubbles from the system

User friendly ergonomic design enables a secure, reliable connection


Allows tubing to move freely or relax without kinking or leaking

Reliable strength and performance in a range of applications

⚠ This graphs is intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.




NS1 SERIES DIMENSIONS



Panel Dimensions

	PANEL OPENING	PANEL THICKNESS MAX. – MIN.	PANEL NUT HEX	PANEL NUT THREAD
COUPLING INSERTS	see drawing	.29 – .05	5/8	1/2-24UNS



Coupling Bodies • POLYPROPYLENE



DESCRIPTION	TUBING SIZE	METRIC EQ.	SHUTOFF	A	B
IN-LINE HOSE BARB	1/8" ID	3.2 MM ID	NS1D170212	0.61	1.33
IN-LINE WITH A 1/4-28 FLAT BOTTOM PORT	1/8" OD OR SMALLER*	3.2 MM OD OR SMALLER*	NS1D19042812	0.61	1.21
IN-LINE WITH A 1/4-28 MALE THREAD			NS1D10042812	0.61	1.28

Coupling Inserts • POLYPROPYLENE



DESCRIPTION	TUBING SIZE	METRIC EQ.	SHUTOFF	A	B
IN-LINE HOSE BARB	1/8" ID	3.2 MM ID	NS1D220212	0.44	1.04
IN-LINE WITH A 1/4-28 FLAT BOTTOM PORT	1/8" OD OR SMALLER*	3.2 MM OD OR SMALLER*	NS1D26042812	0.44	0.92
IN-LINE WITH A 1/4-28 MALE THREAD			NS1D24042812	0.49	0.99
PANEL MOUNT HOSE BARB	1/8" ID	3.2 MM ID	NS1D420212	0.70	1.56
PANEL MOUNT WITH A 1/4-28 FLAT BOTTOM PORT	1/8" OD OR SMALLER*	3.2 MM OD OR SMALLER*	NS1D48042812	0.70	1.45

*Tubing size dependent on nut and ferrule used with 1/4-28 port.

Accessories



DESCRIPTION
BULKHEAD O-RING: For sealing panel mount inserts listed above

MATERIAL
EPDM

PART NO.
731303

Ferrules



FOR 1/4-28 NUTS AND FERRULES, SEE PAGE 33 OR VISIT CPCWORLDWIDE.COM

PMC SERIES CONNECTOR



The 1/8" flow PMC coupling covers a wide variety of general-purpose applications. Featuring the CPC thumb latch, the PMC is easier to use than ball-and-sleeve designs. One-hand connection/disconnection and integral terminations make the PMC the choice for ease of use and manufacture.



This coupling is NuSeal® compatible (see page 27 for details).

FEATURES

- Hose barb shroud
- Integral terminations
- Compatible
- Clicks when connected

BENEFITS

- Extra protection for the 1/16" hose barb
- Fewer leak points, shorter assemblies, faster installations
- Mates with PMC12 and MC Series couplings (see pages 30 and 34)
- Assurance of a reliable connection



Specifications

PRESSURE:

Vacuum to 120 psi, 8.3 bar

TEMPERATURE:

-40°F to 180°F (-40°C to 82°C)

MATERIALS:

Main components and valves: Acetal

Thumb latch: Stainless steel

Valve spring: 316 stainless steel

External springs and pin: Stainless steel

O-rings: Buna-N

COLOR:

Natural white, others available

TUBING SIZES:


1/16" to 1/4" ID, 1.6mm to 6.4mm ID

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC products in their own application conditions.

Also available
in NSF listed
versions. Please visit
our website for part
number information.



These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.



NU-SEAL® QUICK DISCONNECT COUPLING

Nu-Seal® Specifications

PRESSURE:

Vacuum to 20 psi, 1.4 bar

MATERIALS:

Main components:

Low density polyethylene

COLOR:

Translucent

TUBING SIZE:

1/8" ID, 3.2mm ID

Nu-Seal® quick disconnect coupling inserts feature a patented integral seal and are USP Class VI compliant. These economic inserts are ideal for applications that require limited connect/disconnect cycles.

FEATURES

Patented integral seal

Low density polyethylene

Chemically resistant

Compatible

BENEFITS

Economical, allows for disposability and provides leak-free connections

Sterilizable by EtO, E-beam & gamma

Works in many critical USP Class VI material applications

Mates with MC, PMC, PMC12 couplings



TERMINATION
IN-LINE
HOSE BARB

TUBING SIZE
1/8" ID

METRIC EQ.
3.2 mm ID

PART NO.
DSM2202

HEIGHT
.50

LENGTH
.98

Liquid Flow Rate Information for Couplings

The chart below shows the flow rate for CPC couplings. Each coupling was tested with water at 70°F (21°C). To determine flow rates for specific coupling configurations use the formula at the right.

$$Q = C_v \sqrt{\frac{\Delta P}{S}}$$

Q = Flow rate in gallons per minute

C_v = Average coefficient across various flow rates (see chart)


ΔP = Pressure drop across coupling (psi)

S = Specific gravity of liquid

C_v VALUES FOR 1/8" FLOW PMC COUPLINGS

INSERTS BODIES	PMC 2004	PMCD 2004	PMC 2006	PMCD 2006	PMC 2202	PMCD 2202	PMC 2204	PMCD 2204	PMC 2402	PMCD 2402	PMC 2404	PMCD 2304	PMC 2602	PMCD 2304	PMC 2104	PMCD 2304	PMC 2203	PMCD 2203	PMC 2201	PMCD 2201
PMC1002	.40	.18	.50	.19	.25	.16	.50	.19	.50	.20	.51	.19	.50	.50	.38	.24	.30	.17	.03	.03
PMCD1002	.27	.18	.31	.18	.24	.16	.28	.20	.26	.20	.29	.18	.26	.26	.27	.24	.25	.17	.03	.03
PMC1004	.40	.21	.50	.24	.26	.18	.50	.24	.50	.20	.51	.24	.50	.50	.38	.26	.30	.19	.03	.03
PMCD1004	.29	.19	.32	.23	.25	.17	.30	.23	.27	.21	.28	.23	.27	.28	.29	.24	.25	.18	.03	.03
PMC1204	.40	.18	.50	.18	.25	.16	.40	.18	.40	.16	.36	.18	.40	.40	.38	.21	.30	.17	.03	.03
PMCD1204	.21	.17	.22	.17	.20	.16	.22	.17	.21	.17	.20	.17	.21	.22	.21	.18	.21	.16	.03	.03
PMC1602	.23	.15	.28	.18	.19	.14	.27	.15	.27	.15	.28	.18	.27	.27	.23	.16	.20	.14	.03	.03
PMCD1602	.19	.15	.19	.15	.17	.14	.19	.15	.18	.15	.18	.15	.18	.19	.19	.15	.18	.14	.03	.03
PMC1604	.33	.23	.44	.24	.24	.18	.44	.23	.44	.20	.38	.24	.38	.44	.33	.26	.26	.19	.03	.03
PMCD1604	.23	.17	.26	.21	.22	.16	.26	.21	.26	.19	.25	.21	.21	.26	.23	.24	.22	.16	.03	.03
PMC1703	.25	.20	.30	.20	.20	.17	.30	.20	.30	.19	.28	.20	.28	.30	.25	.18	.21	.17	.03	.03
PMCD1703	.20	.17	.20	.17	.19	.15	.21	.17	.19	.17	.20	.17	.19	.20	.20	.16	.19	.16	.03	.03
PMC1701	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.02
PMCD1701	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.02	.02


PMC DIMENSIONS



- A = Height/Diameter
- B = Total Length
- D = Elbow Radial Length

Panel Dimensions

	PANEL OPENING	PANEL THICKNESS MAX. – MIN.	PANEL NUT HEX	PANEL NUT THREAD
COUPLING BODIES	see drawing	.50 – .05	5/8	1/2-24UNS
COUPLING INSERTS	1/2	.30 – .05	5/8	1/2-24UNS



Greenlee® punch
number 60077

Coupling Bodies • ACETAL

	TERMINATION IN-LINE PIPE THREAD	TUBING/THREAD SIZE	METRIC EQ.	STRAIGHT THRU	SHUTOFF	A	B
		1/8" NPT		PMC1002	PMCD1002	.79	1.00
		1/8" BSPT		PMC1002BSPT	PMCD1002BSPT	.79	1.00
		1/4" NPT		PMC1004	PMCD1004	.79	1.10
		1/4" BSPT		PMC1004BSPT	PMCD1004BSPT	.79	1.10
		5/32" OD, .10" ID	4.0mm OD, 2.0mm ID	PMC12M42	PMCD12M42	.77	1.65
		1/4" OD, .17" ID	4.0mm OD, 2.5mm ID	PMC12025	PMCD12025	.77	1.70
			6.4mm OD, 4.3mm ID	PMC1204	PMCD1204	.77	1.72
		1/16" ID	1.6mm ID	PMC1601	PMCD1601	.77	1.40
		1/8" ID	3.2mm ID	PMC1602	PMCD1602	.77	1.65
		3/16" ID	4.8mm ID	PMC1603	PMCD1603	.77	1.85
		1/4" ID	6.4mm ID	PMC1604	PMCD1604	.77	1.85
		10-32 UNF		PMC181032	PMCD181032	.77	1.25
		5/32" OD, .10" ID	4.0mm OD, 2.0mm ID	PMC13M42	PMCD13M42	.81	1.65
			4.0mm OD, 2.5mm ID	PMC13025	PMCD13025	.81	1.65
			5.0mm OD, 3.0mm ID	PMC13M5	PMCD13M5	.81	1.72
		1/4" OD, .17" ID	6.4mm OD, 4.3mm ID	PMC1304	PMCD1304	.81	1.75
		1/16" ID	1.6mm ID	PMC1701	PMCD1701	.81	1.41
		1/8" ID	3.2mm ID	PMC1702	PMCD1702	.81	1.45/1.65
		3/16" ID	4.8mm ID	PMC1703	PMCD1703	.81	1.65/1.85
		1/4" ID	6.4mm ID	PMC1704	PMCD1704	.81	1.65/1.85
		10-32 UNF		PMC191032	PMCD191032	.81	1.25

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.
 †NOTE: CPC's Ferruleless PTF (polytube fitting) terminations do not require ferrules to achieve a secure connection and are therefore easier to use and reuse. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc.

Coupling Inserts • ACETAL

	TERMINATION	TUBING/THREAD SIZE	METRIC EQ.	STRAIGHT THRU	SHUTOFF	A	B	D
	IN-LINE PIPE THREAD	1/8" NPT		PMC2402	PMCD2402	.58	1.03/1.45	
		1/8" BSPT		PMC2402BSPT	PMCD2402BSPT	.58	1.03/1.44	
		1/4" NPT		PMC2404	PMCD2404	.65	1.13/1.42	
		1/4" BSPT		PMC2404BSPT	PMCD2404BSPT	.65	1.13/1.42	
	PANEL MOUNT FERRULELESS POLYTUBE FITTING, PTF† (non-valved shown)	1/4" OD, .17" ID	6.4mm OD, 4.3mm ID	PMC4004	PMCD4004	.72	1.70/1.82	
	PANEL MOUNT HOSE BARB	1/16" ID	1.6mm ID	PMC4201	PMCD4201	.72	1.38/1.50	
		1/8" ID	3.2mm ID	PMC4202	PMCD4202	.72	1.63/1.75	
		3/16" ID	4.8mm ID	PMC4203	PMCD4203	.72	1.83/1.95	
		1/4" ID	6.4mm ID	PMC4204	PMCD4204	.72	1.83/1.95	
	IN-LINE FERRULELESS POLYTUBE FITTING, PTF†	5/32" OD, .10" ID	4.0mm OD, 2.0mm ID	PMC20M42	PMCD20M42	.58	1.08/1.60	
		1/4" OD, .17" ID	4.0mm OD, 2.5mm ID	PMC20025	PMCD20025	.58	1.13/1.65	
		1/4" OD, .17" ID	6.4mm OD, 4.3mm ID	PMC2004	PMCD2004	.58	1.15/1.57	
		3/8" OD, .25" ID	6.4mm OD, 4.3mm ID	PMC2006	PMCD2006	.65	1.40/1.52	
	IN-LINE HOSE BARB (non-valved shown)	1/16" ID	1.6mm ID	PMC2201	PMCD2201	.50	.80/1.47	
		1/8" ID	3.2mm ID	PMC2202	PMCD2202	.50	1.00/1.67	
		3/16" ID	4.8mm ID	PMC2203	PMCD2203	.50	1.20/1.88	
		1/4" ID	6.4mm ID	PMC2204	PMCD2204	.50	1.22/1.70	
	IN-LINE FEMALE THREAD	10-32 UNF		PMC281032	PMCD281032	.58	.63/1.31	
	ELBOW FERRULELESS POLYTUBE FITTING, PTF†	5/32" OD, .10" ID	4.0mm OD, 2.5mm ID	PMC21025		.50	1.17	.75
		1/4" OD, .17" ID	6.4mm OD, 4.3mm ID	PMC2104	PMCD2104	.50	1.17/1.21	.77
	ELBOW HOSE BARB (non-valved shown)	1/8" ID	3.2mm ID	PMC2302	PMCD2302	.50	.85/1.21	.75/.69
		1/4" ID	6.4mm ID	PMC2304	PMCD2304	.50	1.00/1.21	.95/.90

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. Couplings are pictured with valves unless otherwise noted. †NOTE: CPC's Ferruleless PTF (polytube fitting) terminations do not require ferrules to achieve a secure connection and are therefore easier to use and reuse. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc.

PMC12 SERIES CONNECTOR



The 1/8" flow polypropylene PMC12 offers many of the same configuration options as the PMC. The polypropylene material adds greater chemical resistance and is gamma sterilizable. The PMC12 also mates to small diameter rigid tubing. Available with a 1/4-28 flat bottom port and 1/4-28 UNF threads, these couplings eliminate the need to thread and re-thread common compression nuts each time a tubing connection is made.

FEATURES

Polypropylene material

EPDM o-ring

CPC thumb latch

Integral terminations

BENEFITS

Chemically resistant and gamma-sterilizable

Greater chemical resistance

One-hand connection and disconnection

Fewer leak points, shorter assemblies, faster installations

Specifications

PRESSURE:

Vacuum to 120 psi, 8.3 bar

TEMPERATURE:

32°F to 160°F (0°C to 71°C)

MATERIALS:

Main components and valves: Polypropylene

Thumb latch: Stainless steel

Valve spring: 316 stainless steel

External spring and pin: Stainless steel

O-rings: EPDM

STERILIZATION:

Gamma: Up to 50 kGy irradiation




COLOR:

Almond

TUBING SIZES:

Microbore to 1/4" ID, Microbore to 6.4mm ID

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC products in their own application conditions. Use the graph to the right as a guide.



These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.

NOTES:

Liquid Flow Rate Information for Couplings

The chart below shows the flow rate for CPC couplings. Each coupling was tested with water at 70°F (21°C). To determine flow rates for specific coupling configurations use the formula at the right.


$$Q = C_v \sqrt{\frac{\Delta P}{S}}$$

Q = Flow rate in gallons per minute
C_v = Average coefficient across various flow rates (see chart)
ΔP = Pressure drop across coupling (psi)
S = Specific gravity of liquid

C_v VALUES FOR 1/8" FLOW PMC12 COUPLINGS

INSERTS BODIES	PMC12 2004	PMCD12 2004	PMC12 2006	PMCD12 2006	PMC12 2202	PMCD12 2202	PMC12 2204	PMCD12 2204	PMC12 2402	PMCD12 2402	PMC12 2404	PMCD12 2304	PMC12 2602	PMCD12 2304	PMC12 2104	PMCD12 2304	PMC12 2203	PMCD12 2203	PMC12 2201	PMCD12 2201
PMC100212	.40	.18	.50	.19	.25	.16	.50	.19	.50	.20	.51	.19	.50	.50	.38	.24	.30	.17	.03	.03
PMCD100212	.27	.18	.31	.18	.24	.16	.28	.20	.26	.20	.29	.18	.26	.26	.27	.24	.25	.17	.03	.03
PMC100412	.40	.21	.50	.24	.26	.18	.50	.24	.50	.20	.51	.24	.50	.50	.38	.26	.30	.19	.03	.03
PMCD100412	.29	.19	.32	.23	.25	.17	.30	.23	.27	.21	.28	.23	.27	.28	.29	.24	.25	.18	.03	.03
PMC120412	.40	.18	.50	.18	.25	.16	.40	.18	.40	.16	.36	.18	.40	.40	.38	.21	.30	.17	.03	.03
PMCD120412	.21	.17	.22	.17	.20	.16	.22	.17	.21	.17	.20	.17	.21	.22	.21	.18	.21	.16	.03	.03
PMC160212	.23	.15	.28	.18	.19	.14	.27	.15	.27	.15	.28	.18	.27	.27	.23	.16	.20	.14	.03	.03
PMCD160212	.19	.15	.19	.15	.17	.14	.19	.15	.18	.15	.18	.15	.18	.19	.19	.15	.18	.14	.03	.03
PMC160412	.33	.23	.44	.24	.24	.18	.44	.23	.44	.20	.38	.24	.38	.44	.33	.26	.26	.19	.03	.03
PMCD160412	.23	.17	.26	.21	.22	.16	.26	.21	.26	.19	.25	.21	.21	.26	.23	.24	.22	.16	.03	.03
PMC170312	.25	.20	.30	.20	.20	.17	.30	.20	.30	.19	.28	.20	.28	.30	.25	.18	.21	.17	.03	.03
PMCD170312	.20	.17	.20	.17	.19	.15	.21	.17	.19	.17	.20	.17	.19	.20	.20	.16	.19	.16	.03	.03
PMC170112	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.02
PMCD170112	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.03	.02


PMC12 DIMENSIONS



- A** = Height/Diameter
B = Total Length
D = Elbow Radial Length

Panel Dimensions

	PANEL OPENING	PANEL THICKNESS MAX. – MIN.	PANEL NUT HEX	PANEL NUT THREAD
COUPLING BODIES	see drawing	.50 – .05	5/8	1/2-24UNS
COUPLING INSERTS	see drawing	.30 – .06	5/8	1/2-24UNS



Coupling Bodies • POLYPROPYLENE

	TERMINATION IN-LINE PIPE THREAD	TUBING/THREAD SIZE	METRIC EQ.	STRAIGHT THRU	SHUTOFF	A	B
		1/8" NPT		PMC100212	PMCD100212	.88	1.00
		1/8" BSPT		PMC100212BSPT	PMCD100212BSPT	.88	1.00
		1/4" NPT		PMC100412	PMCD100412	.88	1.10
		1/4" BSPT		PMC100412BSPT	PMCD100412BSPT	.88	1.10
		1/4" OD, .17" ID	6.4mm OD, 4.3mm ID	PMC120412	PMCD120412	.79	1.72
		1/16" ID	1.6mm ID	PMC160112	PMCD160112	.88	1.40
		1/8" ID	3.2mm ID	PMC160212	PMCD160212	.88	1.65
		1/4" ID	6.4mm ID	PMC160412	PMCD160412	.88	1.85
		1/4" OD, .17" ID	6.4mm OD, 4.3mm ID	PMC130412	PMCD130412	.89	1.74
		1/16" ID	1.6mm ID	PMC170112	PMCD170112	.89	1.42
		1/8" ID	3.2mm ID	PMC170212	PMCD170212	.89	1.67
		1/4" ID	6.4mm ID	PMC170412	PMCD170412	.89	1.87

PMC12 1/4-28 Coupling Bodies • POLYPROPYLENE

	TERMINATION PANEL MOUNT WITH A 1/4-28 FLAT BOTTOM PORT	SHUTOFF	A	B
		PMCD18042812	0.88	1.57
		PMCD19042812	0.89	1.57

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.
 †NOTE: CPC's Ferruleless PTF (polytube fitting) terminations do not require ferrules to achieve a secure connection and are therefore easier to use and reuse. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc.

Coupling Inserts • POLYPROPYLENE

	TERMINATION	TUBING/THREAD SIZE	METRIC EQ.	STRAIGHT THRU	SHUTOFF	A	B	D
	IN-LINE PIPE THREAD	1/8" NPT		PMC240212	PMCD240212	.58	1.03/1.45	
	IN-LINE FERRULELESS POLYTUBE FITTING, PTF†	1/4" OD, .17" ID	6.4mm OD, 4.3mm ID	PMC200412	PMCD200412	.58	1.15/1.58	
	IN-LINE HOSE BARB (non-valved shown)	1/16" ID	1.6mm ID	PMC220112	PMCD220112	.50	.80/1.47	
		1/8" ID	3.2mm ID	PMC220212	PMCD220212	.50	1.05/1.67	
		1/4" ID	6.4mm ID	PMC220412	PMCD220412	.50	1.20/1.71	
	IN-LINE STRAIGHT THREAD PORT SAE	5/16 SAE-5		PMC24082012	PMCD24082012	.72	1.05/1.15	
	ELBOW FERRULELESS POLYTUBE FITTING, PTF†	5/32" OD, .10" ID	4.0mm OD, 2.5mm ID	PMC2102512	PMCD2102512	.50	1.09/1.21	.77
		1/4" OD, .17" ID	6.4mm OD, 4.3mm ID	PMC210412	PMCD210412	.50	1.17/1.21	.77
	ELBOW HOSE BARB	1/8" ID	3.2mm ID	PMC230212	PMCD230212	.50	1.09/1.21	.69
		1/4" ID	6.4mm ID	PMC230412	PMCD230412	.50	1.09/1.21	.90

PMC12 1/4-28 Coupling Inserts • POLYPROPYLENE

	TERMINATION IN-LINE WITH 1/4-28 UNF THREADS	STRAIGHT THRU PMC24042812	SHUTOFF PMCD24042812	A .50	B 1.48
	PANEL MOUNT WITH A 1/4-28 FLAT BOTTOM PORT		PMCD48042812	.72	1.55

Nuts

TUBING SIZE	DESCRIPTION	PART NUMBER
1/16" and 1.8mm	1/4-28 Polypropylene Nut (natural)	2418900
1/8" and 3mm	1/4-28 Polypropylene Nut (natural)	2419000
1/16" and 1.8mm	1/4-28 Acetal Nut (black)	2419199
1/8" and 3mm	1/4-28 Acetal Nut (black)	2419299

Ferrules

TUBING SIZE	DESCRIPTION	PART NUMBER
1/16"	Ferrule, ETFE (blue)	2419300
1/8"	Ferrule, ETFE (yellow)	2419400
1.8mm	Ferrule, ETFE (green)	2419500
3.0mm	Ferrule, ETFE (orange)	2419600

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. Couplings are pictured with valves unless otherwise noted.

†NOTE: CPC's Ferruleless PTF (polytube fitting) terminations do not require ferrules to achieve a secure connection and are therefore easier to use and reuse. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc.

MC SERIES CONNECTOR



CPC's MC Series chrome-plated brass couplings are built tough and made to last in the most demanding applications. Ideal for use with higher temperatures or pressures, MC Series couplings feature one-hand operation for swift and easy connects and disconnects. These couplings offer the flexibility of multiple configurations and terminations and mate with both PMC acetal and PMC12 polypropylene couplings.

FEATURES

Brass material

High temperature capability

CPC thumb latch

Compatible

BENEFITS

Durable and able to withstand higher pressure and temperature

Versions rated to 400°F (204°C)

One-hand connection and disconnection

MC mates with PMC and PMC12 Series couplings

Specifications

PRESSURE:

Vacuum to 250 psi, 17.3 bar

TEMPERATURE:

-40°F to 180°F (-40°C to 82°C)
(High temperature versions available with ratings to 400°F)

MATERIALS:

Main components:

Chrome-plated brass

Thumb latch: Stainless steel

Valves: Acetal

Valve spring: 316 stainless steel

External springs and pin: Stainless steel

O-rings: Buna-N

FINISH:

Chrome

TUBING SIZES:

1/8" to 1/4" ID, 3.2mm to 6.4mm ID


WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC products in their own application conditions. Use the graph to the right as a guide.

Note:
High temperature versions available with ratings to 400 F. Call customer service for more information.


Also available in NSF listed versions, please visit our website for part number information.



MC Air Flow, 100 psig Inlet Pressure



MC Water Flow



These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.

DID YOU KNOW?



CPC OFFERS KEYED, COLOR-CODED COUPLING OPTIONS:

CPC's MC Series couplings are also available in keyed, color-coded versions? Specifically designed for applications requiring foolproof connections and non-interchangeable lines, these couplings are a durable and attractive solution for high-volume applications. Contact CPC for more information.

Liquid Flow Rate Information for Couplings

The chart below shows the flow rate for CPC couplings. Each coupling was tested with water at 70°F (21°C). To determine flow rates for specific coupling configurations use the formula at the right.

$$Q = C_v \sqrt{\frac{\Delta P}{S}}$$

Q = Flow rate in gallons per minute

C_v = Average coefficient across various flow rates (see chart)


ΔP = Pressure drop across coupling (psi)

S = Specific gravity of liquid

C_v VALUES FOR 1/8" FLOW MC COUPLINGS


BODIES	INSERTS	MC12 2004	MCD12 2004	MC12 2006	MCD12 2006	MC12 2202	MCD12 2202	MC12 2204	MCD12 2204	MC12 2402	MCD12 2402	MC12 2404	MCD12 2304	MC12 2602	MCD12 2304	MC12 2104	MCD12 2304	MC12 2203	MCD12 2203
	MC100212	.40	.18	.50	.19	.25	.16	.50	.19	.50	.20	.51	.19	.50	.50	.38	.24	.30	.17
	MCD100212	.27	.18	.31	.18	.24	.16	.28	.20	.26	.20	.29	.18	.26	.26	.27	.24	.25	.17
	MC100412	.40	.21	.50	.24	.26	.18	.50	.24	.50	.20	.51	.24	.50	.50	.38	.26	.30	.19
	MCD100412	.29	.19	.32	.23	.25	.17	.30	.23	.27	.21	.28	.23	.27	.28	.29	.24	.25	.183
	MC120412	.40	.18	.50	.18	.25	.16	.40	.18	.40	.16	.36	.18	.40	.40	.38	.21	.30	.173
	MCD120412	.21	.17	.22	.17	.20	.16	.22	.17	.21	.17	.20	.17	.21	.22	.21	.18	.21	.16
	MC160212	.23	.15	.28	.18	.19	.14	.27	.15	.27	.15	.28	.18	.27	.27	.23	.16	.20	.14
	MCD160212	.19	.15	.19	.15	.17	.14	.19	.15	.18	.15	.18	.15	.18	.19	.19	.15	.18	.14
	MC160412	.33	.23	.44	.24	.24	.18	.44	.23	.44	.20	.38	.24	.38	.44	.33	.26	.26	.19
	MCD160412	.23	.17	.26	.21	.22	.16	.26	.21	.26	.19	.25	.21	.21	.26	.23	.24	.22	.16
	MC170312	.25	.20	.30	.20	.20	.17	.30	.20	.30	.19	.28	.20	.28	.30	.25	.18	.21	.17
	MCD170312	.20	.17	.20	.17	.19	.15	.21	.17	.19	.17	.20	.17	.19	.20	.20	.16	.19	.16

MC DIMENSIONS



Panel Dimensions

	PANEL OPENING	PANEL THICKNESS MAX.—MIN.	PANEL NUT HEX	PANEL NUT THREAD
COUPLING BODIES (except male thread)	see drawing	.50 — .05	5/8	1/2-24UNS
MALE THREAD	see drawing	.21 — .06	5/8	1/2-24UNS
COUPLING INSERTS	see drawing	.30 — .06	5/8	1/2-24UNS



Coupling Bodies • CHROME-PLATED BRASS

	TERMINATION IN-LINE PIPE THREAD	TUBING/THREAD SIZE	METRIC EQ.	STRAIGHT THRU	SHUTOFF	A	B
	1/8" NPT	1/8" BSPT		MC1002	MCD1002	.76	1.00
	1/8" BSPT			MC1002BSPT	MCD1002BSPT	.76	1.00
	1/4" NPT	1/4" BSPT		MC1004	MCD1004	.76	1.10
	1/4" BSPT			MC1004BSPT	MCD1004BSPT	.76	1.10
	5/32" OD, .10" ID	4.0mm OD, 2.5mm ID		MC12025	MCD12025	.76	1.67
	1/4" OD, .17" ID	6.4mm OD, 4.3mm ID		MC1204	MCD1204	.76	1.77
	1/8" ID	3.2mm ID		MC1602	MCD1602	.76	1.67
	3/16" ID	4.8mm ID		MC1603	MCD1603	.76	1.89
	1/4" ID	6.4mm ID		MC1604	MCD1604	.76	1.89
	10-32 UNF			MC181032	MCD181032	.76	1.22
	1/8" NPT			MC1502	MCD1502	.76	1.20
	1/4" OD, .17" ID	6.4mm OD, 4.3mm ID		MC1304	MCD1304	.76	1.77
	1/8" ID	3.2mm ID		MC1702	MCD1702	.76	1.67
	3/16" ID	4.8mm ID		MC1703	MCD1703	.76	1.89
	1/4" ID	6.4mm ID		MC1704	MCD1704	.76	1.89

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.
 †NOTE: CPC's Ferruleless PTF (polytube fitting) terminations do not require ferrules to achieve a secure connection and are therefore easier to use and reuse. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc.
 NOTE: Elbow configurations are available. Contact CPC for more information.

Coupling Inserts • CHROME-PLATED BRASS



TERMINATION
IN-LINE
PIPE THREAD
(non-valved shown)



IN-LINE
PIPE THREAD
(FEMALE)



PANEL MOUNT
FERRULELESS
POLYTUBE FITTING,
PTF†



PANEL MOUNT
HOSE BARB



IN-LINE
FERRULELESS
POLYTUBE FITTING,
PTF†



IN-LINE
HOSE BARB



IN-LINE
FEMALE THREAD



ELBOW
FERRULELESS
POLYTUBE FITTING,
PTF†



ELBOW
HOSE BARB

TUBING/THREAD SIZE METRIC EQ.

1/8" NPT
1/8" BSPT
1/4" NPT

STRAIGHT THRU

MC2402
MC2402BSPT
MC2404

SHUTOFF

MCD2402
MCD2402BSPT
MCD2404

A

B

D

.58
.58/.72
.65

1.03/1.43
1.03/1.43
1.08/1.43

1/8" NPT Female
1/4" NPT Female
1/4" BSPP Female

MC2602
MC2604
MC2604BSPP

MCD2602
MCD2604
MCD2604BSPP

.58
.72
.72

.95/1.65
1.15/1.82
1.23/1.91

1/4" OD, .17" ID 6.4mm OD, 4.3mm ID

MC4004

MCD4004

.72 1.75/1.85

1/8" ID 3.2mm ID
3/16" ID 4.8mm ID
1/4" ID 6.4mm ID

MC4202
MC4203
MC4204

MCD4202
MCD4203
MCD4204

.72
.72
.72

1.65/1.75
1.87/1.97
1.87/1.97

5/32" OD, .10" ID 4.0mm OD, 2.5mm ID
1/4" OD, .17" ID 6.4mm OD, 4.3mm ID
3/8" OD, .25" ID 9.5mm OD, 6.4mm ID

MC20025
MC2004
MC2006

MCD20025
MCD2004
MCD2006

.58
.58
.58

1.13/1.53
1.15/1.55
1.30/1.50

1/8" ID 3.2mm ID
3/16" ID 4.8mm ID
1/4" ID 6.4mm ID

MC2202
MC2203
MC2204

MCD2202
MCD2203
MCD2204

.58
.58
.58

1.05/1.65
1.25/1.85
1.25/1.67

10-32 UNF

MC281032

MCD281032

.58 .63/1.30

5/32" OD, .10" ID 4.0mm OD, 2.5mm ID
1/4" OD, .17" ID 6.4mm OD, 4.3mm ID

MC21025
MC2104

MCD21025
MCD2104

.63
.63

1.18/1.28 .81
1.18/1.28 .83

1/8" ID 3.2mm ID
1/4" ID 6.4mm ID

MC2302
MC2304

MCD2302
MCD2304

.62
.63

1.18/1.28 .76
1.18/1.28 .76

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. Couplings are pictured with valves unless otherwise noted.

†Note: CPC's Ferruleless PTF (polytube fitting) terminations do not require ferrules to achieve a secure connection and are therefore easier to use and reuse. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc. NOTE: Elbow configurations are available. Contact CPC for more information.

NS212 SERIES CONNECTOR



NS212 Series couplings were built on the company's proven platform of non-spill valves designed to provide fast, safe and leak-free fluid line connections. The NS212 is an easy, twist-to-connect coupling with an integrated locking mechanism and double-sided non-spill shutoff valves. It is also chemically resistant and ideal for a diverse range of applications including printing and ink management, analytical instrumentation, electronic cooling and chemical handling. NS212 couplings provide high-flow fluid transfer in a small footprint.

FEATURES

- Efficient, non-spill design
- Multiple seal materials
- Twist-to-connect locking
- Compact design
- Ultra low air inclusion

BENEFITS

- Disconnect under pressure with no spills
- Broad chemical compatibility for diverse applications
- Easy, non-spill connections in tight spaces
- High flow in a small connector
- Minimizes contaminants, reduces the need to purge lines

Specifications

PRESSURE:

Vacuum to 45 psi, 3.1 bar

TEMPERATURE:

32°F to 120°F (0°C to 49°C)

MATERIALS:

Main components: Glass-filled polypropylene

Valve spring: 316 stainless steel

Seal material:

EPDM (FKM/Simriz® FFKM optional)

COLOR: Gray with black accent standard

TUBING SIZES:



1/8" and 1/4" ID, 3.2mm and 6.4mm ID

SPILLAGE: <0.025 cc/disconnect


INCLUSION: 0.009 cc/connect

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions.

These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.



NS212 DIMENSIONS



A = Height/Diameter

B = Total Length

Panel Dimensions

	PANEL OPENING	PANEL THICKNESS MAX.-MIN.
COUPLING BODIES	see drawing	.30-.05



Coupling Bodies • POLYPROPYLENE



TERMINATION	TUBING	METRIC EQ.	SHUTOFF	A	B
IN-LINE PIPE THREAD	1/8" NPT		NS2D100212	.71	1.74
IN-LINE FERRULELESS POLYTUBE FITTING, PTF†	1/4" OD, .17 ID	6.4mm OD, 4.3mm ID	NS2D130412	.71	1.87
IN-LINE HOSE BARB	1/8" ID 1/4" ID	3.2mm ID 6.4mm ID	NS2D170212 NS2D170412	.71 .71	1.87 2.05
PANEL MOUNT FERRULELESS POLYTUBE FITTING, PTF†	1/4" OD, .17 ID	6.4mm OD, 4.3mm ID	NS2D120412	.88	1.87
PANEL MOUNT HOSE BARB	1/8" ID 1/4" ID	3.2mm ID 6.4mm ID	NS2D160212 NS2D160412	.88 .88	1.79 2.05

Coupling Inserts • POLYPROPYLENE



TERMINATION	TUBING SIZE	METRIC EQ.	SHUTOFF	A	B
IN-LINE PIPE THREAD	1/8" NPT		NS2D240212	.64	1.27
IN-LINE FERRULELESS POLYTUBE FITTING, PTF†	1/4" OD, .17 ID	6.4mm OD, 4.3mm ID	NS2D200412	.64	1.39
IN-LINE HOSE BARB	1/8" ID 1/4" ID	3.2mm ID 6.4mm ID	NS2D220212 NS2D220412	.64 .64	1.32 1.52

Accessories

DESCRIPTION

PANEL MOUNT GASKET REPLACEMENT: For sealing panel mount bodies listed above

MATERIAL

Buna-N

PART NO.

1830300

The NS212 does not mate with NS2. Contact CPC for additional compatibility information.

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc. †NOTE: CPC's Ferruleless PTF (polytube fitting) terminations do not require ferrules to achieve a secure connection and are therefore easier to use and reuse.

PLC SERIES CONNECTOR



The **1/4" flow PLC Series** is proven worldwide in thousands of applications and offers the widest selection of sizes and configurations. PLC couplings are injection molded from acetal thermoplastic and are resistant to most mild chemical solutions. One-hand connection/disconnection, plus integral terminations make the PLC Series the choice for ease of use and manufacture.

FEATURES

CPC thumb latch

Integral terminations

Clicks when connected

Compatible

BENEFITS


One-hand connection and disconnection

Fewer leak points, shorter assemblies, faster installations


Assurance of a reliable connection

Mates with LC and PLC12 Series couplings


PLC Air Flow, 100 psig Inlet Pressure



PLC Water Flow



PLC Pressure Range



These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.

Specifications

PRESSURE:

Vacuum to 120 psi, 8.3 bar

TEMPERATURE:

-40°F to 180°F (-40°C to 82°C)

MATERIALS:

Main components and valves: Acetal

Thumb latch: Stainless steel

Valve spring: 316 stainless steel

External springs and pin: Stainless steel

O-rings: Buna-N

COLOR: Natural white, others available

TUBING SIZES:

1/4" to 3/8" ID, 6.4mm to 9.5mm ID

JG® TUBING SPECIFICATIONS:

Tube tolerances: 1/4" OD, +0.001/-0.004 | 3/8" OD, +0.001/-0.004

Tube Types: Plastic tube: Polyethylene, nylon, polyurethane. For soft or thin wall tubing with JG® terminations, tube supports are recommended.

Metal tube: Brass, copper and mild steel

Also available in NSF listed versions, please visit our website for part number information.



Decoding Coupling Options

Often times, it can be an overwhelming task to decipher which coupling best fits your application needs. The chart below helps to decode popular CPC couplings.

1/4" FLOW OPTIONS	PRIMARY MATERIAL	O-RING	APPLICATION BENEFITS
PLC	Acetal	Buna-N	General purpose plastic connector with metal latch
PLC12	Polypropylene	EPDM	Expanded chemical compatibility
LC	Chrome-Plated Brass	Buna-N	Higher operating temperature and pressure
APC	Acetal	Buna-N	Plastic thumb latch
BREAKAWAY®	Acetal	Buna-N	Breakaway latch
NS4	Glass-filled polypropylene	EPDM	Drybreak, non-spill connect and disconnect, even under pressure

For further information please contact CPC Customer Service at 1-800-444-2474 or 651-645-0091.

Liquid Flow Rate Information for Couplings

The chart below shows the flow rate for CPC couplings. Each coupling was tested with water at 70°F (21°C). To determine flow rates for specific coupling configurations use the formula at the right.


$$Q = C_v \sqrt{\frac{\Delta P}{S}}$$

Q = Flow rate in gallons per minute
C_v = Average coefficient across various flow rates (see chart)
ΔP = Pressure drop across coupling (psi)
S = Specific gravity of liquid

C_v VALUES FOR 1/4" FLOW PLC COUPLINGS

BODIES	INSERTS	PLC 20004	PLCD 20004	PLC 20006	PLCD 20006	PLC 22004	PLCD 22004	PLC 22006	PLCD 22006	PLC 24004	PLCD 24004	PLC 24006	PLCD 24006	PLC 26004
PLC10004		.40	.36	1.05	.58	.83	.56	1.40	.82	1.40	.75	1.40	.77	.83
PLCD10004		.36	.31	.73	.48	.66	.41	.82	.50	.80	.45	.77	.45	.81
PLC10006		.40	.36	1.05	.60	.83	.56	1.40	.81	1.40	.76	1.40	.76	.83
PLCD10006		.37	.31	.81	.47	.70	.43	1.02	.51	.98	.46	.99	.48	.98
PLC12006		.38	.36	.84	.63	.74	.56	1.14	.75	1.14	.70	1.14	.72	.74
PLCD12006		.38	.33	.78	.49	.68	.44	.84	.49	.81	.43	.82	.44	.81
PLC16004		.38	.37	.87	.54	.95	.51	1.00	.70	.95	.64	1.00	.66	.95
PLCD16004		.37	.31	.61	.44	.57	.41	.78	.44	.78	.43	.75	.46	.78
PLC16006		.38	.37	1.00	.57	.95	.53	1.40	.80	1.40	.71	1.40	.73	1.40
PLCD16006		.38	.32	.71	.49	.63	.42	.89	.51	.96	.45	.92	.49	.97


PLC DIMENSIONS



- A = Height/Diameter
- B = Total Length
- D = Elbow Radial Length

Panel Dimensions

	PANEL OPENING	PANEL THICKNESS MAX.—MIN.	PANEL NUT HEX	PANEL NUT THREAD
COUPLING BODIES	see drawing	.50 — .05	13/16	11/16-24UNEF
COUPLING INSERTS	see drawing	.30 — .05	13/16	11/16-24UNEF



Coupling Bodies • ACETAL

	TERMINATION IN-LINE PIPE THREAD	TUBING/THREAD SIZE	METRIC EQ.	STRAIGHT THRU	SHUTOFF	A	B
		1/4" NPT		PLC10004	PLCD10004	.90	1.17
		1/4" BSPT		PLC10004BSPT	PLCD10004BSPT	.90	1.15
		3/8" NPT		PLC10006	PLCD10006	.90	1.15
		3/8" BSPT		PLC10006BSPT	PLCD10006BSPT	.90	1.15
	PANEL MOUNT FERRULELESS POLYTUBE FITTING, PTF†	1/4" OD, .17" ID	6.4mm OD, 4.3mm ID	PLC12004	PLCD12004	.88	1.87
			8.0mm OD, 6.0mm ID	PLC120M8	PLCD120M8	.88	1.95
		3/8" OD, .25" ID	9.5mm OD, 6.4mm ID	PLC12006	PLCD12006	.88	1.95
			10.0mm OD, 8.0mm ID	PLC120M10	PLCD120M10	.88	1.95
	PANEL MOUNT HOSE BARB	1/4" ID	6.4mm ID	PLC16004	PLCD16004	.88	1.95
		5/16" ID	7.9mm ID	PLC16005	PLCD16005	.88	1.95
		3/8" ID	9.5mm ID	PLC16006	PLCD16006	.88	1.95
	PANEL MOUNT JG® PUSH-TO-CONNECT	1/4" OD	6.4mm OD	PLC11004	PLCD11004	.88	1.95
	IN-LINE FERRULELESS POLYTUBE FITTING, PTF†	1/4" OD, .17" ID	6.4mm OD, 4.3mm ID	PLC13004	PLCD13004	.94	1.82
			8.0mm OD, 6.0mm ID	PLC130M8	PLCD130M8	.94	1.95
		3/8" OD, .25" ID	9.5mm OD, 6.4mm ID	PLC13006	PLCD13006	.94	1.95
			10.0mm OD, 8.0mm ID	PLC130M10	PLCD130M10	.94	1.95
	IN-LINE HOSE BARB	1/4" ID	6.4mm ID	PLC17004	PLCD17004	.94	1.80 / 1.95
		5/16" ID	7.9mm ID	PLC17005	PLCD17005	.94	1.95
		3/8" ID	9.5mm ID	PLC17006	PLCD17006	.94	1.80 / 1.95
	IN-LINE JG® PUSH-TO-CONNECT	1/4" OD	6.4mm OD	PLC14004	PLCD14004	.94	1.95
		3/8" OD	9.5mm OD	PLC14006	PLCD14006	.94	2.09
		(See page 162 for JG accessories)					

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.
 †NOTE: CPC's Ferruleless Polytube Fitting terminations do not require ferrules to achieve a secure connection, which makes them easier to use and reuse. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc. NOTE: JG is a registered trademark of John Guest USA, Inc.

Coupling Inserts • ACETAL



TERMINATION IN-LINE PIPE THREAD

PANEL MOUNT FERRULELESS POLYTUBE FITTING, PTF†

PANEL MOUNT HOSE BARB

PANEL MOUNT JG® PUSH-TO- CONNECT

IN-LINE FERRULELESS POLYTUBE FITTING, PTF†

IN-LINE HOSE BARB

IN-LINE JG® PUSH-TO- CONNECT

ELBOW FERRULELESS POLYTUBE FITTING, PTF†

ELBOW HOSE BARB

TUBING/THREAD SIZE METRIC EQ.

STRAIGHT THRU

SHUTOFF

A

B

D

1/4" NPT			PLC24004	PLCD24004	.72	1.25/1.66	
1/4" BSPT			PLC24004BSPT	PLCD24004BSPT	.72	1.53/1.66	
3/8" NPT			PLC24006	PLCD24006	.87	1.25/1.63	
3/8" BSPT			PLC24006BSPT	PLCD24006BSPT	.87	1.51/1.63	
1/4" OD, .17" ID	6.4mm OD, 4.3mm ID		PLC40004	PLCD40004	.94	1.78/1.91	
	8.0mm OD, 6.0mm ID		PLC400M8	PLCD400M8	.94	1.91/2.03	
3/8" OD, .25" ID	9.5mm OD, 6.4mm ID		PLC40006	PLCD40006	.94	1.91/2.05	
	10.0mm OD, 8.0mm ID		PLC400M10	PLCD400M10	.94	1.91/2.05	
1/4" ID	6.4mm ID		PLC42004	PLCD42004	.94	1.91/2.05	
5/16" ID	7.9mm ID		PLC42005	PLCD42005	.94	1.91/2.05	
3/8" ID	9.5mm ID		PLC42006	PLCD42006	.94	1.91/2.05	
1/4" OD	6.4mm OD		PLC41004	PLCD41004	.94	1.91/2.05	
1/4" OD, .17" ID	6.4mm OD, 4.3mm ID		PLC20004	PLCD20004	.72	1.25/1.88	
	8.0mm OD, 6.0mm ID		PLC200M8	PLCD200M8	.72	1.38/1.82	
3/8" OD, .25" ID	9.5mm OD, 6.4mm ID		PLC20006	PLCD20006	.72	1.38/1.82	
	10.0mm OD, 8.0mm ID		PLC200M10	PLCD200M10	.72	1.38/1.82	
1/4" ID	6.4mm ID		PLC22004	PLCD22004	.62	1.35/1.99	
5/16" ID	7.9mm ID		PLC22005	PLCD22005	.62	1.35/1.99	
3/8" ID	9.5mm ID		PLC22006	PLCD22006	.62	1.36/1.81	
1/4" OD	6.4mm OD		PLC29004	PLCD29004	.63	1.35/1.95	
3/8" OD	9.5mm OD		PLC29006	PLCD29006	.78	1.51/2.11	
3/8" OD, .25" ID	9.5mm OD, 6.4mm ID		PLC21006	PLCD21006	.61/.62	1.22/1.35	.85/.96
1/4" ID	6.4mm ID		PLC23004	PLCD23004	.67/.63	1.10/1.28	.85/.96
3/8" ID	9.5mm ID		PLC23006	PLCD23006	.67/.63	1.25/1.28	.90/.96

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. Couplings are pictured with valves unless otherwise noted.

†NOTE: CPC's Ferruleless Polytube Fitting terminations do not require ferrules to achieve a secure connection, which makes them easier to use and reuse. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc. NOTE: JG is a registered trademark of John Guest USA, Inc.

PLC12 SERIES CONNECTOR



The 1/4" flow polypropylene PLC12 offers many of the same configuration options as the PLC. The polypropylene material adds greater chemical resistance for more demanding applications. PLC12 couplings are also gamma sterilizable. PLC12 couplings are also gamma sterilizable and available with optional RFID (Radio Frequency Identification) capability (see page 96).

FEATURES

Polypropylene material

EPDM o-rings

CPC thumb latch

Integral terminations

BENEFITS


Chemically resistant and gamma sterilizable

Greater chemical resistance


One-hand connection and disconnection

Fewer leak points, shorter assemblies, faster installations


PLC12 Air Flow, 100 psig Inlet Pressure



PLC12 Water Flow



PLC12 Pressure Range



These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.

Specifications

PRESSURE:

Vacuum to 120 psi, 8.3 bar

TEMPERATURE:

32°F to 160°F (0°C to 71°C)

MATERIALS:

Main components and valves:

Polypropylene

Thumb latch: Stainless steel

Valve spring: 316 stainless steel

External springs and pin: Stainless steel

O-rings: EPDM

STERILIZATION:

Gamma: Up to 50 kGy irradiation

COLOR:

Almond

TUBING SIZES:

1/4" to 3/8" ID, 6.4mm to 9.5mm ID

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions. Use the graph at the right as a guide.

PLC12 Couplings are gamma sterilizable; see page 162 for more information on sterilization and disinfection

Liquid Flow Rate Information for Couplings

The chart below shows the flow rate for CPC couplings. Each coupling was tested with water at 70°F (21°C). To determine flow rates for specific coupling configurations use the formula at the right.

$$Q = C_v \sqrt{\frac{\Delta P}{S}}$$

Q = Flow rate in gallons per minute

C_v = Average coefficient across various flow rates (see chart)

ΔP = Pressure drop across coupling (psi)


S = Specific gravity of liquid

C_v VALUES FOR 1/4" FLOW PLC12 COUPLINGS

	PLC12 20004	PLCD12 20004	PLC12 20006	PLCD12 20006	PLC12 22004	PLCD12 22004	PLC12 22006	PLCD12 22006	PLC12 24004	PLCD12 24004	PLC12 24006	PLCD12 24006	PLC12 26004
BODIES INSERTS													
PLC1000412	.40	.36	1.05	.58	.83	.56	1.40	.82	1.40	.75	1.40	.77	.83
PLCD1000412	.36	.31	.73	.48	.66	.41	.82	.50	.80	.45	.77	.45	.81
PLC1000612	.40	.36	1.05	.60	.83	.56	1.40	.81	1.40	.76	1.40	.76	.83
PLCD1000612	.37	.31	.81	.47	.70	.43	1.02	.51	.98	.46	.99	.48	.98
PLC1200612	.38	.36	.84	.63	.74	.56	1.14	.75	1.14	.70	1.14	.72	.74
PLCD1200612	.38	.33	.78	.49	.68	.44	.84	.49	.81	.43	.82	.44	.81
PLC1600412	.38	.37	.87	.54	.95	.51	1.00	.70	.95	.64	1.00	.66	.95
PLCD1600412	.37	.31	.61	.44	.57	.41	.78	.44	.78	.43	.75	.46	.78
PLC1600612	.38	.37	1.00	.57	.95	.53	1.40	.80	1.40	.71	1.40	.73	1.40
PLCD1600612	.38	.32	.71	.49	.63	.42	.89	.51	.96	.45	.92	.49	.97


NOTES:

PLC12 DIMENSIONS



Panel Dimensions

	PANEL OPENING	PANEL THICKNESS MAX.-MIN.	PANEL NUT HEX	PANEL NUT THREAD
COUPLING BODIES	see drawing	.30 - .02	13/16	11/16-24UNEF
COUPLING INSERTS	see drawing	.30 - .02	13/16	11/16-24UNEF



Coupling Bodies • POLYPROPYLENE








TERMINATION
IN-LINE
PIPE THREAD

PANEL MOUNT
FERRULELESS
POLYTUBE FITTING,
PTF†

PANEL MOUNT
HOSE BARB

IN-LINE
FERRULELESS
POLYTUBE FITTING,
PTF†

IN-LINE
HOSE BARB

IN-LINE
SOFTUBE™ FITTING

TUBING/THREAD SIZE
METRIC EQ.

1/4" NPT
1/4" BSPT
3/8" NPT
3/8" BSPT

3/8" OD, 1/4" ID

PLC12 Coupling Readers • POLYPROPYLENE

	TERMINATION IN-LINE HOSE BARB (RS-232 Interface)	TUBING/THREAD SIZE METRIC EQ.	STRAIGHT THRU	SHUTOFF	A	B
		1/4" ID	6.4mm ID	iPLCDR1700400	1.39	2.78
		3/8" ID	9.5mm ID	iPLCDR1700600	1.39	2.78
	IN-LINE HOSE BARB (USB Interface)	1/4" ID	6.4mm ID	iPLCDR1700401	1.00	1.38/2.05
		3/8" ID	9.5mm ID	iPLCDR1700601	1.05	1.74/1.87

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.
 †NOTE: CPC's Ferruleless Polytube Fitting terminations do not require ferrules to achieve a secure connection, which makes them easier to use and reuse. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc. NOTE: JG is a registered trademark of John Guest USA, Inc.

Coupling Inserts • POLYPROPYLENE



TERMINATION IN-LINE PIPE THREAD

PANEL MOUNT HOSE BARB

IN-LINE FERRULELESS POLYTUBE FITTING, PTF†

IN-LINE HOSE BARB

IN-LINE SOFTUBE™ FITTING

ELBOW FERRULELESS POLYTUBE FITTING, PTF†

ELBOW HOSE BARB

IN-LINE HOSE BARB (RS-232 Interface)

ELBOW HOSE BARB (RS-232 Interface)

TUBING/THREAD SIZE METRIC EQ.

STRAIGHT THRU

SHUTOFF

A

B

D

1/4" NPT

PLC2400412

PLCD2400412

.72

1.26/1.67

1/4" ID

6.4mm ID

PLC4200412

PLCD4200412

.94

1.91/2.05

3/8" ID

9.5mm ID

PLC4200612

PLCD4200612

.94

1.91/2.05

3/8" OD, 1/4" ID

9.5mm OD, 6.4mm ID

PLC2000612

PLCD2000612

.72

1.68/1.82

1/4" ID

6.4mm ID

PLC2200412

PLCD2200412

.63

1.35/2.00

3/8" ID

9.5mm ID

PLC2200612

PLCD2200612

.63

1.35/1.82

3/8" OD, 1/4" ID

9.5mm OD, 6.4mm ID

PLCD22040612

.72

2.23

1/2" OD, 3/8" ID

12.7mm OD, 9.5mm ID

PLCD22060812

.72

2.18

3/8" OD, 1/4" ID

9.5mm OD, 6.4mm ID

PLC2100612

PLCD2100612

.61/.62

1.29/1.36

.95

1/4" ID

6.4mm ID

PLC2300412

PLCD2300412

.63

1.22/1.36

.96

3/8" ID

9.5mm ID

PLC2300612

PLCD2300612

.63

1.28/1.42

.96

1/4" ID

6.4mm ID

iPLCT2200400

iPLCDT2200400

1.39

2.78

3/8" ID

9.5mm ID

iPLCT2200600

iPLCDT2200600

1.39

2.78

1/4" ID

6.4mm ID

iPLCT2300400

iPLCDT2300400

1.48

1.27/1.40

3/8" ID

9.5mm ID

iPLCT2300600

iPLCDT2300600

1.48

1.33/1.46

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. Couplings are pictured with valves unless otherwise noted.

†NOTE: CPC's Ferruleless Polytube Fitting terminations do not require ferrules to achieve a secure connection, which makes them easier to use and reuse. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc. NOTE: JG is a registered trademark of John Guest USA, Inc.

LC SERIES CONNECTOR



CPC's LC Series chrome-plated brass couplings are built tough and made to last in the most demanding applications. Ideal for use with higher temperature or pressure, the LC Series features a one-hand operation for swift and easy connects and disconnects. These couplings offer the flexibility of multiple configurations and terminations to mate with both the PLC acetal and PLC12 polypropylene couplings.

FEATURES

Brass material

Chrome plating

High temperature capability

CPC thumb latch

Compatible

BENEFITS



Durable construction withstands higher pressure and temperature

Attractive appearance

Versions rated to 400°F (204°C)

One-hand connection and disconnection

LC mates with PLC Series couplings



Specifications

PRESSURE:

Vacuum to 250 psi, 17.3 bar

TEMPERATURE:

-40°F to 180°F (-40°C to 82°C)
(High temperature versions available with ratings to 400°F)

MATERIALS:

Main components: Chrome-plated brass

Thumb latch: Stainless steel

Valves: Acetal

Valve springs: 316 stainless steel

External springs and pin: Stainless steel

O-rings: Buna-N

FINISH:

Chrome

TUBING SIZES:

1/4" to 3/8" ID, 6.4mm to 9.5mm ID

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions.

*Note:
High temperature
versions available with
ratings to 400 F. Call
customer service for
more information.*

*Also available in NSF
listed versions for food-
based applications, please
visit our website for part
number information.*



« These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.

DID YOU KNOW?

O-RING SELECTION IS A KEY DECISION in determining which connector will perform best in your specific application. Understanding the material characteristics and how they can be affected by both the media being transferred and the environment in which the connector is being used is important.

BUNA-N is the most common o-ring seal due to its solvent, oil and water resistance. Temperature range is -40°F to 250°F.

FKM is best suited for applications where chemical and strong acid resistance and/or high temperatures are a requirement. The temperature range is -15°F to 400°F.

EPDM has excellent resistance to polar solvents. This o-ring is not compatible with petroleum. The temperature range is -70°F to 300°F.

SILICONE seals have good temperature resistance. The temperature range is -70°F to 400°F and with special compounds can reach 175°F to 450°F. Silicone can also be supplied with Class VI requirements for medical/bioprocessing applications.

For further information about which o-ring is best suited for your application, please contact CPC Customer Service at 1-800-444-2474 or 651-645-0091.

NOTES:

Liquid Flow Rate Information for Couplings

The chart below shows the flow rate for CPC couplings. Each coupling was tested with water at 70°F (21°C). To determine flow rates for specific coupling configurations use the formula at the right.


$$Q = C_v \sqrt{\frac{\Delta P}{S}}$$

Q = Flow rate in gallons per minute
C_v = Average coefficient across various flow rates (see chart)
ΔP = Pressure drop across coupling (psi)
S = Specific gravity of liquid

C_v VALUES FOR 1/4" FLOW LC COUPLINGS

BODIES	INSERTS	LC 20004	LCD 20004	LC 20006	LCD 20006	LC 22004	LCD 22004	LC 22006	LCD 22006	LC 24004	LCD 24004	LC 24006	LCD 24006	LC 26004
	LC10004	.40	.36	1.05	.58	.83	.56	1.40	.82	1.40	.75	1.40	.77	.83
	LCD10004	.36	.31	.73	.48	.66	.41	.82	.50	.80	.45	.77	.45	.81
	LC10006	.40	.36	1.05	.60	.83	.56	1.40	.81	1.40	.76	1.40	.76	.83
	LCD10006	.37	.31	.81	.47	.70	.43	1.02	.51	.98	.46	.99	.48	.98
	LC12006	.38	.36	.84	.63	.74	.56	1.14	.75	1.14	.70	1.14	.72	.74
	LCD12006	.38	.33	.78	.49	.68	.44	.84	.49	.81	.43	.82	.44	.81
	LC16004	.38	.37	.87	.54	.95	.51	1.00	.70	.95	.64	1.00	.66	.95
	LCD16004	.37	.31	.61	.44	.57	.41	.78	.44	.78	.43	.75	.46	.78
	LC16006	.38	.37	1.00	.57	.95	.53	1.40	.80	1.40	.71	1.40	.73	1.40
	LCD16006	.38	.32	.71	.49	.63	.42	.89	.51	.96	.45	.92	.49	.97


LC DIMENSIONS



- A = Height/Diameter
- B = Total Length
- D = Elbow Radial Length

Product Dimensions

	PANEL OPENING	PANEL THICKNESS MAX.-MIN.	PANEL NUT HEX	PANEL NUT THREAD
COUPLING BODIES	see drawing	.50 - .05	13/16	11/16-24UNEF
COUPLING INSERTS	see drawing	.090 - .300	13/16	11/16-24UNEF



Coupling Bodies • CHROME-PLATED BRASS



**TERMINATION
IN-LINE
PIPE THREAD**



**PANEL MOUNT
FERRULELESS
POLYTUBE FITTING,
PTF†**



**PANEL MOUNT
HOSE BARB**



**PANEL MOUNT
MALE THREAD**



**IN-LINE
FERRULELESS
POLYTUBE FITTING,
PTF†**



**IN-LINE
HOSE BARB**

TUBING/THREAD SIZE METRIC EQ.

1/4" NPT
1/4" BSPT
3/8" NPT
3/8" BSPT

6.4mm OD, 4.3mm ID
9.5mm OD, 6.4mm ID

STRAIGHT THRU

LC10004
LC10004BSPT
LC10006
LC10006BSPT

SHUTOFF

LCD10004
LCD10004BSPT
LCD10006
LCD10006BSPT

A .88
1.15
1.15
1.15

B 1.15
1.15
1.15
1.15

1/4" OD, .17" ID
3/8" OD, .25" ID

6.4mm OD, 4.3mm ID
9.5mm OD, 6.4mm ID

LC12004
LC12006

LCD12004
LCD12006

A .88
1.15
1.15
1.15

B 1.87
2.00

1/4" ID
5/16" ID
3/8" ID

6.4mm ID
7.9mm ID
9.5mm ID

LC16004
LC16005
LC16006

LCD16004
LCD16005
LCD16006

A .88
1.15
1.15
1.15

B 2.00
2.00
2.00

1/4" NPT

LC15004

LCD15004

A .88
1.15
1.15
1.15

B 1.50

1/4" OD, .17" ID
3/8" OD, .25" ID

6.4mm OD, 4.3mm ID
9.5mm OD, 6.4mm ID

LC13004
LC13006

LCD13004
LCD13006

A .88
1.15
1.15
1.15

B 1.87
2.00

1/4" ID
5/16" ID
3/8" ID

6.4mm ID
7.9mm ID
9.5mm ID

LC17004
LC17005
LC17006

LCD17004
LCD17005
LCD17006

A .88
1.15
1.15
1.15

B 2.00
2.00
2.00

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.
†NOTE: CPC's Ferruleless Polytube Fitting terminations do not require ferrules to achieve a secure connection, which makes them easier to use and reuse. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc.

Coupling Inserts • CHROME-PLATED BRASS



TERMINATION IN-LINE PIPE THREAD

TUBING/THREAD SIZE METRIC EQ.

STRAIGHT THRU

SHUTOFF

A

B

D

1/4" NPT	LC24004	LCD24004	.72	1.25/1.68
1/4" BSPT	LC24004BSPT	LCD24004BSPT	.72	1.25/1.68
3/8" NPT	LC24006	LCD24006	.87	1.25/1.55
3/8" BSPT	LC24006BSPT	LCD24006BSPT	.87	1.25/1.55



IN-LINE PIPE THREAD (FEMALE)

1/4" NPT Female	LC26004	LCD26004	.72	1.25/1.90
1/4" BSPP Female	LC26004BSPP	LCD26004BSPP	.72	1.25/1.75



PANEL MOUNT FERRULELESS POLYTUBE FITTING, PTF†

1/4" OD, .17" ID	6.4mm OD, 4.3mm ID	LC40004	LCD40004	.94	1.83/1.98
3/8" OD, .25" ID	9.5mm OD, 6.4mm ID	LC40006	LCD40006	.94	1.96/2.11



PANEL MOUNT HOSE BARB

1/4" ID	6.4mm ID	LC42004	LCD42004	.94	1.96/2.11
5/16" ID	7.9mm ID	LC42005	LCD42005	.94	1.96/2.11
3/8" ID	9.5mm ID	LC42006	LCD42006	.94	1.96/2.11



IN-LINE FERRULELESS POLYTUBE FITTING, PTF†

1/4" OD, .17" ID	6.4mm OD, 4.3mm ID	LC20004	LCD20004	.72	1.25/1.87
3/8" OD, .25" ID	9.5mm OD, 6.4mm ID	LC20006	LCD20006	.72	1.38/1.83



IN-LINE HOSE BARB

1/4" ID	6.4mm ID	LC22004	LCD22004	.63	1.35/2.00
5/16" ID	7.9mm ID	LC22005	LCD22005	.63	1.35/1.85
3/8" ID	9.5mm ID	LC22006	LCD22006	.63	1.35/1.83



ELBOW FERRULELESS POLYTUBE FITTING, PTF†

1/4" OD, .17" ID	6.4mm OD, 4.3mm ID	LC21004	LCD21004	.63	1.28/1.43	.96
3/8" OD, .25" ID	9.5mm OD, 6.4mm ID	LC21006	LCD21006	.63	1.28/1.43	.83




ELBOW HOSE BARB

1/4" ID	6.4mm ID	LC23004	LCD23004	.63/.62	1.28/1.43	1.28
3/8" ID	9.5mm ID	LC23006	LCD23006	.63/.62	1.28/1.43	1.28

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. Couplings are pictured with valves unless otherwise noted.

†NOTE: CPC's Ferruleless Polytube Fitting terminations do not require ferrules to achieve a secure connection, which makes them easier to use and reuse. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc.

APC SERIES CONNECTOR



Specifications ● ● ●

PRESSURE:

Vacuum to 120 psi, 8.3 bar

TEMPERATURE:

-40°F to 180°F (-40°C to 82°C)

MATERIALS:

Main components and valves: Acetal

Thumb latch: Acetal

Valve springs: 316 stainless steel

External springs and pin: Stainless steel

O-rings: Buna-N

COLOR: Natural white with light gray latch

TUBING SIZES:

1/4" to 3/8" ID, 6.4mm to 9.5mm ID

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions.

The **1/4" flow APC Series couplings** feature a plastic thumb latch, fewer moving parts and a smooth contoured design to deliver ease-of-use and excellent flow in a compact size. The APC Series includes couplings with valves and thumb latch shrouds. A more rugged design on some models adds durability to increase the APC's application range.

FEATURES

Plastic thumb latch

Shrouded thumb latch

Integral terminations

Compatibility

BENEFITS

No exposed metal parts

Protects against accidental disconnects


Fewer leak points, shorter assemblies, faster installations

Mates with most EFC couplings


Also available in NSF listed versions, please visit our website for part number information.



APC Air Flow, 100 psig Inlet Pressure



APC Water Flow



These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.

DID YOU KNOW?

THE SHELF LIFE OF A CONNECTOR IS DEPENDENT UPON THE CONNECTOR MATERIALS AND THE STORAGE CONDITIONS.

CPC manufactures quick disconnect couplings and connections made from a variety of metal, plastic and elastomeric raw materials. In general, it is best to store any CPC product in an environment shielded from light at a temperature between 50°F and 90°F.

The shelf life of CPC couplings and connections is estimated to be 3 years minimum if the storage conditions comply with those shown above.

Note: For product containing lubricated o-rings, the lubricant will dry out over time. Prior to use, it may be advisable to re-lubricate external o-rings. For product containing silicone o-rings, if lube is allowable, use of a synthetic lube is recommended.

Liquid Flow Rate Information for Couplings

The chart below shows the flow rate for CPC couplings. Each coupling was tested with water at 70°F (21°C). To determine flow rates for specific coupling configurations use the formula at the right.

$$Q = C_v \sqrt{\frac{\Delta P}{S}}$$

Q = Flow rate in gallons per minute

C_v = Average coefficient across various flow rates (see chart)

ΔP = Pressure drop across coupling (psi)


S = Specific gravity of liquid

C_v VALUES FOR APC COUPLINGS

BODIES	INSERTS	APC 20004	APCD 20004	APC 20006	APCD 20006	APC 22004	APCD 22004	APC 22006	APCD 22006	APC 24004	APCD 24004	APC 24006	APCD 24006
	APC10004	0.4	0.4	1.2	0.9	1.0	0.9	2.0	0.9	1.9	0.8	1.7	0.8
	APCD10004	0.36	0.4	1.0	0.7	1.0	0.7	0.8	0.7	1.2	0.6	0.8	0.6
	APC10006	0.4	0.4	1.2	0.9	1.2	0.7	1.8	0.9	2.0	0.9	1.7	0.8
	APCD10006	0.37	0.4	1.3	0.8	0.6	0.5	1.1	0.7	1.3	0.7	1.0	0.7
	APC13004SH	0.38	0.5	0.5	0.4	0.4	0.4	0.5	0.4	0.5	0.4	0.4	0.4
	APCD13004SH	0.38	0.5	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
	APC13006SH	0.38	0.4	1.0	0.7	0.9	0.6	1.1	0.7	1.1	0.7	1.0	0.7
	APCD13006SH	0.37	0.4	0.8	0.6	0.7	0.5	0.8	0.6	0.9	0.6	0.8	0.6
	APC17004SH	0.38	0.4	0.8	0.6	1.0	0.7	0.9	0.7	0.8	0.6	0.7	0.6
	APCD17004SH	0.38	0.4	0.7	0.5	0.8	0.6	0.7	0.6	0.7	0.5	0.6	0.5
	APC17006SH	0.4	0.4	1.2	0.9	1.4	0.9	1.4	0.9	2.0	0.9	1.9	0.8
	APCD17006SH	0.4	0.4	1.2	0.8	1.3	0.8	1.2	0.7	1.2	0.7	1.1	0.7

NOTES:


APC DIMENSIONS



- A = Height/Diameter
- B = Total Length
- D = Elbow Radial Length

Panel Dimensions

	PANEL OPENING	PANEL THICKNESS MAX.-MIN.	PANEL NUT HEX	PANEL NUT THREAD
COUPLING BODIES	see drawing	.05-.02	13/16	11/16-24UNF



Coupling Bodies • ACETAL



TERMINATION IN-LINE PIPE THREAD

TUBING/THREAD SIZE METRIC EQ.

STRAIGHT THRU

SHUTOFF

A

B

IN-LINE HOSE BARB

IN-LINE WITH SHROUD FERRULELESS POLYTUBE FITTING, PTF†

IN-LINE HOSE BARB

PANEL MOUNT FERRULELESS POLYTUBE FITTING, PTF†

PANEL MOUNT HOSE BARB

1/4" ID	6.4mm ID	APC17004		.93	1.35
3/8" ID	9.5mm ID	APC17006		.93	1.35
1/4" OD, .17" ID	6.4mm OD, 4.3mm ID	APC13004SH	APCD13004SH	1.30	1.94
	8.0mm OD, 6.0mm ID	APC130M8SH	APCD130M8SH	1.30	2.07
3/8" OD, .25" ID	9.5mm OD, 6.4mm ID	APC13006SH	APCD13006SH	1.30	2.07
	10.0mm OD, 8.0mm ID	APC130M10SH	APCD130M10SH	1.30	2.07
1/4" ID	6.4mm ID	APC17004SH	APCD17004SH	1.30	2.07
3/8" ID	9.5mm ID	APC17006SH	APCD17006SH	1.30	2.07
1/4" OD, .17" ID	6.4mm OD, 4.3mm ID	APC12004	APCD12004	1.03	1.97
	8.0mm OD, 6.0mm ID	APC120M8	APCD120M8	1.03	2.10
3/8" OD, .25" ID	9.5mm OD, 6.4mm ID	APC12006	APCD12006	1.03	2.10
	10.0mm OD, 8.0mm ID	APC120M10	APCD120M10	1.03	2.10
1/4" ID	6.4mm ID	APC16004	APCD16004	1.03	2.10
5/16" ID	7.9mm ID	APC16005	APCD16005	1.03	2.10
3/8" ID	9.5mm ID	APC16006	APCD16006	1.03	2.10

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.

†NOTE: CPC's Ferruleless Polytube Fitting terminations do not require ferrules to achieve a secure connection, which makes them easier to use and reuse. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc.

Accessories

DESCRIPTION

PANEL MOUNT GASKET REPLACEMENT: For sealing panel mount bodies listed above

MATERIAL

Buna-N

PART NO.

1830300

Coupling Inserts • ACETAL



TERMINATION IN-LINE PIPE THREAD

TUBING/THREAD SIZE METRIC EQ.

STRAIGHT THRU

SHUTOFF

A

B

D

IN-LINE FERRULELESS POLYTUBE FITTING, PTF†

IN-LINE HOSE BARB

ELBOW FERRULELESS POLYTUBE FITTING, PTF†

ELBOW HOSE BARB

1/4" NPT		APC24004	APCD24004	.72	1.43/1.77	
1/4" BSPT		APC24004BSPT	APCD24004BSPT	.72	1.63/1.77	
3/8" NPT		APC24006	APCD24006	.72	1.50/1.64	
3/8" BSPT		APC24006BSPT	APCD24006BSPT	.72	1.51/1.65	
1/4" OD, .17" ID	6.4mm OD, 4.3mm ID	APC20004	APCD20004	.72	1.86/1.99	
	8.0mm OD, 6.0mm ID	APC200M8	APCD200M8	.72	1.79/1.93	
3/8" OD, .25" ID	9.5mm OD, 6.4mm ID	APC20006	APCD20006	.72	1.78/1.91	
	10.0mm OD, 8.0mm ID	APC200M10	APCD200M10	.72	1.79/1.93	
1/4" ID	6.4mm ID	APC22004	APCD22004	.60/.72	1.40/2.10	
3/8" ID	9.5mm ID	APC22006	APCD22006	.63/.72	1.40/1.92	
1/4" OD, .17" ID	6.4mm OD, 4.3mm ID	APC21004	APCD21004	1.22	1.32/1.45	.91
3/8" OD, .25" ID	9.5mm OD, 6.4mm ID	APC21006	APCD21006	1.27	1.33/1.46	.96
1/4" ID	6.4mm ID	APC23004	APCD23004	.63	1.20/1.45	.96
3/8" ID	9.5mm ID	APC23006	APCD23006	.63	1.20/1.50	.96

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. Couplings are pictured with valves unless otherwise noted.

†NOTE: CPC's Ferruleless Polytube Fitting terminations do not require ferrules to achieve a secure connection, which makes them easier to use and reuse. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc.

BREAKAWAY SERIES CONNECTOR

Specifications ● ● ●

PRESSURE:

0 to 20 psi, 1.4 bar

TEMPERATURE:

0°F to 150°F (-18°C to 66°C)

MATERIALS:

Main components and valves: Acetal

Valve springs: 316 stainless steel

O-rings: Buna-N

Retention ring: PPS

COLOR: White or black

TUBING SIZES:

1/4" and 3/8" ID, 6.4mm and 9.5mm ID

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions.

CPC's BreakAway® Series couplings provide safe and easy fluid transfer with protection from costly product loss and equipment damage. These high quality, leak-free connectors are designed to disconnect when pull force is applied without depressing a latching mechanism, allowing users to make a clean, fast and easy break at critical moments.

FEATURES

Reliable break-away design

Automatic dual shutoff valves

Streamlined, flush finish

BENEFITS





Rapid, automatic disconnection

Safe and clean fluid handling


Easy-to-use for maximum productivity

These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of the graphs represent the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.

Force to disconnect is approximately 11 pounds pull force at 0 psi line pressure and 8 pounds pull force at 20 psi. In some applications and with certain types of tubing, a hose clamp may be required.




BREAKAWAY DIMENSIONS



A = Height/Diameter
B = Total Length

Panel Dimensions

COUPLING BODIES	PANEL OPENING	PANEL THICKNESS MAX.-MIN.
	see drawing	.50-.02



Coupling Bodies

• WHITE ACETAL

	TERMINATION IN-LINE HOSE BARB	TUBING SIZE	METRIC EQ.	STRAIGHT THRU	SHUTOFF	A	B
		1/4" ID	6.4mm ID		BACD17004	0.92	2.29
		3/8" ID	9.5mm ID		BACD17006	0.92	2.29
	PANEL MOUNT HOSE BARB	1/4" ID	6.4mm ID		BACD16004	0.92	2.29
		3/8" ID	9.5mm ID		BACD16006	0.92	2.29

• BLACK ACETAL

	TERMINATION IN-LINE HOSE BARB	TUBING SIZE	METRIC EQ.	STRAIGHT THRU	SHUTOFF	A	B
		1/4" ID	6.4mm ID		BACD17004MBLK	0.92	2.29
		3/8" ID	9.5mm ID		BACD17006MBLK	0.92	2.29
	PANEL MOUNT HOSE BARB	1/4" ID	6.4mm ID		BACD16004MBLK	0.92	2.29
		3/8" ID	9.5mm ID		BACD16006MBLK	0.92	2.29

Coupling Inserts

• WHITE ACETAL

	TERMINATION IN-LINE HOSE BARB	TUBING SIZE	METRIC EQ.	STRAIGHT THRU	SHUTOFF	A	B
		1/4" ID	6.4mm ID	BAC22004	BACD22004	0.58/0.69	1.58/2.10
		3/8" ID	9.5mm ID		BACD22006	0.69	2.10

• BLACK ACETAL

	TERMINATION IN-LINE HOSE BARB	TUBING SIZE	METRIC EQ.	STRAIGHT THRU	SHUTOFF	A	B
		1/4" ID	6.4mm ID	BAC22004MBLK	BACD22004MBLK	0.58/0.69	1.58/2.10
		3/8" ID	9.5mm ID		BACD22006MBLK	0.69	2.10

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.
 MBLK = molded black material.

EFC12 SERIES CONNECTOR



Specifications ● ● ●

PRESSURE:

Vacuum to 105 psi, 7.2 bar

TEMPERATURE:

32°F to 160°F (0°C to 71°C)

MATERIALS:

Main components and valves: Polypropylene

Thumb latch: Polypropylene

Valve spring: 316 stainless steel

Panel mount gasket: EPDM

External springs: 302 stainless steel

O-rings: EPDM

COLOR:

Gray with dark gray latch

TUBING SIZES:

1/4" and 3/8" ID, 6.4mm and 9.5mm ID

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions.

The **9/32" flow EFC12 Series couplings** feature a high efficiency valve design that provides a greater flow capability than any other coupling its size. Chemically resistant polypropylene material makes it ideal for harsh environments. The EFC12 Series adds a bulkhead panel mount option for tight seals against tank walls and drums.

FEATURES

High efficiency valve

Plastic thumb latch

Polypropylene material

Compatible

BENEFITS

More flow than PLC Series in a compact size


Fewer moving parts

Chemically resistant and gamma sterilizable


Mates with most APC couplings

These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.


EFC12 Air Flow, 100 psig Inlet Pressure



EFC12 Water Flow



EFC12 Pressure Range



Liquid Flow Rate Information for Couplings

The chart below shows the flow rate for CPC couplings. Each coupling was tested with water at 70°F (21°C). To determine flow rates for specific coupling configurations use the formula at the right.

$$Q = C_v \sqrt{\frac{\Delta P}{S}}$$

Q = Flow rate in gallons per minute

C_v = Average coefficient across various flow rates (see chart)


ΔP = Pressure drop across coupling (psi)

S = Specific gravity of liquid

C_v VALUES FOR EFC12 COUPLINGS

BODIES \ INSERTS	EFC12 20004	EFC12 20004	EFC12 20006	EFC12 20006	EFC12 22004	EFC12 22004	EFC12 22006	EFC12 22006	EFC12 24004	EFC12 24004
EFC10412	0.51	0.51	0.51	0.51	0.50	0.45	0.50	0.50	0.51	0.51
EFC10612	0.61	0.51	1.13	0.72	0.50	0.45	0.81	0.69	0.51	0.72
EFC16412	0.51	0.51	0.51	0.51	0.50	0.45	0.50	0.50	0.51	0.51
EFC16612	0.61	0.51	1.13	0.72	0.50	0.45	0.81	0.69	0.51	0.72
EFC17412	0.51	0.51	0.51	0.51	0.50	0.45	0.50	0.50	0.51	0.51
EFC17612	0.61	0.51	1.13	0.72	0.50	0.45	0.81	0.69	0.51	0.72

EFC12 DIMENSIONS



Panel Dimensions

	PANEL OPENING	PANEL THICKNESS MAX.-MIN.	PANEL NUT HEX	PANEL NUT THREAD
COUPLING BODIES	see drawing	.25 - .03	13/16	11/16-24UNF

EFC Series
Gasket Thickness: .06"
Mounting Hole: .720" diameter
Coupling Spacing: 1.25" min.
Greenlee® 720 Keyway Punch and
730BB-3/4 Hole Punch.

Coupling Bodies • POLYPROPYLENE

	TERMINATION IN-LINE PIPE THREAD	TUBING/THREAD SIZE METRIC EQ.	STRAIGHT THRU	SHUTOFF	A	B	D
		1/4" NPT 3/8" NPT		EFC10412 EFC10612	.93 .93	2.29 2.29	
	BULKHEAD PANEL MOUNT HOSE BARB	1/4" ID 3/8" ID		EFC16412 EFC16612	.93 .93	2.23 2.23	
	IN-LINE HOSE BARB	1/4" ID 3/8" ID		EFC17412 EFC17612	.93 .93	2.23 2.23	

Coupling Inserts • POLYPROPYLENE

	TERMINATION IN-LINE PIPE THREAD	TUBING/THREAD SIZE METRIC EQ.	STRAIGHT THRU	SHUTOFF	A	B	D
		1/4" NPT 3/8" NPT		EFC24412 EFC24612	.72 .72	1.77 1.77	
	IN-LINE HOSE BARB	1/4" ID 3/8" ID	EFC22412 EFC22612	EFC22412 EFC22612	.60/.72 .60/.72	1.33/2.08 1.33/1.90	
	ELBOW HOSE BARB	1/4" ID 3/8" ID	EFC23412 EFC23612	EFC23412 EFC23612	.63 .63	1.32/1.45 1.32/1.45	.96 .96

Accessories

DESCRIPTION

PANEL MOUNT GASKET REPLACEMENT

For sealing panel mount bodies listed above

MATERIAL

Buna-N

PART NO.

1830300

NS4 SERIES CONNECTOR



NS4 Series couplings feature non-spill valves in a compact size, at a great price. Use the NS4 when even a few drops pose problems regarding safety, media cost or environmental regulations. These innovative couplings are lightweight, chemically resistant and easy to use. The non-spill design effectively eliminates spills, minimizes downtime and enhances operator safety. NS4 couplings are also available with optional RFID (Radio Frequency Identification) capability (see page 97).

FEATURES

Non-spill design
Color coding
Glass-filled polypropylene
Medical-grade ABS

BENEFITS

Disconnect under pressure with no spills
Instant visual differentiation of media lines
Durable and compatible with many chemicals
Gamma sterilizable

Specifications

PRESSURE:

Vacuum to 120 psi, 8.3 bar

TEMPERATURE:

32°F to 160°F (0°C to 71°C)

MATERIALS:

Main components and valves:
Glass-filled polypropylene with TPV* overmold, ABS with TPE* soft-touch overmold

Thumb latch: Glass-filled polypropylene, ABS

Valve spring: 316 stainless steel

External spring: 316 stainless steel

O-rings: EPDM

COLOR:

Polypropylene: Gray with dark gray overmold standard; gray with red or blue overmold available†

ABS: White with teal overmold

TUBING SIZES:

1/8" to 3/8" ID, 3.2mm to 9.5mm ID

LUBRICANTS:

Krytox® PFPE (inert)

SPILLAGE:

<0.10 cc per disconnect at all rated pressures

INCLUSION:

0.26 cc per connect



WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions.

*The overmold material TPV (thermoplastic vulcanizate) is used with the NS4 polypropylene couplings. TPV is an alloy of polypropylene thermoplastic and fully vulcanized EPDM rubber. TPV is typically resistant to water, acids and bases. The overmold material TPE (thermoplastic elastomer) is used with the NS4 ABS couplings. TPE is a blend of additives and copolymers in a special formulation that forms extremely durable bonds to the ABS substrate, while offering the traditional properties of soft-touch overmold.


†NOTE: Standard product is gray; color options require a minimum quantities. Please contact CPC for details.



These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.



NS4 DIMENSIONS




A = Height/Diameter

B = Total Length

Panel Dimensions

	PANEL OPENING	PANEL THICKNESS MAX.-MIN.
COUPLING INSERTS	see drawing	.25 - .03



Coupling Bodies • POLYPROPYLENE / ABS

TERMINATION	TUBING/THREAD SIZE	METRIC EQ.	ABS SHUTOFF	POLYPROPYLENE SHUTOFF	A	B
IN-LINE PIPE THREAD	1/4" NPT		NS4D1000406	NS4D10004	1.05	2.31
	1/4" BSPT		NS4D10004BSPT06	NS4D10004BSPT	1.05	2.29
IN-LINE FERRULESS POLYTUBE FITTING, PTF†	1/4" OD, .17" ID	6.4mm OD, 4.3mm ID		NS4D13004	1.05	2.32
	3/8" OD, 1/4" ID	9.5mm OD, 6.4mm ID	NS4D1300606	NS4D13006	1.05	2.45
IN-LINE HOSE BARB	1/8" ID*	3.2mm ID*	NS4D1700206	NS4D17002	1.05	2.09
	1/4" ID	6.4mm ID	NS4D1700406	NS4D17004	1.05	2.34
	3/8" ID	9.5mm ID	NS4D1700606	NS4D17006	1.05	2.34
IN-LINE HOSE BARB (RS-232 Interface)	1/8" ID	3.2mm		iNS4DR1700200	2.15	3.49
	1/4" ID	6.4mm		iNS4DR1700400	2.15	3.49
	3/8" ID	9.5mm		iNS4DR1700600	2.15	3.49
IN-LINE HOSE BARB (USB Interface)	1/4" ID	6.4mm ID		iNS4DR1700201	2.15	3.40
	3/8" ID	9.5mm ID		iNS4DR1700401	2.15	3.40
	1/2" ID	12.7mm ID		iNS4DR1700601	2.15	3.40

Coupling Inserts • POLYPROPYLENE / ABS

TERMINATION	TUBING/THREAD SIZE	METRIC EQ.	ABS SHUTOFF	POLYPROPYLENE SHUTOFF	A	B
IN-LINE PIPE THREAD	1/4" NPT		NS4D2400406	NS4D24004	.96	1.95
	1/4" BSPT		NS4D24004BSPT06	NS4D24004BSPT	.96	1.95
IN-LINE FERRULESS POLYTUBE FITTING, PTF†	1/4" OD, .17" ID	6.4mm OD, 4.3mm ID		NS4D20004	.96	1.95
	3/8" OD, 1/4" ID	9.5mm OD, 6.4mm ID	NS4D2000606	NS4D20006	.96	2.09
IN-LINE HOSE BARB	1/8" ID*	3.2mm ID*	NS4D2200206	NS4D22002	.96	1.73
	1/4" ID	6.4mm ID	NS4D2200406	NS4D22004	.96	1.98
	3/8" ID	9.5mm ID	NS4D2200606	NS4D22006	.96	1.98
PANEL MOUNT FERRULESS POLYTUBE FITTING, PTF†	1/4" OD, .17" ID	6.4mm OD, 4.3mm ID		NS4D40004	1.17	2.30
	3/8" OD, 1/4" ID	9.5mm OD, 6.4mm ID	NS4D4000606	NS4D40006	1.17	2.43
PANEL MOUNT HOSE BARB	1/8" ID*	3.2mm ID*	NS4D4200206	NS4D42002	1.17	2.07
	1/4" ID	6.4mm ID	NS4D4200406	NS4D42004	1.17	2.32
	3/8" ID	9.5mm ID	NS4D4200606	NS4D42006	1.17	2.32
PANEL MOUNT HOSE BARB ELBOW	1/4" ID	6.4mm ID		NS4D43004	1.19	2.39
	3/8" ID	9.5mm ID		NS4D43006	1.19	2.39
ELBOW HOSE BARB	1/4" ID	6.4mm ID		NS4D23004	0.96	2.04
	3/8" ID	9.5mm ID		NS4D23006	0.96	2.04
IN-LINE HOSE BARB (RS-232 Interface)	1/8" ID	3.2mm		iNS4DT2200200	For product dimensions visit cpcworldwide.com	
	1/4" ID	6.4mm		iNS4DT2200400		
	3/8" ID	9.5mm		iNS4DT2200600		

Accessories

DESCRIPTION

PANEL MOUNT GASKET REPLACEMENT: For sealing panel mount inserts listed above

MATERIAL

EPDM
FKM

PART NO.

1879800
1889500

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc. †NOTE: CPC's Ferruleless PTF (polytube fitting) terminations do not require ferrules to achieve a secure connection and are therefore easier to use and reuse. *NOTE: Patented 1/8" ID (3.2mm) hose barb connection has a support shroud allowing a maximum tube OD of 1/4" (6.4mm).

LQ4 SERIES CONNECTOR



LQ4 Series quick disconnect couplings provide ultra-reliable, dripless connections and disconnections that protect valuable electronics. Designed specifically for liquid cooling applications, LQ4 utilizes patent-pending valve technology that eliminates drips and is able to withstand long-term use.

FEATURES

Non-spill design
Redundant sealing when connected
Color-coding
Friction-free valve
Ruggedness
Rotation allows movement

BENEFITS

Disconnect under pressure with no spills
Extra protection from leaks
Instant visual difference in cooling lines
Valving system designed for extended periods in connected state
Able to withstand long-term, repeated use
Eliminates tube kinking

Specifications

PRESSURE:

Vacuum to 120 psi, 8.3 bar

TEMPERATURE:

0°F to 240°F (-17°C to 115°C)

MAXIMUM FLOW AT DISCONNECT:

3.0 gal/min, 11.3L/min

MATERIALS:

Main housing components:

Chrome-plated brass

Valves and thumb latch: Polysulfone

Valve spring (wetted): Stainless steel

External spring: Stainless steel

Seals: EPDM

COLOR:

Chrome with Cool Blue or Warm Red

TUBING SIZES:

1/4" to 3/8" ID, 6.4mm to 9.5mm ID

LUBRICANTS: Krytox® PFPE




SPILLAGE:

0.025 cc per disconnect rated at 0 psi

0.055 cc per disconnect rated at 120 psi


INCLUSION: 0.025 cc per connect

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions.



These graphs are intended to give you a general idea of the performance capabilities of each product line. Contact CPC for flow of a particular coupling combination.

LQ4 DIMENSIONS



A = Height/Diameter
B = Total Length

Coupling Bodies • CHROME-PLATED BRASS

TERMINATION	TUBING/THREAD SIZE	METRIC EQ.	SHUTOFF	A	B
	IN-LINE	1/4" ID	LQ4D17004RED	0.98	2.49
	HOSE BARB	1/4" ID	LQ4D17004BLU	0.98	2.49
		3/8" ID	LQ4D17006RED	0.98	2.49
		3/8" ID	LQ4D17006BLU	0.98	2.49
	IN-LINE	1/4 SAE-4	LQ4D30004RED	0.98	2.29
	STRAIGHT THREAD	1/4 SAE-4	LQ4D30004BLU	0.98	2.29
	PORT SAE	3/8 SAE-6	LQ4D30006RED	0.98	2.29
		3/8 SAE-6	LQ4D30006BLU	0.98	2.29
	IN-LINE	1/4" NPT	LQ4D10004RED	0.98	2.31
	PIPE THREAD	1/4" NPT	LQ4D10004BLU	0.98	2.31
		3/8" NPT	LQ4D10006RED	0.98	2.31
		3/8" NPT	LQ4D10006BLU	0.98	2.31
	IN-LINE	1/4" ID x 3/8" OD	LQ4D13006RED	0.98	2.46
	PTF	1/4" ID x 3/8" OD	LQ4D13006BLU	0.98	2.46

Coupling Inserts • CHROME-PLATED BRASS

TERMINATION	TUBING/THREAD SIZE	METRIC EQ.	SHUTOFF	A	B
	IN-LINE	1/4" ID	LQ4D22004RED	0.74	2.22
	HOSE BARB	1/4" ID	LQ4D22004BLU	0.74	2.22
		3/8" ID	LQ4D22006BLU	0.74	2.22
		3/8" ID	LQ4D22006RED	0.74	2.22
		3/8" ID	LQ4D22006RED	0.74	2.22
	IN-LINE	1/4 SAE-4	LQ4D46004BLU	0.80	2.02
	STRAIGHT THREAD	1/4 SAE-4	LQ4D46004RED	0.80	2.02
	PORT SAE	3/8 SAE-6	LQ4D46006BLU	0.80	2.02
		3/8 SAE-6	LQ4D46006RED	0.80	2.02
	IN-LINE	1/4" NPT	LQ4D24004RED	0.80	2.04
	PIPE THREAD	1/4" NPT	LQ4D24004BLU	0.80	2.04
		3/8" NPT	LQ4D24006RED	0.80	2.04
		3/8" NPT	LQ4D24006BLU	0.80	2.04
	IN-LINE	1/4" ID x 3/8" OD	LQ4D20006RED	0.80	2.19
	PTF	1/4" ID x 3/8" OD	LQ4D20006BLU	0.80	2.19

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.

NS6 SERIES CONNECTOR



NS6 Series couplings couplings feature non-spill valves at a great price. Use the NS6 when even a few drops of spillage pose problems regarding safety, media cost or environmental regulations. These innovative couplings are lightweight, chemically resistant and easy to use. The non-spill design virtually eliminates spills, minimizes downtime and enhances operator safety. Soft touch overmold makes them comfortable in the hand and very attractive.

FEATURES

Non-spill design
Color coding
Glass-filled polypropylene
CPC thumb latch

BENEFITS

Disconnect under pressure with no spills
Instant visual differentiation of media lines
Durable and compatible with many chemicals
One-hand connection and disconnection

Specifications

PRESSURE:

Vacuum to 120 psi, 8.3 bar

TEMPERATURE:

32°F to 160°F (0°C to 71°C)

MATERIALS:

Main components and valves: Glass-filled polypropylene with TPV* soft touch overmold

Thumb latch: Glass-filled polypropylene

Valve spring (wetted): 316 stainless steel

External spring: 316 stainless steel

O-rings: EPDM

COLOR:

Gray with dark gray overmold standard; gray with red or blue overmold available†

TUBING SIZES:

3/8" and 1/2" ID, 9.5mm and 12.7mm ID

LUBRICANTS:

Krytox® PFPE (inert)

SPILLAGE:

~0.03 cc per disconnect @ 0 psi, ~0.30 cc/disconnect @ 120 psi

INCLUSION:



0.42 cc per connect

*The overmold material is a TPV (thermoplastic vulcanizate). This TPV is an alloy of polypropylene thermoplastic and fully vulcanized EPDM rubber. The material is typically resistant to water, acids and bases.


†NOTE: Standard product is gray; color options require a set-up charge and minimum quantities. Please contact CPC for details.



These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.




NS6 DIMENSIONS



Panel Dimensions

	PANEL OPENING	PANEL THICKNESS MAX.-MIN.
COUPLING INSERTS	see drawing	.25 - .03



Coupling Bodies • POLYPROPYLENE

TERMINATION	TUBING/THREAD SIZE	METRIC EQ.	SHUTOFF	A	B
IN-LINE PIPE THREAD	1/2" NPT 1/2" BSPT		NS6D10008 NS6D10008BSPT	1.31 1.31	3.01 3.01
IN-LINE COMPRESSION	1/2" OD	12.7mm OD	NS6D13008	1.31	3.53
IN-LINE HOSE BARB	3/8" ID 1/2" ID	9.5mm ID 12.7mm ID	NS6D17006 NS6D17008	1.31 1.31	3.16 3.16

Coupling Inserts • POLYPROPYLENE

TERMINATION	TUBING/THREAD SIZE	METRIC EQ.	SHUTOFF	A	B
IN-LINE PIPE THREAD	1/2" NPT 1/2" BSPT		NS6D24008 NS6D24008BSPT	1.31 1.31	2.44 2.44
IN-LINE COMPRESSION	1/2" OD	12.7mm OD	NS6D20008	1.31	3.01
IN-LINE HOSE BARB	3/8" ID 1/2" ID	9.5mm ID 12.7mm ID	NS6D22006 NS6D22008	1.31 1.31	2.59 2.59
PANEL MOUNT COMPRESSION	1/2" OD	12.7mm OD	NS6D40008	1.50	3.32
PANEL MOUNT HOSE BARB	3/8" ID 1/2" ID	9.5mm ID 12.7mm ID	NS6D42006 NS6D42008	1.50 1.50	2.85 2.85

Accessories

DESCRIPTION	MATERIAL	PART NO.
PANEL MOUNT GASKET REPLACEMENT: For sealing panel mount bodies listed above	EPDM	1884300
	FKM	1889600

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. Couplings are pictured with valves unless otherwise noted.

LQ6 SERIES CONNECTOR



LQ6 Series couplings closed-system design provides ultra-reliable, dripless connections and disconnections. The first of their kind, the couplings utilize patent-pending valve technology specifically designed for liquid cooling applications.

FEATURES

Non-spill design
Redundant sealing when connected
Color-coding
Friction-free valve
Ruggedness
Rotation allows movement

BENEFITS

Disconnect under pressure with no spills
Extra protection from leaks
Instant visual difference in cooling lines
Valving system designed for extended periods in connected state
Able to withstand long-term, repeated use
Eliminates tube kinking

Specifications ● ● ●

PRESSURE:

Vacuum to 120 psi, 8.3 bar

TEMPERATURE:

0°F to 240°F (-17°C to 115°C)

MAXIMUM FLOW AT DISCONNECT:

4.0 gal/min, 15.1 L/min

MATERIALS:

Main housing components:

Chrome-plated brass

Valves and thumb latch: Polysulfone

Valve spring (wetted): Stainless steel

External spring: Stainless steel

Seals: EPDM

COLOR:

Chrome with Cool Blue or Warm Red

TUBING SIZES:

3/8" to 1/2" ID, 9.5mm to 12.7mm ID

LUBRICANTS: Krytox® PFPE

SPILLAGE:




0.05 cc per disconnect rated at 0 psi

0.125 cc per disconnect rated at 120 psi


INCLUSION: 0.42 cc per connect

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions.

✓ These graphs are intended to give you a general idea of the performance capabilities of each product line. Contact CPC for flow of a particular coupling combination.



LQ6 DIMENSIONS



A = Height/Diameter

B = Total Length

Coupling Bodies • CHROME-PLATED BRASS

TERMINATION	TUBING/THREAD SIZE	METRIC EQ.	SHUTOFF	A	B
 IN-LINE HOSE BARB	3/8" ID	9.5mm ID	LQ6D17006RED	1.185	2.73
	3/8" ID	9.5mm ID	LQ6D17006BLU	1.185	2.73
	1/2" ID	12.7mm ID	LQ6D17008RED	1.185	2.73
	1/2" ID	12.7mm ID	LQ6D17008BLU	1.185	2.73
 IN-LINE STRAIGHT THREAD PORT SAE	3/8 SAE-6		LQ6D30006RED	1.185	2.48
	3/8 SAE-6		LQ6D30006BLU	1.185	2.48
	1/2 SAE-8		LQ6D30008RED	1.185	2.50
	1/2 SAE-8		LQ6D30008BLU	1.185	2.50
 IN-LINE PIPE THREAD	3/8" NPT		LQ6D10006RED	1.185	2.56
	3/8" NPT		LQ6D10006BLU	1.185	2.56
 IN-LINE PTF	3/8" ID x 1/2" OD		LQ6D13008RED	1.185	2.50
	3/8" ID x 1/2" OD		LQ6D13008BLU	1.185	2.50

Coupling Inserts • CHROME-PLATED BRASS

TERMINATION	TUBING/THREAD SIZE	METRIC EQ.	SHUTOFF	A	B
 IN-LINE HOSE BARB	3/8" ID	9.5mm ID	LQ6D22006RED	.93	2.47
	3/8" ID	9.5mm ID	LQ6D22006BLU	.93	2.47
	1/2" ID	12.7mm ID	LQ6D22008RED	.93	2.47
	1/2" ID	12.7mm ID	LQ6D22008BLU	.93	2.47
 IN-LINE STRAIGHT THREAD PORT SAE	3/8 SAE-6		LQ6D46006RED	1.025	2.22
	3/8 SAE-6		LQ6D46006BLU	1.025	2.22
	1/2 SAE-8		LQ6D46008RED	1.025	2.24
	1/2 SAE-8		LQ6D46008BLU	1.025	2.24
 IN-LINE PIPE THREAD	3/8" NPT		LQ6D24006RED	1.025	2.30
	3/8" NPT		LQ6D24006BLU	1.025	2.30
 IN-LINE PTF	3/8" ID x 1/2" OD		LQ6D20008RED	1.025	2.52
	3/8" ID x 1/2" OD		LQ6D20008BLU	1.025	2.52

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.

NSH SERIES CONNECTOR



NSH Series couplings couplings are general purpose versions of our pressure-balanced, non-spill, ChemQuik® CQG06 couplings. Molded polypropylene, EPDM seals and a 100% springless and metal-free flow path provide broad chemical resistance and exceptionally high flow capacity, allowing instant disconnects (and reconnects), even under pressure. Their non-spill design virtually eliminates spills, minimizes downtime and enhances operator safety in a very low cost package.

FEATURES

Non-spill design

Pressure-balanced design

Springless flow path design

Optional color coding

BENEFITS

Ultimate protection from chemicals and fumes


Failsafe disconnect, even under pressure; easy to reconnect at high pressure

Eliminates source of metallic contaminants

Helps prevent accidental misconnects



These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.



Specifications ● ● ●

PRESSURE:

Vacuum to 120 psi, 8.3 bar

TEMPERATURE:

32°F to 120°F (0°C to 49°C)

MATERIALS:

Main components: Glass-filled polypropylene

Thumb latch: Glass-filled polypropylene

O-rings: EPDM

Springs (non-wetted): 316 stainless steel

Compression nuts: White polypropylene

COLOR:

Gray with dark gray accent standard; red or blue thumb latch and insert tip available.

TUBING SIZES:

3/8" to 3/4" ID, 9.5mm to 19.0mm ID

LUBRICANTS:

Krytox® PFPE (inert)

SPILLAGE:

0.03 cc/connect

INCLUSION:


0.42 cc per connect

PANEL MOUNT:


Optional adaptor kit (see page 69)

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC products in their own application conditions. Use the graphs below as a guide.


Compatible with ChemQuik® Dual Containment System; DrumQuik® Universal Dispense System and Asian Drum Adaptors.



NSH DIMENSIONS



Panel Dimensions



Coupling Bodies • POLYPROPYLENE

	TERMINATION	TUBING/THREAD SIZE	METRIC EQ.	SHUTOFF	A	B
	IN-LINE PIPE THREAD	3/8" FEMALE NPT		NSHD19006	2.0	3.70
		3/8" BSPT		NSHD10006BSPT	2.0	3.67
		1/2" NPT		NSHD10008	2.0	3.81
		3/4" NPT		NSHD10012	2.0	4.01
	IN-LINE COMPRESSION	3/8" OD	9.5mm OD	NSHD13006	2.0	3.97
		1/2" OD	12.7mm OD	NSHD13008	2.0	4.10
	IN-LINE HOSE BARB	3/8" ID	9.5mm ID	NSHD17006	2.0	3.73
		1/2" ID	12.7mm ID	NSHD17008	2.0	3.73
		5/8" ID	15.9mm ID	NSHD17010	2.0	3.88
		3/4" ID	19.0mm ID	NSHD17012	2.0	3.88

Coupling Inserts • POLYPROPYLENE

	TERMINATION	TUBING/THREAD SIZE	METRIC EQ.	SHUTOFF	A	B
	IN-LINE PIPE THREAD	3/8" FEMALE NPT		NSHD26006	1.64	3.87
		3/8" BSPT		NSHD24006BSPT	1.64	3.84
		1/2" NPT		NSHD24008	1.64	3.98
		3/4" NPT		NSHD24012	1.64	3.98
	IN-LINE COMPRESSION	3/8" OD	9.5mm OD	NSHD20006	1.64	4.14
		1/2" OD	12.7mm OD	NSHD20008	1.64	4.27
	IN-LINE HOSE BARB	3/8" ID	9.5mm ID	NSHD22006	1.64	3.90
		1/2" ID	12.7mm ID	NSHD22008	1.64	3.90
		5/8" ID	15.9mm ID	NSHD22010	1.64	4.05
		3/4" ID	19.0mm ID	NSHD22012	1.64	4.05

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.
*Panel mount kit can be used with body for front mount or insert for front or rear mount.

Accessories



DESCRIPTION	PART NO.
PANEL MOUNT KIT: with panel seal Dust plug/cap for body or insert*	NSHPMKIT12 1800700 (not shown)

HFC12 SERIES CONNECTOR



HFC12 Series couplings have flow comparable to many 1/2" flow couplings in a 3/8" body size. Compact and lightweight, HFC couplings replace bulky and heavy brass ball-and-sleeve couplings in a wide range of applications. An ergonomic design and a large, shrouded thumb latch pad produce a coupling that is easy to grip and simple to operate. An efficient valve design leads to high flow and low spillage.

FEATURES

High efficiency valve

Ergonomic design

Polypropylene material

Compatible

BENEFITS

More flow in a compact size

Easy to grip, simple to operate

Chemically resistant and gamma sterilizable

Mates with HFC35 and HFC57 couplings

Specifications

PRESSURE:

Vacuum to 60 psi, 4.2 bar

TEMPERATURE:

32°F to 160°F (0°C to 71°C)

MATERIALS:

Main components and valves: Polypropylene

Thumb latch: Polypropylene

Valve spring (wetted): 316 stainless steel

External springs: 316 stainless steel

O-rings: EPDM

Panel mount gasket: EPDM

Compression nut, gripper, ferrule: Polypropylene

COLOR: Gray with dark gray latch

TUBING SIZES:

3/8" to 3/4" ID, 9.5mm to 19.0mm ID


WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions.

For compression termination specifications: 3/8" OD or 1/2" OD, +0.010/-0.000


Note: Optional o-ring and spring materials are available, please contact CPC for details.

These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.


HFC12 Air Flow, 100 psig Inlet Pressure



HFC12 Water Flow



HFC12 Pressure Range



NOTES:

Liquid Flow Rate Information for Couplings

The chart below shows the flow rate for CPC couplings. Each coupling was tested with water at 70°F (21°C). To determine flow rates for specific coupling configurations use the formula at the right.


$$Q = C_v \sqrt{\frac{\Delta P}{S}}$$

- Q** = Flow rate in gallons per minute
C_v = Average coefficient across various flow rates (see chart)
ΔP = Pressure drop across coupling (psi)
S = Specific gravity of liquid

C_v VALUES FOR HFC12 COUPLINGS

BODIES	INSERTS	HFC 22612	HFCD 22612	HFC 22812	HFCD 22812	HFC 23612	HFCD 23612	HFC 23812	HFCD 23812	HFC 24612	HFCD 24612	HFC 24812	HFCD 24812	HFCD 221212	HFC 221212
	HFCD10612	1.27	1.27	1.62	1.51	1.14	1.14	1.46	1.36	1.80	1.58	1.70	1.65	-	-
	HFCD10812	1.28	1.34	1.62	1.51	1.15	1.24	1.46	1.36	1.81	1.54	1.72	1.56	-	-
	HFCD16612	1.07	1.00	1.17	1.14	0.96	0.90	1.05	1.03	1.33	1.26	1.30	1.24	-	-
	HFCD16812	1.25	1.23	1.61	1.52	1.13	1.11	1.45	1.37	1.79	1.60	1.68	1.56	-	-
	HFCD17612	1.07	1.00	1.17	1.14	0.96	0.90	1.05	1.03	1.33	1.26	1.30	1.24	-	-
	HFCD17812	1.25	1.23	1.61	1.52	1.13	1.11	1.45	1.37	1.79	1.60	1.68	1.56	-	-
	HFC171212	-	-	-	-	-	-	-	-	-	-	-	-	3.94	-
	HFCD171212	-	-	-	-	-	-	-	-	-	-	-	-	-	2.04


HFC12 DIMENSIONS



- A = Height/Diameter
- B = Total Length
- D = Elbow Radial Length

Panel Dimensions

	PANEL OPENING	PANEL THICKNESS MAX.-MIN.
COUPLING BODIES	see drawing	.25-.03



Gasket Thickness: .06"
Mounting Hole: 1.21" diameter
Coupling Spacing: 1.92" minimum

Coupling Bodies • POLYPROPYLENE



TERMINATION IN-LINE PIPE THREAD

BULKHEAD PANEL MOUNT HOSE BARB

BULKHEAD PANEL MOUNT COMPRESSION

IN-LINE HOSE BARB

IN-LINE COMPRESSION

TUBING/THREAD SIZE	METRIC EQ.	STRAIGHT THRU	SHUTOFF	A	B
3/8" NPT		HFC10612	HFCD10612	1.44	2.69
3/8" BSPT		HFC10612BSPT	HFCD10612BSPT	1.44	2.72
1/2" NPT		HFC10812	HFCD10812	1.44	2.88
3/4" NPT		HFC101212	HFCD101212	1.44	3.07
3/8" ID	9.5mm ID	HFC16612	HFCD16612	1.82	2.82
1/2" ID	12.7mm ID	HFC16812	HFCD16812	1.82	2.82
5/8" ID	15.9mm ID	HFC161012	HFCD161012	1.82	2.94
3/4" ID	19.0mm ID	HFC161212	HFCD161212	1.82	2.94
3/8" OD	9.5mm OD	HFC12612	HFCD12612	1.82	2.96
1/2" OD	12.7mm OD	HFC12812	HFCD12812	1.82	3.11
3/8" ID	9.5mm ID	HFC17612	HFCD17612	1.44	2.79
1/2" ID	12.7mm ID	HFC17812	HFCD17812	1.44	2.79
5/8" ID	15.9mm ID	HFC171012	HFCD171012	1.44	2.94
3/4" ID	19.0mm ID	HFC171212	HFCD171212	1.44	2.94
3/8" OD	9.5mm OD	HFC13612	HFCD13612	1.44	2.96
1/2" OD	12.7mm OD	HFC13812	HFCD13812	1.44	3.11

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.

Accessories

DESCRIPTION

PANEL MOUNT GASKET REPLACEMENT: For sealing panel mount bodies listed above

MATERIAL
EPDM

PART NO.
621200

Also available in NSF listed versions, please visit our website for part number information.



Coupling Inserts • POLYPROPYLENE



TERMINATION IN-LINE PIPE THREAD

IN-LINE HOSE BARB (non-valved shown)

IN-LINE COMPRESSION (non-valved shown)

ELBOW HOSE BARB (non-valved shown)

TUBING/THREAD SIZE METRIC EQ.

STRAIGHT THRU

SHUTOFF

A

B

D

3/8" NPT			HFC24612	HFCD24612	1.16	1.77/1.89	
3/8" BSPT			HFC24612BSPT	HFCD24612BSPT	1.16	1.80/1.92	
1/2" NPT			HFC24812	HFCD24812	1.16	1.95/2.07	
3/4" NPT			HFC241212	HFCD241212	1.23	2.14/2.26	
3/8" ID	9.5mm ID		HFC22612	HFCD22612	1.00	1.97/2.09	
1/2" ID	12.7mm ID		HFC22812	HFCD22812	1.00	1.97/2.09	
5/8" ID	15.9mm ID		HFC221012	HFCD221012	1.00	2.01/2.13	
3/4" ID	19.0mm ID		HFC221212	HFCD221212	1.00	2.14/2.26	
3/8" OD	9.5mm OD		HFC20612	HFCD20612	1.00	2.14/2.26	
1/2" OD	12.7mm OD		HFC20812	HFCD20812	1.00	2.29/2.41	
3/8" ID	9.5mm ID		HFC23612	HFCD23612	1.00	1.93/2.05	.93
1/2" ID	12.7mm ID		HFC23812	HFCD23812	1.00	1.97/2.09	.93
3/4" ID	19.0mm ID		HFC231212	HFCD231212	1.00	1.95/2.07	.93

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. Couplings are pictured with valves unless otherwise noted.

DID YOU KNOW?

WHEN SELECTING A VALVED COUPLING FOR YOUR APPLICATION, make sure to order a part number with a D just before the numeric portion of the part number. For example, HFC101212 does not have a shutoff valve; HFCD101212 would be the correct part number to order for a valved coupling.

To visually identify a part to determine whether or not it is valved, disconnect the coupling body and insert, and then look through the part. If you can see light all the way through, your part is non-valved. If there is anything obstructing the light, you probably have a valved part. Please contact Customer Service at 1-800-444-2474 or 651-645-0091 if you need further assistance.

HFC35 & HFC57 SERIES CONNECTOR



HFC35 Series polysulfone couplings are able to withstand demanding applications and feature physical strength, chemical resistance and autoclavability.

HFC57 Series polysulfone couplings are UV resistant and able to withstand continued exposure to harmful UV rays without affecting performance.

Both can operate in harsh environments in temperatures from -40°F to 280°F (-40°C to 138°C) and pressures from vacuum to 125 psi (8.6 bar). An ergonomic design and a large, shrouded thumb latch pad produce a coupling that is easy to grip and simple to operate. An efficient valve design leads to high flow and exceptionally low spillage. Both series also add bulkhead panel mount, garden hose thread and Hastelloy® C spring options.

FEATURES

Polysulfone (HFC35)

UV Polysulfone (HFC57)

High efficiency valve

Ergonomic design

Compatible

BENEFITS

Physically strong and autoclavable

Physically strong and UV resistant

More flow and less spillage in a compact size

Easy to grip, simple to operate

Mates with HFC12 couplings

Specifications ● ● ●

PRESSURE:

Vacuum to 125 psi, 8.6 bar

TEMPERATURE:

-40°F to 280°F (-40°C to 138°C)

MATERIALS:

Main components and valves:

HFC35 - Polysulfone

HFC57 - UV-resistant polysulfone

THUMB LATCH:

HFC35 - Polysulfone

HFC57 - UV-resistant polysulfone

Valve spring: 316 stainless steel

External springs: 316 stainless steel

O-rings: EPDM

Panel mount gasket: EPDM

Female GHT gasket: FDA EPDM

COLORS:

HCF35 - Natural white, dark gray latch

HCF57 - Black, black latch

TUBING SIZES:


3/8" to 3/4" ID, 9.5mm to 19.0mm ID

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC products in their own application conditions. Use the graphs on the following page as a guide.


Also available in NSF listed versions, please visit our website for part number information.




HFC35/57 Air Flow, 100 psig Inlet Pressure



HFC35/57 Water Flow



HFC35/57 Pressure Range



DID YOU KNOW?

THE HFC57 SERIES POLYSULFONE COUPLINGS ARE UV-RESISTANT AND ABLE TO WITHSTAND CONTINUED EXPOSURE TO HARMFUL RAYS WITHOUT AFFECTING PERFORMANCE?

These couplings offer all the same features as our HFC12 and HFC35 Series with the added advantage of UV-resistance to protect the strength and durability of your fluid connections. Use the HFC57 couplings in outdoor applications such as watercraft, lawn irrigation systems and solar heating on roofs and decks where a connector is subjected to the harsh rays of the sun.

These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.

NOTES:

HFC35 DIMENSIONS

HFC35 Coupling Bodies • POLYSULFONE

	TERMINATION	TUBING/THREAD SIZE	METRIC EQ.	STRAIGHT THRU	SHUTOFF	A	B
	IN-LINE PIPE THREAD	3/8" NPT		HFC10635	HFCD10635	1.44	2.73
		3/8" BSPT		HFC10635BSPT	HFCD10635BSPT	1.44	2.73
		1/2" NPT		HFC10835	HFCD10835	1.44	2.88
		1/2" BSPT		HFC10835BSPT	HFCD10835BSPT	1.44	2.88
		3/4" NPT		HFC101235	HFCD101235	1.44	3.12
		3/4" BSPT		HFC101235BSPT	HFCD101235BSPT	1.44	3.12
	IN-LINE PIPE THREAD (FEMALE)	3/4" GHT		HFC191235GHT	HFCD191235GHT	1.44	2.70
		3/4" BSPP		HFC191235BSPP	HFCD191235BSPP	1.44	2.70
	BULKHEAD PANEL MOUNT HOSE BARB	3/8" ID	9.5mm ID	HFC16635	HFCD16635	1.44	2.82
		1/2" ID	12.7mm ID	HFC16835	HFCD16835	1.44	2.82
		5/8" ID	15.9mm ID	HFC161035	HFCD161035	1.44	2.94
		3/4" ID	19.0mm ID	HFC161235	HFCD161235	1.44	2.94
	IN-LINE HOSE BARB	3/8" ID	9.5mm ID	HFC17635	HFCD17635	1.44	2.82
		1/2" ID	12.7mm ID	HFC17835	HFCD17835	1.44	2.82
		5/8" ID	15.9mm ID	HFC171035	HFCD171035	1.44	2.94
		3/4" ID	19.0mm ID	HFC171235	HFCD171235	1.44	2.94

HFC35 Coupling Inserts • POLYSULFONE

	TERMINATION	TUBING/THREAD SIZE	METRIC EQ.	STRAIGHT THRU	SHUTOFF	A	B	D
	IN-LINE PIPE THREAD (non-valved shown)	3/8" NPT		HFC24635	HFCD24635	1.16	1.82/1.94	
		3/8" BSPT		HFC24635BSPT	HFCD24635BSPT	1.16	1.97/2.09	
		1/2" NPT		HFC24835	HFCD24835	1.16	1.97/2.09	
		1/2" BSPT		HFC24835BSPT	HFCD24835BSPT	1.16	1.17/2.09	
		3/4" NPT		HFC241235	HFCD241235	1.23	2.22/2.34	
		3/4" BSPT		HFC241235BSPT	HFCD241235BSPT	1.23	2.21/2.33	
	IN-LINE PIPE THREAD (FEMALE) (non-valved shown)	3/4" GHT		HFC241235GHT	HFCD241235GHT	1.23	2.03/2.15	
		3/4" BSPP		HFC261235BSPP	HFCD261235BSPP	1.37	1.79/1.91	
	IN-LINE HOSE BARB (non-valved shown)	3/8" ID	9.5mm ID	HFC22635	HFCD22635	1.00	1.91/2.03	
		1/2" ID	12.7mm ID	HFC22835	HFCD22835	1.00	1.91/2.03	
		5/8" ID	15.9mm ID	HFC221035	HFCD221035	1.00	2.03/2.15	
		3/4" ID	19.0mm ID	HFC221235	HFCD221235	1.00	2.03/2.15	
	ELBOW HOSE BARB (non-valved shown)	3/8" ID	9.5mm ID	HFC23635	HFCD23635	1.00	1.92/2.04	.93
		1/2" ID	12.7mm ID	HFC23835	HFCD23835	1.00	1.96/2.08	.93

⚡ HFC35 & HFC57 Accessories ⚡

DESCRIPTION

PANEL MOUNT GASKET REPLACEMENT: For sealing panel mount bodies listed above

MATERIAL

EPDM

PART NO.

621200


GHT GASKET REPLACEMENT: For sealing female threads

FDA EPDM

2339400

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.


HFC57 DIMENSIONS



- A** = Height/Diameter
- B** = Total Length
- D** = Elbow Radial Length

Panel Dimensions

	PANEL OPENING	PANEL THICKNESS MAX.-MIN.
COUPLING BODIES	see drawing	.25-.03



Gasket Thickness: .06"
Mounting Hole: 1.21" diameter
Coupling Spacing: 1.92" minimum

HFC57 Coupling Bodies • UV POLYSULFONE

	TERMINATION	TUBING/THREAD SIZE	METRIC EQ.	STRAIGHT THRU	SHUTOFF	A	B
	IN-LINE PIPE THREAD	3/8" BSPT		HFC10657BSPT	HFCD10657BSPT	1.44	2.73
		1/2" NPT		HFC10857	HFCD10857	1.44	2.88
		1/2" BSPT		HFC10857BSPT	HFCD10857BSPT	1.44	2.88
		3/4" BSPT		HFC101257BSPT	HFCD101257BSPT	1.44	3.12
		3/4" GHT		HFC101257GHT	HFCD101257GHT	1.44	2.94
	IN-LINE PIPE THREAD (FEMALE)	3/4" GHT		HFC191257GHT	HFCD191257GHT	1.44	2.70
		3/4" BSPP		HFC191257BSPP	HFCD191257BSPP	1.44	2.70
	BULKHEAD PANEL MOUNT HOSE BARB	3/8" ID	9.5mm ID		HFCD16657	1.82	2.82
		1/2" ID	12.7mm ID		HFCD16857	1.82	2.82
		5/8" ID	15.9mm ID		HFCD161057	1.82	2.94
		3/4" ID	19.0mm ID		HFCD161257	1.82	2.94
	IN-LINE HOSE BARB	3/8" ID	9.5mm ID	HFC17657	HFCD17657	1.44	2.82
		1/2" ID	12.7mm ID	HFC17857	HFCD17857	1.44	2.82
		5/8" ID	15.9mm ID	HFC171057	HFCD171057	1.44	2.94
		3/4" ID	19.0mm ID	HFC171257	HFCD171257	1.44	2.94

HFC57 Coupling Inserts • UV POLYSULFONE

	TERMINATION	TUBING/THREAD SIZE	METRIC EQ.	STRAIGHT THRU	SHUTOFF	A	B
	IN-LINE PIPE THREAD (non-valved shown)	3/8" BSPT		HFC24657BSPT	HFCD24657BSPT	1.16	1.84/1.96
		1/2" BSPT		HFC24857BSPT	HFCD24857BSPT	1.16	1.99/2.07
		1/2" NPT		HFC24857	HFCD24857	1.16	1.95/2.11
		3/4" BSPT		HFC241257BSPT	HFCD241257BSPT	1.23	2.19/2.31
		3/4" GHT		HFC241257GHT	HFCD241257GHT	1.16	2.15/2.27
	IN-LINE PIPE THREAD (FEMALE) (non-valved shown)	3/4" GHT		HFC261257GHT	HFCD261257GHT	1.37	1.79/1.91
		3/4" BSPP		HFC261257BSPP	HFCD261257BSPP	1.37	1.79/1.91
	IN-LINE HOSE BARB (non-valved shown)	3/8" ID	9.5mm ID	HFC22657	HFCD22657	1.00	1.91/2.03
		1/2" ID	12.7mm ID	HFC22857	HFCD22857	1.00	1.91/2.03
		5/8" ID	15.9mm ID	HFC221057	HFCD221057	1.00	2.03/2.15
		3/4" ID	19.0mm ID	HFC221257	HFCD221257	1.00	2.03/2.15

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. Couplings are pictured with valves unless otherwise noted.

FFC35 SERIES CONNECTOR



FFC35 Series 1/2" flow couplings feature double the flow of the HFC Series couplings. The FFC Series has a non-valved bore that increases flow and minimizes turbulence. The polysulfone material is able to withstand demanding applications and features physical strength, chemical resistance and autoclavability. An ergonomic design and a large, shrouded thumb latch pad produce a coupling that is easy to grip and simple to operate.

FEATURES


- No valves
- Polysulfone material
- Ergonomic design

BENEFITS

- Exceptional flow
- Physically strong and autoclavable
- Easy to grip, simple to operate

NON-VALVED

CPC's FFC35 Series couplings feature a wide open, straight-thru flow path.



Specifications ● ● ●

PRESSURE:

Vacuum to 125 psi, 8.6 bar

TEMPERATURE:

-40°F to 280°F (-40°C to 138°C)

MATERIALS:

Main components: Polysulfone

Thumb latch: Polysulfone

External spring: 316 stainless steel

O-rings: FDA Buna-N

Panel mount gasket: EPDM

Female GHT gasket: FDA EPDM



COLOR:

Natural white with dark gray latch


TUBING SIZES: 3/4" ID, 19.0mm ID

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC products in their own application conditions. Use the graphs on the following page as a guide.

These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.




FFC35 DIMENSIONS



A = Height/Diameter
B = Total Length

Panel Dimensions



Coupling Bodies • POLYSULFONE

TERMINATION	TUBING/THREAD SIZE	METRIC EQ.	STRAIGHT THRU	A	B
IN-LINE PIPE THREAD	1/2" NPT		FFC10835	1.44	2.88
	1/2" BSPT		FFC10835BSPT	1.44	2.88
	3/4" NPT		FFC101235	1.44	3.12
	3/4" BSPT		FFC101235BSPT	1.44	3.12
	3/4" GHT		FFC101235GHT	1.44	2.94
IN-LINE PIPE THREAD (FEMALE)	3/4" GHT		FFC191235GHT	1.44	2.70
	3/4" BSPP		FFC191235BSPP	1.44	2.70
BULKHEAD PANEL MOUNT HOSE BARB	3/4" ID	19.0mm ID	FFC161235	1.82	2.94
IN-LINE HOSE BARB	3/4" ID	19.0mm ID	FFC171235	1.44	2.94

Coupling Inserts • POLYSULFONE

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. Couplings are pictured with valves unless otherwise noted.

TERMINATION	TUBING/THREAD SIZE	METRIC EQ.	STRAIGHT THRU	A	B
IN-LINE PIPE THREAD (non-valved shown)	1/2" NPT		FFC24835	1.16	1.95
	1/2" BSPT		FFC24835BSPT	1.16	1.95
	3/4" NPT		FFC241235	1.23	2.14
	3/4" BSPT		FFC241235BSPT	1.23	2.14
	3/4" GHT		FFC241235GHT	1.16	2.01
IN-LINE PIPE THREAD (FEMALE) (non-valved shown)	3/4" GHT		FFC261235GHT	1.37	1.77
	3/4" BSPP		FFC261235BSPP	1.37	1.77
IN-LINE HOSE BARB (non-valved shown)	3/4" ID	19.0mm ID	FFC221235	1.00	2.02

Accessories

DESCRIPTION	MATERIAL	PART NO.
PANEL MOUNT GASKET REPLACEMENT: For sealing panel mount bodies listed above	EPDM	621200
GHT GASKET REPLACEMENT: For sealing female threads	FDA EPDM	2339400

TENTUBE SERIES CONNECTOR



CONNECT UP TO 10 TUBES
IN ONE EASY MOTION!

The Tentube™ coupling provides one easy-to-use quick disconnect for up to ten separate fluid lines. The Tentube is available with valves on the body side in panel mount or in-line configurations for maximum design flexibility. The Tentube can connect and disconnect up to ten lines with the use of a simple slide latch. Tubing orientation is ensured by keying the coupling body and insert. Different fluids and tubing sizes can be accommodated by using acetal or polypropylene inserts in three popular sizes.

FEATURES

- Ten line connection
- Separate flow paths
- Insert is keyed to body
- Acetal or polypropylene inserts

BENEFITS

- Fast, efficient operation
- Pressure and/or vacuum in one coupling
- Ensures correct line orientation
- Maximize design flexibility

Specifications

PRESSURE:

Vacuum to 100 psi, 6.9 bar per line

TEMPERATURE:

Acetal fitting inserts:
-40°F to 180°F (-40°C to 82°C)

Polypropylene fitting inserts:
32°F to 180°F (0°C to 82°C)

MATERIALS:

Main components: Nylon

Valves: Acetal

Valve springs: 316 stainless steel

Fitting inserts: Acetal or polypropylene

O-rings: Buna-N with acetal
or EPDM with polypropylene

Panel mount adapter: Acetal

Tube shroud: Acetal

COLOR:

Main components:

Black with red locking latch



Tube shroud: Black

Panel mount adapter: Black


TUBING SIZES:

1/16" to 1/8" ID, 1.6mm to 3.2mm ID

These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.



TENTUBE DIMENSIONS



Panel Dimensions

	PANEL OPENING	PANEL THICKNESS MAX.—MIN.
COUPLING BODIES	see drawing	.44— .06

Fitting Bodies • ACETAL/POLYPROPYLENE



TERMINATION COMPLETE COUPLING SET

COUPLING BODY WITH FEMALE FITTING BODIES

COUPLING INSERT WITH MALE FITTING INSERTS

TUBING SIZE	METRIC EQ.	ACETAL STRAIGHT THRU	ACETAL SHUTOFF	POLYPROPYLENE STRAIGHT THRU
1/16" ID	1.6mm ID	TT1001	TTD1001	TT100112
1/8" ID	3.0mm ID	TT10M3	TTD10M3	
1/8" ID	3.2mm ID	TT1002	TTD1002	TT100212
1/16" ID	1.6mm ID	TFB1001	TFBD1001	TFB100112
1/8" ID	3.0mm ID	TFB10M3	TFBD10M3	
1/8" ID	3.2mm ID	TFB1002	TFBD1002	TFB100212
Without fitting bodies		TFB10		
1/16" ID	1.6mm ID	TMB1001		TMB100112
1/8" ID	3.0mm ID	TMB10M3		
1/8" ID	3.2mm ID	TMB1002		TMB100212
Without fitting inserts		TMB10		

Fitting Inserts • ACETAL/POLYPROPYLENE



TERMINATION IN-LINE HOSE BARB

IN-LINE HOSE BARB (FEMALE)

TUBING SIZE	METRIC EQ.	ACETAL STRAIGHT THRU	ACETAL SHUTOFF	POLYPROPYLENE STRAIGHT THRU
1/16" ID	1.6mm ID	TMF01		TMF0112
1/8" ID	3.0mm ID	TMFM3		
1/8" ID	3.2mm ID	TMF02		TMF0212
1/16" ID	1.6mm ID	TFF01	TFFD01	TFF0112
1/8" ID	3.0mm ID	TFFM3	TFFDM3	
1/8" ID	3.2mm ID	TFF02	TFFD02	TFF0212

Note: Acetal bodies and inserts are also available in white. To order, add MWHT to the end of the part number.

Accessories



DESCRIPTION

TUBE SHROUD: snaps into either half

PART NO.

TS10

PANEL MOUNT ADAPTER & NUT: 7/16" max. panel thickness; requires 1.875" diameter hole

TPM10

Note: Use TMF and TFF inserts and bodies for custom designed assemblies.

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. Couplings are pictured with valves unless otherwise noted.

TWIN TUBE & SIXTUBE SERIES CONNECTOR

Twin Tube Specifications

PRESSURE:

Vacuum to 120 psi, 8.3 bar per line

TEMPERATURE:

-40°F to 180°F (-40°C to 82°C)

MATERIALS:

Main components: Acetal, ABS

Valves: Acetal

Thumb latch: Stainless steel

External springs and pin: Stainless steel

O-rings: Buna-N

COLOR: Natural white with aqua latch

TUBING SIZES:

1/16" to 1/8" ID, 1.6mm to 3.2mm ID

Sixtube Specifications

PRESSURE:

Vacuum to 100 psi, 6.9 bar per line

TEMPERATURE:

Acetal fitting inserts:

-40°F to 180°F (-40°C to 82°C)

Polypropylene fitting inserts:

32°F to 180°F (0°C to 82°C)

MATERIALS:

Main components: Acetal

Valves: Acetal

Fitting inserts: Acetal, polypropylene

Thumb latch: Acetal

Valve spring: 316 stainless steel

O-rings: Buna-N with acetal or EPDM with polypropylene

COLOR: Natural white with aqua latch

TUBING SIZES:

1/16" to 1/8" ID, 1.6mm to 3.2mm ID

NOTE: Caution must be observed when ordering Sixtube assemblies. Body and insert halves which both contain female or male fittings will not couple. Contact CPC for questions and ordering assistance.

The Twin Tube™ coupling provides one easy-to-use quick disconnect for two separate fluid lines. The non-valved Twin Tube maintains two individual flow paths in one coupling. Featuring the CPC thumb latch, the Twin Tube can disconnect two lines with the push of a button. The panel mount design keeps a low profile on the front of the equipment panel.

The Sixtube™ coupling provides one easy-to-use quick disconnect for up to six separate fluid lines. The Sixtube is available with valves on either side for maximum design flexibility. Featuring the CPC thumb latch, the Sixtube can disconnect up to six lines with the push of a button. The snap-in panel mount design keeps a low profile on the front of the equipment panel.

FEATURES

Two/six line connection

Separate flow paths

Sixtube insert is keyed to body

Free coupling rotation (Twin Tube)

CPC thumb latch

BENEFITS

Fast, efficient operation

Pressure and/or vacuum in one coupling


Ensures correct line orientation

Eliminates kinked tubing


One-hand connection and disconnection

These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.


Twin Tube Water Flow



Sixtube Water Flow




Sixtube Air Flow, 100 psig Inlet Pressure



TWINTUBE & SIXTUBE DIMENSIONS


Twin Tube™ Body Panel Mount Dimensions

	PANEL NUT HEX	PANEL NUT THREAD
COUPLING INSERTS	13/16	11/16-24UNEF



Maximum Panel Thickness: 1/2"
Minimum Panel Thickness: 0.02"

Sixtube™ Insert Panel Mount Dimensions



Twintube Coupling Bodies • ACETAL/ABS



ABS part shown

**TERMINATION
PANEL MOUNT
HOSE BARB**

TUBING SIZE
1/16" ID
1/8" ID

METRIC EQ.
1.6mm ID
3.2mm ID

**ACETAL
STRAIGHT THRU**
PTC16010
PTC16020

**ABS
STRAIGHT THRU**
PTC1602096

Twintube Coupling Inserts • ACETAL/ABS



Acetal part shown

**TERMINATION
IN-LINE
HOSE BARB**

TUBING SIZE
1/16" ID
1/8" ID

METRIC EQ.
1.6mm ID
3.2mm ID

**ACETAL
STRAIGHT THRU**
PTC22010
PTC22020

**ABS
STRAIGHT THRU**
PTC2202096

Sixtube Coupling Bodies • ACETAL/POLYPROPYLENE



Acetal part shown

**TERMINATION
WITH MALE FITTING
INSERTS**

TUBING SIZE
1/16" ID
1/8" ID

METRIC EQ.
1.6mm ID
3.0mm ID
3.2mm ID

**ACETAL
STRAIGHT THRU**
SXM1701
SXM17M3
SXM1702

**ABS
SHUTOFF**

**POLYPROPYLENE
STRAIGHT THRU**
SXM170112
SXM170212

**WITH FEMALE
FITTING BODIES**

1/16" ID
1/8" ID

1.6mm ID
3.0mm ID
3.2mm ID

SXF1701
SXF17M3
SXF1702

SXFD1701
SXFD17M3
SXFD1702

SXF170112
SXF170212

WITHOUT FITTINGS

SX17

Sixtube Coupling Inserts • ACETAL/POLYPROPYLENE



Acetal part shown

**TERMINATION
WITH MALE FITTING
INSERTS**

TUBING SIZE
1/16" ID
1/8" ID

METRIC EQ.
1.6mm ID
3.0mm ID
3.2mm ID

**ACETAL
STRAIGHT THRU**
SXM4201
SXM42M3
SXM4202

**ABS
SHUTOFF**

**POLYPROPYLENE
STRAIGHT THRU**
SXM420112
SXM420212

**WITH FEMALE
FITTING BODIES**

1/16" ID
1/8" ID

1.6mm ID
3.0mm ID
3.2mm ID

SXF4201
SXF42M3
SXF4202

SXFD4201
SXFD42M3
SXFD4202

SXF420112
SXF420212

WITHOUT FITTINGS


SX42

Accessories

DESCRIPTION
SIXTUBE PRESSURE PLUGS

PART NO.
TMPMWH7

MULTI-MOUNT SERIES CONNECTOR



Multi-Mount couplings provide one easy-to-use coupling for connecting from three to five lines at once. Multi-mount couplings are available in a wide variety of materials including acetal and chrome-plated brass. Multi-mounts are keyed to prevent mismatched connections and can be configured with or without valves for maximum design flexibility.

FEATURES

Three to five line connection
Separate flow paths
Insert is keyed to body
Acetal or chrome-plated brass

BENEFITS

Fast, efficient operation
Pressure and/or vacuum in one coupling
Ensures correct line orientation
Maximize design flexibility

Specifications

PRESSURE:

Minimum: Vacuum

Maximum: Brass = 500 psi / no. of stations
or Acetal = 240 psi / no. of stations

TEMPERATURE:

-40°F to 180°F (-40°C to 82°C)

MATERIALS:

Main components: Acetal or chrome-plated brass

Thumb latch: Stainless steel

Mounting Plate: Black anodized aluminum

Valves: Acetal

Valve spring: 316 stainless steel

External springs and pin: Stainless steel

O-ring: Buna-N


TUBING SIZES:

1/8" to 3/8" ID, 3.2mm to 9.5mm ID

Retaining clip is included with each insert

Multiple mount inserts are designed for mounting in 1/4" thick plates

Note: To order in chrome-plated brass, eliminate the "P" at the beginning of the part number.



Four-Step Multi-Mount Ordering Process

STEP 1: Determine flow size and termination type.


STEP 2: Order two "multiple mount plates" (one for the coupling bodies and one for the coupling inserts) with the appropriate number of connection stations for your specific application (available in 3, 4, or 5 connections, or construct your own). Refer to next page.

STEP 3: Order two "standard panel mount coupling bodies with thumb latches" for the exterior stations.

STEP 4: Order an appropriate number of "multiple mount coupling bodies without thumb latches" to accommodate the remaining interior stations.

STEP 5: Order an appropriate number of "multiple mount inserts" to connect with standard and multiple mount bodies.

MULTI-MOUNT SERIES DIMENSIONS




A = Height/Diameter **B** = Total Length **D** = Elbow Radial Length

Multiple mount plates are keyed to prevent misconnections. >>
Multiple mount minimum coupling spacing: CPC offsets the last hole on the mounting plates so they cannot be misconnected.

MM SERIES 1/8" Flow



LM SERIES 1/4" Flow



Multiple Mount Plates

Information in RED indicates 1/8" flow couplings. These are not compatible with 1/4" flow couplings in non-shaded sections.



NUMBER OF STATIONS	1/8" FLOW SIZE	LENGTH	1/4" FLOW SIZE	LENGTH
3	CP103	2.60	LCP103	3.00
4	CP104	3.35	LCP104	3.35
5	CP105	4.10	LCP105	4.90

Retaining Rings

COUPLING SERIES	PART NO. (REPLACEMENTS)
MC/PMC	101700
LC/PLC	278100

Coupling Bodies • ACETAL



TERMINATION
PANEL MOUNT
FERRULELESS
POLYTUBE FITTING,
PTF†

PANEL MOUNT
HOSE BARB

PANEL MOUNT
FEMALE THREAD

TUBING/THREAD SIZE	METRIC EQ.	STRAIGHT THRU	SHUTOFF	A	B	D
1/4" OD, .17" ID	6.4mm OD, 4.3mm ID	PMM1204	PMMD1204	.72	1.72	
1/4" OD, .17" ID	6.4mm OD, 4.3mm ID	PLM12004	PLMD12004	.94	1.82	
3/8" OD, .25" ID	9.5mm OD, 6.4mm ID	PLM12006	PLMD12006	.94	1.95	
1/8" ID	3.2mm ID	PMM1602	PMMD1602	.72	1.65	
3/16" ID	4.8mm ID	PMM1603	PMMD1603	.72	1.85	
1/4" ID	6.4mm ID	PMM1604	PMMD1604	.72	1.85	
1/4" ID	6.4mm ID	PLM16004	PLMD16004	.94	1.95	
5/16" ID	7.9mm ID	PLM16005	PLMD16005	.94	1.95	
3/8" ID	9.5mm ID	PLM16006	PLMD16006	.94	1.95	
10-32 UNF		PMM181032	PMMD181032	.72	1.25	

Coupling Inserts • ACETAL



TERMINATION
IN-LINE
FERRULELESS
POLYTUBE FITTING,
PTF†

IN-LINE
HOSE BARB

ELBOW
FERRULELESS
POLYTUBE FITTING,
PTF†

TUBING/THREAD SIZE	METRIC EQ.	STRAIGHT THRU	SHUTOFF	A	B	D
5/32" OD, .10" ID	4.0mm OD, 2.5mm ID	PMM20025	PMMD20025	.58	1.86/1.96	
1/4" OD, .17" ID	6.4mm OD, 4.3mm ID	PMM2004	PMMD2004	.58	1.77/1.87	
1/4" OD, .17" ID	6.4mm OD, 4.3mm ID	PLM20004	PLMD20004	.72	2.10/2.23	
3/8" OD, .25" ID	9.5mm OD, 6.4mm ID	PLM20006	PLMD20006	.72	2.02/2.15	
1/8" ID	3.2mm ID	PMM2202	PMMD2202	.56	1.87/1.97	
3/16" ID	4.8mm ID	PMM2203	PMMD2203	.58	2.08/2.18	
1/4" ID	6.4mm ID	PMM2204	PMMD2204	.58	1.83/1.93	
1/4" ID	6.4mm ID	PLM22004	PLMD22004	.72	2.20/2.33	
5/16" ID	7.9mm ID	PLM22005	PLMD22005	.72	2.20/2.33	
3/8" ID	9.5mm ID	PLM22006	PLMD22006	.72	2.03/2.16	
1/4" OD, .17" ID	6.4mm OD, 4.3mm ID	PMM2104	PMMD2104	.53	1.41/1.51	.77

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. Couplings are pictured with valves unless otherwise noted. †NOTE: CPC's Ferruleless Polytube Fitting terminations do not require ferrules to achieve a secure connection, which makes them easier to use and reuse. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc.

BQ45GL SERIES CONNECTOR

Specifications ● ● ●

TEMPERATURE:

32°F to 120°F (0°C to 49°C)

MATERIALS:

Base Cap: High density polyethylene

Gasket: Low density polyethylene

Packaging Vent: Hydrophobic PTFE

Quick Disconnects: Polypropylene, with 316 stainless steel springs and EPDM o-rings

FitQuik Connector: Polypropylene

COLOR: Blue

TUBING SIZES:

FitQuik connector: 1/4" OD

DIP tube interface: 1/4" ID

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC products in their own application conditions.



BQ45GL Series Bottle Caps include a quick disconnect coupling or FitQuik® connector integrated into a cap designed for 45GL bottles. The BQ45GL series feature a hydrophobic packaging vent, polyethylene gasket and a hose barb for mounting a dip tube. Adding quick disconnects to media bottles makes changing laboratory consumable products safer and easier.

FEATURES

Factory installed quick disconnects

Hydrophobic packaging vent

Polyethylene foam gasket

Integral hose barb

BENEFITS


Ensures cap properly seals to bottle (even without sealing rings)

Encourages proper fluid handling protocol allowing easy disconnections to replace or refill consumables in the correct location

Allows dispensing from container while preventing accidental spillage

Allows for mounting of 1/4" ID DIP tube

BQ45GL DIMENSIONS



- A = Coupling
- B = Cap Height
- C = Cap Diameter

Bottle Caps • POLYETHYLENE



DESCRIPTION
 GL45 HDPE CAP WITH POLYETHYLENE FOAM SEALING GASKET, HYDROPHOBIC VENT AND INTEGRAL VALVED PMC12 BODY QUICK DISCONNECT INTERFACE

PART NO.	DIP TUBE SIZE	CONNECTOR SIZE	A	B	C
BQ45GL1001	1/4" ID	1/4" OD	0.68"	0.83"	2.04"


GL45 HDPE CAP WITH POLYETHYLENE FOAM SEALING GASKET, HYDROPHOBIC VENT AND INTEGRAL VALVED PMC12 INSERT QUICK DISCONNECT INTERFACE

BQ45GL2001	1/4" ID	1/4" OD	1.08"	0.83"	2.04"
------------	---------	---------	-------	-------	-------


GL45 HDPE CAP WITH POLYETHYLENE FOAM SEALING GASKET, HYDROPHOBIC VENT AND INTEGRAL POLYPROPYLENE ELBOW FITTING (WITH 1/4" HOSE BARB)

BQ45GL5001	1/4" ID	1/4" OD	0.63"	0.83"	2.04"
------------	---------	---------	-------	-------	-------

NOTES:



HYBRID SERIES CONNECTOR



Hybrid Connectors integrate air lines, electrical connections and fluid lines into a single, compact connection point for remote tools on medical devices and equipment. Eliminating the potential for misconnecting tubing and wires, CPC's Hybrid Connector platform options reduce multiple connections and allow clinicians or patients to quickly and easily change or replace modular tools, umbilicals or hand pieces.

Large Format Hybrid Connector – Now available with four times the flow capacity, this connector features multiple dry-break couplings and easy-to-use twist latch for secure, repeatable connection of multiple lines.

Specifications ● ● ●

PRESSURE:

Vacuum to 45 psi, 3.1 bar

TEMPERATURE:

32°F to 120°F (0°C to 49°C)

MATERIALS:

Non-wetted coupler components: Glass-filled polypropylene

Wetted coupler components: Glass-filled polypropylene

Springs: Stainless steel

Electrical contacts: Gold-plated copper alloy

O-rings: EPDM

Fluid tubing: Polyurethane (PU)

Umbilical tubing: PVC

COLOR: Gray

TERMINATIONS:

Panel: Two 1/8" (3.2mm) hose barbs on panel and four 20 ga wires with 12" (304.3mm) pigtail

Umbilical Hose: 8' (2.44M) umbilical with two 1/8" (3.2mm) ID PU tubing and four 20ga wires with 3" (76.2mm) pigtail

NUMBER OF FLUID LINES: 2

ELECTRICAL SPECIFICATIONS

Voltage: Up to 24VDC

Current: Up to 3 Amps

Wire gauge: 20AWG

Number of contacts: 4

FEATURES

Single connection point for pneumatic, fluid, and power connections between a device and its tool/hand piece

Non-spill shutoff valves with dry-break technology

Turnkey solution

Off-the-shelf assembly

Custom options available

BENEFITS

Increases safety and makes systems data more user friendly


Eliminate fluid drips upon disconnect and minimize air inclusion

Reduces multiple components

Minimizes engineering design and manufacturing effort


Flexibility to add additional fluid connector or electrical contacts

HYBRID SERIES DIMENSIONS



A = Height/Diameter B = Total Length C = Pigtail D = Umbilical

Panel Dimensions




Coupling Hose • POLYPROPYLENE




CONFIGURATION HOSE	FLOW PATHS 1/8" ID (3.2mm)	PART NO. HQC17002	A 2.00	B 2.80	C 3.00	D 8.00
------------------------------	--------------------------------------	-----------------------------	------------------	------------------	------------------	------------------

Coupling Panel • POLYPROPYLENE



CONFIGURATION PANEL MOUNT	FLOW PATHS 1/8" ID (3.2mm)	PART NO. HQC42001	A 1.96	B 1.12	C 12.00	D
-------------------------------------	--------------------------------------	-----------------------------	------------------	------------------	-------------------	----------



MINI HYBRID SERIES CONNECTOR



Mini Hybrid Connector – A compact, single connection point with a smaller form factor that is ideal for use in low-pressure applications where ease of use and ergonomics are important. This connector makes it easy to connect power, signal and gases in one simple motion.

FEATURES

- Easy-to-use breakaway design
- Small package design
- Streamlined exterior
- Proven design

BENEFITS

- Quick, automatic disconnect
- Minimize device size
- Clean, attractive appearance
- Accelerate product development

Specifications ● ● ●

PRESSURE:

Vacuum to 25 psi, 1.7 bar

TEMPERATURE:

40°F to 80°F (4°C to 27°C)

MATERIALS:

- External coupler components: PET
- Air coupler components: Acetal
- Springs: Stainless steel
- Panel Mount Nut: Zinc-plated steel
- Electrical contacts: Gold-plated copper alloy
- O-rings: Buna-N
- Air line: PVC

COLOR: Gray

EXTERNAL UMBILICAL HOSE: 4 feet (121 cm) PVC

WIRE: 22AWG PVC jacket

TERMINATIONS:



- Panel: 1/16" hose barb and two 22AWG wires with 11" pigtail
- Umbilical: 4' (121 cm) umbilical with one 1/16" ID PVC tube and two 22AWG wires with 6" pigtail
- Number of air lines: 1

ELECTRICAL SPECIFICATIONS

- Voltage: Up to 24VDC
- Current: Up to 3 Amps
- Wire: 22AWG with PVC jacket
- Number of contacts: 2

MINI HYBRID SERIES DIMENSIONS

Panel Dimensions




Coupling Hose • PET AND ACETAL

	CONFIGURATION HOSE	FLOW PATH 1/16" ID (1.6mm)	PART NO. MHQC17000	A .62	B 2.00

Coupling Panel • PET AND ACETAL

	CONFIGURATION PANEL MOUNT	FLOW PATH 1/16" ID (1.6mm)	PART NO. MHQC42000	A 1.00	B .60

NOTES:





INTELLIGENT FLUID CONNECTIONS





Redefine what's possible for controlling, protecting and streamlining fluid handling processes. RFID-enabled quick disconnect couplings allow the robust transfer of fluid and information in a limitless number of applications across multiple industries.

INTELLIGENT FLUID CONNECTIONS



RFID-based IdentiQuik® quick disconnect couplings redefine what's possible for controlling, protecting and streamlining fluid handling processes. A patented design embeds RFID-based electronic intelligence into a variety of our most popular and industry-leading coupling configurations, enabling the exchange of rewritable data once the coupling halves come within a few centimeters of one another. This intelligent technology allows you to protect your brand, minimize misconnections, prolong equipment life and increase efficiency.

IdentiQuik couplings are ideal for applications with a product involving: onboard electronics and parts or media that are consumable or expensive; the need to control the process to ensure the use of the right tool at the right time.

IdentiQuik couplings allow the robust transfer of fluid and information in a limitless number of applications across multiple industries.

Examples of potential applications include:

- >> ***Connection validation***
- >> ***Media validation***
- >> ***Operational control settings***
- >> ***Track and trace***
- >> ***Usage control***

THOUSANDS OF CONFIGURATIONS TO MEET YOUR NEEDS

IdentiQuik couplings are available in a vast array of sizes and configurations that includes all our most popular product lines, opening endless new possibilities for your fluid handling processes.

Use this table to quickly find the right IdentiQuik coupling for your application. Can't find the ideal solution from our standard offering? Let our engineered solutions team design one for you.

Flow Capacity



Spillage Upon Disconnect



OUR HIGHEST-FLOW-CAPACITY COUPLING

IdentiQuik® Universal Dispensing Coupler (UDC)



IdentiQuik Universal Dispensing Couplers (UDC) provide a universal connection to a 38mm fitment neck, allowing you to make instant connections to bulk packaging systems. The automatic flush face valves minimize costly or dangerous spillage, and an ergonomic design and large, shrouded thumb latch pad make the coupling easy to grip and simple to operate.

APPLICATIONS FOR UDC COUPLINGS INCLUDE:

- Bag-in-box (BIB) packaging systems
- Rigid bulk packaging systems
- Flexible bulk packaging systems
- Many more

UDC Coupling Readers • POLYPROPYLENE

TERMINATION	TUBING SIZE	METRIC EQ.	SHUTOFF	A	B
IN-LINE HOSE BARB (RS-232 Interface)	1/4" ID	6.4mm ID	iUDCDR1700400	2.00	3.49
	3/8" ID	9.5mm ID	iUDCDR1700600	2.00	3.49
	1/2" ID	12.7mm ID	iUDCDR1700800	2.00	3.49
	5/8" ID	15.9mm ID	iUDCDR1701000	2.00	3.49
	3/4" ID	19mm ID	iUDCDR1701200	2.00	3.49
IN-LINE HOSE BARB (USB Interface)	1/4" ID	6.4mm ID	iUDCDR1700401	2.0	3.49
	3/8" ID	9.5mm ID	iUDCDR1700601	2.0	3.49
	1/2" ID	12.7mm ID	iUDCDR1700801	2.0	3.49
PANEL MOUNT HOSE BARB (RS-232 Interface)	1/4" ID	6.4mm ID	iUDCDR1600400	For product dimensions visit cpcworldwide.com	
	3/8" ID	9.5mm ID	iUDCDR1600600		
	1/2" ID	12.7mm ID	iUDCDR1600800		
PANEL MOUNT HOSE BARB (USB Interface)	1/4" ID	6.4mm ID	iUDCDR1600401	For product dimensions visit cpcworldwide.com	
	3/8" ID	9.5mm ID	iUDCDR1600601		
	1/2" ID	12.7mm ID	iUDCDR1600801		

UDC Caps • ACETAL

TERMINATION	DESCRIPTION	METRIC EQ.	SHUTOFF	A	B
THREAD-ON 38MM VALVED	Without thread seal	38mm	iUDCDTCN3803	1.70	1.47
	With thread seal	38mm	iUDCDTCS3803	1.70	1.47

• POLYPROPYLENE

TERMINATION	DESCRIPTION	METRIC EQ.	SHUTOFF	A	B
SNAP-IN 38MM VALVED		38mm	iUDCDTSN0000	1.62	1.76
Note: Snap-in closure designed to fit Scholle 900 bag necks.					
THREAD-ON 38MM VALVED	Without thread seal	38mm	iUDCDTCN3800	1.70	1.48
	With thread seal	38mm	iUDCDTCS3800	1.70	1.48

Specifications

PRESSURE:

20" Hg Vacuum to 15 psi, 1 bar (body only)

TEMPERATURE:

32°F to 150°F (0°C to 65°C)

MATERIALS:

Main body components and valves:
Polypropylene and Acetal

Thumb latch: Polypropylene

Springs: 316 stainless steel

O-rings (food grade): Silicone, Buna-N and EPDM

INTERFACE: Multi-drop 2-ft. (60 cm) cable with RS-232 or USB connector

OPERATING VOLTAGE:

RS-232: 8V – 24V • USB: 5V

POWER CONSUMPTION:

1.2W maximum

RF COMMUNICATION RANGE:

Approximately 1"

RFID TAG:

ISO 15693, 13.56MHz, 112 bytes programmable

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. Couplings are pictured with valves unless otherwise noted.

CHEMICAL-RESISTANT AND HIGHLY VERSATILE

IdentiQuik® PLC12 Coupling



IdentiQuik PLC12 Couplings are injection-molded from polypropylene thermoplastic and are resistant to many chemical solutions.

This popular coupling features one-hand connection and disconnection, and offers the flexibility of multiple configurations and terminations. Its polypropylene provides superior chemical resistance, and the EPDM o-ring adds expanded chemical compatibility for more demanding applications.

PLC12 couplings can be ordered in a vast range of sizes and configurations to meet the needs of your application.

APPLICATIONS FOR PLC12 COUPLINGS INCLUDE:

- Flavor concentrates
- Laser cooling
- Cosmetic ingredients
- Many more

Specifications

PRESSURE:

Vacuum to 120 psi, 8.3 bar

TEMPERATURE:

32°F to 150°F (0°C to 65°C)

MATERIALS:

Main components and valves: Polypropylene

Thumb latch: Stainless steel

Valve spring: 316 stainless steel

External springs and pin: Stainless steel

O-rings: EPDM

COLOR:

Almond

TUBING SIZE:

1/4" to 3/8", 6.4mm to 9.5mm

INTERFACE:

Multi-drop 2-ft. (60 cm) cable with RS-232 or USB connector

OPERATING VOLTAGE:

RS-232: 8V – 24V

USB: 5V

POWER CONSUMPTION:

1.2W maximum

RF COMMUNICATION RANGE:

Approximately 1"

RFID TAG:

ISO 15693, 13.56MHz, 112 bytes programmable

Coupling Readers • POLYPROPYLENE

TERMINATION IN-LINE HOSE BARB (RS-232 Interface)	TUBING SIZE	METRIC EQ.	STRAIGHT THRU	SHUTOFF	A	B
	1/4" ID 3/8" ID	6.4mm ID 9.5mm ID		iPLCDR1700400 iPLCDR1700600	1.39 1.39	2.78 2.78
IN-LINE HOSE BARB (USB Interface)	1/4" ID 3/8" ID	6.4mm ID 9.5mm ID		iPLCDR1700401 iPLCDR1700601	1.00 1.05	1.38/2.05 1.74/1.87

Coupling Inserts • POLYPROPYLENE

TERMINATION IN-LINE HOSE BARB (RS-232 Interface)	TUBING SIZE	METRIC EQ.	STRAIGHT THRU	SHUTOFF	A	B
	1/4" ID 3/8" ID	6.4mm ID 9.5mm ID	iPLCT2200400 iPLCT2200600	iPLCDT2200400 iPLCDT2200600	1.39 1.39	2.78 2.78
ELBOW HOSE BARB (RS-232 Interface)	1/4" ID 3/8" ID	6.4mm ID 9.5mm ID	iPLCT2300400 iPLCT2300600	iPLCDT2300400 iPLCDT2300600	1.48 1.48	1.27/1.40 1.33/1.46

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. Couplings are pictured with valves unless otherwise noted.

FAST, SAFE AND LEAK-FREE FLUID CONNECTIONS

IdentiQuik® NS4 Non-Spill (NS) Coupling



Specifications ● ● ●

PRESSURE: Vacuum to 120 psi, 8.3 bar

TEMPERATURE: 32°F to 150°F (0°C to 65°C)

MATERIALS:

Main body components and valves:
Glass-filled polypropylene

Thumb latch: Glass-filled polypropylene

Springs: 316 stainless steel

Valve spring: 316 stainless steel

External spring: 316 stainless steel

O-rings: EPDM (FKM optional)

Soft-touch overmold: TPV*

COLOR: Gray with dark gray overmold

LUBRICANTS: Krytox® PFPE (inert)

TUBING SIZE: 1/8" to 3/8", 3.2mm to 9.5mm

INTERFACE:

Multi-drop 2-ft. (60 cm) cable with RS-232 or USB connector

OPERATING VOLTAGE:

RS-232: 8V – 24V

USB: 5V

POWER CONSUMPTION: 1.2W maximum

RF COMMUNICATION RANGE:

Approximately 1"

RFID TAG:

ISO 15693, 13.56MHz, 112 bytes programmable

*The overmold material is known as TPV (thermoplastic vulcanizate). This TPV is an alloy of polypropylene thermoplastic and fully vulcanized EPDM rubber. The material is typically resistant to water, acids and bases.

IdentiQuik NS4 Non-Spill (NS) Couplings are designed with double-sided non-spill shutoff valves that enable drip-free disconnections and prevent air entering the lines at connection, minimizing downtime and enhancing operator safety. These easy-to-use, lightweight couplings are chemically resistant and offer broad chemical compatibility.

APPLICATIONS FOR NS4 COUPLINGS INCLUDE:

- Large-format printing
- Blood analysis
- Inkjet printing
- Many more

Coupling Readers • POLYPROPYLENE



TERMINATION
IN-LINE
HOSE BARB
(RS-232 Interface)

TUBING SIZE

1/8" ID
1/4" ID
3/8" ID

METRIC EQ.

3.2mm
6.4mm
9.5mm

SHUTOFF

iNS4DR1700200
iNS4DR1700400
iNS4DR1700600

A

2.15
2.15
2.15

B

3.49
3.49
3.49

IN-LINE
HOSE BARB
(USB Interface)

1/4" ID
3/8" ID
1/2" ID

6.4mm ID
9.5mm ID
12.7mm ID

iNS4DR1700201
iNS4DR1700401
iNS4DR1700601

2.15
2.15
2.15

3.40
3.40
3.40

Coupling Inserts • POLYPROPYLENE



TERMINATION
IN-LINE
HOSE BARB
(RS-232 Interface)

TUBING SIZE

1/8" ID
1/4" ID
3/8" ID

METRIC EQ.

3.2mm
6.4mm
9.5mm

SHUTOFF

iNS4DT2200200
iNS4DT2200400
iNS4DT2200600

A


For product
dimensions visit
cpcworldwide.com

B

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. Couplings are pictured with valves unless otherwise noted.

OUR MOST COMPACT COUPLING

IdentiQuik® Subminiature Coupling (SMC)



IdentiQuik Subminiature Couplings (SMC) offer a reliable and secure alternative to luer-type connections, combining twist-to-connect simplicity with the security of RFID technology. Free rotation eliminates kinking and accidental connection during use.

APPLICATIONS FOR SMC COUPLINGS INCLUDE:

- Air lines
- Reagents
- Surgical irrigation lines
- Many more

Coupling Bodies • ACETAL



TERMINATION
IN-LINE
HOSE BARB

TUBING SIZE
1/16" ID
1/8" ID

METRIC EQ.
1.6mm ID
3.2mm ID

STRAIGHT THRU
iSMFT0103
iSMFT0203

SHUTOFF
iSMFDT0103
iSMFDT0203

A
.76
.76

B
.76/.91
.91/.91

• POLYPROPYLENE



TERMINATION
IN-LINE
HOSE BARB

TUBING SIZE
1/16" ID
1/8" ID

METRIC EQ.
1.6mm ID
3.2mm ID

STRAIGHT THRU
iSMFT0100
iSMFT0200

A
.76
.76

B
.76
.91

Coupling Inserts • ACETAL



TERMINATION
IN-LINE HOSE BARB
(Acetal Locking Sleeve)

TUBING SIZE
1/16" ID
1/8" ID

METRIC EQ.
1.6mm ID
3.2mm ID

STRAIGHT THRU
iSMMT0103
iSMMT0203

A
.76
.76

B
.76
.91

• POLYPROPYLENE



TERMINATION
IN-LINE HOSE BARB
(Acetal Locking Sleeve)

TUBING SIZE
1/16" ID
1/8" ID

METRIC EQ.
1.6mm ID
3.2mm ID

STRAIGHT THRU
iSMMT0100
iSMMT0200

A
.76
.76

B
.76
.91

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. Couplings are pictured with valves unless otherwise noted.

Specifications

PRESSURE: Vacuum to 100 psi, 6.9 bar

TEMPERATURE: 32°F to 150°F (0°C to 65°C)

MATERIALS:

Main components and valves: Acetal, Polypropylene

Locking sleeves: Acetal

Valves: Acetal

Valve spring: 316 stainless steel

O-rings: Buna-N with acetal or EPDM with polypropylene

COLOR (MAIN COMPONENTS):

Natural white (acetal), almond (polypropylene)

TUBING SIZE:

1/16" to 1/8" ID, 1.6mm to 3.2mm ID

NOTE: For 1/16" ID tubing, maximum tube OD is .150".

INTERFACE: Multi-drop 2-ft. (60 cm) cable with RS-232 or USB connector

OPERATING VOLTAGE:

RS-232: 8V – 24V • USB: 5V

POWER CONSUMPTION: 1.2W maximum

RF COMMUNICATION RANGE:

Approximately 1"

RFID TAG:

ISO 15693, 13.56MHz, 112 bytes programmable

UNMATCHED CUSTOMIZATION CAPABILITIES




For more than 35 years, CPC engineers have worked with customers worldwide to design application-specific solutions that resolve their fluid handling-related challenges and improve product performance. We can do the same for you.

COMMON IDENTIQUIK® COUPLINGS CUSTOM APPLICATIONS INCLUDE:

- Weight, pressure, temperature and flow sensing
- Bulkhead mount readers
- Multiplexing technology

CONNECTIONS for LIFE SCIENCES MEDICAL & BIOPROCESSING






CPC is the leading provider of quick disconnect couplings, connectors and fittings for the life sciences and the leader in single-use connection technology for bioprocessing applications.

CPC thinks beyond the point of connection to improve patient safety, prevent misconnections and increase the overall usability and effectiveness of medical devices. Our products are used across a broad range of medical devices and equipment, including surgical, dialysis, blood pressure monitoring, patient therapy devices and in vitro diagnostics.

CPC's wide range of robust sterile connect and disconnect solutions allow biopharmaceutical manufacturers to easily combine multiple components, single-use or hybrid systems while maintaining media sterility and integrity. Our genderless sterile connector technology maximizes system flexibility and simplifies process integration.

CPC's Quality Management System is ISO 13485 certified and our products for the life sciences are manufactured in an ISO Class 7 certified cleanroom.

SMC SERIES



The SMC is a twist-to-connect coupling that provides a reliable and more secure alternative to luer-type connections. It also allows for the tubing to rotate freely when connected. This important feature prevents both kinked tubing and accidental disconnection during use.

FEATURES

- Twist to connect
- Free coupling rotation
- Safer; prevents misconnections

BENEFITS

- Prevents accidental disconnects
- Eliminates kinked tubing
- Does not mate to luers

Liquid Flow Rate Information for Couplings

The chart below shows the flow rate for CPC couplings. Each coupling was tested with water at 70°F (21°C). To determine flow rates for specific coupling configurations use the formula at the right.

C_v VALUES FOR SUBMINIATURE COUPLINGS

BODIES	INSERTS	SMM01	SMM02
SMF01		.03	.03
SMF02		.03	.19

$$Q = C_v \sqrt{\frac{\Delta P}{S}}$$

- Q = Flow rate in gallons per minute
- C_v = Average coefficient across various flow rates (see chart)
- ΔP = Pressure drop across coupling (psi)
- S = Specific gravity of liquid

Specifications

PRESSURE:

Vacuum to 100 psi, 6.9 bar

TEMPERATURE:

-40°F to 250°F (-40°C to 121°C)

MATERIALS:

Main components: Polycarbonate, USP Class VI, ADCF

Locking sleeves: Polycarbonate, USP Class VI, ADCF

O-rings: Buna-N, USP Class V, ADCF

COLOR:

Main components: Purple tint



STERILIZATION:

Gamma: Up to 50 kGy irradiation


TUBING SIZES:

1/16" to 1/8" ID, 1.6mm to 3.2mm ID

These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.



SMC SERIES DIMENSIONS



Coupling Bodies • POLYCARBONATE

	TERMINATION	TUBING SIZE	METRIC EQ.	STRAIGHT THRU	A	B
	IN-LINE	1/16" ID	1.6mm ID	SMF0191	.48	.75/.90
	HOSE BARB	1/8" ID	3.2mm ID	SMF0291	.48	.90

Coupling Inserts • POLYCARBONATE

	TERMINATION	TUBING SIZE	METRIC EQ.	STRAIGHT THRU	A	B
	IN-LINE	1/16" ID	1.6mm ID	SMM0191	.48	.75
	HOSE BARB	1/8" ID	3.2mm ID	SMM0291	.48	.90

Coupling Set • POLYCARBONATE

	TERMINATION	TUBING SIZE	METRIC EQ.	STRAIGHT THRU	A	B
	HOSE BARB	1/16" ID	1.6mm ID	SMC0191	.48	1.32
		1/8" ID	3.2mm ID	SMC0291	.48	1.61

SRC SERIES



The SRC connector is a small bore connector that eliminates the potential for misconnections with luer fittings. The intuitive design is simple for end users to operate and provides an audible "click" for added assurance and a secure, leak-free connection. This new connector features a unique elastomeric seal with a smooth, gap-free flow path that provides better flow characteristics and eliminates stagnant flow areas.

FEATURES

- Prevents misconnections
- Reliable elastomeric seals
- Audible "click" and positive feel
- Allows tubing rotation

BENEFITS

- Won't connect to IV lines and other non-compatible applications
- Leak-free connections
- Operators know when a secure, reliable connection is made
- Prevents accidental disconnect or kinked tubing

Specifications ● ● ●

PRESSURE:

Vacuum to 25 psi, 1.7 bar

TEMPERATURE:

32°F to 110°F (0°C to 43°C)
(rated for shipment uncoupled up to 160°F)

MATERIALS:

Main components: Polypropylene with overmolded TPE* pads, USP Class VI, ADCF

INTEGRAL SEALS:

Overmolded TPE*, USP Class VI, ADCF

COLOR:

White with blue pads

STERILIZATION:


EtO, e-beam or gamma

TUBING SIZES:


1/8" to 3/16" ID, 3.2mm to 4.8mm ID

**The overmold material TPV (thermoplastic vulcanizate) is used with the SRC polypropylene couplings. TPV is an alloy of polypropylene thermoplastic and fully vulcanized EPDM rubber. TPV is typically resistant to water, acids and bases. The overmold material TPE (thermoplastic elastomer) is used with the NS4 ABS couplings. TPE is a blend of additives and copolymers in a special formulation that forms extremely durable bonds to the ABS substrate, while offering the traditional properties of soft-touch overmold.*

✓ This graph is intended to give you a general idea of the performance capabilities of the product.



SRC SERIES DIMENSIONS



A = Height/Diameter
B = Total Length

Panel Dimensions

	PANEL OPENING	PANEL THICKNESS MAX.-MIN.	PANEL NUT HEX	PANEL NUT THREAD
COUPLING INSERTS	7/16	.21- .03	1/2	7/16-24UNS

Coupling Bodies

• POLYPROPYLENE

Add "CL" to the end of the plastic SRC part numbers below for cleanroom manufactured versions.

TERMINATION IN-LINE HOSE BARB	TUBING SIZE	METRIC EQ.	STRAIGHT THRU	A	B
	1/8" ID 3/16" ID	3.2mm ID 4.8mm ID	SRC1702 SRC1703	.62 .62	1.18 1.18

Coupling Inserts

• POLYPROPYLENE

TERMINATION IN-LINE HOSE BARB	TUBING SIZE	METRIC EQ.	STRAIGHT THRU	A	B
	1/8" ID 3/16" ID	3.2mm ID 4.8mm ID	SRC2202 SRC2203	.38 .38	1.19 1.19

• CHROME-PLATED BRASS

TERMINATION PANEL MOUNT HOSE BARB	TUBING SIZE	METRIC EQ.	STRAIGHT THRU	A	B
	1/8" ID 3/16" ID	3.2mm ID 4.8mm ID	SRC4202CB SRC4203CB	.57 .57	1.66 1.66

Accessories



PART NO.	DESCRIPTION	MATERIALS
SRC3L	Tethered cap and plug for SRC body and insert	White medical-grade TPE

MPC SERIES CONNECTOR

Specifications ● ● ●

PRESSURE:

Vacuum to 60 psi, 4.1 bar

TEMPERATURE:

ABS:

-40°F to 160°F (-40°C to 71°C)

Polycarbonate:

-40°F to 250°F (-40°C to 121°C)

Polysulfone:

-40°F to 300°F (-40°C to 149°C)

MATERIALS:

Main components:

ABS (white), USP Class VI

Polycarbonate (purple tint), USP Class VI, ADCF

Polysulfone (amber tint), USP Class VI, ADCF

Locking sleeves:

Polysulfone (white), USP Class VI, ADCF

Thumb Latches:

Polycarbonate (white), USP Class VI, ADCF

Polysulfone (amber tint), USP Class VI, ADCF

O-rings: Silicone (clear), platinum-cured, USP

Class VI, ADCF and Buna-N (black), USP Class V

STERILIZATION:

Gamma: Up to 50 kGy irradiation

Autoclave:

Polycarbonate: Up to 250°F (121°C), 30 minutes, up to 10 repetitions. Sterilize uncoupled only.

Polysulfone: Up to 270°F (132°C) for 60 minutes, up to 25 repetitions. Sterilize uncoupled only.

MPC Series couplings add ease of use and security to critical fluid handling applications. Choose from a full line of connectors and configurations, including pressure sealing caps and plugs, in sizes to fit 1/8" to 3/8" tubing. MPC couplings offer optional locking sleeves to further guard against accidental disconnects. In addition, coupling halves can be rotated when connected to reduce tube kinks.

FEATURES

Ergonomic thumb latch

USP Class VI materials

Sterilizable by autoclave, EtO, e-beam, or gamma

Parting line-free hose barb

ADCF-free materials

BENEFITS

Easy to operate – even with gloved hands


Meet biocompatibility requirements

Reusable, yet economical enough to allow disposability

Eliminates potential leak path

Meet BSE/TSE requirements

Product Dimensions




A = Height/Diameter
B = Total Length

TUBING SIZES:

1/8" to 3/8" ID (3.2mm to 9.5mm)

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions.

✓ This graph is intended to give you a general idea of the performance capabilities of each product line. The shaded area of the graph represents the operating range of the product family, i.e. upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.



MPC SERIES CONNECTOR DIMENSIONS

Coupling Bodies

A = Height/Diameter

B = Total Length

• ABS



TERMINATION
IN-LINE
HOSE BARB

TUBING
1/4" ID
3/8" ID

METRIC EQ.
6.4mm ID
9.5mm ID

FLOW
.21"
.29"

STRAIGHT THRU
MPC17004T
MPC17006T

A
.96 (24.4)
.96 (24.4)

B
1.30 (33.0)
1.30 (33.0)

• POLYCARBONATE



TERMINATION
IN-LINE
HOSE BARB

TUBING
1/8" ID
1/4" ID
3/8" ID

METRIC EQ.
3.2mm ID
6.4mm ID
9.5mm ID

FLOW
.09"
.21"
.29"

STRAIGHT THRU
MPC17002T03
MPC17004T03
MPC17006T03

A
.96 (24.4)
.96 (24.4)
.96 (24.4)

B
1.10 (27.9)
1.10 (27.9)
1.10 (27.9)



IN-LINE HOSE BARB
WITH LOCK

1/8" ID
1/4" ID
3/8" ID

3.2mm ID
6.4mm ID
9.5mm ID

.09"
.21"
.29"

MPCK17002T03
MPCK17004T03
MPCK17006T03

.99 (25.2)
.99 (25.2)
.99 (25.2)

1.10 (27.9)
1.30 (33.0)
1.30 (33.0)

• POLYSULFONE



TERMINATION
IN-LINE
HOSE BARB

TUBING
1/8" ID
1/4" ID
3/8" ID

METRIC EQ.
3.2mm ID
6.4mm ID
9.5mm ID

FLOW
.09"
.21"
.29"

STRAIGHT THRU
MPC17002T39
MPC17004T39
MPC17006T39

A
.96 (24.4)
.96 (24.4)
.96 (24.4)

B
1.10 (27.9)
1.10 (27.9)
1.10 (27.9)



IN-LINE HOSE BARB
WITH LOCK

1/8" ID
1/4" ID
3/8" ID

3.2mm ID
6.4mm ID
9.5mm ID

.09"
.21"
.29"

MPCK17002T39
MPCK17004T39
MPCK17006T39

.99 (25.2)
.99 (25.2)
.99 (25.2)

1.10 (27.9)
1.30 (33.0)
1.30 (33.0)

Coupling Inserts

• ABS



TERMINATION
IN-LINE
HOSE BARB

TUBING
1/4" ID
3/8" ID

METRIC EQ.
6.4mm ID
9.5mm ID

FLOW
.21"
.29"

STRAIGHT THRU
MPC22004TM
MPC22006TM

O-RING
Silicone Seal USP Class VI
Silicone Seal USP Class VI

A
.60 (15.2)
.60 (15.2)

B
1.30 (33.0)
1.30 (33.0)



IN-LINE
HOSE BARB

1/4" ID
3/8" ID

6.4mm ID
9.5mm ID

.21"
.29"

MPC22004T
MPC22006T

Buna-N Seal USP Class V
Buna-N Seal USP Class V

.60 (15.2)
.60 (15.2)

1.30 (33.0)
1.30 (33.0)

• POLYCARBONATE



TERMINATION
IN-LINE
HOSE BARB

TUBING
1/8" ID
1/4" ID
3/8" ID

METRIC EQ.
3.2mm ID
6.4mm ID
9.5mm ID

FLOW
.09"
.21"
.29"

STRAIGHT THRU
MPC22002T03M
MPC22004T03M
MPC22006T03M

O-RING
Silicone Seal USP Class VI
Silicone Seal USP Class VI
Silicone Seal USP Class VI

A
.60 (15.2)
.60 (15.2)
.60 (15.2)

B
1.10 (27.9)
1.30 (33.0)
1.30 (33.0)



IN-LINE
HOSE BARB

1/8" ID
1/4" ID
3/8" ID

3.2mm ID
6.4mm ID
9.5mm ID

.09"
.21"
.29"

MPC22002T03
MPC22004T03
MPC22006T03

Buna-N Seal USP Class V
Buna-N Seal USP Class V
Buna-N Seal USP Class V

.60 (15.2)
.60 (15.2)
.60 (15.2)

1.10 (27.9)
1.30 (33.0)
1.30 (33.0)

• POLYSULFONE



TERMINATION
IN-LINE
HOSE BARB

TUBING
1/8" ID
1/4" ID
3/8" ID

METRIC EQ.
3.2mm ID
6.4mm ID
9.5mm ID

FLOW
.09"
.21"
.29"

STRAIGHT THRU
MPC22002T39M
MPC22004T39M
MPC22006T39M

O-RING
Silicone Seal USP Class VI
Silicone Seal USP Class VI
Silicone Seal USP Class VI

A
.60 (15.2)
.60 (15.2)
.60 (15.2)

B
1.10 (27.9)
1.30 (33.0)
1.30 (33.0)

MPC SERIES CONNECTOR (cont.)

Mating Parts



SEALING CAP
MPC32003
MPC32039

SEALING CAP W/LOCK
MPCK32003
MPCK32039

MATERIAL
Polycarbonate
Polysulfone

A
.96 (24.4)
.99 (25.2)

B
1.30 (33.0)
1.30 (33.0)

SEALING PLUG
MPC30003M
MPC30039M

O-RING
Silicone Seal USP Class VI
Silicone Seal USP Class VI

MATERIAL
Polycarbonate
Polysulfone

A
.75 (19.1)
.75 (19.1)

B
1.24 (31.5)
1.24 (31.5)

PART NO.
MPC30L
MPC32L

DESCRIPTION
Leash plug for MPC body
Leash cap for MPC insert

MATERIALS
Soft, flexible, medical-grade PVC
Soft, flexible, medical-grade PVC

Liquid Flow Rate Information for Couplings

The chart below shows the flow rate for CPC couplings. Each coupling was tested with water at 70°F (21°C). To determine flow rates for specific coupling configurations use the formula at the right.

C_v VALUES FOR MPC SERIES COUPLINGS

BODIES	INSERTS	MPC22002T03	MPC22004T03	MPC22006T03
MPC17002T03		0.11	-	0.21
MPC17004T03		-	2.8	2.8
MPC17006T03		0.14	2.8	5.5

$$Q = C_v \sqrt{\frac{\Delta P}{S}}$$

Q = Flow rate in gallons per minute

C_v = Average coefficient across various flow rates (see chart)

ΔP = Pressure drop across coupling (psi)

S = Specific gravity of liquid

Note:
MPC Series mates with Back-to-Back Adapters (page 109), SaniQuik™ and Sanitary Series (pages 112-115).



BACK-TO-BACK SERIES CONNECTOR



MPC/MPX Back-to-Back Adapters give end users the flexibility of connecting single-use systems that feature identical coupling connections at the end of their tubing. Combining both MPC and MPX couplings provides a reducing option for users who need to transition between tubing diameters ranging from 1/8" to 1/2".

FEATURES

Compatible with MPC and MPX Series inserts

Tubing reduction option

Ergonomic thumb latches

ADCF-free materials

BENEFITS

Easy conversion to industry standard connections or single-use systems

Allows easy transition between multiple size tubing from 1/8" to 1/2" ID

Easy to operate - even with gloved hands

Meet BSE/TSE requirements

Specifications

PRESSURE:

Vacuum to 60 psi, 4.1 bar

TEMPERATURE:

Polycarbonate:

-40°F to 250°F (-40°C to 121°C)

Polysulfone:

-40°F to 300°F (-40°C to 149°C)

MATERIALS:

Main Components:

Polycarbonate (purple tint), USP Class VI, ADCF

Polysulfone (amber tint), USP Class VI, ADCF

Thumb Latches:

Polycarbonate (white), USP Class VI, ADCF

Polysulfone (amber tint), USP Class VI, ADCF

O-rings:

Silicone (clear), platinum-cured, USP Class VI, ADCF

STERILIZATION:

Gamma: Up to 50 kGy irradiation

Autoclave:

Polycarbonate: Up to 250°F (121°C) for 30 minutes, up to 10 repetitions.

Sterilize uncoupled only.

Polysulfone: Up to 270°F (132°C) for 60 minutes, up to 25 repetitions.

Sterilize uncoupled only.

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions.

Back-To-Back Insert Adapters

• POLYSULFONE



PART NO.

MPC22C2239M
MPC22X2239M
MPX22X2239M

TYPE

MPC to MPC
MPC to MPX
MPX to MPX

A

0.74 (18.8)
0.98 (25.0)
0.98 (25.0)

B

2.04 (51.0)
2.42 (61.5)
2.73 (69.5)

Note:
Mates with MPC and MPX bodies, inserts and sealing caps and plugs (pages 106-111).

Back-To-Back Body Adapters

• POLYCARBONATE



PART NO.

MPC17C1703
MPX17X1703
MPC17X1703

TYPE

MPC to MPC
MPX to MPX
MPC to MPX

A

.96 (24.5)
1.28 (32.5)
1.28 (32.5)

B

1.81 (46.0)
2.44 (62.0)
2.13 (54.1)

• POLYSULFONE



PART NO.

MPC17C1739
MPX17X1739
MPC17X1739

TYPE

MPC to MPC
MPX to MPX
MPC to MPX


A

.96 (24.5)
1.28 (32.5)
1.28 (32.5)

B

1.81 (46.0)
2.44 (62.0)
2.13 (54.1)

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.



A = Height/Diameter

B = Total Length

MPX SERIES CONNECTOR



MPX Series couplings add ease of use and security to your most critical fluid handling applications. Choose from a full line of connectors and configurations, including pressure sealing caps and plugs in sizes to fit 3/8" and 1/2" tubing. MPX couplings offer optional locking sleeves to further guard against accidental disconnects. In addition, coupling halves can be rotated when connected reducing tube kinks.

FEATURES

Ergonomic thumb latch
USP Class VI materials
Sterilizable by autoclave, EtO, e-beam, or gamma
Parting line-free hose barb
ADCF-free materials

BENEFITS

Easy to operate – even with gloved hands
Meet biocompatibility requirements
Reusable, yet economical enough to allow disposability
Eliminates potential leak path
Meet BSE/TSE requirements

Specifications ● ● ●

PRESSURE:

Vacuum to 60 psi, 4.1 bar

TEMPERATURE:

Polycarbonate:

-40°F to 250°F (-40°C to 121°C)

Polysulfone:

-40°F to 300°F (-40°C to 149°C)

MATERIALS:

Main components:

Polycarbonate (purple tint), USP Class VI, ADCF
Polysulfone (amber tint), USP Class VI, ADCF

Locking sleeves:

Polysulfone (white), USP Class VI, ADCF

Thumb Latches:

Polycarbonate (white), USP Class VI, ADCF
Polysulfone (amber tint), USP Class VI, ADCF

O-rings: Silicone (clear), platinum-cured, USP Class VI, ADCF

STERILIZATION:

Gamma: Up to 50 kGy irradiation

Autoclave:


Polycarbonate: Up to 250°F (121°C), 30 minutes, up to 10 repetitions. Sterilize uncoupled only.

Polysulfone: Up to 270°F (132°C) for 60 minutes, up to 25 repetitions. Sterilize uncoupled only.


TUBING SIZES: 3/8" to 1/2" ID (9.5mm to 12.7mm)

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions.

⚠ This graph is intended to give you a general idea of the performance capabilities of each product line. The shaded area of the graph represents the operating range of the product family, i.e. upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.



MPX SERIES CONNECTOR DIMENSIONS



A = Height/Diameter

B = Total Length

Coupling Bodies

• POLYCARBONATE



TERMINATION
IN-LINE
HOSE BARB

TUBING
1/2" ID

METRIC EQ.
12.7mm ID

FLOW
.50"

STRAIGHT THRU
MPX17803

A
1.28 (32.5)

B
1.96 (49.8)

IN-LINE HOSE BARB
WITH LOCK

1/2" ID

12.7mm ID

.50"

MPXK17803

1.28 (32.5)

1.96 (49.8)

• POLYSULFONE



TERMINATION
IN-LINE
HOSE BARB

TUBING
1/2" ID

METRIC EQ.
12.7mm ID

FLOW
.50"

STRAIGHT THRU
MPX17839

A
1.28 (32.5)

B
1.96 (49.8)

IN-LINE HOSE BARB
WITH LOCK

1/2" ID

12.7mm ID

.50"

MPXK17839

1.28 (32.5)

1.96 (49.8)

Coupling Inserts

• POLYCARBONATE



TERMINATION
IN-LINE
HOSE BARB

TUBING
3/8" ID
1/2" ID

METRIC EQ.
9.5mm ID
12.7mm ID

FLOW
.38"
.50"

STRAIGHT THRU
MPX22603M
MPX22803M

O-RING

Silicone Seal USP Class VI
Silicone Seal USP Class VI

A
.85 (21.6)
.85 (21.6)

B
1.90 (48.3)
1.90 (48.3)

• POLYSULFONE



TERMINATION
IN-LINE
HOSE BARB

TUBING
3/8" ID
1/2" ID

METRIC EQ.
9.5mm ID
12.7mm ID

FLOW
.38"
.50"

STRAIGHT THRU
MPX22639M
MPX22839M

O-RING

Silicone Seal USP Class VI
Silicone Seal USP Class VI

A
.85 (21.6)
.85 (21.6)

B
1.90 (48.3)
1.90 (48.3)

Mating Parts



SEALING CAP
MPX32003

SEALING CAP W/LOCK
MPXK32003

MATERIAL
Polycarbonate

A
1.28 (32.5)

B
1.67 (42.4)

MPX32039

MPXK32039

Polysulfone

1.28 (32.5)

1.67 (42.4)

SEALING PLUG
MPX30003M

O-RING
Silicone Seal USP Class VI

MATERIAL
Polycarbonate

A
1.10 (27.9)

B
1.66 (42.2)

MPX30039M

Silicone Seal USP Class VI

Polysulfone

1.10 (27.9)

1.66 (42.2)

Note:
MPX Series
mates with Back-to-
Back Adapters (page
109), SaniQuik™ and
Sanitary Series
(pages 112-115).

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.

SANITARY SERIES CONNECTOR



Sanitary couplings attach directly to 3/4", 1" and 1-1/2" sanitary terminations to provide greater flexibility for integrating components into single-use or hybrid (single-use to stainless) process systems. Standard bag systems with quick couplings can be easily connected to equipment with sanitary terminations, while single-use cartridge filters can be converted to incorporate quick couplings for greater system modularity.

FEATURES

3/4", 1" and 1-1/2" sanitary terminations

Compatible with MPC and MPX Series couplings

Integral coupling adaptor

ADCF-free materials

BENEFITS

Install to equipment with sanitary gaskets and sanitary clamps

Quick and easy connections to industry standard plastic couplings on single-use bags and tube sets

Provides flexibility to easily convert sanitary terminations on filter cartridge or equipment

Meet BSE/TSE requirements

Specifications ● ● ●

PRESSURE:

Vacuum to 60 psi, 4.1 bar

TEMPERATURE:

-40°F to 300°F (-40°C to 149°C)

MATERIALS:

Main components:

Polysulfone (amber tint), USP Class VI, ADCF

O-rings: Silicone (clear), platinum-cured, USP Class VI, ADCF

STERILIZATION:

Gamma: Up to 50 kGy irradiation

Autoclave: Up to 270°F (132°C) for 60 minutes, up to 25 repetitions. Sterilize uncoupled only.


TERMINATION SIZES:

3/4", 1" and 1-1/2" sanitary

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions.

Note:
Mates with MPC and MPX bodies, inserts and sealing caps and plugs and Back-to-Back Adapters (pages 106-111).

SANITARY SERIES CONNECTOR DIMENSIONS



Coupling Bodies • POLYSULFONE




PART NO.	SIZE	A	B	C
MPC3301239	3/4"	.98 (24.9)	1.40 (35.6)	1.0 (25.4)
MPX3301239	3/4"	1.28 (32.5)	1.70 (43.2)	1.0 (25.4)
MPC3301639	1"	1.50 (38.1)	1.40 (35.6)	1.50 (38.1)

Coupling Inserts • POLYSULFONE



PART NO.	SIZE	O-RING	A	B
MPC44012T39M	3/4"	Silicone Seal USP Class VI	.98 (24.9)	1.40 (35.6)
MPC44024T39M	1-1/2"	Silicone Seal USP Class VI	1.98 (50.3)	1.40 (35.6)
MPX44012T39M	3/4"	Silicone Seal USP Class VI	.98 (24.9)	1.71 (43.4)
MPX44024T39M	1-1/2"	Silicone Seal USP Class VI	1.98 (50.3)	1.71 (43.4)

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. Note: Sanitary couplings are compatible with both stainless steel and plastic clamps. Clamps and gaskets are referenced for illustration and are not available through CPC.



SANIQUIK™ SERIES CONNECTOR



Specifications ● ● ●

PRESSURE:

Vacuum to 60 psi, 4.1 bar

TEMPERATURE:

-40°F to 300°F (-40°C to 149°C)

MATERIALS:

Main component: 316L stainless steel

O-rings: Silicone (clear), platinum-cured, USP Class VI, ADCF

STERILIZATION:

Autoclave

TERMINATION SIZES:

3/4" and 1-1/2" sanitary

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions.

CPC's SaniQuik™ connection answers the question of how to integrate single-use components with your existing stainless processing equipment. This integral sanitary termination attaches to hard-plumbed systems with tri-clover clamps. Once attached it permits quick and easy connection to single-use bag systems, manifolds or tube sets with CPC disposable coupling bodies. SaniQuik connections reduce sanitary gasket replacement, enabling cost-effective media transfer solutions for feeding, harvesting or sampling applications.

Note:
Mates with MPC and MPX bodies, inserts and sealing plugs and Back-to-Back Adapters (pages 106-111).

FEATURES

3/4" and 1-1/2" sanitary standard terminations

Compatible with MPC and MPX Series couplings

Integral coupling adaptor

ADCF-free materials

BENEFITS


Connect to hard plumbed systems with sanitary gaskets and sanitary clamps

Quick and easy connections to industry standard plastic couplings on single-use bag and tube sets

Disconnecting coupling reduces sanitary gasket replacement

Meet BSE/TSE requirements

SANQUIK™ SERIES CONNECTOR DIMENSIONS



A = Height/Diameter
B = Total Length

Connections • 316L STAINLESS



DESCRIPTION
 SILICONE SEAL
 USP CLASS VI

PART NO.
 SQCC221212M
 SQCC222424M
 SQCX221212M
 SQCX222416M
 SQCX222424M

MATING COUPLING
 MPC Series
 MPC Series
 MPX Series
 MPX Series
 MPX Series

SANITARY SIZE
 3/4"
 1-1/2"
 3/4"
 1-1/2"
 1-1/2"

SANITARY BORE
 3/4"
 1-1/2"
 3/4"
 1"
 1-1/2"

A
 .98" (24.9)
 1.98" (50.3)
 .98" (24.9)
 1.98" (50.3)
 1.98" (50.3)

B
 1.39" (35.3)
 1.50" (38.1)
 1.43" (39.1)
 1.50" (38.1)
 1.50" (38.1)

Accessories • SILICONE (CLEAR)

DESCRIPTION
 PLATINUM-CURED
 USP CLASS VI
 REPLACEMENT
 SEALS

PART NO.
 2260100
 2260200

MATING SANQUIK
 SQCC221212M, SQCC222424M
 SQCX221212M, SQCX222416M, SQCX222424M

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.

NOTES:

MPU SERIES CONNECTOR



The MPU's twist-to-connect design features an easy-to-use locking mechanism that guards against accidental disconnects and provides a reliable, secure connection. A 3/4" hose barb provides smooth, rapid media transfer.

FEATURES

- 3/4" hose barb
- Locking feature
- Sharp barb end
- Shrouded, leak-free seal & smooth, internal flow path
- ADCF-free materials

BENEFITS

- Facilitates rapid fill and empty of bioprocessing bags
- Guards against accidental disconnects
- Minimizes fluid turbulence and dead space
- Protect valuable fluids and eliminate potential to contaminate fluid path
- Meet BSE/TSE requirements

Specifications ● ● ●

PRESSURE:

Vacuum to 35 psi, 2.4 bar

TEMPERATURE:

-40°F to 300°F (-40°C to 149°C)

MATERIALS:

Main components:
Polysulfone (amber tint), USP Class VI, ADCF

O-rings: Silicone (clear), platinum-cured, USP Class VI, ADCF

STERILIZATION:



Gamma: Up to 50 kGy irradiation

Autoclave: Up to 270°F (132°C) for 60 minutes, up to 25 repetitions. Sterilize uncoupled only.


TUBING SIZES: 3/4" ID (19.0 mm)

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions.

These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.



MPU SERIES CONNECTOR DIMENSIONS



A = Height/Diameter
B = Total Length

Coupling Bodies • POLYSULFONE

	TERMINATION IN-LINE HOSE BARB	TUBING 3/4" ID	METRIC EQ. 19.0mm ID	FLOW .71"	STRAIGHT THRU MPU171239	A 1.75 (44.5)	B 2.37 (60.2)

Coupling Inserts • POLYSULFONE

	TERMINATION IN-LINE HOSE BARB	TUBING 3/4" ID	METRIC EQ. 19.0mm ID	FLOW .71"	STRAIGHT THRU MPU221239M	O-RING Silicone Seal USP Class VI	A 1.56 (39.6)	B 2.88 (73.2)

Accessories • POLYSULFONE



	SEALING CAP MPU32039		MATERIAL Polysulfone USP Class VI	A 1.75 (44.5)	B .79 (20.1)
	SEALING PLUG MPU30039M	O-RING Silicone Seal	MATERIAL Polysulfone USP Class VI	A 1.56 (39.6)	B 1.38 (35.1)

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.

HFC39 SERIES CONNECTOR



Specifications ● ● ●

PRESSURE:

Vacuum to 125 psi, 8.6 bar

TEMPERATURE:

-40°F to 280°F (-40°C to 138°C)

MATERIALS:

Main components:

Polysulfone (amber tint), USP Class VI, ADCF

O-rings: Silicone (clear), platinum-cured, USP Class VI, ADCF

Springs: 316L stainless steel

STERILIZATION:

Gamma: Up to 50 kGy irradiation. Sterilize coupled or uncoupled.

Autoclave: Up to 270°F (132°C) for 60 minutes. Up to 25 repetitions for uncoupled units and up to one repetition for coupled units.

TERMINATION SIZES:

1/4", 3/8" and 1/2" ID hose barb
(6.4mm, 9.5mm and 12.7mm)

HFC39 Series sterile disconnect couplings prevent external organisms from entering into the media flow path upon disconnection. Automatic shutoff valves close off the flow path aseptically protecting valuable media while also eliminating the need for pinch clamps and tube welders. The easy-to-use thumb latch design provides a secure, leak-free connection and enables one-hand disconnects.

FEATURES

Simple one-step disconnection

Automatic shutoff valves

CPC Click

Lightweight

ADCF-free materials

BENEFITS

Maintains media sterility in each half by preventing external organisms from entering the flow path



Stop flow and eliminate need for pinch clamps

Audible confirmation of secure connection


Easy integration with single-use assemblies

Meet BSE/TSE requirements

These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of the graph represents the operating range of the product family, i.e. upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.



HFC39 SERIES DIMENSIONS



Coupling Bodies • POLYSULFONE



TERMINATION
IN-LINE
HOSE BARB

TUBING SIZE	METRIC EQ.	FLOW	SHUTOFF	A	B
1/4" ID	6.4mm ID	1/4"	HFCD17439M	1.44 (36.6)	2.82 (71.6)
3/8" ID	9.5mm ID	3/8"	HFCD17639M	1.44 (36.6)	2.82 (71.6)
1/2" ID	12.5mm ID	3/8"	HFCD17839M	1.44 (36.6)	2.82 (71.6)

Coupling Inserts • POLYSULFONE



TERMINATION
IN-LINE
HOSE BARB

TUBING SIZE	METRIC EQ.	FLOW	STRAIGHT THRU	SHUTOFF	A	B
1/4" ID	6.4mm ID	1/4"	HFC22439M	HFCD22439M	1.00 (25.4)	2.02 (51.3)
3/8" ID	9.5mm ID	3/8"	HFC22639M	HFCD22639M	1.00 (25.4)	2.02 (51.3)
1/2" ID	12.5mm ID	3/8"	HFC22839M	HFCD22839M	1.00 (25.4)	2.02 (51.3)

Mating Parts



SEALING CAP	O-RING	MATERIAL	A	B
HFC32039		Polysulfone	1.44 (36.6)	2.73 (69.3)
SEALING PLUG				
HFC30039M	Silicone Seal USP Class VI	Polysulfone	1.00 (25.4)	1.81 (46.0)

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. Couplings are pictured with valves unless otherwise noted.

For validation reports,
visit cpcworldwide.com/bio
and for extractables data
contact
info@cpcworldwide.com

ASEPTIQUICK® S SERIES CONNECTORS



AseptiQuick® S Small Format 1/8" and 1/4" Connectors

provide quick and easy sterile connections for small-flow applications, even in non-sterile environments. The "FLIP-CLICK-PULL" design of AseptiQuick S enables users to easily transfer small volumes of media with less risk of operator error. The connector's genderless and robust design provides reliable performance without the need for clamps, fixtures or tube welders. Biopharmaceutical manufacturers can now make 1/8" and 1/4" sterile connections with the quality and market availability they expect from the leader in single-use connection technology.

FEATURES

Genderless design

FLIP-CLICK-PULL

Integrated pull tab covers

Robust construction

CPC Click

BENEFITS

Eases single-use systems specifications with one part number for both halves

Intuitive three-step connection process reduces risk of operator error

Provide pre-assembly protection and ensure simultaneous removal of both membranes

Repeatable and reliable performance with no additional hardware required

Audible confirmation of assembly

Specifications ● ● ●

PRESSURE:

Up to 60 psi, 4.1 bar

TEMPERATURE:

39°F to 104°F (4°C to 40°C)

STERILIZATION:

Gamma: Up to 50kGy irradiation

AutoClave High Temp (HT) Version:

Up to 266°F (130°C) for 60 minutes

TERMINATION SIZES:

1/8", 1/4" and 3/8" ID hose barb (3.2mm, 6.4mm and 9.5mm), 3/4" sanitary and MPC insert

MATERIALS:

Main Components:

Polycarbonate (white), USP Class VI, ADCF

Pull Tabs/Caps:

Polycarbonate (blue, standard version),
USP Class VI, ADCF

Polycarbonate (white, HT version),
USP Class VI, ADCF

Seals:


Silicone (clear), platinum-cured,
USP Class VI, ADCF

Membrane:


Polyethylene (standard version),
USP Class VI, ADCF

Hydrophobic polyethersulfone (HT version),
USP Class VI, ADCF, PTFE strip sticker

✓ This graph is intended to give you a general idea of the performance capabilities of each product line. The shaded area of the graph represents the operating range of the product family, i.e. upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.



ASEPTIQUIK® S SERIES DIMENSIONS



- A** = Height/Diameter
- B** = Total Length
- C** = Hose Barb Length

For validation reports,
visit cpcworldwide.com/bio
and for extractables
data, contact
info@cpcworldwide.com

Coupling Bodies

• POLYCARBONATE with Blue Pull Tabs



TERMINATION
1/8" HOSE BARB
1/4" HOSE BARB
3/8" HOSE BARB
3/4" SANITARY
MPC INSERT

PART NO.
AQS17002
AQS17004
AQS17006
AQS33012
AQS17MPC

A
2.25
2.25
2.25
2.25
2.25

B
1.30
1.45
1.45
1.60
1.49

C
0.50
0.65
0.65
0.80
0.69

• POLYCARBONATE HT with White Pull Tabs



TERMINATION
1/8" HOSE BARB
1/4" HOSE BARB
3/8" HOSE BARB
3/4" SANITARY
MPC INSERT


PART NO.
AQS17002HT
AQS17004HT
AQS17006HT
AQS33012HT
AQS17MPCHT

A
2.25
2.25
2.25
2.25
2.25

B
1.30
1.45
1.45
1.60
1.49


C
0.50
0.65
0.65
0.80
0.69

FLIP-CLICK-PULL Assembly Procedure




1

Unsnap and flip down the protective pull tab covers on each connector half.



2

Align the connector halves with the pull tabs hanging down. Slide the two halves together. Independently squeeze each side of the connector until you hear an audible "CPC Click."



3

To complete the connection, simply snap the pull tabs together by pushing on the CPC logos and pull the membranes from the connector.

ASEPTIQUIK® G SERIES CONNECTORS



Genderless AseptiQuik® G Connectors enable quick and easy sterile connections, even in non-sterile environments. The easy-to-use genderless design simplifies system integration and minimizes the risk of operator error. The connectors' robust construction provides enhanced user confidence and reliable performance without the need for clamps, fixtures or tube welders. Biopharmaceutical manufacturers benefit from a full range of interchangeable 1/4" to 3/4" flow solutions with the quality and market availability they expect from the leader in single-use connection technology.

FEATURES

Genderless design

Robust construction

FLIP-CLICK-PULL

Integrated pull tab covers

CPC Click

BENEFITS

Eases integration of single-use systems with one part number for both halves

Repeatable and reliable performance with no additional hardware required

Innovative three-step connection process reduces risk of operator error

Pull tabs act as protective cover reducing part complexity and ensure simultaneous removal of both membranes

Audible confirmation of assembly

Specifications ● ● ●

PRESSURE:

Up to 60 psi, 4.1 bar
Up to 75 psi, 5.1 bar for 48 hours

TEMPERATURE:

34°F to 104°F (1°C to 40°C)

STERILIZATION:

Gamma: Up to 50kGy irradiation

Autoclave High Temp (HT) Version:

Up to 266°F (130°C) for 60 minutes

TERMINATION SIZES:

1/4", 3/8", 1/2", 3/4" ID hose barb (6.4mm, 9.5mm, 12.7mm, 19.0mm) and 3/4" sanitary

MATERIALS:

Main Components:

Polycarbonate (white), USP Class VI, ADCF

Pull Tabs/Caps:

Polycarbonate (blue, standard version),
USP Class VI, ADCF

Polycarbonate (white, HT version),
USP Class VI, ADCF

Seals:

Silicone (clear), platinum-cured, USP Class VI, ADCF


Membrane:

Polyethylene (standard version), USP Class VI, ADCF

Hydrophobic polyethersulfone (HT version),
USP Class VI, ADCF, PTFE strip sticker


Genderless interface allows easy transition between multiple tubing sizes from 1/4" to 3/4".

⚠ This graph is intended to give you a general idea of the performance capabilities of each product line. The shaded area of the graph represents the operating range of the product family, i.e. upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.



ASEPTIQUIK® G SERIES DIMENSIONS

- A** = Height/Diameter
- B** = Total Length
- C** = Hose Barb Length



Coupling Bodies

• POLYCARBONATE with Blue Pull Tabs



TERMINATION

1/4" HOSE BARB
3/8" HOSE BARB
1/2" HOSE BARB
3/4" HOSE BARB
3/4" SANITARY

PART NO.

AQG17004
AQG17006
AQG17008
AQG17012
AQG33012

A

2.62
2.62
2.62
2.62
2.62

B

1.62
1.62
1.95
2.36
1.66

C

0.82
0.82
1.15
1.56
0.86

• POLYCARBONATE HT with White Pull Tabs



TERMINATION

1/4" HOSE BARB
3/8" HOSE BARB
1/2" HOSE BARB
3/4" HOSE BARB
3/4" SANITARY

PART NO.

AQG17004HT
AQG17006HT
AQG17008HT
AQG17012HT
AQG33012HT

A

2.62
2.62
2.62
2.62
2.62

B


1.62
1.62
1.95
2.36
1.66

C

0.82
0.82
1.15
1.56
0.86


Validation reports
are available at
cpcworldwide.com/bio.

FLIP-CLICK-PULL Assembly Procedure




1

Unsnap and flip down the protective pull tab covers on each connector half.



2

Align the connector halves with the pull tabs hanging down. Slide the two halves together. Independently squeeze each side of the connector until you hear an audible "CPC Click."



3

To complete the connection, simply snap the pull tabs together by pushing on the CPC logos and pull the membranes from the connector.

ASEPTIQUIK® C SERIES CONNECTORS



AseptiQuik® C Connectors provide quick and easy sterile connections, even in non-sterile environments. AseptiQuik's "CLICK-PULL-TWIST" design enables users to transfer media easily with less risk of operator error. The connector's robust design provides reliable performance without the need for clamps, fixtures or tube welders. Biopharmaceutical manufacturers can make sterile connections with the quality and market availability they expect from the leader in single-use connection technology.

FEATURES

CLICK-PULL-TWIST design

Membrane pull tabs

Robust construction

Integrated lock ring

CPC Click

Market availability

BENEFITS

Intuitive three-step connection process reduces risk of operator error

Ensure simultaneous and secure removal of both membranes

Repeatable and reliable performance with no additional hardware required

Secures final connection preventing disassembly

Audible confirmation of completed assembly steps

Open access through multiple supply chain partners

Specifications ● ● ●

PRESSURE:

Up to 60 psi, 4.1 bar

TEMPERATURE:

39°F to 104°F (4°C to 40°C)

TYPICAL FLOW RATE:

Cv = 14.4 max

STERILIZATION:

Gamma: Up to 50kGy irradiation

Autoclave High Temp (HT) Version:
Up to 266°F (130°C) for 30 minutes

TERMINATION SIZES:

3/8" (9.5mm) and 1/2" (12.7mm) ID hose barb, and 3/4" sanitary

MATERIALS:

Main Components:

Polycarbonate (white), USP Class VI, ADCF

Lock Ring:

Polycarbonate (blue), USP Class VI, ADCF

Pull Tabs:

Polycarbonate (blue, standard version),
USP Class VI, ADCF

Polycarbonate (white, HT version),
USP Class VI, ADCF

Caps:

Polypropylene (clear), USP Class VI, ADCF

Seals:


Silicone (clear), platinum-cured, USP Class VI, ADCF

Membrane:

Polyethylene (standard version),
USP Class VI, ADCF


Hydrophobic polyethersulfone (HT version),
USP Class VI, ADCF

This graph is intended to give you a general idea of the performance capabilities of each product line. The shaded area of the graph represents the operating range of the product family, i.e. upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.



ASEPTIQUIK® C SERIES DIMENSIONS

- A** = Height/Diameter
- B** = Total Length
- C** = Hose Barb Length



Coupling Bodies

• POLYCARBONATE with Blue Pull Tabs

TERMINATION	PART NO.	FLOW	A	B	C
3/8" HOSE BARB	AQC17006	.34	2.36 (59.9)	2.74 (69.6)	0.65 (16.5)
1/2" HOSE BARB	AQC17008	.50	2.36 (59.9)	2.95 (74.9)	0.89 (22.6)
3/4" SANITARY	AQC33012	.50	2.36 (59.9)	2.73 (69.3)	0.70 (17.8)

• POLYCARBONATE HT with White Pull Tabs

TERMINATION	PART NO.	FLOW	A	B	C
3/8" HOSE BARB	AQC17006HT	.34	2.36 (59.9)	2.74 (69.6)	0.65 (16.5)
1/2" HOSE BARB	AQC17008HT	.50	2.36 (59.9)	2.95 (74.9)	0.89 (22.6)
3/4" SANITARY	AQC33012HT	.50	2.36 (59.9)	2.73 (69.3)	0.70 (17.8)

Coupling Inserts


• POLYCARBONATE with Blue Pull Tabs

TERMINATION	PART NO.	FLOW	A	B	C
3/8" HOSE BARB	AQC22006	.34	2.50 (63.5)	2.90 (73.7)	0.65 (16.5)
1/2" HOSE BARB	AQC22008	.50	2.50 (63.5)	2.99 (75.9)	0.89 (22.6)
3/4" SANITARY	AQC44012	.50	2.50 (63.5)	2.80 (71.1)	0.70 (17.8)

• POLYCARBONATE HT with White Pull Tabs

TERMINATION	PART NO.	FLOW	A	B	C
3/8" HOSE BARB	AQC22006HT	.34	2.50 (63.5)	2.90 (73.7)	0.65 (16.5)
1/2" HOSE BARB	AQC22008HT	.50	2.50 (63.5)	2.99 (75.9)	0.89 (22.6)
3/4" SANITARY	AQC44012HT	.50	2.50 (63.5)	2.80 (71.1)	0.70 (17.8)

CLICK-PULL-TWIST Assembly Procedure



1
Align male and female couplings, push together until "CPC Click" confirmation.
Slight rotation of lock ring may be required for proper alignment prior to connection.



2
Snap membrane pull tabs together and pull from connector.



3
Twist the blue lock ring clock-wise until "CPC Click" and rib to arrow alignment confirms secure final connection.

ASEPTIQUIK® DC SERIES CONNECTORS



AseptiQuik® DC Connectors are the first all-in-one single-use connection technology to offer both a sterile connect and sterile disconnect. With the AseptiQuik DC Connector, manufacturers can make a quick and easy sterile connection and disconnection, even in non-sterile environments.

AseptiQuik DC's intuitive "CLICK-PULL-TWIST" design enables users to transfer media easily with less risk of operator error. After transfer is complete, the connector features a simple one-step disconnection that maintains media sterility by preventing external organisms from entering into the media flow path. The connector's robust design and automatic shutoff valves provide reliable performance without the need for sanitary clamps, fixtures or tube welders.

FEATURES

CLICK-PULL-TWIST design

Simple one-step disconnection

Membrane pull tabs

Robust construction

CPC Click

Market availability

BENEFITS

Intuitive three-step connection process reduces risk of operator error

Maintains media sterility in each half by preventing external organisms from entering the flow path

Ensure simultaneous and secure removal of both membranes

Repeatable and reliable performance with no additional hardware required

Audible confirmation of completed assembly steps

Open access through multiple supply chain partners

Specifications

PRESSURE:

Up to 60 psi, 4.1 bar

TEMPERATURE:

39°F to 104°F (4°C to 40°C)

STERILIZATION:

Gamma: Up to 50kGy irradiation

Autoclave High Temp (HT) Version: Up to 266°F (130°C) for 30 minutes

TERMINATION SIZES:

1/4", 3/8" and 1/2" ID hose barb
(6.4mm, 9.5mm and 12.7mm)

MATERIALS:

Main Components: Polycarbonate (white), USP Class VI, ADCF

Lock Ring: Polycarbonate (blue), USP Class VI, ADCF

Pull Tabs:

Polycarbonate (blue, standard version), USP Class VI, ADCF

Polycarbonate (white, HT version), USP Class VI, ADCF

Caps: Polypropylene (clear), USP Class VI, ADCF

Seals: Silicone (clear), platinum-cured, USP Class VI, ADCF

Membrane:

Polyethylene (standard version), USP Class VI, ADCF

Hydrophobic polyethersulfone (HT version), USP Class VI, ADCF


Springs: 316L stainless steel

Mates with standard AseptiQuik halves:

AQCDC inserts mate with standard AQC bodies


AQCDC bodies mate with standard AQC inserts

This graph is intended to give you a general idea of the performance capabilities of each product line. The shaded area of the graph represents the operating range of the product family, i.e. upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.



ASEPTIQUIK® DC SERIES DIMENSIONS

- A** = Height/Diameter
- B** = Total Length
- C** = Hose Barb Length



Coupling Bodies • POLYCARBONATE



TERMINATION
1/4" HOSE BARB
3/8" HOSE BARB
1/2" HOSE BARB

PART NO.
AQCDC17004
AQCDC17006
AQCDC17008

FLOW
1/4"
3/8"
3/8"

A
2.36 (59.9)
2.36 (59.9)
2.36 (59.9)

B
5.33 (135.4)
5.33 (135.4)
5.62 (142.7)

C
0.60 (15.2)
0.60 (15.2)
0.89 (22.6)

Coupling Inserts • POLYCARBONATE



TERMINATION
1/4" HOSE BARB
3/8" HOSE BARB
1/2" HOSE BARB

PART NO.
AQCDC22004
AQCDC22006
AQCDC22008


FLOW
1/4"
3/8"
3/8"

A
2.50 (63.5)
2.50 (63.5)
2.50 (63.5)

B
5.41 (137.4)
5.41 (137.4)
5.70 (144.8)

C
0.60 (15.2)
0.60 (15.2)
0.89 (22.6)

CLICK-PULL-TWIST Assembly Procedure



1
Align male and female couplings, push together until audible "CPC Click" confirmation.
Slight rotation of lock ring may be required for proper alignment prior to connection.



2
Snap membrane pull tabs together and pull from connector.



3
Twist the blue lock ring clock-wise until "CPC Click" and rib to arrow alignment confirms secure final connection.

To Disconnect



When fluid transfer is finished, press the thumb latch down to complete the sterile disconnection. Both halves will remain sterile.

ASEPTIQUIK® X SERIES CONNECTORS

Specifications ● ● ●

PRESSURE:

Up to 60 psi, 4.1 bar

TEMPERATURE:

39°F to 104°F (4°C to 40°C)

STERILIZATION:

Gamma: Up to 50kGy irradiation

Autoclave High Temp (HT) Version: Up to 266°F (130°C) for 30 minutes

TERMINATION SIZES:

3/4" and 1" ID hose barb (19.0mm and 25.4mm),
1-1/2" sanitary

MATERIALS:

Main Components:

PVDF (white), USP Class VI, ADCF

Lock Ring:

PVDF (blue), USP Class VI, ADCF

Pull Tabs:

Polycarbonate (blue, standard version),
USP Class VI, ADCF

Polycarbonate (white, HT version), USP Class VI,
ADCF

Caps:

Polypropylene (clear), USP Class VI, ADCF

Seals:

Silicone (clear), platinum-cured,
USP Class VI, ADCF

Membrane:

Polyethylene (standard version),
USP Class VI, ADCF

Hydrophobic polyethersulfone (HT version),
USP Class VI, ADCF, PTFE strip sticker

AseptiQuik® X Large Format 1" Connectors provide quick and easy sterile connections for high flow applications, even in non-sterile environments. AseptiQuik X's "TWIST-PULL-TWIST" design enables users to quickly transfer large volumes of media easily with less risk of operator error. The connector's robust design provides reliable performance without the need for clamps, fixtures or tube welders. Biopharmaceutical manufacturers can now make 1" sterile connections with the quality and market availability they expect from the leader in single-use connection technology.

FEATURES

TWIST-PULL-TWIST Design

Membrane pull tabs

Robust construction

Integrated lock ring

CPC Click

BENEFITS

Intuitive three-step connection process reduces risk of operator error


Ensure simultaneous and secure removal of both membranes

Repeatable and reliable performance with no additional hardware required

Secures final connection preventing disassembly


Audible confirmation of completed assembly steps

✓ This graph is intended to give you a general idea of the performance capabilities of each product line. The shaded area of the graph represents the operating range of the product family, i.e. upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.



ASEPTIQUIK® X SERIES DIMENSIONS

- A** = Height/Diameter
- B** = Total Length
- C** = Hose Barb Length



Coupling Bodies

• POLYCARBONATE with Blue Pull Tabs



TERMINATION
3/4" HOSE BARB
1" HOSE BARB
1-1/2" SANITARY

PART NO.
AQX17012
AQX17016
AQX33024

A
3.54
3.54
3.54

B
3.93
4.04
4.18

C
1.50
1.53
1.73

• POLYCARBONATE HT with White Pull Tabs



TERMINATION
3/4" HOSE BARB
1" HOSE BARB
1-1/2" SANITARY

PART NO.
AQX17012HT
AQX17016HT
AQX33024HT

A
3.54
3.54
3.54

B
3.93
4.04
4.18

C
1.50
1.53
1.73

Coupling Inserts

• POLYCARBONATE with Blue Pull Tabs



TERMINATION
3/4" HOSE BARB
1" HOSE BARB
1-1/2" SANITARY

PART NO.
AQX22012
AQX22016
AQX44024

A
3.76
3.76
3.76

B
4.34
4.45
4.58

C
1.50
1.53
1.74

• POLYCARBONATE HT with White Pull Tabs



TERMINATION
3/4" HOSE BARB
1" HOSE BARB
1-1/2" SANITARY


PART NO.
AQX22012HT
AQX22016HT
AQX44024HT

A
3.76
3.76
3.76

B
4.34
4.45
4.58

C
1.50
1.53
1.74

TWIST-PULL-TWIST Assembly Procedure



1

Align male and female connectors using the START alignment feature of the blue lock ring with the rib indicator of the white body. Insert the two halves together.



2

Twist the blue lock ring clockwise (approximately 75°) until audible "CPC Click" is heard. Alignment of the small blue lock ring rib indicator with the white body's rib indicator confirms final rotation is complete.



3

Snap the membrane pull tabs together and pull from connector.



4

Twist the blue lock ring clockwise until the final audible "CPC Click" is heard (90° from the initial starting point). Alignment of the long blue lock ring rib indicator with the white body's rib indicator confirms initial rotation is complete.

STEAM-THRU® SERIES CONNECTOR



Steam-Thru Connections allow a quick and easy sterile connection between stainless steel biopharmaceutical processing equipment and disposable bag and tube assemblies. The single-use design saves time and money by eliminating unnecessary cleaning procedures and reducing validation burden associated with reusable components.

FEATURES

Innovative three-port design

Patented valve design

Thumb latch/Tear-away sleeve

3/4" and 1-1/2" Terminations

ADCF-free materials

BENEFITS

Allows a true steam-through SIP process which eliminates "dead legs" and the need for laminar flow hoods

Allows sterile connection and disconnection and permits high media flow rate

Secures valve position, provides visual indicator of process stage

Easily connects to process equipment

Meet BSE/TSE requirements

Specifications

PRESSURE:

Steam position:

Up to 30 psi, 2.1 bar (Steam-Thru)
Up to 35 psi, 2.4 bar (Steam-Thru II)

Flow position: Vacuum to 20 psi, 1.4 bar

TEMPERATURE:

Steam position:

Up to 266°F (130°C) for 60 minutes (Steam-Thru)
Up to 275°F (135°C) for 60 minutes (Steam-Thru II)

Flow position: 39°F to 104°F (4°C to 40°C)

MATERIALS:

Connection: Polysulfone (amber tint), USP Class VI, ADCF

O-rings: Silicone (clear), platinum-cured, USP Class VI, ADCF

Tear-away sleeve: Polyethylene or polycarbonate (Steam-Thru only), USP Class VI

TYPICAL FLOW RATE:

$C_v = 4.2 - 4.6$ (Steam-Thru)

$C_v = 5.2 - 8.0$ (Steam-Thru II)

STERILIZATION:

Gamma: Up to 50 kGy irradiation

Autoclave: Up to 265°F (129°C) for 60 minutes, up to two cycles (applies only to part numbers STC1700500-STC1700800 and STC2020000-STC2021000)

SIP process:

Up to 266°F (130°C) for 60 minutes (Steam-Thru)
Up to 275°F (135°C) for 60 minutes (Steam-Thru II)



TERMINATION SIZES:

3/8" (9.5mm) to 1/2" (12.7mm) ID hose barb (Steam-Thru)

3/8" (9.5mm) to 1/2" (12.7mm) ID hose barb and 3/4" sanitary (Steam-Thru II)




These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of the graph represents the operating range of the product family, i.e. upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.



STEAM-THRU SERIES DIMENSIONS

Steam-Thru® Configurations

Steam-Thru Connection's patented three-port design allows steam to pass directly through the lower ports to "steam on" to stainless equipment. After the SIP cycle is completed, the connector's valve is actuated, creating a sterile flow path to single-use systems.



- A = Diameter
- B = Total Length
- C = Actuated Length
- D = Height
- E = Hose Barb Length

Coupling Bodies • POLYSULFONE



**DESCRIPTION
WITH POLYETHYLENE
SLEEVE**

PART NO.	TERMINATIONS	A	B	C	D	E
STC1700000	3/4" x 3/4" sanitary x 1/2" HB	1.20 (30.5)	5.09 (129.3)	4.44 (112.8)	2.00 (50.8)	0.89 (22.6)
STC1700100	3/4" x 3/4" sanitary x 3/8" HB	1.20 (30.5)	4.80 (121.9)	4.15 (105.4)	2.00 (50.8)	0.60 (15.2)
STC1700200	3/4" x 1-1/2" sanitary x 1/2" HB	1.20 (30.5)	5.09 (129.3)	4.44 (112.8)	2.00 (50.8)	0.89 (22.6)
STC1700300	3/4" x 1-1/2" sanitary x 3/8" HB	1.20 (30.5)	4.80 (121.9)	4.15 (105.4)	2.00 (50.8)	0.60 (15.2)




**DESCRIPTION
WITH
AUTOCCLAVABLE
POLYCARBONATE
SLEEVE**

PART NO.	TERMINATIONS	A	B	C	D	E
STC1700500	3/4" x 3/4" sanitary x 1/2" HB	1.20 (30.5)	5.09 (129.3)	4.44 (112.8)	2.00 (50.8)	0.89 (22.6)
STC1700600	3/4" x 3/4" sanitary x 3/8" HB	1.20 (30.5)	4.80 (121.9)	4.15 (105.4)	2.00 (50.8)	0.60 (15.2)
STC1700700	3/4" x 1-1/2" sanitary x 1/2" HB	1.20 (30.5)	5.09 (129.3)	4.44 (112.8)	2.00 (50.8)	0.89 (22.6)
STC1700800	3/4" x 1-1/2" sanitary x 3/8" HB	1.20 (30.5)	4.80 (121.9)	4.15 (105.4)	2.00 (50.8)	0.60 (15.2)

Steam-Thru II Configurations

Steam-Thru II Connections offer the flexibility of "steam on" and "steam off" functionality. The innovative design allows the valve to be returned to the steam position enabling a second SIP cycle following media transfer. The "steam off" disconnection of single-use systems minimizes cross-contamination risks associated with reusable components.



- A = Diameter
- B = Total Length
- C = Actuated Length
- D = Height
- E = Hose Barb Length

Coupling Bodies • POLYSULFONE




**DESCRIPTION
WITH
POLYCARBONATE
SLEEVE**

PART NO.	TERMINATIONS	A	B	C	D	E
STC2020000	3/4" x 3/4" sanitary x 1/2" HB	1.42 (36.1)	6.84 (173.7)	5.93 (150.6)	2.40 (61.0)	.88 (22.4)
STC2020100	3/4" x 3/4" sanitary x 3/8" HB	1.42 (36.1)	6.76 (171.7)	5.93 (150.6)	2.40 (61.0)	.80 (20.3)
STC2020200	3/4" x 1-1/2" sanitary x 1/2" HB	1.42 (36.1)	6.84 (173.7)	5.93 (150.6)	2.40 (61.0)	.88 (22.4)
STC2020300	3/4" x 1-1/2" sanitary x 3/8" HB	1.42 (36.1)	6.76 (171.7)	5.93 (150.6)	2.40 (61.0)	.80 (20.3)
STC2020900	3/4" x 3/4" sanitary x 3/4" sanitary	1.42 (36.1)	6.60 (167.6)	5.93 (150.6)	2.40 (61.0)	.62 (15.7)
STC2021000	3/4" x 1-1/2" sanitary x 3/4" sanitary	1.42 (36.1)	6.60 (167.6)	5.93 (150.6)	2.40 (61.0)	.62 (15.7)

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.

ASEPTIQUIK® STC SERIES CONNECTOR



AseptiQuik® STC Connectors integrate the AseptiQuik® sterile connector and the Steam-Thru® II SIP connector, giving manufacturers even greater flexibility for hybrid stainless steel and single-use processing. The AseptiQuik STC connector combines either an AseptiQuik G or AseptiQuik C sterile connector with a Steam-Thru II connection that can be mounted directly to a stainless steel vessel via a sanitary termination. AseptiQuik STC connectors utilizing an AseptiQuik G sterile connector offer a genderless design, simplifying system integration at the aseptic connector end. AseptiQuik STC connectors utilizing an AseptiQuik C sterile connector allow system designers to incorporate a keyed female-to-male connection at the aseptic connector end.

The union of the two connectors into a single unit through a sanitary clamp allows an AseptiQuik sterile connection to be steamed on to stainless equipment via SIP. After the SIP cycle, a wide range of single-use systems can be connected. The SIP process can be done in advance allowing a quick and easy sterile connection to the AseptiQuik half without having to wait 30-60 minutes for SIP prior to harvest.

FEATURES

BENEFITS

AseptiQuik design	Innovative three-step connection process reduces risk of operator error
Genderless design	Eases integration of single-use systems with universal mating between AseptiQuik G Connectors
Innovative three-port steam design	Allows a true steam-through SIP process which eliminates "dead legs"
Robust construction	Repeatable and reliable performance with no additional hardware required
Patented steam valve design	Allows sterile connection and disconnection to stainless equipment and permits a high media flow rate.
Sanitary interface between the two connectors	More secure connection than tubing with cable ties
CPC Click	Audible confirmation of assembly steps
Market availability	Open access through multiple supply chain partners

Specifications ● ● ●

PRESSURE:

Steam position: Up to 35 psi, 2.4 bar

Flow position: Up to 20 psi, 1.4 bar

TEMPERATURE:

Steam position:

Up to 275°F (135°C) for 60 minutes

Flow position: 39°F to 104°F (4°C to 40°C)

STERILIZATION:

Gamma: Up to 50kGy irradiation

AutoClave: High Temp (HT) version:

Up to 266°F (130°C) for 30 minutes (AQSTC)

Up to 266°F (130°C) for 60 minutes (AQGSTC)

Note: A slight clockwise rotation of the clamp nut may be needed after autoclave.

MATERIALS:

Main Components:

AseptiQuik - Polycarbonate (white),
USP Class VI, ADCF

Steam-Thru II - Polysulfone (amber tint), USP
Class VI, ADCF

Seals: Silicone (clear), platinum-cured,
USP Class VI, ADCF

Pull Tabs:

Polycarbonate (blue, standard version),
USP Class VI, ADCF

Polycarbonate (white, HT version),
USP Class VI, ADCF

Caps: Polypropylene (clear), USP Class VI, ADCF

Membrane:


Polyethylene (standard version), USP Class VI,
ADCF

Hydrophobic polyethersulfone (HT versions), USP
Class VI, ADCF, PTFE strip sticker

Clamp: Nylon 66 (white),
USP Class VI

*Note: Mates with
gendered and
genderless AseptiQuik
connectors.*

ASEPTIQUIK® STC SERIES DIMENSIONS



- A** = Height/Diameter
- B** = Total Length
- C** = Actuated Length

Mates with
gendered
male and female
AseptiQuik
Series.

Coupling Bodies

• POLYCARBONATE with Blue Pull Tabs




TERMINATION
3/4" X 3/4" SANITARY STEAM-THRU II
WITH ASEPTIQUIK BODY

3/4" X 1-1/2" SANITARY STEAM-THRU II
WITH ASEPTIQUIK BODY (PICTURED)

PART NO.	A	B	C
AQSTC2330900	2.78 (70.6 mm)	9.25 (235 mm)	8.42 (213.9 mm)
AQSTC2331000	2.78 (70.6 mm)	9.25 (235 mm)	8.42 (213.9 mm)

• POLYCARBONATE HT with White Pull Tabs




TERMINATION
3/4" X 3/4" SANITARY STEAM-THRU II
WITH ASEPTIQUIK BODY (PICTURED)

3/4" X 1-1/2" SANITARY STEAM-THRU II
WITH ASEPTIQUIK BODY

PART NO.	A	B	C
AQSTC2330900HT	2.78 (70.6 mm)	9.25 (235 mm)	8.42 (213.9 mm)
AQSTC2331000HT	2.78 (70.6 mm)	9.25 (235 mm)	8.42 (213.9 mm)

ASEPTIQUIK® G STC SERIES DIMENSIONS



- A** = Height/Diameter
- B** = Total Length
- C** = Actuated Length

Mates with
genderless
AseptiQuik G
Series.

Coupling Bodies

• POLYCARBONATE with Blue Pull Tabs




TERMINATION
3/4" X 3/4" SANITARY STEAM-THRU II
WITH GENDERLESS ASEPTIQUIK G BODY

3/4" X 1-1/2" SANITARY STEAM-THRU II
WITH GENDERLESS ASEPTIQUIK G BODY

PART NO.	A	B	C
AQGSTC2330900	3.05	8.26	7.36
AQGSTC2331000	3.05	8.26	7.36

• POLYCARBONATE HT with White Pull Tabs












TERMINATION
3/4" X 3/4" SANITARY STEAM-THRU II
WITH GENDERLESS ASEPTIQUIK G BODY

3/4" X 1-1/2" SANITARY STEAM-THRU II
WITH GENDERLESS ASEPTIQUIK G BODY

PART NO.	A	B	C
AQGSTC2330900HT	3.05	8.26	7.36
AQGSTC2331000HT	3.05	8.26	7.36

ASEPTIQUIK® STC SERIES ASSEMBLY PROCEDURE

CLICK-PULL-TWIST Assembly Procedure



ASEPTIQUICK® G STC SERIES ASSEMBLY PROCEDURE

FLIP-CLICK-PULL Assembly Procedure

1

Steam flows from the process equipment through the Steam-Thru II in a steam trap creating a "steam on" sterile connection.

2

Unsnap and flip down the protective pull tab covers on each genderless AseptiQuick G connector half.

FLIP

3

"CLICK"

"CLICK"

Align genderless AseptiQuick G couplings, push together until "CPC Click" confirmation.

4

PUSH

Pull the snapped-together membrane pull tabs from the connector. Remove the Steam-Thru II lock sleeve.

5

PRESS

PUSH

Once the genderless AseptiQuick G assembly is complete and the steam trap has been closed, simply press the thumb latch to allow the valve to be pushed into the flow position. The "CPC Click" confirms the transition is complete.

6

Once the valve is locked into the flow position, you are ready for sterile fluid transfer to or from the process equipment.

7

PRESS

PULL

After sterile media transfer is complete, simply press the thumb latch and pull the valve back into the steam position. The "CPC Click" confirms the transition is complete.

8

With the valve locked securely into the steam position, complete a second SIP cycle to "steam off" the connection.



CONNECTIONS for CHEMICAL HANDLING APPLICATIONS






CPC is the leading provider of quick disconnect couplings and fittings for chemical handling and chemical packaging. Used in a broad range of applications, innovative coupling and connection technologies from CPC allow flexible tubing to be quickly connected and disconnected. CPC makes people's lives better by developing innovative high quality products that make fluid handling safe and easy.

CPC's wide range of chemically resistant quick disconnect couplings and DrumQuik® closed chemical dispensing systems provide non-spill operation and improve employee and environmental safety in chemical management environments. Applications include water treatment, janitorial and sanitation, Diesel Exhaust Fluid (DEF) dispensing, semiconductor and pharmaceutical manufacturing as well as pump, filter and de-ionized water connections.

DrumQuik PRO systems create a closed transfer system for general chemicals. Rugged and cost-effective DrumQuik dispensing systems minimize chemical exposure and facilitate the delivery of chemicals from bulk transfer containers to end use applications. For high purity applications, DrumQuik PUR provides the assurance of chemical compatibility and cleanroom assembly for contamination prevention.

CQH/CQV SERIES CONNECTOR



The **CQH and CQV Series** are designed for high-purity use and feature all plastic construction. Molded, virgin materials and lubricant-free design enable use in the most demanding applications. Broad chemical compatibility and cleanroom manufacturing make them ideal for use in critical wet processes.

FEATURES

100% metal free

High flow valve design

Disconnect under pressure

Polypropylene and PVDF

BENEFITS

No risk of metal contaminants or corrosion

High flow in a compact package

Speeds servicing and reduces risk of injury

Broad chemical compatibility

Specifications ● ● ●

CQH PRESSURE:

0 - 80 psig (0 - 5.5 bar)

CQH TEMPERATURE:

32°F to 225°F (0°C to 107°C)

CQH MATERIALS:

Main components: Natural, virgin polypropylene
Valve o-rings: FKM (black)
External insert o-ring: Simriz® FFKM perfluoro black)
Valve (wetted) and thumb latch spring: PEEK®
Flare nuts: PVDF
Lubricants: None used

CQV PRESSURE: 0 - 80 psig (0 - 5.5 bar)

CQV TEMPERATURE:

0°F to 225°F (-18°C to 107°C)

CQV MATERIALS:

Main components: Natural, virgin PVDF
Valve o-rings: Chemraz FFKM perfluoro (white)
External insert o-ring: Chemraz FFKM perfluoro (white)
Valve (wetted) and thumb latch spring: PEEK
Flare nuts: PVDF
Lubricants: None used

SPILLAGE/AIR INCLUSION:


~1.5 cc (ml)/disconnect (reconnect)

TUBING SIZES:


1/4" to 1/2" flare; 3/8" to 3/4" NPT

NOTE: CQH & CQV are also available with optional PPS springs and Chemraz FFKM or EPDM seals.


CQHD06 Pressure Range




CQVD06 Pressure Range



CQHD06 Water Flow




CQVD06 Water Flow




These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.

See page 141 for
ChemQuik Dual
Containment Nut
options.

CQH/CQV SERIES CONNECTOR DIMENSIONS



- A** = Height/Diameter
- B** = Total Length (including valve)
- C** = Hex Size on Main Component



Gasket Thickness: .06"
 Mounting Hole: 1.21" diameter
 Coupling Spacing: 1.92" minimum
 Panel Thickness: .25"

	PANEL OPENING	PANEL THICKNESS MAX.-MIN.
COUPLING BODIES	see drawing	.25 - .03

CQH Coupling Bodies • POLYPROPYLENE

TERMINATION	TUBING/THREAD SIZE	TERMINATION TYPE	SHUTOFF	A	B	C
IN-LINE	1/4" OD	Flare compression	CQHD06100104	1.44	3.32	
	3/8" OD	Flare compression	CQHD06100106	1.44	3.38	
	1/2" OD	Flare compression	CQHD06100108	1.44	3.38	
	3/8" Taper	Male NPT	CQHD06100206	1.44	2.73	1.00
PANEL MOUNT	1/4" OD	Flare compression	CQHD06110104	1.82	3.32	
	3/8" OD	Flare compression	CQHD06110106	1.82	3.38	
	1/2" OD	Flare compression	CQHD06110108	1.82	3.37	
	3/8" Taper	Male NPT	CQHD06110206	1.82	2.73	1.00

CQH Coupling Inserts • POLYPROPYLENE

TERMINATION	TUBING/THREAD SIZE	TERMINATION TYPE	SHUTOFF	A	B	C
IN-LINE	1/4" OD	Flare compression	CQHD06200104	1.00	2.49	
	3/8" OD	Flare compression	CQHD06200106	1.00	2.55	
	1/2" OD	Flare compression	CQHD06200108	1.00	2.56	
	3/8" Taper	Male NPT	CQHD06200206	1.16	1.90	1.00
	3/4" Taper	Male NPT	CQHD06200212	1.16	2.26	1.00

CQV Coupling Bodies • PVDF


TERMINATION	TUBING/THREAD SIZE	TERMINATION TYPE	SHUTOFF	A	B	C
IN-LINE	1/4" OD	Flare compression	CQVD06100104	1.44	3.31	
	3/8" OD	Flare compression	CQVD06100106	1.44	3.38	
	1/2" OD	Flare compression	CQVD06100108	1.44	3.37	
	3/8" Taper	Male NPT	CQVD06100206	1.44	2.70	1.00
PANEL MOUNT	1/4" OD	Flare compression	CQVD06110104	1.82	3.24	
	3/8" OD	Flare compression	CQVD06110106	1.82	3.38	
	1/2" OD	Flare compression	CQVD06110108	1.82	3.37	
	3/8" Taper	Male NPT	CQVD06110206	1.82	2.70	1.00

CQV Coupling Inserts • PVDF

TERMINATION	TUBING/THREAD SIZE	TERMINATION TYPE	SHUTOFF	A	B	C
IN-LINE	1/4" OD	Flare compression	CQVD06200104	1.00	2.41	
	3/8" OD	Flare compression	CQVD06200106	1.00	2.57	
	1/2" OD	Flare compression	CQVD06200108	1.00	2.57	
	3/8" Taper	Male NPT	CQVD06200206	1.16	1.89	1.00

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.

CQG SERIES CONNECTOR



The CQG06 Series high purity couplings feature our patented pressure-balanced, non-spill design. Molded virgin polypropylene and a 100% springless flow path provide broad chemical resistance and exceptionally high flow capacity, allowing instant disconnects (and reconnects), even under pressure.

FEATURES

Non-spill design

Pressure-balanced

Springless flow path design

BENEFITS

Ultimate protection from chemicals and fumes

Failsafe disconnect, even under pressure; easy to reconnect at high pressure

Eliminates source of metallic contaminants

Specifications ● ● ●

PRESSURE:

0 - 80 psig (0 - 5.5 bar)

TEMPERATURE:

32°F to 150°F (0°C to 66°C)

MATERIALS:

Main components:

Natural, virgin polypropylene

Seals: FKM (Simriz® FFKM optional)

Springs (non-wetted): Hastelloy® C

Flare nuts: PVDF

Lubricants: None used

Dual Containment Nut and Panel Mount Fitting:

Virgin, natural polypropylene

Flare nuts: PVDF

Panel nuts: HDPE

Panel mount o-rings: FKM

SPILLAGE/AIR INCLUSION:

<0.1 cc (ml)/disconnect (reconnect)

PANEL MOUNT: Optional adapter kit



TUBING SIZES:

3/8" to 3/4" flare; 3/8" to 3/4" NPT


WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions.



These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.



CQG SERIES CONNECTOR DIMENSIONS



Coupling Bodies • POLYPROPYLENE

TERMINATION IN-LINE	TUBING/THREAD SIZE	TERMINATION TYPE	SHUTOFF	A	B	C
	3/8" OD	Flare compression	CQGD06100106	1.96	4.21	
	1/2" OD	Flare compression	CQGD06100108	1.96	4.42	
	3/4" OD	Flare compression	CQGD06100112	1.96	4.49	
	1/2" Taper	Male NPT	CQGD06100208	1.96	3.81	1.00

Coupling Inserts • POLYPROPYLENE

TERMINATION IN-LINE	TUBING/THREAD SIZE	TERMINATION TYPE	SHUTOFF	A	B	C
	3/8" OD	Flare compression	CQGD06200106	1.62	4.35	
	1/2" OD	Flare compression	CQGD06200108	1.62	4.45	
	3/4" OD	Flare compression	CQGD06200112	1.62	4.63	
	3/8" Taper	Male NPT	CQGD06200206±	1.62	3.81	1.00
	1/2" Taper	Male NPT	CQGD06200208	1.62	3.95	1.00
	3/4" Taper	Male NPT	CQGD06200212±	1.62	4.15	1.00

Panel Mount Adaptor • POLYETHYLENE

DESCRIPTION	PART NO.
Panel mount adapter kit (fits both bodies & inserts)	CQG06PMKIT01

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.

ChemQuik® Dual Containment Flare Nuts • POLYPROPYLENE



The ChemQuik® Dual Containment System is an easy way to "double contain" critical chemical lines, protecting plant and personnel in case a primary process line ruptures or "sweats". The system provides a protective secondary line to catch any fluid and routes it to a safe location.

These fittings work with any ChemQuik coupling with fine thread flare terminations or a common flare style fitting. In addition, the panel mount version can be mounted into a pump cabinet or other panel mount connection point. The primary line can then be routed from the coupling directly to a pump, connected to a ChemQuik coupling at the panel mount fitting.

The "weep port" serves to vent the area between the primary and secondary lines so that pressure cannot build up in case of a primary line rupture. The leaking fluid can then be routed to a containment vessel or to a leak detector.

FLARE NUT	DESCRIPTION
CQDCNUT0408	Dual containment nut, 1/4" OD process line x 1/2" OD secondary containment line.
CQDCNUT0612	Dual containment nut, 3/8" OD process line x 3/4" OD secondary containment line.
CQDCNUT0812	Dual containment nut, 1/2" OD process line x 3/4" OD secondary containment line.
CQDCNUT1216	Dual containment nut, 3/4" OD process line x 1" OD secondary containment line.

FLARE FITTING	DESCRIPTION
CQPMDCNUT0408	Panel mount dual containment nut, 1/4" OD Process line x 1/2" OD secondary containment line.
CQPMDCNUT0612	Panel mount dual containment nut, 3/8" OD Process line x 3/4" OD secondary containment line.
CQPMDCNUT0812	Panel mount dual containment nut, 1/2" OD Process line x 3/4" OD secondary containment line.
CQPMDCNUT1216	Panel mount dual containment nut, 3/4" OD Process line x 1" OD secondary containment line.

DRUMQUIK PRO / DRUMQUIK PUR

DrumQuik Dispensing Systems for Safer Chemical Management

Whether you're dispensing edible oils, condiments, detergents, specialty automotive fluids, or industrial chemicals, acids, caustics or solvents, DrumQuik PRO and the high purity DrumQuik PUR can make your process cleaner, faster, safer and smarter.

- Provide the critical connection between your chemical container and the end use process
- Create a closed transfer system to protect workers and keep a cleaner work environment

DrumQuik solutions are available for a variety of container types providing interchangeable, reusable connections for:

- Plastic or steel drums
- Chemical packs
- IBCs or totes

Note: For high purity applications DrumQuik PUR provides the assurance of compatibility with chemicals used in semiconductor and flat panel production, pharmaceutical and photovoltaic or solar cell manufacturing.

DrumQuik® PRO and DrumQuik PUR dispensing systems are used with common pumps to create a closed transfer system for both general and high purity chemicals. These easy-to-use products meet the strict safety requirements of chemical handling applications as well as the demands of harsh operating environments. DrumQuik dispensing systems minimize chemical exposure and facilitate the delivery of chemicals from bulk transfer containers to end use applications.


For general chemical dispensing, DrumQuik PRO offers a rugged and cost-effective solution. DrumQuik PUR is a 100% metal-free, cleanroom packaged, PVDF product designed specifically for applications demanding the highest level of purity. All materials are compliant with FDA standards for food and consumables applications.


The DrumQuik PRO dispensing system has been UN/DOT certified with many common drums and IBCs for use with hazardous chemicals per 49 CFR 173 and German BAM 11027.

Made from virgin materials compliant with FDA and ROHS standards.



This graph characterizes the flow of the DrumQuik PRO with the coupler vent port open to the atmosphere and a pump drawing liquid out.





Specifications ● ● ●

PRESSURE:

Uncoupled: Vacuum to 45 psig, 3.1 bar
Coupled: Vacuum to drum rating

TEMPERATURE:

Drum insert: -20°F to 120°F (-20°C to 49°C)
Coupler: HDPE, 32°F to 120°F (0°C to 49°C)
PVDF, 0°F to 120°F (-18°C to 49°C)

MATERIALS:

Drum insert & dip-tube:
Virgin polyethylene (HDPE)

Shipping plug:
Virgin polyethylene (HDPE)

Coupler:
Virgin polypropylene (DrumQuik PRO)
Virgin PVDF (DrumQuik PUR)

Spring (coupler only):
316 stainless steel, Hastelloy® C, virgin PEEK
UHP, PPS or PTFE encapsulated 316 stainless steel (TESS)

Seals:
Coupler seals: EPDM, FKM, Simriz® UHP
FFKM Perfluoroelastomer

Bung seal: Polyolefin, EPDM, FKM

Shipping plug seal: EPDM, FKM

Torque specifications:
2" Buttress - 20ft-lbs (27 N-m)
BCS 56x4 - 20ft-lbs (27 N-m)
BCS 70mm - 22ft-lbs (30 N-m)
2" NPS (plastic drum) - 20ft-lbs (27 N-m)
2" NPS (steel drum) - 15ft-lbs (20 N-m)
Shipping plug - 15inch-lbs (1.7 N-m)

NOTE: The torque specifications listed above are general recommendations which may need to be adjusted + or - depending on specific application.

DrumQuik® PRO and DrumQuik PUR are changing the world of chemical management with their unique closed-system design. Innovative DrumQuik systems help companies reduce costs, increase worker safety and protect the environment. From basic chemical handling to specialty high purity and pharmaceutical applications, DrumQuik dispensing systems make chemical management cleaner, faster, safer and smarter.

DrumQuik PRO

FEATURES	BENEFITS
Quick connect/disconnect	Allows faster drum change-outs
Automatic shutoff valve	Stops flow when disconnected
Disposable drum insert	Reduces messy handling and chemical exposure
Ported vent system for vapor management	Allows make-up air into drum or connection of blanket gas (N2,C02)
Multiple standard thread sizes	Can be used with many common steel and plastic containers

DrumQuik PUR

FEATURES	BENEFITS
Quick connect/disconnect	Allows faster drum change-outs
All plastic construction	No metallic corrosion/contamination
Automatic shutoff valve	Stops flow when disconnected
Cleanroom manufactured	Assures high level of purity
Disposable drum insert	Minimizes chemical exposure & contamination

Couplers • POLYPROPYLENE

DRUMQUIK PRO	PART NUMBER	DESCRIPTION
	DQPRO120312	3/4" Hose barb (EPDM seals, 316 SST spring)
	DQPRO120208	1/2" Male NPT (EPDM seals, 316 SST spring)
	DQPRO120208202	1/2" Male NPT (FKM seals, 316 SST spring)
	DQPRO120208206	1/2" Male NPT (EPDM seals, Hastelloy C spring)
	DQPRO120208207	1/2" Male NPT (FKM seals, Hastelloy C spring)
	DQPRO120712	3/4" Male BSPP (EPDM seals, 316 SST spring)
	DQPRO120712202	3/4" Male BSPP (FKM seals, 316 SST spring)
	DQPRO120712206	3/4" Male BSPP (EPDM seals, Hastelloy C spring)
	DQPRO120712207	3/4" Male BSPP (FKM seals, Hastelloy C spring)

Couplers • PVDF (3/4" FLARE TERMINATION)

DRUMQUIK PUR	PART NUMBER	DESCRIPTION
	DQPUR120112	FKM liquid contact seals, FKM vent seal, PEEK plastic spring
	DQPUR120112203	Simriz® FFKM liquid contact seals, FKM vent seal, PEEK plastic spring
	DQPUR120112208	FKM liquid contact seals, FKM vent seal, PPS plastic spring
	DQPUR120112209	Simriz FFKM liquid contact seals, FKM vent seal, PPS plastic spring
	DQPUR120112210	FKM liquid contact seals, FKM vent seal, PTFE encapsulated 316 stainless steel (TESS) spring
	DQPUR120112211	Simriz FFKM liquid contact seals, FKM vent seal, PTFE encapsulated 316 stainless steel (TESS) spring

Drum Inserts • POLYETHYLENE (HDPE)

DRUMQUIK PRO & DRUMQUIK PUR	PART NUMBER	DESCRIPTION
	DQPRO20BCS70	70mm thread, EPDM seals (70x6 and 70x5 plastic drums)
	DQPRO20BCS70202	70mm thread, FKM seals (70x6 and 70x5 plastic drums)
	DQPRO202BUT	2" American buttress thread, EPDM seals (No. Am. Plastic drums)
	DQPRO202BUT202	2" American buttress thread, FKM seals (No. Am. Plastic drums)
	DQPRO2056X4	BCS 56x4 thread, EPDM seals (European plastic drums)
	DQPRO2056X4202	BCS 56x4 thread, FKM seals (European plastic drums)
	DQPRO20G2NPSST	2" NPS (ISO G2) thread, EPDM seals (steel drums and IBC caps)
	DQPRO20G2NPSST202	2" NPS (ISO G2) thread, FKM seals (steel drums and IBC caps)
	DQPRO20G2NPSPL	2" NPS (ISO G2) thread, EPDM flat bung seal (plastic drums and IBC caps)
	DQPRO20G2NPSPL202	2" NPS (ISO G2) thread, FKM flat bung seal (plastic drums and IBC caps)
	DQPUR202BUT	2" American buttress thread, Polyolefin (POE) bung seal, EPDM shipping plug seal
	DQPUR202BUT202	2" American buttress thread, Polyolefin (POE) bung seal, FKM shipping plug seal


Dip-Tubes • POLYETHYLENE (HDPE)

DRUMQUIK PRO & PUR	PART NUMBER	DESCRIPTION
	DQPRODT0410	13.0" (330mm) long for 5 gal/25L jerry cans
	DQPRODT0985	35.5" (905mm) long for 55 gal/200L drums
	DQPRODT1070	39.0" (990mm) long for 275 gal/1040L IBCs
	DQPRODT1274	47.0" (1194mm) long for 330 gal/1250L IBCs
	DQPURDT0410	13.0" (330mm) long for 5 gal/25L jerry cans
	DQPURDT0985	35.5" (905mm) long for 55 gal/200L drums
	DQPURDT1070	39.0" (990mm) long for 275 gal/1040L IBCs
	DQPURDT1274	47.0" (1194mm) long for 330 gal/1250L IBCs

Assembled Drum Inserts & Dip-Tubes

DRUMQUIK PUR	PART NUMBER	DESCRIPTION
	DQPUR2BUT0410	Drum insert assembly, NAMPAC square jerry can, 20L, 330mm long (from sealing surface)
	DQPUR2BUT0985	Drum insert assembly with universal dip-tube (drum), 905mm long (from sealing surface)
	DQPUR2BUT1070	Drum insert assembly with universal dip-tube (drum), 990mm long (from sealing surface)
	DQPUR2BUT1274	Drum insert assembly with universal dip-tube (IBC), 1194mm long (from sealing surface)

DrumQuik® PRO & PUR Dispensing Connector System



VAPOR MANAGEMENT OPTIONS:

- 1. OPEN:** Vent port left open to atmosphere
- 2. REMOTE:** Vent port routed to fume hood, scrubber or vapor recovery system
- 3. CHECKED:** Connect vent check valve to allow make-up air in without allowing fumes to escape
- 4. BLANKET GAS:** Connect a CPC quick disconnect coupling for blanket gas (N₂, CO₂)
- 5. FILTERED:** Connect vent filter

DRUMQUIK PRO / DRUMQUIK PUR ACCESSORIES

Color Coding and Keying Options

• COLORED KEY KITS FOR PHYSICAL CODING: POLYETHYLENE

DQPRO PART NUMBER	DQPUR PART NUMBER	DESCRIPTION
DQPROKEYCPGRY00	DQPURKEYCPGRY00	Key kit for coupler, gray
DQPROKEYCPRED01	DQPURKEYCPRED01	Key kit for coupler, red
DQPROKEYCPYEL02	DQPURKEYCPYEL02	Key kit for coupler, yellow
DQPROKEYCPGRN03	DQPURKEYCPGRN03	Key kit for coupler, green
DQPROKEYCPBRN04	DQPURKEYCPBRN04	Key kit for coupler, brown
DQPROKEYCPBLU05	DQPURKEYCPBLU05	Key kit for coupler, blue
DQPROKEYCPBLK99	DQPURKEYCPBLK99	Key kit for coupler, black
DQPROKEYCPCOMBO	DQPURKEYCPCOMBO	One of every coupler key ring and cap
<i>Key kits for coupler include coupler key ring and cap.</i>		
DQPROKEYDIRE01	DQPURKEYDIRE01	Key kit for drum insert, red
DQPROKEYDIYEL02	DQPURKEYDIYEL02	Key kit for drum insert, yellow
DQPROKEYDIGRN03	DQPURKEYDIGRN03	Key kit for drum insert, green
DQPROKEYDIBRN04	DQPURKEYDIBRN04	Key kit for drum insert, brown
DQPROKEYDIBLU05	DQPURKEYDIBLU05	Key kit for drum insert, blue
DQPROKEYDIBLK99	DQPURKEYDIBLK99	Key kit for drum insert, black
DQPROKEYDICOMBO	DQPURKEYDICOMBO	One of every drum insert key ring and button plug
<i>Key kits for drum insert include drum insert key ring and button plug.</i>		


Color Coded Parts

• COLORED CAPS & BUTTON PLUGS FOR VISUAL CODING: POLYETHYLENE

PART NUMBER	DESCRIPTION
DQPROCAPGRY00	Colored cap for coupler, gray
DQPROCAPRED01	Colored cap for coupler, red
DQPROCAPYEL02	Colored cap for coupler, yellow
DQPROCAPGRN03	Colored cap for coupler, green
DQPROCAPBRN04	Colored cap for coupler, brown
DQPROCAPBLU05	Colored cap for coupler, blue
DQPROCAPBLK99	Colored cap for coupler, black
DQPROCAPCOMBO	One each of every color cap
DQPROPLUGGRY00	Colored button plug for drum insert, gray
DQPROPLUGRED01	Colored button plug for drum insert, red
DQPROPLUGYEL02	Colored button plug for drum insert, yellow
DQPROPLUGGRN03	Colored button plug for drum insert, green
DQPROPLUGBRN04	Colored button plug for drum insert, brown
DQPROPLUGBLU05	Colored button plug for drum insert, blue
DQPROPLUGBLK99	Colored button plug for drum insert, black
DQPROPLUGCOMBO	One each of every color plug

Note: Colored caps and button plugs can be used with both DrumQuik PRO and DrumQuik PUR.

DrumQuik® PRO & PUR Key Kits



Color Coding



DRUMQUIK PRO / DRUMQUIK PUR ACCESSORIES

Tools



- 1 Fully press dip-tube into drum insert socket.



- 2 Place the drum insert assembly in drum.



- 3 Turn shipping plug counterclockwise to remove. (Use a large, flat blade or #4 Phillips screwdriver.)



- 4 Insert coupler into drum insert assembly.



- 5 Turn the coupler locking ring clockwise until stop is reached (approximately 2 full turns); valve is opened during this process.

PART NUMBER

DESCRIPTION

2408900	Torque socket tool (blue, glass-filled nylon)
2479100	Bung wrench (aluminum)
2375600	Key installation tool for key kits (Shipping plug may also be used to install keys)
DQPURFT08	Flaring Tool, 1/2" tubing
DQPURFT12	Flaring Tool, 3/4" tubing

Sample Kits (Includes one coupler, one insert and one dip-tube)

PART NUMBER

DESCRIPTION

DQPRONASAMP	2" Buttress drum insert, 905mm dip-tube, 1/2 NPT coupler (EPDM O-rings, 316 SST spring in coupler)
DQPRONASAMP207	2" Buttress drum insert, 905mm dip-tube, 1/2 NPT coupler (FKM seals & Hastelloy® C spring in coupler)
DQPROEUSAMP	BSC 56x4 drum insert, 905mm dip-tube, 3/4 BSPP coupler (EPDM seals, 316 SST spring in coupler)
DQPROEUSAMP207	BSC 56x4 drum insert, 905mm dip-tube, 3/4 BSPP coupler (FKM seals & Hastelloy® C spring in coupler)
DQPRONPSSTSAMP	2" NPS (ISO G2) drum insert, 905mm dip-tube, 1/2 NPT coupler (EPDM Bung O-rings, 316 SST spring in coupler)
DQPRONPSSTSAMP207	2" NPS (ISO G2) drum insert, 905mm dip-tube, 1/2 NPT coupler (FKM seals & Hastelloy® C spring in coupler)
DQPRONPSLSAMP	2" NPS (ISO G2) drum insert, 905mm dip-tube, 1/2 NPT coupler (EPDM Flat Gasket, 316 SST Spring)
DQPRONPSLSAMP207	2" NPS (ISO G2) drum insert, 905mm dip-tube, 1/2 NPT coupler (FKM seals & Hastelloy® C spring in coupler)
DQPURSAMP202	Kit includes 1 Coupler (DQPUR 12 0112 (PEEK® & FKM) & 1 assembled Dip-tube (DQPUR 2BUT 0985 202)
DQPURSAMP209	Kit includes 1 Coupler (DQPUR 12 0112 209 (PPS & Simriz®) & 1 Dip-tube assy. (DQPUR 2BUT 0985 202)

Shipping Plugs

PART NUMBER

DESCRIPTION

DQPROPUMPAD	Internal 3/4 NPT Thread pump adaptor shipping plug (HDPE, EPDM)
DQPROPUMPAD202	Internal 3/4 NPT Thread pump adaptor shipping plug (HDPE, FKM)
DQPRPUMPAD202	Extended shipping plug for venting internal pressure from
DQPROSHPLUGEX	drum (HDPE, EPDM)
DQPROSHPLUGEX202	Extended shipping plug for venting internal pressure from drum (HDPE, FKM)
2007900	Shipping plug for drum insert (Does not include shipping plug o-ring)
2290100	Shipping plug o-ring, EPDM
2307200	Shipping plug o-ring, FKM
DQPURSP	Shipping Plug with EPDM seal
DQPURSP202	Shipping Plug with FKM seal

Sample Kits (Includes one coupler, one insert and one dip-tube)

PART NUMBER

DESCRIPTION

DQPURDISEALPOE	Drum insert POE bung seal
DQPURDISEALFEP	Drum insert FEP encapsulated silicone bung seal
DQPURCPSEALFKM	Coupler seal kit (2 seals), FKM
DQPURCPSEALSMZ	Coupler seal kit (2 seals), Simriz®
2423400	Coupler o-ring kit, EPDM (Includes 2 o-rings)
2423500	Coupler o-ring kit, FKM (Includes 2 o-rings)
2166000	Drum insert flat gasket, 2" buttress, FDA EPDM
2166100	Drum insert flat gasket, 2" buttress, FKM
2165800	Drum insert o-ring, 2" NPS (ISO G2) EPDM for steel drums
2165900	Drum insert o-ring, 2" NPS (ISO G2) FKM for steel drums
2165800	Drum insert o-ring, BCS 56x4, EPDM (same as ISO G2 for steel)
2165900	Drum insert o-ring, BCS 56x4, FKM (same as ISO G2 for steel)
2525200	Drum insert flat gasket, 2" NPS (ISO G2) EPDM for plastic drums
2525300	Drum insert flat gasket, 2" NPS (ISO G2) FKM for plastic drums
2594900	Replacement Drum Insert Seal, 2" Buttress, FDA
DQPR070X6AD	70 X 6 Adaptor with EPDM O-Ring
DQPR070X6AD202	70 X 6 Adaptor with FKM (Viton®) O-Rings

Accessories

PART NUMBER

DESCRIPTION

TETHER/DUST CAP

DQPROTETHER

Tether/Dust Cap for use with DrumQuik PRO shipping plugs and couplers (PVC, Vinyl)

COUPLER VENT PORT OPTIONS

2879800	Vent check valve, 1/2" ID x 1/4" male NPT (316 SST, Santoprene)
2879801	Vent check valve, 1/2" ID x 1/4" male NPT (Hastelloy® C, FKM)
DQPROFIL01	Air filter, coupler vent port, 1/4" male NPT (polypropylene, 70 micron)
APCD24004	Vent coupling insert, 1/4" male NPT (Acetal, 316 SST, Buna-N)
APCD17004SH	Vent coupling body with shroud, 1/4" hose barb (Acetal, 316 SST, Buna-N)
APCD17006SH	Vent coupling body with shroud, 3/8" hose barb (Acetal, 316 SST, Buna-N)
EFC024412	Vent coupling insert, 1/4" male NPT (Polypropylene, 316 SST, EPDM)
EFC017412	Vent coupling body, 1/4" hose barb (Polypropylene, 316 SST, EPDM)
EFC017612	Vent coupling body, 3/8" hose barb (Polypropylene, 316 SST, EPDM)

NOTE: Parts listed above are suggested for use in the vent port, but any 1/4" NPT CPC coupling can be used for blanket gas applications (see page 144)

BACKFLOW PREVENTION OPTIONS • POLYPROPYLENE

2478900	Check valve for couplers, 1/2" female NPT x 1/2" male NPT (EPDM, 302 SST)
2478901	Check valve for couplers, 1/2" female NPT x 1/2" male NPT (FKM, 302 SST)
2478902	Check valve for couplers, 1/2" female NPT x 1/2" male NPT (EPDM, Hastelloy C)
2478903	Check valve for couplers, 1/2" female NPT x 1/2" male NPT (FKM, Hastelloy C)
2479000	Foot valve for dip-tube, 1/2" hose barb (EPDM, 316 SST)
2479001	Foot valve for dip-tube, 1/2" hose barb (FKM, 316 SST)
2479002	Foot valve for dip-tube, 1/2" hose barb (EPDM, Hastelloy C)
2479003	Foot valve for dip-tube, 1/2" hose barb (FKM, Hastelloy C)

NOTE: CPC distributes the above check valves and foot valves. These valves are not produced by CPC and CPC makes no claims or warranty regarding suitability for use in specific applications.

COUPLER LIQUID PORT FITTINGS • POLYPROPYLENE

2402600	1/2" female NPT x 3/8" OD compression
2402700	1/2" female NPT x 1/2" OD compression
2402800	1/2" female NPT x 5/8" OD compression
2402900	1/2" female NPT x 3/8" ID hose barb
2403000	1/2" female NPT x 1/2" ID hose barb
2403100	1/2" female NPT x 3/4" ID hose barb

DQPUR ACCESSORY FITTINGS

DQPUR MC0404	Male Connector, PVDF, 1/4" Flare x 1/4" NPT
DQPUR MC0604	Male Connector, PVDF, 3/8" Flare x 1/4" NPT
DQPUR MC0804	Male Connector, PVDF, 1/2" Flare x 1/4" NPT
DQPUR FR1208	Flare Reducer, PFA, 3/4" Female Flare x 1/2" Male Flare
DQPUR FI1216	Flare Increaser, PFA, 3/4" Female Flare x 1" Male Flare
DQPUR TFMC1208	Female flare x male connector, PFA, 3/4" Female Flare x 1/2" Male NPT
DQPUR SE0808	Sweep Elbow, PFA, 1/2" Female Flare x 1/2" Male Flare
DQPURSE1212	Sweep Elbow, PFA, 3/4" Female Flare x 3/4" Male Flare
DQPURDCPM0812	Double Containment Panel Mount Fitting, PFA, 1/2" process line x 3/4" secondary containment line
DQPURDCPM1216	Double Containment Panel Mount Fitting, PFA, 3/4" process line x 1" secondary containment line
DQPURDCN0812	Double Containment Adapter, PFA, 1/2" process line x 3/4" secondary containment line
DQPURDCN1216	Double Containment Adapter, PFA, 3/4" process line x 1" secondary containment line

Use shipping plug or key installation tool to install keys. Orient ring with lugs down and drum insert key ring with shoulder up.

Torque Tool



Bung Wrench

Refer to specifications for torque requirements (page 143)



Backflow Check and Foot Valves

Prevents liquid from draining back into drum when pump is off




Coupler Liquid Port Fittings



Shipping Plug



Key installation Tool



DRUMQUIK PRO / DRUMQUIK PUR ACCESSORIES



Universal 3-Port Drum Adaptor Kit
(shown with HFC12 and NS4)



DrumQuik® 3-Port UDA Kit • POLYPROPYLENE

The 3-Port UDA features a 3/4" male NPT thread that mates with common containers, bung plugs and caps. The adaptor ports enable simultaneous chemical extraction, venting or application of blanket gas. In addition, the third port can be used to recirculate priming chemical to the container in metering pump applications.

Optional system components including foot valves, air filters and vent check valves are also available. For your convenience, CPC offers a variety of drum adaptor plugs to facilitate easy drum connections. (See plugs and caps on page 149.)

PART NUMBER	DESCRIPTION
DQUA3PKIT	3-port adaptor, EPDM seal, locking nut, 35.5" (905mm) dip-tube, 1/2" x 3/8" & 1/2" x 1/4" reducer bushings and 1/4" & 3/8" NPT plugs
DQUA3PKIT202	3-port adaptor, FKM seal, locking nut, 35.5" (905mm) dip-tube, 1/2" x 3/8" & 1/2" x 1/4" reducer bushings and 1/4" & 3/8" NPT plugs
DQUA3P	3-port adaptor bulk packaged (1/2" female NPT liquid outlet port, 3/8" & 1/4" NPT vent/recirculation ports)
DQUA3PNUT	Locking nut for the 3-port adaptor
2717000	EPDM seal for the 3-port adaptor
2717100	FKM seal for the 3-port adaptor
2621100	Reducer bushing, black polypropylene, 1/2" male NPT x 3/8" female NPT
2621200	Reducer bushing, black polypropylene, 1/2" male NPT x 1/4" female NPT
2621300	Pipe plug, black polypropylene, 1/4" male NPT
2621400	Pipe plug, black polypropylene, 3/8" male NPT

Note: DrumQuik® UDA 3-Port uses DrumQuik PRO dip-tubes and accessories.

DrumQuik UDA Kit • POLYPROPYLENE

The DrumQuik® UDA Kit turns ChemQuik® or general purpose (HFC or NSH) couplings into a dip-tube that can easily be threaded into the 3/4" female NPS port of common drum closures. It provides a simple and inexpensive way to dispense chemicals in pumped systems. For your convenience, CPC offers a variety of drum adaptor plugs to facilitate easy drum connections. (See plugs and caps on page 149.)

Press together to assemble



Dip-tube



Bushing



Coupling Insert



Coupling Body

PART NUMBER	DESCRIPTION
DQUADKIT	Adaptor & DQPRODT1274 47" long dip-tube



Universal Drum Adaptor Kit
(shown with NSH Series)

Can be
used with many
standard CPC quick
disconnect couplings
and standard bung
plugs and bottle
caps

BottleQuik® 2-Port Kit UDA • POLYPROPYLENE

The BottleQuik® is intended for use on reagent bottles with SP400-38mm threads. It can be used in either the upright position or inverted and has two 3/8" female NPT ports for liquid and vent ports.

PART NUMBER	DESCRIPTION
DQUDACAP2PKITPP	2-Port adaptor CAP for 38mm SP400 bottles & dip-tubes, 17.75" (451mm) long, FKM o-ring, 3/8" female NPT liquid port, 3/8" female NPT vent port, 3/8" female NPT vent port. Use above kits with CQG, CQH and CQV Series couplings.

DrumQuik Asian Drum Adaptors • POLYPROPYLENE

The DrumQuik® Asian drum adaptors allow ChemQuik® or general purpose (HFC or NSH) couplings to be easily connected to the unique threads common in many drum closures (with integral dip-tubes) manufactured in Asia, e.g., Kodama, Accelo, Stella, Dung Woo, etc. A 3/4" female NPT inner thread can accept any coupling or fitting with a 3/4" male NPT termination.

PART NUMBER	DESCRIPTION
DQADAPP0212 • TYPE A	Adaptor, FKM seals, 3/4" female NPT inner port x 3/4" NPS male thread to fit drum plug.
DQADAPP0622 • TYPE B	Adaptor, FKM seals, 3/4" female NPT inner port x 1-3/8" TYPE B male buttress thread to fit drum plug.

DrumQuik Plugs and Caps

For your convenience, CPC offers several sizes of common bung plugs and caps that have the internal 3/4" female NPS thread, into which the DrumQuik Universal Drum Adaptors/ChemQuik couplings are threaded.

PART NUMBER	DESCRIPTION
DQMBUNGPP2BUT12	Bung closure, polypropylene, EPDM o-ring, 2" buttress x 3/4" female NPS
DQMBUNGPP2NPS12	Bung closure, polypropylene, EPDM o-ring, 2" NPS x 3/4" female NPS
DQMBUNGPP56X412	Bung closure, polypropylene, EPDM o-ring, BCS56x4 x 3/4" female NPS
DQMBUNGPP70X612	Bung closure, polypropylene, EPDM o-ring, BCS70x6, 3/4" female NPS
DQMCAPP70mm	Cap closure, polypropylene, EPDM o-ring, 70mm x 3/4" female NPS
DQMCAPP63MM	Cap closure, polypropylene, EPDM o-ring, 63mm, 3/4" female NPS

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. **NOTE:** The DQ UDA kits are designed to work with CPC couplings that have 3/4" NPT male terminations. The DQ UDA 3-Port kits are designed to work with a 1/2" NPT male on the liquid port and a 1/4" NPT male on the vent port. A 1/2" male NPT to 1/4" female NPT reducer bushing may be required to accommodate smaller NS4, PLC and PMC Series couplings. BottleQuik features two 3/8" female NPT ports. **NOTE:** DrumQuik Adaptors are intended for end-use applications not requiring compliance with UN/DOT standards for use in transportation of hazardous materials.



BottleQuik 2-Port UDA Bottle Adaptor Kit
(shown with CQG and CQH)



Type A

For use with closure plugs with a 3/4" NPS center port.



Type B

For use with closure plugs with a 1-3/8" buttress center port.



3/4" NPT inner port incorporates a face seal to assure a leak-free connection.



DQ UDA kits can be used with a wide range of closures.

UDC SERIES CONNECTOR

Specifications ● ● ●

PRESSURE:

20" Hg vacuum to 15 psi, 1.0 bar (body only)

TEMPERATURE:

32°F to 160°F (0°C to 71°C)

MATERIALS:

Main body components and valves:
Polypropylene

Springs:

Body: 316 stainless steel
Cap: 302 stainless steel

UDC caps: Acetal, polypropylene

O-rings (food grade):

UDC: EPDM, silicone, Buna-N

iUDC: EPDM, silicone

CIP adapter: Acetal

COLOR: Light gray with dark gray latch

CLOSURE SIZE: SP-400 thread/38mm
snap-in

TUBING SIZES:

3/8" to 3/4" ID, 9.5mm to 19.0mm ID

The patented 3/8" flow Universal Dispensing Coupler (UDC)

provides a universal connection to a 38mm threaded or snap-in fitment neck. Make instant connections to bulk packaging systems including bag-in-box (BIB), flexible and rigid packaging styles. Automatic flush face valves minimize costly or dangerous spillage. An ergonomic design and a large, shrouded thumb latch pad produce a coupling that is easy to grip and simple to operate.

The UDC Series is also available with optional RFID (Radio Frequency Identification) capability (see page 95).


FEATURES

Universal 38mm cap
Flush face/non-spill valves
Integral terminations
Shrouded thumb latch
RFID technology (iUDC only)

BENEFITS

Fits industry standard fitment necks
Minimize spillage
Fewer leak points, shorter assemblies, faster installations
Protects against accidental disconnects
Helps maintain warranty, integrity, brand protection

All UDC series products are listed under NSF/ANSI standard 169



A = Height/Diameter
B = Total Length
D = Elbow Radial Length

UDC SERIES DIMENSIONS

Coupling Bodies • POLYPROPYLENE



TERMINATION	TUBING SIZE	SILICONE O-RING	BUNA-N O-RING	EPDM O-RING	A	B	D
IN-LINE HOSE BARB	3/8" ID	99000	98400	98500	1.73	3.06	
	1/2" ID	95600	97600	95300	1.73	3.06	
	5/8" ID	99100	97900	98100	1.73	3.20	
	3/4" ID	99200	98600	98700	1.73	3.21	
ELBOW HOSE BARB	3/8" ID	99300	97800	99400	1.73	3.25	.93
	1/2" ID	95400	97700	95100	1.73	3.25	.93

Caps • ACETAL



TERMINATION	DESCRIPTION	SILICONE O-RING	BUNA-N O-RING	EPDM O-RING	A	B
THREAD-ON 38MM VALVED	Without thread seal	95800	96400	97400	1.70	1.47
	With thread seal	95801	96401	97401	1.70	1.47

• POLYPROPYLENE



TERMINATION	DESCRIPTION	SILICONE O-RING	EPDM O-RING	A	B
SNAP-IN 38MM VALVED		9461300	9500000	1.15	1.77
	Note: Snap-in closure designed to fit Scholle 900 bag necks.				
THREAD-ON 38MM VALVED	With thread seal		9462000	1.70	1.48

Clean-in-Place (CIP) Adapter • ACETAL



TERMINATION	DESCRIPTION	PART NO.	A	B
IN-LINE	1/2" HB (no o-ring)	96000	1.15	1.56

Coupling Readers • POLYPROPYLENE



TERMINATION	TUBING SIZE	METRIC EQ.	SHUTOFF (RS-232)	SHUTOFF (USB)	A	B
IN-LINE HOSE BARB	1/4" ID	6.4mm ID	iUDCDR1700400	iUDCDR1700401	2.00	3.49
	3/8" ID	9.5mm ID	iUDCDR1700600	iUDCDR1700601	2.00	3.49
	1/2" ID	12.7mm ID	iUDCDR1700800	iUDCDR1700801	2.00	3.49
	5/8" ID	15.9mm ID	iUDCDR1701000		2.00	3.49
	3/4" ID	19mm ID	iUDCDR1701200		2.00	3.49
PANEL MOUNT HOSE BARB	1/4" ID	6.4mm ID	iUDCDR1600400	iUDCDR1600401	Refer to cpcworldwide.com for dimensions	
	3/8" ID	9.5mm ID	iUDCDR1600600	iUDCDR1600601		
	1/2" ID	12.7mm ID	iUDCDR1600800	iUDCDR1600801		

Caps • ACETAL



TERMINATION	DESCRIPTION	METRIC EQ.	SHUTOFF	A	B
THREAD-ON 38MM VALVED	Without thread seal	38mm	iUDCDTCN3803	1.70	1.47
	With thread seal	38mm	iUDCDTCS3803	1.70	1.47

• POLYPROPYLENE



TERMINATION	DESCRIPTION	METRIC EQ.	SHUTOFF	A	B
SNAP-IN 38MM VALVED		38mm	iUDCDTSN0000	1.62	1.76
THREAD-ON 38MM VALVED	Without thread seal	38mm	iUDCDTCN3800	1.70	1.48
	With thread seal	38mm	iUDCDTCS3800	1.70	1.48

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. Couplings are pictured with valves unless otherwise noted.

PUNCTURE SEAL SERIES CONNECTOR

Specifications

PRESSURE:

120 psi, 8.3 bar (coupling body)

TEMPERATURE:

32°F to 160°F (0°C to 71°C)

MATERIALS:

Main components and valves: Polypropylene

38mm closure: Polyethylene (LDPE)

Thumb latch: Stainless steel

Valve spring: 316 stainless steel

External spring and pin: Stainless steel

O-rings: EPDM

CLOSURE SIZE: SP-400 38mm

TUBING SIZES:

1/4" and 3/8" ID, 6.4mm and 9.5mm ID

The 1/4" flow Puncture Seal dispensing system provides clean and safe liquid dispensing from bag-in-box (BIB) or other types of flexible packaging. The system consists of a Puncture Seal closure cap and a specially designed quick disconnect coupling body. The closure makes a positive thread or snap-in seal with a 38mm fitment neck. The Puncture Seal coupling body automatically breaks the membrane seal on the closure cap when connected. To switch to a new container, simply depress the CPC thumb latch to disconnect the system and then connect the Puncture Seal coupling body to a fresh container.

Also
available in
NSF listed versions.
Please visit our
website for part
number information

NSF

FEATURES

Puncture Seal coupling

Polypropylene and
polyethylene materials

Puncture Seal membrane

CPC thumb latch

BENEFITS

Easily breaks the Puncture Seal
membrane

Greater chemical resistance

Eliminates shipping caps and o-rings

One-hand connection and disconnection

Coupling Bodies • POLYPROPYLENE



TERMINATION
IN-LINE
HOSE BARB

TUBING SIZE
1/4" ID
3/8" ID

METRIC EQ.
6.4mm ID
9.5 mm ID

STRAIGHT THRU
PS1700412
PS1700612

SHUTOFF
PSD1700412
PSD1700612

LENGTH
1.95
1.95

Closure • POLYETHYLENE

Note: Snap-in closure designed to fit Scholle 900 bag necks.



TERMINATION
THREAD-ON
38MM VALVED

PART NO.
PSC38mm

LENGTH
1.7

HEIGHT
1.12




SNAP-IN 38MM
VALVED

496200

1.88

1.62

Closure Detail




DID YOU KNOW?

CPC'S PUNCTURE SEAL CLOSURES CAN BE USED TO DISPENSE VIRTUALLY ANY LIQUID FROM FLEXIBLE PACKAGES?

The Puncture Seal makes transporting and dispensing cleaning concentrates, dry cleaning chemicals and soaps cleaner and safer. Printing inks, photo developers and dying agents can also be dispensed quickly and easily, without messy drips or spills. The Puncture Seal can also be used with beverage and condiment dispensing systems, just look for the NSF-listed part numbers.

NOTES:



FITQUIK[®] **CONNECTORS**

● ● ●



CPC® LOGO lets you know you have a genuine CPC FitQuik Connector.

PRECISION MOLDED HOSE BARB
designed for maximum holding power. No tube clamps required.

PARTING LINE-FREE HOSE BARB
ensures a leak-free connection.

PRECISION MOLDED THREADS
for a secure connection into a variety of threaded ports.

FitQuik® Connectors from CPC are high quality fittings for leak-free tubing connections. These precision molded fittings are designed to eliminate tubing leak points in applications such as medical devices, analytical instrumentation or air-driven equipment.

Cost-competitive FitQuik Connectors are offered in many standard configurations and in custom designs to meet unique customer specifications.

Designed to fit. Quality FitQuik® Connectors are instrumentation - grade fittings that ensure a secure fit in even the most demanding applications. These fittings feature precise hose barbs and thread forms to ensure the right fit every time.

Materials available: Black and white nylon, polypropylene, PVDF and polycarbonate (available in medical-grade and USP Class VI, ADCF)

TUBE TO TUBE FITTINGS

Tube to Tube Fittings - Straight

PART NO.	DESCRIPTION
HS2	Polypropylene Straight Fitting, 1/16" Hose Barbs
HS230	White Nylon Straight Fitting, 1/16" Hose Barbs
HS231	Black Nylon Straight Fitting, 1/16" Hose Barbs
HS270	PVDF Straight Fitting, 1/16" Hose Barb
HS291	Purple Tint Polycarbonate Straight Fitting, 1/16" Hose Barbs
HS3	Polypropylene Straight Fitting, 3/32" Hose Barbs
HS330	White Nylon Straight Fitting, 3/32" Hose Barbs
HS331	Black Nylon Straight Fitting, 3/32" Hose Barbs
HS370	PVDF Straight Fitting, 3/32" Hose Barb
HS391	Purple Tint Polycarbonate Straight Fitting, 3/32" Hose Barbs
HS4	Polypropylene Straight Fitting, 1/8" Hose Barbs
HS430	White Nylon Straight Fitting, 1/8" Hose Barbs
HS431	Black Nylon Straight Fitting, 1/8" Hose Barbs
HS470	PVDF Straight Fitting, 1/8" Hose Barb
HS491	Purple Tint Polycarbonate Straight Fitting, 1/8" Hose Barbs
HS5	Polypropylene Straight Fitting, 5/32" Hose Barbs
HS530	White Nylon Straight Fitting, 5/32" Hose Barbs
HS531	Black Nylon Straight Fitting, 5/32" Hose Barbs
HS570	PVDF Straight Fitting, 5/32" Hose Barb
HS591	Purple Tint Polycarbonate Straight Fitting, 5/32" Hose Barbs
HS6	Polypropylene Straight Fitting, 3/16" Hose Barbs
HS630	White Nylon Straight Fitting, 3/16" Hose Barbs
HS631	Black Nylon Straight Fitting, 3/16" Hose Barbs
HS670	PVDF Straight Fitting, 3/16" Hose Barb
HS691	Purple Tint Polycarbonate Straight Fitting, 3/16" Hose Barbs
HS8	Polypropylene Straight Fitting, 1/4" Hose Barbs
HS830	White Nylon Straight Fitting, 1/4" Hose Barbs
HS831	Black Nylon Straight Fitting, 1/4" Hose Barbs
HS870	PVDF Straight Fitting, 1/4" Hose Barb
HS891	Purple Tint Polycarbonate Straight Fitting, 1/4" Hose Barbs
HS12	Polypropylene Straight Fitting, 3/8" Hose Barbs
HS1230	White Nylon Straight Fitting, 3/8" Hose Barbs
HS1231	Black Nylon Straight Fitting, 3/8" Hose Barbs
HS1270	PVDF Straight Fitting, 3/8" Hose Barbs

Tube to Tube Fittings - Elbow

PART NO.	DESCRIPTION
HE2	Polypropylene Elbow Fitting, 1/16" Hose Barbs
HE230	White Nylon Elbow Fitting, 1/16" Hose Barbs
HE231	Black Nylon Elbow Fitting, 1/16" Hose Barbs
HE270	PVDF Elbow Fitting, 1/16" Hose Barbs
HE291	Purple Tint Polycarbonate Elbow Fitting, 1/16" Hose Barbs
HE3	Polypropylene Elbow Fitting, 3/32" Hose Barbs
HE330	White Nylon Elbow Fitting, 3/32" Hose Barbs
HE331	Black Nylon Elbow Fitting, 3/32" Hose Barbs
HE370	PVDF Elbow Fitting, 3/32" Hose Barbs
HE391	Purple Tint Polycarbonate Elbow Fitting, 3/32" Hose Barbs

Tube to Tube Fittings - Elbow (cont.)

PART NO.	DESCRIPTION
HE4	Polypropylene Elbow Fitting, 1/8" Hose Barbs
HE430	White Nylon Elbow Fitting, 1/8" Hose Barbs
HE431	Black Nylon Elbow Fitting, 1/8" Hose Barbs
HE470	PVDF Elbow Fitting, 1/8" Hose Barbs
HE491	Purple Tint Polycarbonate Elbow Fitting, 1/8" Hose Barbs
HE5	Polypropylene Elbow Fitting, 5/32" Hose Barbs
HE530	White Nylon Elbow Fitting, 5/32" Hose Barbs
HE531	Black Nylon Elbow Fitting, 5/32" Hose Barbs
HE570	PVDF Elbow Fitting, 5/32" Hose Barbs
HE591	Purple Tint Polycarbonate Elbow Fitting, 5/32" Hose Barbs
HE6	Polypropylene Elbow Fitting, 3/16" Hose Barbs
HE630	White Nylon Elbow Fitting, 3/16" Hose Barbs
HE631	Black Nylon Elbow Fitting, 3/16" Hose Barbs
HE670	PVDF Elbow Fitting, 3/16" Hose Barbs
HE691	Purple Tint Polycarbonate Elbow Fitting, 3/16" Hose Barbs
HE8	Polypropylene Elbow Fitting, 1/4" Hose Barbs
HE830	White Nylon Elbow Fitting, 1/4" Hose Barbs
HE831	Black Nylon Elbow Fitting, 1/4" Hose Barbs
HE870	PVDF Elbow Fitting, 1/4" Hose Barbs
HE891	Purple Tint Polycarbonate Elbow Fitting, 1/4" Hose Barbs
HE12	Polypropylene Elbow Fitting, 3/8" Hose Barbs
HE1230	White Nylon Elbow Fitting, 3/8" Hose Barbs
HE1231	Black Nylon Elbow Fitting, 3/8" Hose Barbs
HE1270	PVDF Elbow Fitting, 3/8" Hose Barbs

FitQuik polycarbonate fittings are compatible with autoclave sterilization. See sterilization guide on page 163.

Tube to Tube Fittings - Tee

PART NO.	DESCRIPTION
HT2	Polypropylene Tee Fitting, 1/16" Hose Barbs
HT230	White Nylon Tee Fitting, 1/16" Hose Barbs
HT231	Black Nylon Tee Fitting, 1/16" Hose Barbs
HT270	PVDF Tee Fitting, 1/16" Hose Barbs
HT291	Purple Tint Polycarbonate Tee Fitting, 1/16" Hose Barbs
HT3	Polypropylene Tee Fitting, 3/32" Hose Barbs
HT330	White Nylon Tee Fitting, 3/32" Hose Barbs
HT331	Black Nylon Tee Fitting, 3/32" Hose Barbs
HT370	PVDF Tee Fitting, 3/32" Hose Barbs
HT391	Purple Tint Polycarbonate Tee Fitting, 3/32" Hose Barbs
HT4	Polypropylene Tee Fitting, 1/8" Hose Barbs
HT430	White Nylon Tee Fitting, 1/8" Hose Barbs
HT431	Black Nylon Tee Fitting, 1/8" Hose Barbs
HT470	PVDF Tee Fitting, 1/8" Hose Barbs
HT491	Purple Tint Polycarbonate Tee Fitting, 1/8" Hose Barbs
HT5	Polypropylene Tee Fitting, 5/32" Hose Barbs
HT530	White Nylon Tee Fitting, 5/32" Hose Barbs
HT531	Black Nylon Tee Fitting, 5/32" Hose Barbs
HT570	PVDF Tee Fitting, 5/32" Hose Barbs
HT591	Purple Tint Polycarbonate Tee Fitting, 5/32" Hose Barbs

Note: Parts not shown to scale. For customer drawings and technical specifications please visit cpcworldwide.com

Tube to Tube Fittings - Tee (cont.)

	PART NO.	DESCRIPTION
	HT6	Polypropylene Tee Fitting, 3/16" Hose Barbs
	HT630	White Nylon Tee Fitting, 3/16" Hose Barbs
	HT631	Black Nylon Tee Fitting, 3/16" Hose Barbs
	HT670	PVDF Tee Fitting, 3/16" Hose Barbs
	HT691	Purple Tint Polycarbonate Tee Fitting, 3/16" Hose Barbs
	HT8	Polypropylene Tee Fitting, 1/4" Hose Barbs
	HT830	White Nylon Tee Fitting, 1/4" Hose Barbs
	HT831	Black Nylon Tee Fitting, 1/4" Hose Barbs
	HT870	PVDF Tee Fitting, 1/4" Hose Barbs
	HT891	Purple Tint Polycarbonate Tee Fitting, 1/4" Hose Barbs
	HT12	Polypropylene Tee Fitting, 3/8" Hose Barbs
	HT1230	White Nylon Tee Fitting, 3/8" Hose Barbs
	HT1231	Black Nylon Tee Fitting, 3/8" Hose Barbs
	HT1270	PVDF Tee Fitting, 3/8" Hose Barbs

Tube to Tube Fittings - Y

	PART NO.	DESCRIPTION
	HY2	Polypropylene Y Fitting, 1/16" Hose Barbs
	HY230	White Nylon Y Fitting, 1/16" Hose Barbs
	HY231	Black Nylon Y Fitting, 1/16" Hose Barbs
	HY270	PVDF Y Fitting, 1/16" Hose Barbs
	HY291	Purple Tint Polycarbonate Y Fitting, 1/16" Hose Barbs
	HY3	Polypropylene Y Fitting, 3/32" Hose Barbs
	HY330	White Nylon Y Fitting, 3/32" Hose Barbs
	HY331	Black Nylon Y Fitting, 3/32" Hose Barbs
	HY370	PVDF Y Fitting, 3/32" Hose Barbs
	HY391	Purple Tint Polycarbonate Y Fitting, 3/32" Hose Barbs
	HY4	Polypropylene Y Fitting, 1/8" Hose Barbs
	HY430	White Nylon Y Fitting, 1/8" Hose Barbs
	HY431	Black Nylon Y Fitting, 1/8" Hose Barbs
	HY470	PVDF Y Fitting, 1/8" Hose Barbs
	HY491	Purple Tint Polycarbonate Y Fitting, 1/8" Hose Barbs
	HY5	Polypropylene Y Fitting, 5/32" Hose Barbs
	HY530	White Nylon Y Fitting, 5/32" Hose Barbs
	HY531	Black Nylon Y Fitting, 5/32" Hose Barbs
	HY570	PVDF Y Fitting, 5/32" Hose Barbs
	HY591	Purple Tint Polycarbonate Y Fitting, 5/32" Hose Barbs
	HY6	Polypropylene Y Fitting, 3/16" Hose Barbs
	HY630	White Nylon Y Fitting, 3/16" Hose Barbs
	HY631	Black Nylon Y Fitting, 3/16" Hose Barbs
	HY670	PVDF Y Fitting, 3/16" Hose Barbs
	HY691	Purple Tint Polycarbonate Y Fitting, 3/16" Hose Barbs
	HY8	Polypropylene Y Fitting, 1/4" Hose Barbs
	HY830	White Nylon Y Fitting, 1/4" Hose Barbs
	HY831	Black Nylon Y Fitting, 1/4" Hose Barbs
	HY870	PVDF Y Fitting, 1/4" Hose Barbs
	HY891	Purple Tint Polycarbonate Y Fitting, 1/4" Hose Barbs
	HY12	Polypropylene Y Fitting, 3/8" Hose Barbs
	HY1230	White Nylon Y Fitting, 3/8" Hose Barbs
	HY1231	Black Nylon Y Fitting, 3/8" Hose Barbs
	HY1270	PVDF Y Fitting, 3/8" Hose Barbs

Tube to Tube Fittings - Straight Reducer

	PART NO.	DESCRIPTION
	HSR32	Polypropylene Reducer Fitting, 3/32" to 1/16" Hose Barb
	HSR3230	White Nylon Reducer Fitting, 3/32" to 1/16" Hose Barb
	HSR3231	Black Nylon Reducer Fitting, 3/32" to 1/16" Hose Barb
	HSR3270	PVDF Straight Reducer Fitting, 3/32" to 1/16" Hose Barb
	HSR3291	Purple Tint Polycarbonate Reducer Fitting, 3/32" to 1/16" Hose Barb
	HSR42	Polypropylene Reducer Fitting, 1/8" to 1/16" Hose Barb
	HSR4230	White Nylon Reducer Fitting, 1/8" to 1/16" Hose Barb
	HSR4231	Black Nylon Reducer Fitting, 1/8" to 1/16" Hose Barb
	HSR4270	PVDF Straight Reducer Fitting, 1/8" to 1/16" Hose Barb
	HSR4291	Purple Tint Polycarbonate Reducer Fitting, 1/8" to 1/16" Hose Barb
	HSR43	Polypropylene Reducer Fitting, 1/8" to 3/32" Hose Barb
	HSR4330	White Nylon Reducer Fitting, 1/8" to 3/32" Hose Barb
	HSR4331	Black Nylon Reducer Fitting, 1/8" to 3/32" Hose Barb
	HSR4370	PVDF Straight Reducer Fitting, 1/8" to 3/32" Hose Barb
	HSR4391	Purple Tint Polycarbonate Reducer Fitting, 1/8" to 3/32" Hose Barb
	HSR52	Polypropylene Reducer Fitting, 5/32" to 1/16" Hose Barb
	HSR5230	White Nylon Reducer Fitting, 5/32" to 1/16" Hose Barb
	HSR5231	Black Nylon Reducer Fitting, 5/32" to 1/16" Hose Barb
	HSR5270	PVDF Straight Reducer Fitting, 5/32" to 1/16" Hose Barb
	HSR5291	Purple Tint Polycarbonate Reducer Fitting, 5/32" to 1/16" Hose Barb
	HSR53	Polypropylene Reducer Fitting, 5/32" to 3/32" Hose Barb
	HSR5330	White Nylon Reducer Fitting, 5/32" to 3/32" Hose Barb
	HSR5331	Black Nylon Reducer Fitting, 5/32" to 3/32" Hose Barb
	HSR5370	PVDF Straight Reducer Fitting, 5/32" to 3/32" Hose Barb
	HSR5391	Purple Tint Polycarbonate Reducer Fitting, 5/32" to 3/32" Hose Barb
	HSR54	Polypropylene Reducer Fitting, 5/32" to 1/8" Hose Barb
	HSR5430	White Nylon Reducer Fitting, 5/32" to 1/8" Hose Barb
	HSR5431	Black Nylon Reducer Fitting, 5/32" to 1/8" Hose Barb
	HSR5470	PVDF Straight Reducer Fitting, 5/32" to 1/8" Hose Barb
	HSR5491	Purple Tint Polycarbonate Reducer Fitting, 5/32" to 1/8" Hose Barb
	HSR62	Polypropylene Reducer Fitting, 3/16" to 1/16" Hose Barb
	HSR6230	White Nylon Reducer Fitting, 3/16" to 1/16" Hose Barb
	HSR6231	Black Nylon Reducer Fitting, 3/16" to 1/16" Hose Barb
	HSR6270	PVDF Straight Reducer Fitting, 3/16" to 1/16" Hose Barb
	HSR6291	Purple Tint Polycarbonate Reducer Fitting, 3/16" to 1/16" Hose Barb
	HSR63	Polypropylene Reducer Fitting, 3/16" to 3/32" Hose Barb
	HSR6330	White Nylon Reducer Fitting, 3/16" to 3/32" Hose Barb
	HSR6331	Black Nylon Reducer Fitting, 3/16" to 3/32" Hose Barb
	HSR6370	PVDF Straight Reducer Fitting, 3/16" to 3/32" Hose Barb
	HSR6391	Purple Tint Polycarbonate Reducer Fitting, 3/16" to 3/32" Hose Barb
	HSR64	Polypropylene Reducer Fitting, 3/16" to 1/8" Hose Barb
	HSR6430	White Nylon Reducer Fitting, 3/16" to 1/8" Hose Barb
	HSR6431	Black Nylon Reducer Fitting, 3/16" to 1/8" Hose Barb
	HSR6470	PVDF Straight Reducer Fitting, 3/16" to 1/8" Hose Barb
	HSR6491	Purple Tint Polycarbonate Reducer Fittings, 3/16" to 1/8" Hose Barb
	HSR65	Polypropylene Reducer Fitting, 3/16" to 5/32" Hose Barb
	HSR6530	White Nylon Reducer Fitting, 3/16" to 5/32" Hose Barb
	HSR6531	Black Nylon Reducer Fitting, 3/16" to 5/32" Hose Barb
	HSR6570	PVDF Straight Reducer Fitting, 3/16" to 5/32" Hose Barb
	HSR6591	Purple Tint Polycarbonate Reducer Fittings, 3/16" to 5/32" Hose Barb

TUBE TO TUBE FITTINGS

Tube to Tube Fittings - Straight Reducer

	PART NO.	DESCRIPTION
	HSR84	Polypropylene Reducer Fitting, 1/4" to 1/8" Hose Barb
	HSR8430	White Nylon Reducer Fitting, 1/4" to 1/8" Hose Barb
	HSR8431	Black Nylon Reducer Fitting, 1/4" to 1/8" Hose Barb
	HSR8470	PVDF Straight Reducer Fitting, 1/4" to 1/8" Hose Barb
	HSR8491	Purple Tint Polycarbonate Reducer Fittings, 1/4" to 1/8" Hose Barb
	HSR85	Polypropylene Reducer Fitting, 1/4" to 5/32" Hose Barb
	HSR8530	White Nylon Reducer Fitting, 1/4" to 5/32" Hose Barb
	HSR8531	Black Nylon Reducer Fitting, 1/4" to 5/32" Hose Barb
	HSR8570	PVDF Straight Reducer Fitting, 1/4" to 5/32" Hose Barb
	HSR8591	Purple Tint Polycarbonate Reducer Fittings, 1/4" to 5/32" Hose Barb
	HSR86	Polypropylene Reducer Fitting, 1/4" to 3/16" Hose Barb
	HSR8630	White Nylon Reducer Fitting, 1/4" to 3/16" Hose Barb
	HSR8631	Black Nylon Reducer Fitting, 1/4" to 3/16" Hose Barb
	HSR8670	PVDF Straight Reducer Fitting, 1/4" to 3/16" Hose Barb
	HSR8691	Purple Tint Polycarbonate Reducer Fittings, 1/4" to 3/16" Hose Barb
	HSR128	Polypropylene Reducer Fitting, 3/8" to 1/4" Hose Barb
	HSR12830	White Nylon Reducer Fitting, 3/8" to 1/4" Hose Barb
	HSR12831	Black Nylon Reducer Fitting, 3/8" to 1/4" Hose Barb
	HSR12870	PVDF Straight Reducer Fitting, 3/8" to 1/4" Hose Barb

PLUGS AND THREAD TO THREAD

Threaded Plugs

	PART NO.	DESCRIPTION
	MP	Polypropylene Threaded Plug, Tapered 10-32
	MP30	White Nylon Threaded Plug, Tapered 10-32
	MP31	Black Nylon Threaded Plug, Tapered 10-32
	MP70	PVDF Threaded Plug Fitting, Tapered 10-32
	N2P	Polypropylene Threaded Plug, 1/16" NPT
	N2P30	White Nylon Threaded Plug, 1/16" NPT
	N2P31	Black Nylon Threaded Plug, 1/16" NPT
	N2P70	PVDF Threaded Plug, 1/16" NPT
	N4P	Polypropylene Threaded Plug, 1/8" NPT
	N4P30	White Nylon Threaded Plug, 1/8" NPT
	N4P31	Black Nylon Threaded Plug, 1/8" NPT
	N4P70	PVDF Threaded Plug Fitting, 1/8" NPT
	N8P	Polypropylene Threaded Plug, 1/4" NPT
	N8P30	White Nylon Threaded Plug, 1/4" NPT
	N8P31	Black Nylon Threaded Plug, 1/4" NPT
	N8P70	PVDF Threaded Plug Fitting, 1/4" NPT

Thread to Thread -Straight

	PART NO.	DESCRIPTION
	N32	Polypropylene Straight Fitting, Tapered 10-32 Threads
	N3230	White Nylon Straight Fitting, Tapered 10-32 Threads
	N3231	Black Nylon Straight Fitting, Tapered 10-32 Threads
	N3270	PVDF Straight Fitting, Tapered 10-32 Threads

THREAD TO TUBE FITTINGS

Thread to Tube Fittings - Straight

	PART NO.	DESCRIPTION
	KS2	Polypropylene Straight Fitting, 1/4-28 UNF to 1/16" Hose Barb
	KS230	White Nylon Straight Fitting, 1/4-28 UNF to 1/16" Hose Barb
	KS231	Black Nylon Straight Fitting, 1/4-28 UNF to 1/16" Hose Barb
	KS270	PVDF Straight Fitting, 1/4-28 UNF to 1/16" Hose Barb
	KS3	Polypropylene Straight Fitting, 1/4-28 UNF to 3/32" Hose Barb
	KS330	White Nylon Straight Fitting, 1/4-28 UNF to 3/32" Hose Barb
	KS331	Black Nylon Straight Fitting, 1/4-28 UNF to 3/32" Hose Barb
	KS370	PVDF Straight Fitting, 1/4-28 UNF to 3/32" Hose Barb
	KS4	Polypropylene Straight Fitting, 1/4-28 UNF to 1/8" Hose Barb
	KS430	White Nylon Straight Fitting, 1/4-28 UNF to 1/8" Hose Barb
	KS431	Black Nylon Straight Fitting, 1/4-28 UNF to 1/8" Hose Barb
	KS470	PVDF Straight Fitting, 1/4-28 UNF to 1/8" Hose Barb
	KS5	Polypropylene Straight Fitting, 1/4-28 UNF to 5/32" Hose Barb
	KS530	White Nylon Straight Fitting, 1/4-28 UNF to 5/32" Hose Barb
	KS531	Black Nylon Straight Fitting, 1/4-28 UNF to 5/32" Hose Barb
	KS570	PVDF Straight Fitting, 1/4-28 UNF to 5/32" Hose Barb
	MS2	Polypropylene Straight Fitting, Tapered 10-32 to 1/16" Hose Barb
	MS230	White Nylon Straight Fitting, Tapered 10-32 to 1/16" Hose Barb
	MS231	Black Nylon Straight Fitting, Tapered 10-32 to 1/16" Hose Barb
	MS270	PVDF Straight Fitting, Tapered 10-32 to 1/16" Hose Barb
	MS3	Polypropylene Straight Fitting, Tapered 10-32 to 3/32" Hose Barb
	MS330	White Nylon Straight Fitting, Tapered 10-32 to 3/32" Hose Barb
	MS331	Black Nylon Straight Fitting, Tapered 10-32 to 3/32" Hose Barb
	MS370	PVDF Straight Fitting, Tapered 10-32 to 3/32" Hose Barb
	MS4	Polypropylene Straight Fitting, Tapered 10-32 to 1/8" Hose Barb
	MS430	White Nylon Straight Fitting, Tapered 10-32 to 1/8" Hose Barb
	MS431	Black Nylon Straight Fitting, Tapered 10-32 to 1/8" Hose Barb
	MS470	PVDF Straight Fitting, Tapered 10-32 to 1/8" Hose Barb
	MS5	Polypropylene Straight Fitting, Tapered 10-32 to 5/32" Hose Barb
	MS530	White Nylon Straight Fitting, Tapered 10-32 to 5/32" Hose Barb
	MS531	Black Nylon Straight Fitting, Tapered 10-32 to 5/32" Hose Barb
	MS570	PVDF Straight Fitting, Tapered 10-32 to 5/32" Hose Barb
	MS6	Polypropylene Straight Fitting, Tapered 10-32 to 3/16" Hose Barb
	MS630	White Nylon Straight Fitting, Tapered 10-32 to 3/16" Hose Barb
	MS631	Black Nylon Straight Fitting, Tapered 10-32 to 3/16" Hose Barb
	MS670	PVDF Straight Fitting, Tapered 10-32 to 3/16" Hose Barb
	N2S2	Polypropylene Straight Fitting, 1/16" NPT to 1/16" Hose Barb
	N2S230	White Nylon Straight Fitting, 1/16" NPT to 1/16" Hose Barb
	N2S231	Black Nylon Straight Fitting, 1/16" NPT to 1/16" Hose Barb
	N2S270	PVDF Straight Fitting, 1/16" NPT to 1/16" Hose Barb
	N2S3	Polypropylene Straight Fitting, 1/16" NPT to 3/32" Hose Barb
	N2S330	White Nylon Straight Fitting, 1/16" NPT to 3/32" Hose Barb
	N2S331	Black Nylon Straight Fitting, 1/16" NPT to 3/32" Hose Barb
	N2S370	PVDF Straight Fitting, 1/16" NPT to 3/32" Hose Barb
	N2S4	Polypropylene Straight Fitting, 1/16" NPT to 1/8" Hose Barb
	N2S430	White Nylon Straight Fitting, 1/16" NPT to 1/8" Hose Barb
	N2S431	Black Nylon Straight Fitting, 1/16" NPT to 1/8" Hose Barb
	N2S470	PVDF Straight Fitting, 1/16" NPT to 1/8" Hose Barb
	N2S5	Polypropylene Straight Fitting, 1/16" NPT to 5/32" Hose Barb
	N2S530	White Nylon Straight Fitting, 1/16" NPT to 5/32" Hose Barb
	N2S531	Black Nylon Straight Fitting, 1/16" NPT to 5/32" Hose Barb
	N2S570	PVDF Straight Fitting, 1/16" NPT to 5/32" Hose Barb
	N4S2	Polypropylene Straight Fitting, 1/8" NPT to 1/16" Hose Barb
	N4S230	White Nylon Straight Fitting, 1/8" NPT to 1/16" Hose Barb
	N4S231	Black Nylon Straight Fitting, 1/8" NPT to 1/16" Hose Barb
	N4S270	PVDF Straight Fitting, 1/8" NPT to 1/16" Hose Barb

Note: Parts not shown to scale. For customer drawings and technical specifications please visit cpcworldwide.com

Thread to Tube Fittings - Straight (cont.)

	PART NO.	DESCRIPTION
	N4S3	Polypropylene Straight Fitting, 1/8" NPT to 3/32" Hose Barb
	N4S330	White Nylon Straight Fitting, 1/8" NPT to 3/32" Hose Barb
	N4S331	Black Nylon Straight Fitting, 1/8" NPT to 3/32" Hose Barb
	N4S370	PVDF Straight Fitting, 1/8" NPT to 3/32" Hose Barb
	N4S4	Polypropylene Straight Fitting, 1/8" NPT to 1/8" Hose Barb
	N4S430	White Nylon Straight Fitting, 1/8" NPT to 1/8" Hose Barb
	N4S431	Black Nylon Straight Fitting, 1/8" NPT to 1/8" Hose Barb
	N4S470	PVDF Straight Fitting, 1/8" NPT to 1/8" Hose Barb
	N4S5	Polypropylene Straight Fitting, 1/8" NPT to 5/32" Hose Barb
	N4S530	White Nylon Straight Fitting, 1/8" NPT to 5/32" Hose Barb
	N4S531	Black Nylon Straight Fitting, 1/8" NPT to 5/32" Hose Barb
	N4S570	PVDF Straight Fitting, 1/8" NPT to 5/32" Hose Barb
	N4S6	Polypropylene Straight Fitting, 1/8" NPT to 3/16" Hose Barb
	N4S630	White Nylon Straight Fitting, 1/8" NPT to 3/16" Hose Barb
	N4S631	Black Nylon Straight Fitting, 1/8" NPT to 3/16" Hose Barb
	N4S670	PVDF Straight Fitting, 1/8" NPT to 3/16" Hose Barb
	N4S8	Polypropylene Straight Fitting, 1/8" NPT to 1/4" Hose Barb
	N4S830	White Nylon Straight Fitting, 1/8" NPT to 1/4" Hose Barb
	N4S831	Black Nylon Straight Fitting, 1/8" NPT to 1/4" Hose Barb
	N4S870	PVDF Straight Fitting, 1/8" NPT to 1/4" Hose Barb
	N8S4	Polypropylene Straight Fitting, 1/4" NPT to 1/8" Hose Barb
	N8S430	White Nylon Straight Fitting, 1/4" NPT to 1/8" Hose Barb
	N8S431	Black Nylon Straight Fitting, 1/4" NPT to 1/8" Hose Barb
	N8S470	PVDF Straight Fitting, 1/4" NPT to 1/8" Hose Barb
	N8S5	Polypropylene Straight Fitting, 1/4" NPT to 5/32" Hose Barb
	N8S530	White Nylon Straight Fitting, 1/4" NPT to 5/32" Hose Barb
	N8S531	Black Nylon Straight Fitting, 1/4" NPT to 5/32" Hose Barb
	N8S570	PVDF Straight Fitting, 1/4" NPT to 5/32" Hose Barb
	N8S6	Polypropylene Straight Fitting, 1/4" NPT to 3/16" Hose Barb
	N8S630	White Nylon Straight Fitting, 1/4" NPT to 3/16" Hose Barb
	N8S631	Black Nylon Straight Fitting, 1/4" NPT to 3/16" Hose Barb
	N8S670	PVDF Straight Fitting, 1/4" NPT to 3/16" Hose Barb
	N8S8	Polypropylene Straight Fitting, 1/4" NPT to 1/4" Hose Barb
	N8S830	White Nylon Straight Fitting, 1/4" NPT to 1/4" Hose Barb
	N8S831	Black Nylon Straight Fitting, 1/4" NPT to 1/4" Hose Barb
	N8S870	PVDF Straight Fitting, 1/4" NPT to 1/4" Hose Barb
	N8S10	Polypropylene Straight Fitting, 1/4" NPT to 5/16" Hose Barb
	N8S1030	White Nylon Straight Fitting, 1/4" NPT to 5/16" Hose Barb
	N8S1031	Black Nylon Straight Fitting, 1/4" NPT to 5/16" Hose Barb
	N8S1070	PVDF Straight Fitting, 1/4" NPT to 5/16" Hose Barb
	N8S12	Polypropylene Straight Fitting, 1/4" NPT to 3/8" Hose Barb
	N8S1230	White Nylon Straight Fitting, 1/4" NPT to 3/8" Hose Barb
	N8S1231	Black Nylon Straight Fitting, 1/4" NPT to 3/8" Hose Barb
	N8S1270	PVDF Straight Fitting, 1/4" NPT to 3/8" Hose Barb

Thread to Tube Fittings - Elbow

	PART NO.	DESCRIPTION
	ME2	Polypropylene Elbow Fitting, Tapered 10-32 to 1/16" Hose Barb
	ME230	White Nylon Elbow Fitting, Tapered 10-32 to 1/16" Hose Barb
	ME231	Black Nylon Elbow Fitting, Tapered 10-32 to 1/16" Hose Barb
	ME270	PVDF Elbow Fitting, Tapered 10-32 to 1/16" Hose Barbs
	ME3	Polypropylene Elbow Fitting, Tapered 10-32 to 3/32" Hose Barb
	ME330	White Nylon Elbow Fitting, Tapered 10-32 to 3/32" Hose Barb
	ME331	Black Nylon Elbow Fitting, Tapered 10-32 to 3/32" Hose Barb
	ME370	PVDF Elbow Fitting, Tapered 10-32 to 3/32" Hose Barbs

Thread to Tube Fittings - Elbow (cont.)

	PART NO.	DESCRIPTION
	ME4	Polypropylene Elbow Fitting, Tapered 10-32 to 1/8" Hose Barb
	ME430	White Nylon Elbow Fitting, Tapered 10-32 to 1/8" Hose Barb
	ME431	Black Nylon Elbow Fitting, Tapered 10-32 to 1/8" Hose Barb
	ME470	PVDF Elbow Fitting, Tapered 10-32 to 1/8" Hose Barbs
	ME5	Polypropylene Elbow Fitting, Tapered 10-32 to 5/32" Hose Barb
	ME530	White Nylon Elbow Fitting, Tapered 10-32 to 5/32" Hose Barb
	ME531	Black Nylon Elbow Fitting, Tapered 10-32 to 5/32" Hose Barb
	ME570	PVDF Elbow Fitting, Tapered 10-32 to 5/32" Hose Barbs
	N4E4	Polypropylene Elbow Fitting, 1/8" NPT to 1/8" Hose Barb
	N4E430	White Nylon Elbow Fitting, 1/8" NPT to 1/8" Hose Barb
	N4E431	Black Nylon Elbow Fitting, 1/8" NPT to 1/8" Hose Barb
	N4E470	PVDF Elbow Fitting, 1/8" NPT to 1/8" Hose Barb
	N4E6	Polypropylene Elbow Fitting, 1/8" NPT to 3/16" Hose Barb
	N4E630	White Nylon Elbow Fitting, 1/8" NPT to 3/16" Hose Barb
	N4E631	Black Nylon Elbow Fitting, 1/8" NPT to 3/16" Hose Barb
	N4E670	PVDF Elbow Fitting, 1/8" NPT to 3/16" Hose Barb
	N4E8	Polypropylene Elbow Fitting, 1/8" NPT to 1/4" Hose Barb
	N4E830	White Nylon Elbow Fitting, 1/8" NPT to 1/4" Hose Barb
	N4E831	Black Nylon Elbow Fitting, 1/8" NPT to 1/4" Hose Barb
	N4E870	PVDF Elbow Fitting, 1/8" NPT to 1/4" Hose Barb
	N8E8	Polypropylene Elbow Fitting, 1/4" NPT to 1/4" Hose Barb
	N8E830	White Nylon Elbow Fitting, 1/4" NPT to 1/4" Hose Barb
	N8E831	Black Nylon Elbow Fitting, 1/4" NPT to 1/4" Hose Barb
	N8E870	PVDF Elbow Fitting, 1/4" NPT to 1/4" Hose Barb
	N8E12	Polypropylene Elbow Fitting, 1/4" NPT to 3/8" Hose Barb
	N8E1230	White Nylon Elbow Fitting, 1/4" NPT to 3/8" Hose Barb
	N8E1231	Black Nylon Elbow Fitting, 1/4" NPT to 3/8" Hose Barb
	N8E1270	PVDF Elbow Fitting, 1/4" NPT to 3/8" Hose Barb

Thread to Tube Fittings - Tee

	PART NO.	DESCRIPTION
	MT2	Polypropylene Tee Fitting, Tapered 10-32 to 1/16" Hose Barbs
	MT230	White Nylon Tee Fitting, Tapered 10-32 to 1/16" Hose Barbs
	MT231	Black Nylon Tee Fitting, Tapered 10-32 to 1/16" Hose Barbs
	MT270	PVDF Tee Fitting, Tapered 10-32 to 1/16" Hose Barbs
	MT3	Polypropylene Tee Fitting, Tapered 10-32 to 3/32" Hose Barbs
	MT330	White Nylon Tee Fitting, Tapered 10-32 to 3/32" Hose Barbs
	MT331	Black Nylon Tee Fitting, Tapered 10-32 to 3/32" Hose Barbs
	MT370	PVDF Tee Fitting, Tapered 10-32 to 3/32" Hose Barbs
	MT4	Polypropylene Tee Fitting, Tapered 10-32 to 1/8" Hose Barbs
	MT430	White Nylon Tee Fitting, Tapered 10-32 to 1/8" Hose Barbs
	MT431	Black Nylon Tee Fitting, Tapered 10-32 to 1/8" Hose Barbs
	MT470	PVDF Tee Fitting, Tapered 10-32 to 1/8" Hose Barbs
	MT5	Polypropylene Tee Fitting, Tapered 10-32 to 5/32" Hose Barbs
	MT530	White Nylon Tee Fitting, Tapered 10-32 to 5/32" Hose Barbs
	MT531	Black Nylon Tee Fitting, Tapered 10-32 to 5/32" Hose Barbs
	MT570	PVDF Tee Fitting, Tapered 10-32 to 5/32" Hose Barbs

The unique shrouded hose barb on our 1/16" fittings provides additional stability to prevent breakage in applications where small tubing connections might be pulled or twisted during use.

BLOOD PRESSURE

Blood Pressure Fittings - Male Bayonet

PART NO.	DESCRIPTION
BC330	White Nylon Male Bayonet Fitting to 3/32" Hose Barb
BC331	Black Nylon Male Bayonet Fitting to 3/32" Hose Barb
BC430	White Nylon Male Bayonet Fitting to 1/8" Hose Barb
BC431	Black Nylon Male Bayonet Fitting to 1/8" Hose Barb
BC530	White Nylon Male Bayonet Fitting to 5/32" Hose Barb
BC531	Black Nylon Male Bayonet Fitting to 5/32" Hose Barb
BC630	White Nylon Male Bayonet Fitting to 3/16" Hose Barb
BC631	Black Nylon Male Bayonet Fitting to 3/16" Hose Barb

Blood Pressure Fittings - Screw-type

PART NO.	DESCRIPTION
GS320	White Acetal Screw-type Fitting, 5/16" UNF to 3/32" Hose Barb
GS420	White Acetal Screw-type Fitting, 5/16" UNF to 1/8" Hose Barb
GS520	White Acetal Screw-type Fitting, 5/16" UNF to 5/32" Hose Barb
GS620	White Acetal Screw-type Fitting, 5/16" UNF to 3/16" Hose Barb
GM430M2	White Nylon with Polypropylene and TPE rotating nut, Buna-N seal. 5/16" UNF rotating internal thread X 1/8" HB
GM530M2	White Nylon with Polypropylene and TPE rotating nut, Buna-N seal. 5/16" UNF rotating internal thread X 5/32" HB
GM630M2	White Nylon with Polypropylene and TPE rotating nut, Buna-N seal. 5/16" UNF rotating internal thread X 3/16" HB

FOR SMC AND SMF1 BLOOD PRESSURE CONNECTORS, SEE PAGE 18-21.



LUERS

Male Luers

Male luers feature an integral locking ring!

PART NO.	DESCRIPTION
LM21	Polypropylene Male Luer to 1/16" Hose Barb
LM2130	White Nylon Male Luer to 1/16" Hose Barb
LM2131	Black Nylon Male Luer to 1/16" Hose Barb
LM2170	PVDF Male Luer to 1/16" Hose Barb
LM2191	Purple Tint Polycarbonate Male Luer to 1/16" Hose Barb
LM31	Polypropylene Male Luer to 3/32" Hose Barb
LM3130	White Nylon Male Luer to 3/32" Hose Barb
LM3131	Black Nylon Male Luer to 3/32" Hose Barb
LM3170	PVDF Male Luer to 3/32" Hose Barb
LM3191	Purple Tint Polycarbonate Male Luer to 3/32" Hose Barb
LM41	Polypropylene Male Luer to 1/8" Hose Barb
LM4130	White Nylon Male Luer to 1/8" Hose Barb
LM4131	Black Nylon Male Luer to 1/8" Hose Barb
LM4170	PVDF Male Luer to 1/8" Hose Barb
LM4191	Purple Tint Polycarbonate Male Luer to 1/8" Hose Barb
LM51	Polypropylene Male Luer to 5/32" Hose Barb
LM5130	White Nylon Male Luer to 5/32" Hose Barb
LM5131	Black Nylon Male Luer to 5/32" Hose Barb
LM5170	PVDF Male Luer to 5/32" Hose Barb
LM5191	Purple Tint Polycarbonate Male Luer to 5/32" Hose Barb
LM61	Polypropylene Male Luer to 3/16" Hose Barb
LM6130	White Nylon Male Luer to 3/16" Hose Barb
LM6131	Black Nylon Male Luer to 3/16" Hose Barb
LM6170	PVDF Male Luer to 3/16" Hose Barb
LM6191	Purple Tint Polycarbonate Male Luer to 3/16" Hose Barb
LM8170	PVDF Male Luer to 1/4" Hose Barb

Female Luers

PART NO.	DESCRIPTION
LF21	Polypropylene Female Luer to 1/16" Hose Barb
LF2130	White Nylon Female Luer to 1/16" Hose Barb
LF2131	Black Nylon Female Luer to 1/16" Hose Barb
LF2170	PVDF Female Luer to 1/16" Hose Barb
LF2191	Purple Tint Polycarbonate Female Luer to 1/16" Hose Barb
LF31	Polypropylene Female Luer to 3/32" Hose Barb
LF3130	White Nylon Female Luer to 3/32" Hose Barb
LF3131	Black Nylon Female Luer to 3/32" Hose Barb
LF3170	PVDF Female Luer to 3/32" Hose Barb
LF3191	Purple Tint Polycarbonate Female Luer to 3/32" Hose Barb
LF41	Polypropylene Female Luer to 1/8" Hose Barb
LF4130	White Nylon Female Luer to 1/8" Hose Barb
LF4131	Black Nylon Female Luer to 1/8" Hose Barb
LF4170	PVDF Female Luer to 1/8" Hose Barb
LF4191	Purple Tint Polycarbonate Female Luer to 1/8" Hose Barb
LF51	Polypropylene Female Luer to 5/32" Hose Barb
LF5130	White Nylon Female Luer to 5/32" Hose Barb
LF5131	Black Nylon Female Luer to 5/32" Hose Barb
LF5170	PVDF Female Luer to 5/32" Hose Barb
LF5191	Purple Tint Polycarbonate Female Luer to 5/32" Hose Barb
LF61	Polypropylene Female Luer to 3/16" Hose Barb
LF6130	White Nylon Female Luer to 3/16" Hose Barb
LF6131	Black Nylon Female Luer to 3/16" Hose Barb
LF6170	PVDF Female Luer to 3/16" Hose Barb
LF6191	Purple Tint Polycarbonate Female Luer to 3/16" Hose Barb
LF81	Polypropylene Female Luer to 1/4" Hose Barb
LF8130	White Nylon Female Luer to 1/4" Hose Barb
LF8131	Black Nylon Female Luer to 1/4" Hose Barb
LF8170	PVDF Female Luer to 1/4" Hose Barb
LF8191	Purple Tint Polycarbonate Female Luer to 1/4" Hose Barb

Note: Parts not shown to scale. For customer drawings and technical specifications please visit cpcworldwide.com

Panel Mount Male Luers

PART NO.	DESCRIPTION
PMLM21	Polypropylene Panel Mount Male Luer to 1/16" Hose Barb
PMLM2130	White Nylon Panel Mount Male Luer to 1/16" Hose Barb
PMLM2131	Black Nylon Panel Mount Male Luer to 1/16" Hose Barb
PMLM2170	PVDF Panel Mount Male Luer to 1/16" Hose Barb
PMLM31	Polypropylene Panel Mount Male Luer to 3/32" Hose Barb
PMLM3130	White Nylon Panel Mount Male Luer to 3/32" Hose Barb
PMLM3131	Black Nylon Panel Mount Male Luer to 3/32" Hose Barb
PMLM3170	PVDF Panel Mount Male Luer to 3/32" Hose Barb
PMLM41	Polypropylene Panel Mount Male Luer to 1/8" Hose Barb
PMLM4130	White Nylon Panel Mount Male Luer to 1/8" Hose Barb
PMLM4131	Black Nylon Panel Mount Male Luer to 1/8" Hose Barb
PMLM4170	PVDF Panel Mount Male Luer to 1/8" Hose Barb
PMNUTSST	Stainless Steel 1/4-28 UNF Nut
PMNUT30	White Nylon Panel Mount 1/4-28 UNF Nut

Note: Panel mount luers require a 1/4" diameter panel opening

All CPC luer fittings and connectors interconnect with products manufactured to ISO standards 594-1 and 594-2.

Panel Mount Female Luers

PART NO.	DESCRIPTION
PMLF21	Polypropylene Panel Mount Female Luer to 1/16" Hose Barb
PMLF2130	White Nylon Panel Mount Female Luer to 1/16" Hose Barb
PMLF2131	Black Nylon Panel Mount Female Luer to 1/16" Hose Barb
PMLF2170	PVDF Panel Mount Female Luer to 1/16" Hose Barb
PMLF31	Polypropylene Panel Mount Female Luer to 3/32" Hose Barb
PMLF3130	White Nylon Panel Mount Female Luer to 3/32" Hose Barb
PMLF3131	Black Nylon Panel Mount Female Luer to 3/32" Hose Barb
PMLF3170	PVDF Panel Mount Female Luer to 3/32" Hose Barb
PMLF41	Polypropylene Panel Mount Female Luer to 1/8" Hose Barb
PMLF4130	White Nylon Panel Mount Female Luer to 1/8" Hose Barb
PMLF4131	Black Nylon Panel Mount Female Luer to 1/8" Hose Barb
PMLF4170	PVDF Panel Mount Female Luer to 1/8" Hose Barb
PMNUTSST	Stainless Steel 1/4-28 UNF Nut
PMNUT30	White Nylon Panel Mount 1/4-28 UNF Nut

Luer Caps and Plugs

PART NO.	DESCRIPTION
LCAP	Polypropylene Luer Cap
LCAP30	White Nylon Luer Cap
LCAP31	Black Nylon Luer Cap
LCAP70	PVDF Luer Cap
LPLUG	Polypropylene Luer Plug
LPLUG30	White Nylon Luer Plug
LPLUG31	Black Nylon Luer Plug
LPLUG70	PVDF Luer Plug

Color-coded rings can be used for visual line identification or to prevent connector rotation in panel mount applications.

Male Slip Luers

PART NO.	DESCRIPTION
SLM21	Polypropylene Male Slip Luer to 1/16" Hose Barb
SLM2130	White Nylon Male Slip Luer to 1/16" Hose Barb
SLM2131	Black Nylon Male Slip Luer to 1/16" Hose Barb
SLM2170	PVDF Male Slip Luer to 1/16" Hose Barb
SLM2191	Purple Tint Polycarbonate Male Slip Luer to 1/16" Hose Barb
SLM31	Polypropylene Male Slip Luer to 3/32" Hose Barb
SLM3130	White Nylon Male Slip Luer to 3/32" Hose Barb
SLM3131	Black Nylon Male Slip Luer to 3/32" Hose Barb
SLM3170	PVDF Male Slip Luer to 3/32" Hose Barb
SLM3191	Purple Tint Polycarbonate Male Slip Luer to 3/32" Hose Barb
SLM41	Polypropylene Male Slip Luer to 1/8" Hose Barb
SLM4130	White Nylon Male Slip Luer to 1/8" Hose Barb
SLM4131	Black Nylon Male Slip Luer to 1/8" Hose Barb
SLM4170	PVDF Male Slip Luer to 1/8" Hose Barb
SLM4191	Purple Tint Polycarbonate Male Slip Luer to 1/8" Hose Barb
SLM51	Polypropylene Male Slip Luer to 5/32" Hose Barb
SLM5130	White Nylon Male Slip Luer to 5/32" Hose Barb
SLM5131	Black Nylon Male Slip Luer to 5/32" Hose Barb
SLM5170	PVDF Male Slip Luer to 5/32" Hose Barb
SLM5191	Purple Tint Polycarbonate Male Slip Luer to 5/32" Hose Barb
SLM61	Polypropylene Male Slip Luer to 3/16" Hose Barb
SLM6130	White Nylon Male Slip Luer to 3/16" Hose Barb
SLM6131	Black Nylon Male Slip Luer to 3/16" Hose Barb
SLM6170	PVDF Male Slip Luer to 3/16" Hose Barb
SLM6191	Purple Tint Polycarbonate Male Slip Luer to 3/16" Hose Barb

Luer Accessories

PART NO.	DESCRIPTION
LMSL	Polypropylene Stationary Luer Lock Ring
LMSL30	White Nylon Stationary Luer Lock Ring
LMSL31	Black Nylon Stationary Luer Lock Ring
LMSL32	Yellow Nylon Stationary Luer Lock Ring
LMSL33	Blue Nylon Stationary Luer Lock Ring
LMSL34	Red Nylon Stationary Luer Lock Ring
LMSL35	Green Nylon Stationary Luer Lock Ring
LMSL36	Orange Nylon Stationary Luer Lock Ring
LMSL70	PVDF Stationary Luer Lock Ring
LMSL91	Purple Tint Polycarbonate Stationary Luer Lock Ring
LMSR	Polypropylene Rotating Luer Lock Ring
LMSR30	White Nylon Rotating Luer Lock Ring
LMSR31	Black Nylon Rotating Luer Lock Ring
LMSR32	Yellow Nylon Rotating Luer Lock Ring
LMSR33	Blue Nylon Rotating Luer Lock Ring
LMSR34	Red Nylon Rotating Luer Lock Ring
LMSR35	Green Nylon Rotating Luer Lock Ring
LMSR36	Orange Nylon Rotating Luer Lock Ring
LMSR70	PVDF Rotating Luer Lock Ring
LMSLR91	Purple Tint Polycarbonate Rotating Luer Lock Ring
PMRL	Polypropylene Luer Color Coded Ring
PMRL30	White Nylon Luer Color Coded Ring
PMRL31	Black Nylon Luer Color Coded Ring
PMRL32	Yellow Nylon Luer Color Coded Ring
PMRL33	Blue Nylon Luer Color Coded Ring
PMRL34	Red Nylon Luer Color Coded Ring
PMRL35	Green Nylon Luer Color Coded Ring
PMRL36	Orange Nylon Luer Color Coded Ring
PMRL70	PVDF Panel Mount Luer Color Coded Ring
PMNUTSST	Stainless Steel 1/4-28 UNF Nut

ACCESSORIES

Accessories



**TERMINATION
FERRULELESS
POLYTUBE FITTING, PTF†**

PIPE THREAD	TUBING	TUBING DIMENSION	PART NO.	LENGTH
10-32*	1/8"	.07" ID .125 OD	TF1002	.64
10-32*	1/4"	.17" ID .250 OD	TF1004	.86
1/8" NPT	1/8"	.07" ID .125 OD	TF2002	.98
1/8" NPT	1/4"	.17" ID .250 OD	TF2004	1.10
1/8" NPT	3/8"	.25" ID .375 OD	TF2006	1.24
1/4" NPT	1/4"	.17" ID .250 OD	TF4004	1.20
1/4" NPT	3/8"	.25" ID .375 OD	TF4006	1.34



**TERMINATION
FERRULELESS POLYTUBE
FITTING NUTS, PTF†**

TUBING	PART NO.	TUBING	PART NO.
1/8" OD	153600	4.0mm OD	269700
5/32" OD	269700	8.0mm OD	339500
1/4" OD	100800	10.0mm OD	358400
3/8" OD	108900		



**DESCRIPTION
INSERT SEALS**

COUPLING SERIES	BUNA-N	FLUOROCARBON	EPDM
MC, PMC, PMC12	730800	730804	730803
LC, PLC, PLC12, APC, Twin Tube™ (large o-ring),			
ZLC, NS4, NS406, BreakAway®	731100	731104	731103
SMC, Twin Tube (small o-ring)	730600	730604	730603
HFC (all), FFC	731600	731604	731603
NS1 Bulkhead Seal			731303
NS6		731404	731403



**DESCRIPTION
PANEL MOUNT
NUTS**

COUPLING SERIES NUTS	NICKEL BRASS	ACETAL	316 STAINLESS	POLYPROPYLENE (PP) POLYSULFONE (PSF)
MC, PMC, PMC12	100900	664400	100901	—
LC, PLC, EFC, PLC12, APC,				
ZLC, BreakAway	120700	520300	120701	—
HFC	—	—	—	621300 (PP) 694300 (PSF)
SRC, SMF	404300	—	—	—
NS4 ABS	2137600	—	—	—
NS6	—	—	1884400	—



**DESCRIPTION
DUST CAPS & PLUGS**

COUPLING SERIES	BODY PLUG	INSERT CAP
MC, PMC non-sealing	PMC31	PMC32
LC, PLC non-sealing	PLC310	PLC320
APC, EFC non-sealing	—	PLC320
PMC pressure-sealing	PMC30	—
PLC pressure-sealing	PLC300	—
HFC/FFC non-sealing (not shown)	HFC312 L (with leash)	—
	HFC312 (no leash)	—

Manifolds • SPECIFICATIONS • Material: Aluminum • Finish: Black anodized



**DESCRIPTION
10-32 PORTED
MANIFOLD WITH 1/8"
NPT END PORT**

PART NO.	SIDE PORTS	END PORTS	LENGTH
32M3	3	1	2.30"
32M4	4	1	2.80"
32M5	5	1	3.30"



**DESCRIPTION
1/8" NPT PORTED
MANIFOLD WITH 1/8"
NPT END PORT**

PART NO.	SIDE PORTS	END PORTS	LENGTH
2M3	3	1	3.10"
2M4	4	1	4.00"
2M5	5	1	4.90"



**DESCRIPTION
1/4" NPT PORTED
MANIFOLD WITH 1/4" NPT
END PORT**

PART NO.	SIDE PORTS	END PORTS	LENGTH
4M3	3	2	3.80"
4M4	4	2	4.80"
4M5	5	2	5.80"

JG® Push-To-Connect Accessories

DESCRIPTION	TUBING	PART NO.	DESCRIPTION	TUBING	PART NO.
IN-LINE LOCKING CLIPS, RED	1/4" Tube OD	1011900	In-Line Collet Covers, Color Coded	1/4" Tube OD	1012101 to 06
	3/8" Tube OD	1012000		3/8" Tube OD	1012201 to 06

Colors available, shown right. Please indicate color using the following suffix codes: 01=Black, 02=Red, 03=Yellow, 04=Gray, 05=Blue, 06=Green (Example: 1012101 is the code for a 1/4" collet cover in black.) **NOTE:** See pages 42 and 43 for JG couplings.



†NOTE: CPC's Ferruleless Polytube Fitting terminations do not require ferrules to achieve a secure connection, which makes them easier to use and reuse. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc. ***NOTE:** Gaskets are not included with 10-32 PTF style fittings. To prevent leakage with these fittings, we recommend using LOCTITE® Removable Threadlocker 242 or Permanent Threadlocker 262.

STERILIZATION AND DISINFECTANT METHODS

METHOD									
KEY	Y = Excellent, recommended material for this sterilization method N = No, not recommended N/A = Not Applicable	DISINFECTANTS			ETHYLENE OXIDE	AUTOCLAVE	E-BEAM IRRADIATION	GAMMA IRRADIATION	DRY HEAT
		FORMALIN	ISOPROPYL ALCOHOL	ETHYL ALCOHOL			50 KILOGRAYS	50 KILOGRAYS	250°F
MATERIAL	METALS								
	302 STAINLESS STEEL	Y	Y	Y	Y	Y	Y	Y	Y
	316 STAINLESS STEEL	Y	Y	Y	Y	Y	Y	Y	Y
	CHROME-PLATED								
	BRASS-CDA 360	N	Y	Y	Y	Y	Y	Y	Y
	POLYMERS								
	ABS	N	N/A	Y	Y	N	Y	Y	N
	ACETAL	Y	Y	Y	Y	Y	N	N	N
	LDPE	Y	Y	Y	Y	N	Y	Y	N
	NYLON	Y	N	N	Y	N	N	N	N
	POLYCARBONATE	Y	Y	Y	Y	Y	Y	Y	Y
	POLYPROPYLENE (excludes glass-filled)	Y	Y	Y	Y	N	Y	Y	N
	POLYSULFONE	Y	Y	Y	Y	Y	Y	Y	Y
	ELASTOMERS								
	NITRILE/BUNA-N	Y	Y	Y	N	N	Y	Y	Y
	SILICONE	Y	Y	Y	Y	Y	Y	Y	Y
	KALREZ®	Y	Y	Y	Y	Y	N	N	Y
	EPR/EPDM	Y	Y	Y	Y	Y	Y	Y	Y
	FKM/VITON®	Y	Y	Y	N	N	N	N	Y

Sterilization Methods

DISINFECTANTS: 70°F (20°C), Formalin, ethyl alcohol, etc.
Sterilize coupled or uncoupled.

ETHYLENE OXIDE, ETO: Four hours, 100% EtO @ 110°F (43°C), up to five repetitions, coupled or uncoupled.

AUTOCLAVE:

Acetal: 250°F (121°C), 30 minutes max, up to 10 repetitions. Sterilize uncoupled only.

Polycarbonate: 250°F (121°C), 30 minutes, up to 10 repetitions. Sterilize uncoupled only.

Polysulfone: 270°F (132°C) for 60 minutes, up to 25 repetitions. Sterilize uncoupled only.

Steam-Thru Connection: 265°F (129°C) for 30 minutes, up to two cycles. (part number specific)

HFC39: 270°F (132°C) for 60 minutes, up to 25 repetitions for uncoupled units and up to one repetition for coupled units.

Electron Beam (E-Beam): Maximum cumulative exposure of 50 kilograys. Sterilize coupled or uncoupled.

Gamma: Maximum cumulative exposure of 50 kilograys. Sterilize coupled or uncoupled.

Dry Heat: 250°F (121°C), 12 hours, no pressure. Sterilize uncoupled only.

SIP process:

Up to 266°F (130°C) for 60 minutes
(Steam-Thru Connection)

Up to 275°F (135°C) for 60 minutes
(Steam-Thru II Connection)

Unsure of the chemical compatibility for your application? Consult the ChemCheck tool on cpcworldwide.com or contact CPC customer service to receive product samples for in-house testing and verification.

REGULATORY AND COMPLIANCE

ISO 13485:2003 Certification

ISO 13485:2003 is recognized by regulators around the world as a good basis for addressing medical device design and manufacturing regulatory requirements. It allows us to enhance product safety by proactively identifying and managing product and project risks. Becoming ISO 13485:2003 certified has allowed us to better control the consistency of manufactured products.

ISO 9001:2008 Certification

ISO 9001:2008 is a standard which assures consistency of a product ordered by customers. Organizations having ISO 9001:2008 certification have demonstrated compliance to the ISO 9001:2008 requirements by an independent registration authority. CPC's Quality Management System has been approved and certified under the ISO 9001:2008 standard.

Cleanroom Manufacturing

CPC manufactures certain Life Sciences and Chemical Management product lines in a cleanroom certified by an external testing service to meet or exceed ISO Class 7 (10,000) at 0.5 mm per ISO 14644 and the former Federal Standard 209E. Certification data is available upon request.

FDA and USDA

The U.S. Food and Drug Administration publishes, through the Code of Federal Regulations, standardized criteria which govern the acceptability of materials used in food contact. The U.S. Department of Agriculture publishes similar standards that mirror FDA criteria. Neither agency approves or disapproves products for particular applications. Most of CPC's products are made using resins that comply with applicable FDA or USDA standards. When necessary, the standard o-ring seals are replaced with specific, recognized materials.

REACH

REACH is the Regulation for Registration, Evaluation, Authorisation and Restriction of Chemicals. It entered into force on 1st June 2007 to streamline and improve the former legislative framework on chemicals of the European Union (EU). REACH places greater responsibility on industry to manage the risks that chemicals may pose to the health and the environment. CPC publishes a list of CPC products that are compliant with the EU regulation 1907/2006.

Regulation of Hazardous Substances

The RoHS Directive stands for "the restriction of the use of certain hazardous substances in electrical and electronic equipment." This Directive bans the placing on the EU market of new electrical and electronic equipment containing more than agreed levels of lead, cadmium, mercury, hexavalent chromium, polybrominated biphenyl (PBB) and polybrominated diphenyl ether (PBDE) flame retardants.

NSF

NSF International, based in Ann Arbor, Michigan, develops and publishes consensual criteria that govern the acceptability of materials and equipment used in food and beverage processing. They also do testing to verify the performance of materials or devices to their published criteria. CPC lists many of its product lines under the criteria of NSF/ANSI Standards, which governs components used in food and beverage contact applications.



Distributed by:

COLDER PRODUCTS COMPANY
1001 WESTGATE DRIVE
ST. PAUL, MINNESOTA 55114
U.S.A.

PHONE: +1 651-645-0091
FAX: +1 651-645-5404
TOLL FREE: 800-444-2474
info@cpeworldwide.com
cpeworldwide.com

COLDER PRODUCTS COMPANY GMBH
OSTRING 19
D-63762 GROSSOSTHEIM
GERMANY

PHONE: +49-6026-9973-0
FAX: +49-6026-9973-173

cpcgmbh@cpeworldwide.com
cpeworldwide.com

COLDER PRODUCTS COMPANY LIMITED
FLAT B, 29/F, WEST GATE TOWER,
7 WING HONG STREET, CHEUNG SHA WAN
KOWLOON, HONG KONG

PHONE: +852-2987-5272
FAX: +852-2987-2509

asiapacific@cpeworldwide.com
cpeworldwide.com



CPC WARRANTY STATEMENT: CPC (Colder Products Company) warrants its products against defects in workmanship and materials for a period of 12 months from the date of sale by CPC to its initial customer (regardless of any subsequent sale of the products). This warranty is void if the product is misused, altered, tampered with or is installed or used in a manner that is inconsistent with CPC's written recommendations, specifications and/or instructions, or fails to perform due to normal wear and tear. CPC does not warrant the suitability of the product for any particular application. Determining product application suitability is solely the customer's responsibility. CPC is not liable for special, indirect, incidental, consequential or other damages including, but not limited to, loss, damage, personal injury, or any other expense directly or indirectly arising from the use of or inability to use its products either separately or in combination with other products. ALL OTHER WARRANTIES EXPRESS OR IMPLIED, WHETHER ORAL, WRITTEN OR IN ANY OTHER FORM, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. The sole and exclusive remedy under this warranty is limited, at the option of CPC, to replacement of the defective product or an account credit in the amount of the original selling price. All allegedly defective CPC products must be returned prepaid transportation to CPC, together with information describing the product's application and performance, unless otherwise authorized in writing by CPC.

CPC PATENT STATEMENT: CPC takes pride in its innovative quick disconnect coupling and fittings solutions, many of which have been awarded United States and international patents. CPC has a strong tradition of

leadership in the quick disconnect market, and aggressively pursues and protects its proprietary information and intellectual property. In cases where it is practical and has a benefit to its customers, CPC has licensed its proprietary technology. Please contact CPC to discuss your unique needs.

CPC TRADEMARK STATEMENT: AseptiQuik®, BottleQuik®, BreakAway®, ChemQuik®, DrumQuik®, FitQuik®, IdentiQuik®, Nu-Seal®, SnapQuik®, Steam-Thru®, Softube® are registered trademarks with the U.S. Patent & Trademark Office. All other trademarks or service marks are property of their respective owners. **WARNING:** Due to the wide variety of possible fluid media and operating conditions, unintended consequences may result from the use of this product, all of which are beyond the control of CPC. It is the user's responsibility to carefully determine and test for compatibility for use with their application. All such risks shall be assumed by the buyer.

COPYRIGHT © 2014 COLDER PRODUCTS COMPANY. All rights reserved. Colder Products Company, Colder Products and CPC are registered trademarks with the US Patent & Trademark Office.

WARNING: Due to the wide variety of possible fluid media and operating conditions, unintended consequences may result from the use of this product, all of which are beyond the control of CPC. It is the user's responsibility to carefully determine and test for compatibility for use with their application. All such risks shall be assumed by the buyer.

CAT2020 12/15 WC/15K PRINTED IN U.S.A.