



For Diaphragm Valve Type DIASTAR Electric position indicator with 2 inductive switches PNP

C

- Connection: Plug

DN-DN [mm]	Inch [inch]	Type	Voltage	Part No.		lbs	
15 - 50	½ - 2	ER 52-4	5-30 V= 100 mA	199 190 308		0.503	
65 - 150	2 ½ - 6	ER 53-4	10-30 V= 100 mA	199 190 295		1.067	



For Diaphragm Valve Type DIASTAR Electric position indicator with 2 inductive switches Namur Exei (intrinsically safe)

C

- Connection: Plug

DN-DN [mm]	Inch [inch]	Type	Voltage	Part No.		lbs	
15 - 50	½ - 2	ER 52-5	8 V=	199 190 309		1.093	
65 - 150	2 ½ - 6	ER 53-5	8 V=	199 190 296		1.433	



For Diaphragm Valve Type DIASTAR Electric position indicator with 2 auxiliary switches Exed

C

- Connection: Cable, 2 m

DN-DN [mm]	Inch [inch]	Type	Voltage	Part No.		lbs	
15 - 50	½ - 2	ER 52-6	250 V ~ 5 A	199 190 405		1.433	
65 - 150	2 ½ - 6	ER 53-6	250 V ~ 5 A	199 190 298		1.433	



For Diaphragm Valve Type DIASTAR Adapter set

C

for combination electric position indicator / stroke limiter / manual override

Inch	Type	Series DIASTAR 10	Series DIASTAR 16	Series DIASTAR 10
½	ER 52	199 190 387	199 190 387	199 190 387
¾	ER 52	199 190 387	199 190 387	199 190 387
1	ER 52	199 190 387	199 190 388	199 190 387
1¼	ER 52	199 190 388	199 190 389	199 190 388
1½	ER 52	199 190 389	199 190 389	199 190 389
2	ER 52	199 190 389	199 190 389	199 190 389
2½-6	ER 53	-	199 190 310	199 190 310

Adapter Part No.		lbs	
199 190 387		0.137	
199 190 388		0.134	
199 190 389		0.150	
199 190 310		0.353	