


Schedule 80 PVC Piping Systems

Flange (Blind)

150 psi @ 73°F (10.3 bar @ 22.7°C)

10", 12", 14" & 16" 50 psi @ 73°F (3.5 bar @ 22.7°C)

HC = Honeycomb (Front)



Size [inch]	P/L	Part No.			# holes	Bolt Dia. [inch]	bolt cir. dia. [inch]	D [inch]	L [inch]	R [inch]	Design
½	08	853-005			4	½	2.38	3.50	0.50	0.43	HC
¾	08	853-007			4	½	2.75	3.88	0.50	0.44	HC
1	08	853-010			4	½	3.13	4.25	0.60	0.57	HC
1 ¼	08	853-012			4	½	3.50	4.63	0.63	0.56	HC
1 ½	08	853-015			4	½	3.88	5.00	0.82	0.71	HC
2	08	853-020			4	¾	4.75	6.00	0.92	0.74	HC
2 ½	08	853-025			4	¾	5.50	7.00	0.96	0.78	HC
3	08	853-030			4	¾	6.00	7.50	1.03	0.89	HC
4	08	853-040			8	¾	7.50	9.00	1.35	1.12	HC
6	08	853-060			8	¾	9.50	11.00	1.49	1.27	HC
8	08	853-080			8	¾	11.75	13.50	1.63	1.45	HC
10	05	853-100N *			12	1	14.25	16.00	1.00	1.00	SOLID
12	05	853-120N *			12	1	17.00	19.00	1.00	1.00	SOLID
14	05	853-140N *			12	1	18.75	21.00	1.00	1.00	SOLID
16	05	853-160N *			16	1	21.25	23.50	1.00	1.00	SOLID
18	05	853-180N *			16	1 ¼	22.75	25.00	1.00	1.00	SOLID
20	05	853-200N *			20	1 ¼	25.00	27.50	1.00	1.00	SOLID
24	05	853-240N *			20	1 ¼	29.50	32.00	1.00	1.00	SOLID