

GF Piping Systems

Datasheet

valid from
9/28/10

Adaptor fittings for butt fusion

PROGEF Natural adaptor socket metric NPT



Model:

- Material: PP-R unpigmented
- With butt fusion spigot **SDR11** and NPT tapered female thread, reinforced
- Connection to plastic or metal threads
- Reinforcing ring stainless (A2)
- Do not use thread sealing pastes that are harmful to PP
- Install with low mechanical stress and avoid large cyclic temperature changes

d [mm]	FM	NPT [inch]	PN	Code	SP	kg	L [mm]	L1 [mm]	s [mm]	e [mm]	
20	BCF, IR	½	10	728 914 056	-	0.017	49	28	32	1.9	
25	BCF, IR	¾	10	728 914 057	-	0.022	51	28	36	2.3	
32	BCF, IR	1	10	728 914 058	-	0.039	54	28	46	2.9	
40	BCF, IR	1 ¼	10	728 914 059	-	0.057	56	28	55	3.7	
50	BCF, IR	1 ½	10	728 914 060	5	0.085	60	28	64	4.6	
63	BCF, IR	2	10	728 914 061	5	0.140	62	28	80	5.8	

The technical data are not binding and not expressly warranted characteristics of the goods. They are subject to change. Our General Conditions of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
 Phone +41 -(0)52-631 1111
 e-mail: info.ps@georgfischer.com
 Internet: <http://www.piping.georgfischer.com>