



PROGEF Standard adaptor nipple metric R

Model:

- Material: PP-H
- With butt fusion spigot and BSP tapered male thread
- Do not use thread sealing pastes that are harmful to PP
- Install with low mechanical stress and avoid large cyclic temperature changes

d [mm]	R [inch]	PN [bar]	FM	Code	SP	Weight [kg]	L [mm]	L1 [mm]	s [mm]	e [mm]	
20	1/2	10	IR	727 910 556	10	0.013	51	23	32	1,9	
25	3/4	10	IR	727 910 557	10	0.014	52	23	36	2,3	
32	1	10	IR	727 910 558	10	0.027	55	23	46	2,9	
40	1 1/4	10	IR	727 910 559	10	0.041	58	23	55	3,7	
50	1 1/2	10	IR	727 910 560	10	0.062	60	23	65	4,6	
63	2	10	IR	727 910 561	5	0.096	67	26	80	5,8	

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
 Phone +41 -(0)52-631 1111
 e-mail: info.ps@georgfischer.com
 Internet: <http://www.gfps.com>