




PROGEF Standard reducer S5/SDR11


Model:

- Material: PP-H
- Conventional butt-welding according to DVS 2207 part 11
- IR = Infrared-(IR Plus®) compatible. Choose fusion parameters: PP-H

¹ Material: PP-R



	d [mm]	d1 [mm]	FM	Code	Weight [kg]	e [mm]	e1 [mm]	L [mm]	L1 [mm]	L2 [mm]	
	25	20	IR	727 908 537	0.007	2.3	1.9	50	20	20	
	32	20	IR	727 908 542	0.010	2.9	1.9	50	20	20	
	32	25	IR	727 908 541	0.010	2.9	2.3	50	20	20	
	40	20	IR	727 908 548	0.016	3.7	1.9	58	20	23	
	40	25	IR	727 908 547	0.016	3.7	2.3	55	20	20	
	40	32	IR	727 908 546	0.018	3.7	2.9	55	20	20	
	50	25	IR	727 908 554	0.024	4.6	2.3	60	20	20	
	50	32	IR	727 908 553	0.027	4.6	2.9	60	20	20	
	50	40	IR	727 908 552	0.030	4.6	3.7	60	20	20	
	63	32	IR	727 908 560	0.043	5.8	2.9	65	20	20	
	63	40	IR	727 908 559	0.047	5.8	3.7	65	20	20	
	63	50	IR	727 908 558	0.051	5.8	4.6	65	20	20	
	75	40	IR	727 908 566	0.062	6.8	3.7	68	20	20	
	75	50	IR	727 908 565	0.071	6.8	4.6	65	20	20	
	75	63	IR	727 908 564	0.075	6.8	5.8	65	20	20	
	90	63	IR	727 908 571	0.115	8.2	5.8	75	22	19	
	90	75	IR	727 908 570	0.130	8.2	6.8	75	22	19	
	110	75	IR	727 908 577	0.215	10.0	6.8	90	28	18	
	110	90	IR	727 908 576	0.225	10.0	8.2	90	28	30	
	125	110	IR	727 908 580	0.335	11.4	10.0	100	32	30	
	140	110	IR	727 908 585	0.423	12.7	10.0	110	33	29	
	140	125	IR	727 908 584	0.462	12.7	11.4	110	34	30	
	160	110	IR	727 908 590	0.586	14.6	10.0	120	39	27	
	160	140	IR	727 908 588	0.647	14.6	12.7	120	40	35	
	180	90	IR	727 908 978	0.968	16.4	8.8	157	45	22	
	180	110	IR	727 908 977	0.987	16.4	10.0	157	45	28	
	180	125	IR	727 908 976	0.890	16.4	11.4	136	45	32	
	180	140	IR	727 908 975	0.917	16.4	12.7	136	45	35	
	180	160	IR	727 908 974	1.031	16.4	14.6	136	45	35	
	200	160	IR	727 908 592	1.149	18.2	14.6	145	50	40	
	200	180	IR	727 908 979	1.350	18.2	16.4	151	50	45	
	225	110	IR	727 908 595	1.485	20.5	10.0	160	55	35	
	225	160	IR	727 908 596	1.563	20.5	14.6	160	55	40	
	225	180	IR	727 908 983	1.893	20.5	16.4	171	55	45	
	225	200	IR	727 908 597	1.723	20.5	18.2	160	55	50	
	250	160	--	727 908 990	1.483	22.7	14.6	194	60	55	
	250	225	--	727 908 987	2.592	22.7	20.5	182	60	55	
1	280	225	--	727 908 992	1.854	25.4	20.5	105	30	20	
1	280	250	--	727 908 991	1.311	25.4	22.7	70	30	18	
1	315	225	--	727 908 997	2.857	28.6	20.5	130	30	20	
1	315	250	--	727 908 996	3.500	28.6	22.7	100	30	20	
1	315	280	--	727 908 995	1.577	28.6	25.4	63	30	18	
1	355	250	--	727 908 963	5.490	32.3	22.7	245	90	60	
1	355	280	--	727 908 962	5.462	32.2	25.4	245	90	70	
1	355	315	--	727 908 961	3.700	32.2	28.6	245	90	80	
1	400	315	--	727 908 966	5.300	36.3	28.6	260	95	80	
1	400	355	--	727 908 965	4.800	36.3	32.2	260	95	90	
	450	280	--	727 908 960	9.000	40.9	25.4	230	60	70	
	450	315	--	727 908 948	8.000	40.9	28.6	230	60	80	
	450	355	--	727 908 950	7.400	40.9	32.2	230	60	90	
	450	400	--	727 908 951	6.000	40.9	36.3	230	60	95	



	d [mm]	d1 [mm]	FM	Code	Weight [kg]	e [mm]	e1 [mm]	L [mm]	L1 [mm]	L2 [mm]	
	500	315	--	727 908 953	12.000	45.4	28.6	230	60	80	
	500	355	--	727 908 954	10.800	45.4	32.2	230	60	90	
	500	400	--	727 908 956	10.000	45.4	36.3	230	60	95	
	500	450	--	727 908 964	8.300	45.4	40.9	230	60	60	

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
 Phone +41 -(0)52-631 1111
 e-mail: info.ps@georgfischer.com
 Internet: <http://www.gfps.com>