

GF Piping Systems

Datasheet


valid from

12/2/09

Adaptor fittings

Adaptor socket PVC-U metric Rp

21 91 02



Model:

- With solvent cement socket metric and parallel female thread Rp
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Do not use thread sealing pastes that are harmful to PVC-U
- Install with low mechanical stress and avoid large cyclic temperature changes

d [mm]	Rp [inch]	PN	Code	SP	kg	z [mm]	L [mm]	s [mm]	
12	¼	16	721 910 204	10	0.010	4	27	22	
16	⅜	16	721 910 205	10	0.017	5	31	27	
20	½	16	721 910 206	10	0.025	5	36	32	
25	⅝	16	721 910 207	10	0.032	5	40	36	
32	1	16	721 910 208	10	0.070	5	45	46	
40	1 ¼	16	721 910 209	10	0.085	5	51	55	
50	1 ½	16	721 910 210	10	0.125	7	59	65	
63	2	16	721 910 211	5	0.170	7	69	80	

The technical data are not binding and not expressly warranted characteristics of the goods. They are subject to change. Our General Conditions of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.piping.georgfischer.com>