

GF Piping Systems

Datasheet


valid from

12/2/09

Adaptor fittings

Adaptor socket PVC-U metric NPT

21 91 42



Model:

- With solvent cement socket metric and NPT (ASTM) taper female thread
- Connection to plastic threads only
- Do not use thread sealing pastes that are harmful to PVC-U
- Install with low mechanical stress and avoid large cyclic temperature changes

d [mm]	NPT [inch]	PN	Code	SP	kg	z [mm]	L [mm]	s [mm]	
20	½	10	721 914 206	10	0.022	5	35	32	
25	¾	10	721 914 207	10	0.027	6	40	36	
32	1	10	721 914 208	10	0.050	6	45	46	
40	1 ¼	10	721 914 209	10	0.075	6	51	55	
50	1 ½	10	721 914 210	10	0.109	10	59	65	
63	2	10	721 914 211	5	0.176	10	69	80	
75	2 ½	10	721 914 212	10	0.247	11	82	90	
90	3	10	721 914 213	5	0.381	14	94	110	
110	4	10	721 914 214	5	0.557	18	110	130	

The technical data are not binding and not expressly warranted characteristics of the goods. They are subject to change. Our General Conditions of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.piping.georgfischer.com>