



Cap PVC-U Rp

Model:

- With parallel female thread Rp
- Connection to plastic thread only
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U

Rp [inch]	PN [bar]	Code	SP	Weight [kg]	D [mm]	L [mm]	s [mm]	
1/8	10	721 960 603	10	0.013	20	14	17	
1/4	10	721 960 604	10	0.024	25	16	22	
3/8	10	721 960 605	10	0.012	31	19	27	
1/2	10	721 960 606	10	0.018	37	21	32	
3/4	10	721 960 607	10	0.024	42	24	36	
1	10	721 960 608	10	0.040	50	26	46	
1 1/4	10	721 960 609	10	0.060	60	29	55	
1 1/2	10	721 960 610	10	0.072	65	31	60	
2	10	721 960 611	5	0.127	81	36	75	

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
 Phone +41 -(0)52-631 1111
 e-mail: info.ps@georgfischer.com
 Internet: <http://www.gfps.com>