



Backing flange PVC-U metric

Model:

- For socket systems
- Connecting dimension: ISO 7005, EN 1092, BS 4504, DIN 2501
- **Bolt circle PN 10**
- Maximum medium- or ambient temperature 45 °C

¹ Connecting dimension: ISO 2536, bolt circle acc. DN125, suitable for flange adaptor d125/DN100

² Connecting dimension: ISO 2536, bolt circle acc. DN225, suitable for flange adaptor d250/DN250

AL: number of holes

	d [mm]	Size [inch]	DN [mm]	PN [bar]	Code	SP	Weight [kg]
1	16	3/8	10	10	721 700 005	100	0.053
	20	1/2	15	10	721 700 006	90	0.067
	25	3/4	20	10	721 700 007	50	0.092
	32	1	25	10	721 700 008	40	0.133
	40	1 1/4	32	10	721 700 009	25	0.198
	50	1 1/2	40	10	721 700 010	20	0.247
	63	2	50	10	721 700 011	30	0.312
	75	2 1/2	65	10	721 700 012	25	0.376
	90	3	80	10	721 700 013	20	0.464
	110	4	100	10	721 700 014	30	0.543
	125	4 1/2	125	10	721 700 015	12	0.904
2	140	5	125	10	721 700 016	12	0.758
	160	6	150	10	721 700 017	9	1.009
	200	7	200	10	721 700 019	8	1.669
	225	8	200	10	721 700 020	8	1.377
	250	9	250	6	721 700 021	1	2.376
	250	9	225	6	721 700 136	1	1.800
	280	10	250	6	721 700 137	1	1.746
	315	12	300	6	721 700 138	1	2.349
	355	14	350	6	721 700 139	1	3.485
	400	16	400	6	721 700 140	1	4.526

	d [mm]	D [mm]	D1 [mm]	D2 [mm]	D3 [mm]	H [mm]	r [mm]	AL	SC
1	16	90	60	23	14	10	1	4	M12
	20	95	65	28	14	11	1	4	M12
	25	105	75	34	14	12	2	4	M12
	32	115	85	42	14	14	2	4	M12
	40	140	100	51	18	15	2	4	M16
	50	150	110	62	18	16	2	4	M16
	63	165	125	78	18	18	3	4	M16
	75	185	145	92	18	19	3	4	M16
	90	200	160	110	18	20	3	8	M16
	110	220	180	133	18	22	3	8	M16
	125	250	210	150	18	26	5	8	M16
2	140	250	210	167	18	26	4	8	M16
	160	285	240	190	22	28	4	8	M20
	200	340	295	226	22	32	4	8	M20
	225	340	295	250	22	32	4	8	M20
	250	395	350	277	22	36	4	12	M20
	250	370	325	277	22	36	4	8	M20
	280	395	350	310	22	36	4	12	M20
	315	445	400	348	22	36	4	12	M20
	355	505	460	388	22	38	5	16	M20
	400	565	515	442	26	42	5	16	M24

Datasheet

valid from: 7/7/15



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
Phone +41 -(0)52-631 1111
e-mail: info.ps@georgfischer.com
Internet: <http://www.gfps.com>