



45° Elbow, PN 16, PVDF-Standard




d [mm]	FM	code	weight [lb]	e [mm]	L [mm]	L1 [mm]	
20	BCF, IR	735 158 606	0.042	1.9	32	25	
25	BCF, IR	735 158 607	0.055	1.9	34	26	
32	BCF, IR	735 158 608	0.084	2.4	36	26	
40	BCF, IR	735 158 609 ^	0.119	2.4	39	28	
50	BCF, IR	735 158 610	0.185	3.0	42	30	
63	BCF, IR	735 158 611	0.267	3.0	47	31	
75	BCF, IR	735 158 612 ^	0.353	3.6	49	32	
90	BCF, IR	735 158 613	0.648	4.3	57	37	
110	BCF, IR	735 158 614	1.058	5.3	70	46	

45° Elbow, PN 10, PVDF-Standard



d [mm]	FM	code	weight [lb]	e [mm]	L [mm]	L1 [mm]	
160	IR	735 158 517 *	2.183	4.9	100	62	
200	IR	735 158 519 *	4.542	6.2	124	77	
225	IR	735 158 520 *	6.444	6.9	140	88	

Tee, PN 16, PVDF-Standard



d [mm]	FM	code	weight [lb]	e [mm]	L [mm]	L1 [mm]	
20	BCF, IR	735 208 606	0.062	1.9	38	25	
25	BCF, IR	735 208 607	0.088	1.9	42	27	
32	BCF, IR	735 208 608	0.143	2.4	46	27	
40	BCF, IR	735 208 609 ^	0.209	2.4	51	28	
50	BCF, IR	735 208 610	0.344	3.0	58	28	
63	BCF, IR	735 208 611	0.595	3.0	66	28	
75	BCF, IR	735 208 612 ^	0.802	3.6	75	32	
90	BCF, IR	735 208 613	1.385	4.3	90	39	
110	BCF, IR	735 208 614	2.474	5.3	110	48	