



35 15 85

Elbow 45°, PN 10, PVDF-HP**K**

PF 2 37 249

d [mm]	PN	Code	kg	e [mm]	L [mm]	L1 [mm]	
90	10	735 158 538	0.181	2.8	57	37	
110	10	735 158 539	0.330	3.4	70	46	
125	10	735 158 540	0.490	3.9	79	51	
140	10	735 158 541	0.680	4.3	88	57	
160	10	735 158 542	0.990	4.9	100	62	
200	10	735 158 544	1.940	6.2	124	77	
225	10	735 158 545	2.780	6.9	140	88	

35 20 86

T 90° equal ; PN 16, PVDF-HP**K**

PF 2 37 249

d [mm]	PN	Code	kg	e [mm]	L [mm]	L1 [mm]	
20	16	735 208 631	0.023	1.9	38	25	
25	16	735 208 632	0.032	1.9	42	27	
32	16	735 208 633	0.056	2.4	46	27	
40	16	735 208 634	0.083	2.4	51	28	
50	16	735 208 635	0.140	3.0	58	28	
63	16	735 208 636	0.231	3.0	66	28	
75	16	735 208 637	0.370	3.6	75	32	
90	16	735 208 638	0.660	4.3	90	39	
110	16	735 208 639	1.210	5.3	110	48	
140	16	735 208 641	2.600	6.7	140	62	
160	16	735 208 642	5.200	7.7	160	71	
200	16	735 208 644	6.630	9.6	200	80	
225	16	735 208 645	9.120	10.8	220	86	