



35 20 85

T 90° reduced; PN 10, PVDF-HP**K**

PF 2 37 425

d - d1 [mm]	PN [bar]	Code	kg	e [mm]	e1 [mm]	L [mm]	L1 [mm]	L2 [mm]	L3 [mm]	
160 - 90	10 / 16	735 208 587	2.300	4.9	4.3	155	130	60	25	
160 - 110	10 / 16	735 208 586	2.300	4.9	5.3	155	130	60	25	
225 - 90	10 / 16	735 208 595	4.400	6.9	4.3	155	160	60	25	
225 - 110	10 / 16	735 208 594	4.400	6.9	5.3	155	160	60	25	

35 91 86

Restraint Fitting, PN 16, PVDF-HP**K**

PF 2 37 249

d [mm]	PN	Code	kg	D [mm]	e [mm]	L [mm]	L1 [mm]	L2 [mm]	
20	16	735 918 656	0.027	28	1.9	100	53	32	
25	16	735 918 657	0.036	33	1.9	100	53	32	
32	16	735 918 658	0.054	40	2.4	100	53	32	
40	16	735 918 659	0.067	48	2.4	100	53	32	
50	16	735 918 660	0.100	58	3.0	100	53	32	
63	16	735 918 661	0.131	71	3.0	105	53	32	
75	16	735 918 662	0.252	87	3.6	125	70	40	
90	16	735 918 663	0.353	105	4.3	125	70	40	
110	16	735 918 664	0.516	127	5.3	125	70	40	



35 91 88

Instrument Installation Fitting, PN16, PVDF-HP**K****Model:**

- Suitable for hole diameters from 1/4 - 3/4
- Injection-moulded version

Note:

- Hole needs to be milled, HAND HELD DRILLING MUST NOT BE DONE



PF 2 37 425

d [mm]	PN	Code	kg	D [mm]	e [mm]	d1 [mm]	d2 [mm]	H [mm]	L [mm]	L1 [mm]	
63	16	735 918 811	0.235	85	3.0	40	17	89	120	25	
75	16	735 918 812	0.326	96	3.6	40	17	101	130	25	
90	16	735 918 813	0.418	110	4.3	40	17	116	130	25	
110	16	735 918 814	0.561	127	5.3	40	17	136	130	25	