


MOLDED



ASTM D2665, F1866, F2135, CSA B181.2 WHERE APPLICABLE

CONCENTRIC REDUCER COUPLING HxH
PVC SOLVENT WELD DWV

PART NO.	SIZE IN INCHES	H1	H2	L1	T	W	D1
* D606-4	6 x 4	3 1/16	1 25/32	1 1/2	7 7/32	6 11/32	5 1/32
* D608-4	8 x 4	4 1/16	1 25/32	2 19/32	9 11/32	8 7/16	5 1/32
* D608-6	8 x 6	4 1/16	3 1/16	1 5/8	9 11/32	8 3/4	7 7/32
* D6010-4	10 x 4	5 1/16	1 25/32	2 1/2	11 17/32	9 11/32	5 1/32
* D6010-6	10 x 6	5 1/16	3 1/16	1 19/32	11 17/32	9 23/32	7 7/32
* D6010-8	10 x 8	5 1/16	4 1/16	1 7/16	11 17/32	10 9/16	9 11/32
* D6012-4	12 x 4	6 1/16	1 25/32	2 27/32	13 19/32	10 11/16	5 1/32
* D6012-6	12 x 6	6 1/16	3 1/16	2 1/2	13 19/32	11 5/8	7 7/32
* D6012-8	12 x 8	6 1/16	4 1/16	1 13/16	13 19/32	11 15/16	9 11/32
* D6012-10	12 x 10	6 1/16	5 1/16	1 1/4	13 19/32	12 3/8	11 17/32

-- DIMENSIONS AND APPEARANCE ARE APPROXIMATE AND SUBJECT TO CHANGE WITHOUT NOTICE DUE TO DESIGN OR PRODUCTION MODIFICATIONS
-- MOLDED FITTING TOLERANCE = ±1/8" OVERALL LENGTH
-- FABRICATED FITTING TOLERANCE = ±1" LINEAR, ± 2° ANGULAR

* MOLDED FITTING
† ASSEMBLED FROM MOLDED COMPONENTS
ALL OTHER FITTINGS ARE FABRICATED