
SPECIAL REINFORCED 90° ELBOW


Socket x SR Fipt



Part Number	Size	G	G1	H	H1	M	M1	Approx. Wt. (Lbs.)
807-005CSR	1/2	15/32	23/32	1-11/32	1-9/32	1-3/16	1-7/32	.09
807-007CSR	3/4	9/16	21/32	1-9/16	1-13/32	1-3/8	1-3/8	.12
807-010CSR	1	19/32	13/16	1-23/32	1-23/32	1-11/16	1-23/32	.21
807-012CSR	1-1/4	23/32	1-1/32	1-31/32	1-31/32	2-1/16	2-1/16	.31
807-015CSR	1-1/2	31/32	1-5/32	2-3/8	2-1/8	2-11/32	2-7/16	.44
807-020CSR	2	1-7/32	1-1/2	2-15/32	2-7/16	2-31/32	2-31/32	.91
807-030CSR	3	1-13/16	2-7/32	3-23/32	3-9/16	4-9/32	4-9/32	2.08
807-040CSR	4	2-9/32	2-25/32	4-9/16	4-7/32	5-1/4	5-1/4	3.02

SPECIAL REINFORCED REDUCING 90° ELBOW


Socket x SR Fipt



Part Number	Size	G	G1	H	H1	M	M1	Approx. Wt. (Lbs.)
807-101CSR	3/4x1/2	1/2	13/16	1-17/32	1-17/32	1-13/32	1-3/16	.12
807-130CSR	1x1/2	9/16	1	1-23/32	1-5/8	1-23/32	1-3/16	.14

TRANSITION 90° ELBOW

Socket x Brass Fipt



Part Number	Size	G	G1	H	H1	M	M1	Approx. Wt. (Lbs.)
807-005CBR	1/2	13/32	31/32	1-9/32	1-17/32	1-5/32	1-3/16	.15
807-007CBR	3/4	1/2	1-5/32	1-1/2	1-25/32	1-3/8	1-13/32	.21

Not intended to convey or dispense water for human consumption through drinking or cooking

Suitable for Oil-Free air handling to 25 psi, not for distribution of compressed air or gas
Spears® Manufacturing Company
Due to Material Cost Variations, Prices Subject to Change. Check On-line Catalog @ www.spearsmfg.com