




Schedule 80 CPVC Technical Information

Schedule 80 CPVC Fittings

REDUCER COUPLING

Fipt x Fipt




Part Number	Size	L	M	M1	N	Approx. Wt. (Lbs.)
830-072C ¹	1/2x1/4	1-31/32	1-5/16	1-5/32	5/8	.08
830-073C ¹	1/2x3/8	1-29/32	1-7/32	1-7/32	19/32	.08
830-101C	3/4x1/2	1-23/32	1-3/8	1-7/32	7/32	.08

¹ Outlet sized with bushing

SPECIAL REINFORCED REDUCER COUPLING


SR Fipt x SR Fipt



Part Number	Size	L	M	M1	N	Approx. Wt. (Lbs.)
830-101CSR	3/4x1/2	1-23/32	1-3/8	1-7/32	7/32	.09
830-130CSR	1x1/2	2-1/4	1-23/32	1-7/32	21/32	.17
830-131CSR	1x3/4	2-13/32	1-23/32	1-3/8	23/32	.17
830-210CSR	1-1/2x3/4	2-7/8	2-7/16	1-3/8	1-7/32	.29
830-211CSR	1-1/2x1	2-15/16	2-7/16	1-11/16	7/16	.36
830-212CSR	1-1/2x1-1/4	2-7/8	2-1/2	2-3/32	15/16	.34
830-249CSR	2x1	3-3/16	3	1-23/32	1-17/32	.48
830-251CSR	2x1-1/2	3-1/4	3	2-7/16	1-7/16	.52

GROOVED COUPLING ADAPTER

Groove x Socket



Part Number	Size	L	M1	N	Approx. Wt. (Lbs.)
833-012C	1-1/4	2-13/16	2-1/16	1-9/16	.17
833-015C	1-1/2	2-29/32	2-11/32	1-1/2	.20
833-020C	2	3-1/16	2-7/8	1-9/16	.30
833-025C	2-1/2	3-3/8	3-1/2	1-5/8	.52
833-030C	3	3-9/16	4-3/16	1-11/16	.72