
UNION (Old Style)

Socket x Fipt

Dimensions Also Applicable to
899-XXXC EPDM O-ring Seal Units

235 psi @ 73°F



Part Number w/FKM O-ring Seal	Size	L	M	N	Nut O.D.	Approx. Wt. (Lbs.)
859-005C	1/2	2-3/32	1-9/32	15/32	1-31/32	.17
859-007C	3/4	2-3/8	1-17/32	9/16	2-1/2	.29
859-010C	1	2-9/16	1-27/32	13/32	2-7/8	.40
859-012C	1-1/4	2-7/8	2-7/32	5/8	3-5/16	.54
859-015C	1-1/2	3-1/8	2-19/32	27/32	3-9/16	.66
859-020C	2	3-5/8	3-1/32	1-1/16	4-3/16	1.10
859-025C	2-1/2	4-3/8	3-5/8	1-13/32	4-7/8	1.66
859-030C	3	5-1/16	4-3/8	1-1/2	5-3/4	2.61
859-040C	4	5-7/8	5-7/16	1-7/8	7-1/16	4.13


1) For (Socket X Fipt) Unions Equipped With EPDM O-ring, Replace The 859 With An 899 Before The Dash.
e.g. Part Number 899-002C = 1/4" PVC, Union, Socket x Fipt, With EPDM O-rings.

TRANSITION UNION

Socket x Brass Fipt Threaded Insert and FKM O-ring Seal

Dimensions Also Applicable to 899-XXXCBR EPDM O-ring Seal Units

235 psi @ 73°F



Part Number w/FKM O-ring Seal	Size	L	M	N	Nut O.D.	Approx. Wt. (Lbs.)
859-005CBR	1/2	2-1/4	1-9/32	3/4	1-31/32	. 22
859-007CBR	3/4	2-11/16	1-17/32	15/16	2-1/2	.36
859-010CBR	1	2-13/16	1-7/8	1-1/32	2-7/8	.55
859-012CBR	1-1/4	3-9/32	2-7/32	1-1/16	3-5/16	.71
859-015CBR	1-1/2	3-1/2	2-9/16	1-3/32	3-17/32	.92
859-020CBR	2	3-5/8	2-7/8	1-1/4	4-5/16	1.64

Not intended to convey or dispense water for human consumption through drinking or cooking

1) For (Socket X Metal Fipt) Unions Equipped With EPDM O-ring, Replace The 859 With An 899 Before The Dash.
e.g. Part Number 899-010CBR = 1" PVC, Union Socket x Metal Fipt With EPDM O-rings.

Suitable for Oil-Free air handling to 25 psi, not for distribution of compressed air or gas
Spears® Manufacturing Company
Due to Material Cost Variations, Prices Subject to Change. Check On-line Catalog @ www.spearsmfg.com