


**SPECIAL REINFORCED UNION (Old style)**

Socket x SR Fipt

Dimensions Also Applicable to

899-XXXCSR EPDM O-ring Seal Units

235 psi @ 73°F




Part Number w/FKM O-ring Seal	Size	L	M	N	Nut O.D.	Approx. Wt. (Lbs.)
859-002CSR	1/4	2-1/16	15/16	25/32	1-21/32	.10
859-003CSR	3/8	2-9/32	1-1/32	29/32	1-25/32	.15
859-005CSR	1/2	2-9/32	1-9/32	21/32	1-31/32	.19
859-007CSR	3/4	2-19/32	1-17/32	25/32	2-1/2	.27
859-010CSR	1	2-15/16	1-27/32	25/32	2-7/8	.42
859-012CSR	1-1/4	3-5/32	2-7/32	29/32	3-5/16	.59
859-015CSR	1-1/2	3-13/32	2-9/16	1-1/32	3-9/16	.71
859-020CSR	2	4-3/32	3-1/32	1-19/32	4-3/16	1.21
859-030CSR	3	5-1/4	4-3/8	1-11/16	5-3/4	2.60
859-040CSR	4	5-7/8	5-13/32	2-1/8	7-3/32	4.21

1) For (Socket X SR Fipt) Unions Equipped With EPDM O-ring, Replace The 859 With An 899 Before The Dash.

e.g. Part Number **899-002CSR** = 1/4" PVC, Union, Socket x SR Fipt, With **EPDM** O-rings.**UNION 2000**

Socket x Socket

Dimensions Also Applicable to

8097-XXC EPDM O-ring Seal Units1/2" - 4" 235 psi @ 73°F
6" 150 psi @ 73°F

Part Number w/FKM O-ring Seal	Size	L	M	N	Nut O.D.	Approx. Wt. (Lbs.)
8057-005C	1/2	2-3/32	1-3/16	11/32	1-7/8	.08
8057-007C	3/4	2-3/8	1-13/32	3/8	2-9/32	.19
8057-010C	1	2-11/16	1-23/32	7/16	2-9/16	.17
8057-012C	1-1/4	2-15/16	2-3/32	7/16	3-3/32	.40
8057-015C	1-1/2	3-1/4	2-3/8	1/2	3-1/2	.51
8057-020C	2	3-17/32	2-7/8	17/32	4-9/32	.89
8057-025C	2-1/2	4-7/32	3-1/2	25/32	6-5/32	2.25
8057-030C	3	4-1/4	4-3/16	1/2	6-5/32	2.50
8057-040C	4	5-1/8	5-1/4	5/8	7-3/4	3.97
8057-060C	6	6-27/32	7-1/2	25/32	11-5/8	10.88

