




## Schedule 40 Fittings & Accessories Technical Information

### Schedule 40 Fittings Dimensions & Information

#### 90° ELBOW

Socket x Socket



| Part Number | Size  | G       | H        | M        | Approx. Wt. (Lbs.) |
|-------------|-------|---------|----------|----------|--------------------|
| 406-003     | 3/8   | 3/8     | 1-1/8    | 7/8      | .03                |
| 406-005     | 1/2   | 1/2     | 1-1/4    | 1-1/8    | .05                |
| 406-007     | 3/4   | 9/16    | 1-1/2    | 1-11/32  | .07                |
| 406-010     | 1     | 11/16   | 1-13/16  | 1-5/8    | .12                |
| 406-012     | 1-1/4 | 31/32   | 2-5/32   | 2        | .20                |
| 406-015     | 1-1/2 | 1-1/16  | 2-11/32  | 2-1/4    | .25                |
| 406-020     | 2     | 1-5/16  | 2-11/16  | 2-3/4    | .38                |
| 406-025     | 2-1/2 | 1-1/2   | 3-1/4    | 3-11/32  | .73                |
| 406-030     | 3     | 1-27/32 | 3-23/32  | 4        | 1.03               |
| 406-040     | 4     | 2-13/32 | 4-13/32  | 5-1/32   | 1.73               |
| 406-045F    | 4-1/2 | 8-5/8   | 6-1/8    | 5-7/16   | 3.13               |
| 406-050     | 5     | 3-1/16  | 6-1/8    | 6-5/32   | 3.58               |
| 406-060     | 6     | 3-17/32 | 6-9/16   | 7-9/32   | 4.52               |
| 406-080     | 8     | 4-13/32 | 8-7/16   | 9-3/8    | 8.84               |
| 406-100     | 10    | 5-13/16 | 10-27/32 | 11-19/32 | 15.75              |
| 406-100F    | 10    | 9-1/2   | 14-3/4   | 11-1/2   | 17.40              |
| 406-120     | 12    | 7-1/16  | 13-9/16  | 14-1/4   | 27.98              |
| 406-120F    | 12    | 10-1/2  | 16-3/4   | 13-9/16  | 25.94              |
| 406-140     | 14    | 7-1/2   | 14-1/2   | 15-11/16 | 53.35              |
| 406-140F    | 14    | 12-1/4  | 19-1/4   | 14-7/8   | 47.26              |
| 406-160F    | 16    | 14-1/8  | 22-1/8   | 17       | 69.70              |
| 406-180F    | 18    | 17-1/4  | 26-1/4   | 19-1/8   | 104.20             |
| 406-200F    | 20    | 18-3/4  | 28-3/4   | 21-3/16  | 131.93             |
| 406-240F    | 24    | 22-1/4  | 34-1/4   | 25-3/8   | 216.00             |