


**SPECIAL REINFORCED UNION (Old style)**

Socket x SR Fipt

Dimensions Also Applicable to

899-XXXSR EPDM O-ring Seal Units

235 psi @ 73°F




Part Number w/FKM O-ring Seal	Size	L	M	N	Nut O.D.	Approx. Wt. (Lbs.)
859-002SR	1/4	2-1/16	15/16	25/32	1-21/32	.09
859-003SR	3/8	2-9/32	1-1/32	29/32	1-25/32	.13
859-005SR	1/2	2-9/32	1-9/32	21/32	1-31/32	.17
859-007SR	3/4	2-19/32	1-17/32	25/32	2-1/2	.28
859-010SR	1	2-15/16	1-27/32	25/32	2-7/8	.40
859-012SR	1-1/4	3-5/32	2-7/32	29/32	3-5/16	.55
859-015SR	1-1/2	3-13/32	2-9/16	1-1/32	3-9/16	.67
859-020SR	2	4-3/32	3-1/32	1-19/32	4-3/16	1.12
859-030SR	3	5-1/4	4-3/8	1-11/16	5-3/4	2.50
859-040SR	4	5-7/8	5-13/32	2-1/8	7-3/32	3.96

1) For (Socket X SR Fipt) Unions Equipped With EPDM O-ring, Replace The 859 With An 899 Before The Dash.

e.g. Part Number **899-002SR** = 1/4" PVC, Union, Socket x SR Fipt, With **EPDM** O-rings.**UNION 2000**

Socket x Socket

Dimensions Also Applicable to

8097-XXX EPDM O-ring Seal Units1/2" - 4" 235 psi @ 73°F
6" 150 psi @ 73°F

Part Number w/FKM O-ring Seal	Size	L	M	N	Nut O.D.	Approx. Wt. (Lbs.)
8057-005	1/2	2-3/32	1-3/16	11/32	1-7/8	.12
8057-007	3/4	2-3/8	1-13/32	3/8	2-9/32	.17
8057-010	1	2-11/16	1-23/32	7/16	2-9/16	.28
8057-012	1-1/4	2-15/16	2-3/32	7/16	3-3/32	.36