

# Timing Pulley Part Number Identification

B&B Manufacturing offers thousands of off-the-shelf timing pulleys. All of our stock sizes are listed in this catalog. Our part numbers are similar to that of other manufacturers but offer some additional information. Below is an explanation of our numbering system.

**Example 1:** Trapezoidal shaped tooth minimum plain bore: 16XL037-6FA3

<u>Number of Teeth</u>	<u>Pitch</u>	<u>Belt Width</u>	-	<u>Construction</u>	<u>Material</u>	<u>Bore Size</u>
16	XL	037	-	6F	A	3

**Example 2:** Curvilinear shaped tooth minimum plain bore: 15-3M09-6CA2

<u>Number of Teeth</u>	-	<u>Pitch</u>	<u>Belt Width</u>	-	<u>Construction</u>	<u>Material</u>	<u>Bore Size</u>
15	-	3M	09	-	6C	A	2

**Example 3:** Timing pulleys bored for QD or Taper-lock style bushings: TL28L050

<u>Bushing Style</u>	<u>Number of Teeth</u>	<u>Pitch</u>	<u>Belt Width</u>
TL	28	L	050

Listed below are the codes for the various types of pulley configurations we offer.

<u>Pitch</u>	<u>Belt Width</u>	<u>Belt Width</u>	<u>Construction</u>	<u>Material</u>	<u>Bore Size</u>
MP = 0.080 Pitch	012 = 1/8"	06 = 6mm	6C	A = Aluminum	1 = 1/8"
LT = 0.0816 Pitch	187 = 3/16"	09 = 9mm	6F	S = Steel or Iron	2 = 3/16"
XL = 0.200 Pitch	025 = 1/4"	15 = 15mm	3F		3 = 1/4"
L = 0.375 Pitch	312 = 5/16"	20 = 20mm	6		4 = 5/16"
H = 0.500 Pitch	037 = 3/8"	25 = 25mm	6W		5 = 3/8"
3M = 3mm Pitch	050 = 1/2"	30 = 30mm			6 = 1/2"
5M = 5mm Pitch	075 = 3/4"	50 = 50mm			7 = 5/8"
8M = 8mm Pitch	100 = 1"				8 = 3/4"
	150 = 1 1/2"				9 = 7/8"
	200 = 2"				10 = 1"
	300 = 3"				